

## FCC PART 15.249

## TEST REPORT

For

### OKIN Refined Electric Technology Co., Ltd.

Plant 4, No. 410, Xinyonglian Road, Wangjiangjing Development Zone, Jiaxing, Zhejiang, China

**FCC ID: PCU-CB1322**

|                                        |                                                                                                                                                                                                                               |                                     |  |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|--|
| <b>Report Type:</b><br>Original Report |                                                                                                                                                                                                                               | <b>Product Type:</b><br>Control Box |  |
| <b>Test Engineer:</b>                  | Chris Wang <i>Chris. Wang</i>                                                                                                                                                                                                 |                                     |  |
| <b>Report Number:</b>                  | RSHA170816005-00A                                                                                                                                                                                                             |                                     |  |
| <b>Report Date:</b>                    | 2017-09-05                                                                                                                                                                                                                    |                                     |  |
| <b>Reviewed By:</b>                    | Oscar Ye<br>RF Leader <i>Oscar. Ye</i>                                                                                                                                                                                        |                                     |  |
| <b>Test Laboratory:</b>                | Bay Area Compliance Laboratories Corp. (Kunshan)<br>No.248 Chenghu Road, Kunshan, Jiangsu province, China<br>Tel: +86-0512-86175000<br>Fax: +86-0512-88934268<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                     |  |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

|                                                                                           |           |
|-------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                           | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                  | 3         |
| OBJECTIVE .....                                                                           | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                                        | 3         |
| TEST METHODOLOGY .....                                                                    | 3         |
| MEASUREMENT UNCERTAINTY.....                                                              | 4         |
| TEST FACILITY .....                                                                       | 4         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                     | <b>5</b>  |
| JUSTIFICATION .....                                                                       | 5         |
| EUT EXERCISE SOFTWARE .....                                                               | 5         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                  | 5         |
| EXTERNAL I/O CABLE.....                                                                   | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                         | 6         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                      | <b>8</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                                          | <b>9</b>  |
| <b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>                                              | <b>10</b> |
| APPLICABLE STANDARD .....                                                                 | 10        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                      | 10        |
| <b>FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS .....</b>                                | <b>11</b> |
| APPLICABLE STANDARD .....                                                                 | 11        |
| EUT SETUP .....                                                                           | 11        |
| EMI TEST RECEIVER SETUP.....                                                              | 11        |
| TEST PROCEDURE .....                                                                      | 11        |
| CORRECTED FACTOR & MARGIN CALCULATION .....                                               | 12        |
| TEST RESULTS SUMMARY .....                                                                | 12        |
| TEST DATA .....                                                                           | 12        |
| <b>FCC§15.205, §15.209&amp;§15.249- RADIATED EMISSIONS&amp; OUT OF BAND EMISSION.....</b> | <b>15</b> |
| APPLICABLE STANDARD .....                                                                 | 15        |
| EUT SETUP .....                                                                           | 15        |
| TEST EQUIPMENT SETUP.....                                                                 | 16        |
| TEST PROCEDURE .....                                                                      | 16        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                            | 17        |
| TEST RESULTS SUMMARY .....                                                                | 17        |
| TEST DATA .....                                                                           | 17        |
| <b>FCC §15.215(C) – 20 DB BANDWIDTH TESTING.....</b>                                      | <b>20</b> |
| APPLICABLE STANDARD .....                                                                 | 20        |
| TEST PROCEDURE .....                                                                      | 20        |
| TEST DATA .....                                                                           | 20        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                  |                                            |
|------------------|--------------------------------------------|
| Applicant        | OKIN Refined Electric Technology Co., Ltd. |
| Tested Model     | CB.13.22.02                                |
| Series Model     | CB.13.22.01, CB.13.22.03, CB.13.22.04      |
| Model Difference | Model names                                |
| Product Type     | Control Box                                |
| Dimension        | 159mm(L)×85mm(W)×41mm(H)                   |
| Power Supply     | DC 29V from adapter                        |

*All measurement and test data in this report was gathered from production sample serial number: 20170816005. (Assigned by BACL, Kunshan). The EUT was received on 2017-08-16.*

### Objective

This type approval report is prepared on behalf of OKIN Refined Electric Technology Co., Ltd. in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

### Related Submittal(s)/Grant(s)

FCC Part15.249 DXX submission with FCC ID: PCU-RF3019.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

| Item                               |             | Uncertainty |
|------------------------------------|-------------|-------------|
| AC Power Lines Conducted Emissions |             | 3.19 dB     |
| RF conducted test with spectrum    |             | 0.9dB       |
| RF Output Power with Power meter   |             | 0.5dB       |
| Radiated emission                  | 30MHz~1GHz  | 6.11dB      |
|                                    | 1GHz~6GHz   | 4.45dB      |
|                                    | 6GHz~18GHz  | 5.23dB      |
|                                    | 18GHz~40GHz | 4.88dB      |
| Occupied Bandwidth                 |             | 0.5kHz      |
| Temperature                        |             | 1.0°C       |
| Humidity                           |             | 6%          |

**Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road,Kunshan,Jiangsu province,China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Justification

Channel list for GFSK modulation:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2403            | 40      | 2442            |
| 2       | 2404            | 41      | 2443            |
| ...     | ...             | ...     | ...             |
| 38      | 2440            | 77      | 2479            |
| 39      | 2441            | 78      | 2480            |

EUT was tested with channel 1, 40 and 78.

### EUT Exercise Software

No software was used during the test.

### Support Equipment List and Details


| Manufacturer | Description                                                       | Model         | Serial Number |
|--------------|-------------------------------------------------------------------|---------------|---------------|
| OKIN         | Head Motor                                                        | B15313        | Q17071700001  |
| OKIN         | Foot Motor                                                        | B15312        | Q17071400002  |
| OKIN         | Message                                                           | JLDK.04.05.01 | JLDK-4        |
| OKIN         | MFP                                                               | 74389         | Qww286616540  |
| OKIN         | Adapter<br>Input: AC100-240V 50/60Hz 1.5A<br>Output: DC 29V, 1.8A | 09-290018     | RBD7174000646 |
| OKIN         | LED Strip                                                         | R5.113.00.011 | /             |
| OKIN         | Control Box                                                       | CB.13.22.02   | /             |

### External I/O Cable


| Cable Description | Length(m) | From Port | To          |
|-------------------|-----------|-----------|-------------|
| LED Strip Tieline | 0.8       | EUT       | LED Strip   |
| Lan Cable         | 0.8       | EUT       | Control Box |

## Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



**SUMMARY OF TEST RESULTS**

| FCC Rules                | Description of Test                      | Result     |
|--------------------------|------------------------------------------|------------|
| §15.203                  | Antenna Requirement                      | Compliance |
| §15.207(a)               | Conduction Emissions                     | Compliance |
| 15.205, §15.209, §15.249 | Radiated Emissions& Out of Band Emission | Compliance |
| §15.215 (c)              | 20 dB Bandwidth                          | Compliance |

**TEST EQUIPMENT LIST**

| Manufacturer                               | Description        | Model           | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------------------------|--------------------|-----------------|---------------|------------------|----------------------|
| <b>Radiated Emission Test (Chamber 1#)</b> |                    |                 |               |                  |                      |
| Rohde & Schwarz                            | EMI Test Receiver  | ESCI            | 100195        | 2016-11-25       | 2017-11-24           |
| Sunol Sciences                             | Broadband Antenna  | JB3             | A040914-2     | 2016-01-09       | 2019-01-08           |
| Sonoma Instrument                          | Pre-amplifier      | 310N            | 171205        | 2017-08-15       | 2018-08-14           |
| Rohde & Schwarz                            | Auto test Software | EMC32           | 100361        | /                | /                    |
| MICRO-COAX                                 | Coaxial Cable      | Cable-8         | 008           | 2017-08-15       | 2018-08-14           |
| MICRO-COAX                                 | Coaxial Cable      | Cable-9         | 009           | 2017-08-15       | 2018-08-14           |
| MICRO-COAX                                 | Coaxial Cable      | Cable-10        | 010           | 2017-08-15       | 2018-08-14           |
| <b>Radiated Emission Test (Chamber 2#)</b> |                    |                 |               |                  |                      |
| Rohde & Schwarz                            | Signal Analyzer    | FSIQ26          | 100048        | 2016-11-25       | 2017-11-24           |
| ETS-LINDGREN                               | Horn Antenna       | 3115            | 6229          | 2016-01-11       | 2019-01-10           |
| ETS-LINDGREN                               | Horn Antenna       | 3116            | 00084159      | 2016-10-18       | 2019-10-17           |
| Narda                                      | Pre-amplifier      | AFS42-00101800  | 2001270       | 2016-12-12       | 2017-12-11           |
| Heatsink Required                          | Amplifier          | QLW-18405536-J0 | 15964001009   | 2016-12-12       | 2017-12-11           |
| Rohde & Schwarz                            | Auto test Software | EMC32           | 100361        | /                | /                    |
| MICRO-COAX                                 | Coaxial Cable      | Cable-6         | 006           | 2017-08-15       | 2018-08-14           |
| MICRO-COAX                                 | Coaxial Cable      | Cable-11        | 011           | 2017-08-15       | 2018-08-14           |
| MICRO-COAX                                 | Coaxial Cable      | Cable-12        | 012           | 2017-08-15       | 2018-08-14           |
| MICRO-COAX                                 | Coaxial Cable      | Cable-13        | 013           | 2017-08-15       | 2018-08-14           |
| <b>RF Conducted Test</b>                   |                    |                 |               |                  |                      |
| Rohde & Schwarz                            | Signal Analyzer    | FSIQ26          | 836131/009    | 2016-09-21       | 2017-09-20           |
| OKIN                                       | RF Cable           | N/A             | N/A           | 2017-08-22       | 2018-08-21           |
| <b>Conducted Emission Test</b>             |                    |                 |               |                  |                      |
| Rohde & Schwarz                            | EMI Test Receiver  | ESCI            | 100195        | 2016-11-25       | 2017-11-24           |
| Rohde & Schwarz                            | LISN               | ESH3-Z5         | 862770/011    | 2016-10-10       | 2017-10-09           |
| Rohde & Schwarz                            | LISN               | ENV216          | 3560655016    | 2016-11-25       | 2017-11-24           |
| BACL                                       | BACL-EMC           | V1.0            | CE001         | /                | /                    |
| Narda                                      | Attenuator/6dB     | 10690812-2      | 26850-6       | 2017-01-10       | 2018-01-09           |
| MICRO-COAX                                 | Coaxial Cable      | Cable-15        | 015           | 2017-08-15       | 2018-08-14           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

### **Antenna Connector Construction**

The EUT has a PCB antenna arrangement and antenna gain is 0dBi, which was permanently attached ,fulfill the requirement of this section, please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

### Test Data

#### Environmental Conditions


|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.6°C    |
| <b>Relative Humidity:</b> | 52%       |
| <b>ATM Pressure:</b>      | 101.2 kPa |

*The testing was performed by Chris Wang on 2017-08-28.*

*EUT operation mode: Transmitting in high channel(worst case)*

## AC 120V/60 Hz, Line


Full Spectrum



| Frequency (MHz) | QuasiPeak (dBμV) | Average (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Limit (dB μ V) | Margin (dB) | Comment    |
|-----------------|------------------|------------------|-----------------|------|------------|----------------|-------------|------------|
| 0.150000        | ---              | 16.71            | 9.000           | L1   | 16.1       | 56.00          | 39.29       | Compliance |
| 0.150000        | 41.98            | ---              | 9.000           | L1   | 16.1       | 66.00          | 24.02       | Compliance |
| 0.170000        | ---              | 16.23            | 9.000           | L1   | 16.1       | 54.96          | 38.73       | Compliance |
| 0.170000        | 39.77            | ---              | 9.000           | L1   | 16.1       | 64.96          | 25.19       | Compliance |
| 0.190000        | ---              | 17.45            | 9.000           | L1   | 16.1       | 54.04          | 36.59       | Compliance |
| 0.190000        | 38.19            | ---              | 9.000           | L1   | 16.1       | 64.04          | 25.85       | Compliance |
| 0.240000        | ---              | 14.89            | 9.000           | L1   | 16.0       | 52.10          | 37.21       | Compliance |
| 0.240000        | 32.18            | ---              | 9.000           | L1   | 16.0       | 62.10          | 29.92       | Compliance |
| 0.450000        | ---              | 24.92            | 9.000           | L1   | 16.1       | 46.88          | 21.96       | Compliance |
| 0.450000        | 38.81            | ---              | 9.000           | L1   | 16.1       | 56.88          | 18.07       | Compliance |
| 10.840000       | ---              | 18.70            | 9.000           | L1   | 16.1       | 50.00          | 31.30       | Compliance |
| 10.840000       | 30.77            | ---              | 9.000           | L1   | 16.1       | 60.00          | 29.23       | Compliance |

**AC 120V/60 Hz, Neutral**

Full Spectrum



| Frequency (MHz) | QuasiPeak (dBμV) | Average (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Limit (dB μ V) | Margin (dB) | Comment    |
|-----------------|------------------|------------------|-----------------|------|------------|----------------|-------------|------------|
| 0.150000        | ---              | 20.27            | 9.000           | N    | 16.1       | 56.00          | 35.73       | Compliance |
| 0.150000        | 42.30            | ---              | 9.000           | N    | 16.1       | 66.00          | 23.70       | Compliance |
| 0.210000        | ---              | 14.62            | 9.000           | N    | 16.1       | 53.21          | 38.59       | Compliance |
| 0.210000        | 33.85            | ---              | 9.000           | N    | 16.1       | 63.21          | 29.36       | Compliance |
| 0.290000        | ---              | 16.18            | 9.000           | N    | 16.1       | 50.52          | 34.34       | Compliance |
| 0.290000        | 33.10            | ---              | 9.000           | N    | 16.1       | 60.52          | 27.42       | Compliance |
| 0.340000        | ---              | 13.27            | 9.000           | N    | 16.1       | 49.20          | 35.93       | Compliance |
| 0.340000        | 30.32            | ---              | 9.000           | N    | 16.1       | 59.20          | 28.88       | Compliance |
| 0.380000        | ---              | 15.33            | 9.000           | N    | 16.1       | 48.28          | 32.95       | Compliance |
| 0.380000        | 27.88            | ---              | 9.000           | N    | 16.1       | 58.28          | 30.40       | Compliance |
| 0.440000        | ---              | 18.09            | 9.000           | N    | 16.1       | 47.06          | 28.97       | Compliance |
| 0.440000        | 35.45            | ---              | 9.000           | N    | 16.1       | 57.06          | 21.61       | Compliance |

**Note:**

- 1) Corr.=LISN VDF (Voltage Division Factor) + Cable Loss
- 2) Corrected Amplitude = Reading + Corr.
- 3) Margin = Limit –Corrected Amplitude

## FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

### Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


| Fundamental frequency | Field strength of fundamental<br>(millivolts/meter) | Field strength of harmonics<br>(microvolts/meter) |
|-----------------------|-----------------------------------------------------|---------------------------------------------------|
| 902–928 MHz           | 50                                                  | 500                                               |
| 2400–2483.5 MHz       | 50                                                  | 500                                               |
| 5725–5875 MHz         | 50                                                  | 500                                               |
| 24.0–24.25 GHz        | 250                                                 | 2500                                              |

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

### Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz   | 120 kHz | QP       |

| Frequency Range | RBW  | Video B/W | Detector |
|-----------------|------|-----------|----------|
| 1GHz – 25GHz    | 1MHz | 3 MHz     | PK       |
|                 | 1MHz | 10 Hz     | Ave.     |

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.205 & 15.249.

### Test Data

#### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.6°C    |
| <b>Relative Humidity:</b> | 52%       |
| <b>ATM Pressure:</b>      | 101.2 kPa |

*The testing was performed by Chris Wang on 2017-09-04.*

*Test Mode: Transmitting (Scan with X-Axis, Y-Axis and Z-Axis position, the worst case X-Axis was recorded)*

**30MHz-25GHz:**

| Frequency<br>(MHz)       | Receiver          |                              | Turntable<br>Degree | Rx Antenna     |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.249/205/209 |                |
|--------------------------|-------------------|------------------------------|---------------------|----------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                          | Reading<br>(dBμV) | Detector<br>(PK/QP/<br>Ave.) |                     | Height<br>(cm) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| Low Channel (2403.00MHz) |                   |                              |                     |                |                |                             |                                    |                            |                |
| 171.26                   | 33.88             | QP                           | 125                 | 216            | V              | -13.70                      | 20.18                              | 43.5                       | 23.32          |
| 2403.00                  | 90.92             | PK                           | 305                 | 144            | V              | -4.93                       | 85.99                              | 114                        | 28.01          |
| 2403.00                  | 90.02             | Ave                          | 305                 | 144            | V              | -4.93                       | 85.09                              | 94                         | 8.91           |
| 2403.00                  | 80.60             | PK                           | 99                  | 192            | H              | -4.93                       | 75.67                              | 114                        | 38.33          |
| 2403.00                  | 79.68             | Ave                          | 99                  | 192            | H              | -4.93                       | 74.75                              | 94                         | 19.25          |
| 2390.00                  | 42.94             | PK                           | 160                 | 225            | V              | -4.96                       | 37.98                              | 74                         | 36.02          |
| 2390.00                  | 30.47             | Ave                          | 160                 | 225            | V              | -4.96                       | 25.51                              | 54                         | 28.49          |
| 2400.00                  | 45.59             | PK                           | 270                 | 219            | V              | -4.94                       | 40.65                              | 74                         | 33.35          |
| 2400.00                  | 32.33             | Ave                          | 270                 | 219            | V              | -4.94                       | 27.39                              | 54                         | 26.61          |
| 1534.47                  | 42.44             | PK                           | 14                  | 159            | V              | -7.91                       | 34.53                              | 74                         | 39.47          |
| 1534.47                  | 29.56             | Ave                          | 14                  | 159            | V              | -7.91                       | 21.65                              | 54                         | 32.35          |
| 4806.00                  | 45.72             | PK                           | 243                 | 121            | V              | 2.48                        | 48.20                              | 74                         | 25.80          |
| 4806.00                  | 36.23             | Ave                          | 243                 | 121            | V              | 2.48                        | 38.71                              | 54                         | 15.29          |
| 7209.00                  | 37.04             | PK                           | 79                  | 237            | V              | 9.79                        | 46.83                              | 74                         | 27.17          |
| 7209.00                  | 24.51             | Ave                          | 79                  | 237            | V              | 9.79                        | 34.30                              | 54                         | 19.70          |

| Frequency<br>(MHz)          | Receiver          |                              | Turntable<br>Degree | Rx Antenna     |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBµV/m) | FCC Part<br>15.249/205/209 |                |
|-----------------------------|-------------------|------------------------------|---------------------|----------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                             | Reading<br>(dBµV) | Detector<br>(PK/QP/<br>Ave.) |                     | Height<br>(cm) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBµV/m)          | Margin<br>(dB) |
| Middle Channel (2442.00MHz) |                   |                              |                     |                |                |                             |                                    |                            |                |
| 171.26                      | 33.85             | QP                           | 111                 | 156            | V              | -13.70                      | 20.15                              | 43.5                       | 23.35          |
| 2442.00                     | 90.43             | PK                           | 305                 | 191            | V              | -4.82                       | 85.61                              | 114                        | 28.39          |
| 2442.00                     | 89.54             | Ave                          | 305                 | 191            | V              | -4.82                       | 84.72                              | 94                         | 9.28           |
| 2442.00                     | 80.02             | PK                           | 99                  | 150            | H              | -4.82                       | 75.20                              | 114                        | 38.80          |
| 2442.00                     | 79.13             | Ave                          | 99                  | 150            | H              | -4.82                       | 74.31                              | 94                         | 19.69          |
| 1534.47                     | 42.41             | PK                           | 160                 | 118            | V              | -7.91                       | 34.50                              | 74                         | 39.50          |
| 1534.47                     | 29.54             | Ave                          | 160                 | 118            | V              | -7.91                       | 21.63                              | 54                         | 32.37          |
| 4139.68                     | 39.77             | PK                           | 270                 | 124            | V              | 1.08                        | 40.85                              | 74                         | 33.15          |
| 4139.68                     | 27.87             | Ave                          | 270                 | 124            | V              | 1.08                        | 28.95                              | 54                         | 25.05          |
| 4884.00                     | 45.46             | PK                           | 14                  | 155            | V              | 2.65                        | 48.11                              | 74                         | 25.89          |
| 4884.00                     | 36.00             | Ave                          | 14                  | 155            | V              | 2.65                        | 38.65                              | 54                         | 15.35          |
| 6662.33                     | 39.35             | PK                           | 243                 | 210            | H              | 8.66                        | 48.01                              | 74                         | 25.99          |
| 6662.33                     | 27.79             | Ave                          | 243                 | 210            | H              | 8.66                        | 36.45                              | 54                         | 17.55          |
| 7326.00                     | 36.76             | PK                           | 79                  | 218            | V              | 9.97                        | 46.73                              | 74                         | 27.27          |
| 7326.00                     | 24.28             | Ave                          | 79                  | 218            | V              | 9.97                        | 34.25                              | 54                         | 19.75          |

| Frequency<br>(MHz)        | Receiver          |                              | Turntable<br>Degree | Rx Antenna     |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.249/205/209 |                |
|---------------------------|-------------------|------------------------------|---------------------|----------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                           | Reading<br>(dBμV) | Detector<br>(PK/QP/<br>Ave.) |                     | Height<br>(cm) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| High Channel (2480.00MHz) |                   |                              |                     |                |                |                             |                                    |                            |                |
| 171.26                    | 33.90             | QP                           | 158                 | 189            | V              | -13.70                      | 20.20                              | 43.5                       | 23.30          |
| 2480.00                   | 90.98             | PK                           | 305                 | 159            | V              | -4.72                       | 86.26                              | 114                        | 27.74          |
| 2480.00                   | 90.09             | Ave                          | 305                 | 159            | V              | -4.72                       | 85.37                              | 94                         | 8.63           |
| 2480.00                   | 80.83             | PK                           | 99                  | 105            | H              | -4.72                       | 76.11                              | 114                        | 37.89          |
| 2480.00                   | 79.94             | Ave                          | 99                  | 105            | H              | -4.72                       | 75.22                              | 94                         | 18.78          |
| 2483.50                   | 43.56             | PK                           | 160                 | 130            | V              | -4.71                       | 38.85                              | 74                         | 35.15          |
| 2483.50                   | 31.49             | Ave                          | 160                 | 130            | V              | -4.71                       | 26.78                              | 54                         | 27.22          |
| 2583.17                   | 42.64             | PK                           | 270                 | 143            | V              | -4.22                       | 38.42                              | 74                         | 35.58          |
| 2583.17                   | 30.33             | Ave                          | 270                 | 143            | V              | -4.22                       | 26.11                              | 54                         | 27.89          |
| 4960.00                   | 45.36             | PK                           | 14                  | 107            | V              | 2.82                        | 48.18                              | 74                         | 25.82          |
| 4960.00                   | 34.88             | Ave                          | 14                  | 107            | V              | 2.82                        | 37.70                              | 54                         | 16.30          |
| 6662.33                   | 39.34             | PK                           | 243                 | 163            | H              | 8.66                        | 48.00                              | 74                         | 26.00          |
| 6662.33                   | 27.77             | Ave                          | 243                 | 163            | H              | 8.66                        | 36.43                              | 54                         | 17.57          |
| 7440.00                   | 36.61             | PK                           | 79                  | 169            | V              | 10.14                       | 46.75                              | 74                         | 27.25          |
| 7440.00                   | 24.12             | Ave                          | 79                  | 169            | V              | 10.14                       | 34.26                              | 54                         | 19.74          |

**Note:**

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor = Antenna factor (Rx) + cable loss – amplifier factor

Margin = Limit - Corr. Amplitude

## **FCC §15.215(c) – 20 dB BANDWIDTH TESTING**

### **Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### **Test Data**

#### **Environmental Conditions**

|                           |          |
|---------------------------|----------|
| <b>Temperature:</b>       | 24.2°C   |
| <b>Relative Humidity:</b> | 51 %     |
| <b>ATM Pressure:</b>      | 101.2kPa |


*The testing was performed by Chris Wang on 2017-08-22.*

*Test Mode: Transmitting*


**Test Result:** Compliant.

| Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |
|---------|-----------------|-----------------------|
| Low     | 2403.00         | 0.992                 |
| Middle  | 2442.00         | 0.986                 |
| High    | 2480.00         | 0.998                 |


### Low Channel



### Middle Channel



### High Channel



\*\*\*\*\* END OF REPORT \*\*\*\*\*