

FCC PART 15.249 TEST REPORT

For

OKIN Refined Electric Technology Co., Ltd.

No.465 Xinnanyang Road,Wangjiangjing Development Zone,Jiaxing Zhejiang China

FCC ID: PCU-CB3432

Report Type: Original Report	Product Type: CONTROL BOX
Test Engineer:	Winnie Yang <i>Winnie Yang</i>
Report Number:	RSA191016001-00C
Report Date:	2019-12-11
Reviewed By:	Oscar Ye EMC Manager <i>Oscar Ye</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	10
TEST EQUIPMENT LIST	11
FCC§15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
FACTOR & OVER LIMIT CALCULATION.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION.....	17
APPLICABLE STANDARD	17
EUT SETUP	17
TEST EQUIPMENT SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION (FOR ABOVE 1 GHz).....	19
TEST RESULTS SUMMARY	19
TEST DATA	19
FCC §15.215(C) – 20 DB BANDWIDTH TESTING.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	OKIN Refined Electric Technology Co., Ltd.
Tested Model:	CB3432
Product Type:	CONTROL BOX
Power Supply:	DC 29V
RF Function:	BLE,2.4G SRD
Operating Band/Frequency:	BLE: 2402-2480MHz ,2.4G SRD: 2403-2480MHz
Channel Number:	BLE:40,2.4G SRD: 78
Channel Separation:	BLE: 2MHz ,2.4G SRD: 1MHz
Antenna Type:	PCB antenna
Maximum Antenna Gain:	1dBi

All measurement and test data in this report was gathered from production sample serial number: 20191016001. (Assigned by BACL, Kunshan). The EUT was received on 2019-10-16.

Objective

This type approval report is prepared on behalf of *OKIN Refined Electric Technology Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS Submittal with FCC ID: PCU-CB3432.
FCC Part 15.249 DXX Grant with FCC ID: PCU-RF2517.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403	40	2442
2	2404	...	...
...	...	...	...
38	2440	77	2479
39	2441	78	2480

EUT was tested with Channel 1, 40 and 78.

EUT Exercise Software

RF test tool: Uart Assist exe

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Apple	Mobile Phone1	ML7J2CH/A	F4HR2B0TGRYD
HUAWEI	Mobile Phone2	EVA-TL00	862266039775394
OKIN	Adapter1	09-290018	RBD7567002029
/	Adapter2	W52RA199-290018	/
OKIN	Control Box	CB3342	/
OKIN	Electrical machinery 1	ALPHADRIVE 5 ADZ5	Q080830 0017
OKIN	Electrical machinery 2	ALPHADRIVE 5 ADZ5	Q080830 0018
OKIN	Electrical machinery 3	ALPHADRIVE 5 ADZ5	Q080830 0020

External I/O Cable


Cable Description	Length (m)	From Port	To
Cable	1.0	EUT	Adapter
Cable	1.0	Control Box	Adapter
Cable	1.2	EUT	Electrical machinery 1
Cable	1.2	EUT	Electrical machinery 2
Cable	1.2	EUT	Electrical machinery 3
Cable	1.5	EUT	Motor
Cable	1.0	EUT	Socket
Cable	0.8	EUT	Tape lights
Cable	1.0	Socket	Adapter
Cable	1.0	Socket	AC Source
Cable	1.0	EUT	Phone

Block Diagram of Test Setup

For Conducted Emissions



For Radiated Emissions(Below 1GHz):



Turntable
2m Diameter

AC Source

Adapter 2

Control Box

Socket

Electrical machinery1

Electrical machinery2

Adapter 1

Type light

EUT

Phone

Electrical machinery 3

Phone

Motor1

Motor 2

Non-Conductive Table
150cm above Ground Plane

1.5 Meter

1.0 Meter

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
15.205, §15.209, §15.249	Radiated Emissions& Out of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-30	2019-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-30	2019-11-29
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-12-12	2019-12-11
MICRO-TRONICS	Notch Filter	BRM50702	G024	2019-08-05	2020-08-04
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
SELECTOR	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	ESIB26	100146	2018-11-30	2019-11-29
Rohde & Schwarz	Signal Analyzer	ESIB26	100146	2019-11-30	2020-11-29
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
KEESON	RF Cable	KEESON C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
ROHDE&SCHWARZ	LISN	ENV216	3560655016	2018-11-30	2019-11-29
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2018-11-30	2019-11-29
Audix	Test Software	e3	V9	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2019-01-10	2020-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-09-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna for BLE and SRD, which was permanently attached to the EUT, antenna gain is 1dBi, fulfill the requirement of this section, please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions


Temperature:	25°C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by Winnie Yang on 2019-10-23.


Test Result: Compliant.

EUT operation mode: Transmitting in low channel. (Worst case)

AC 120V/60Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.156	10.60	19.82	30.42	55.65	-25.23	Average
2	0.156	26.00	19.82	45.82	65.65	-19.83	QP
3	0.270	5.00	19.82	24.82	51.12	-26.30	Average
4	0.270	17.20	19.82	37.02	61.12	-24.10	QP
5	0.452	12.90	19.75	32.65	46.85	-14.20	Average
6	0.452	24.80	19.75	44.55	56.85	-12.30	QP
7	0.675	-5.20	19.75	14.55	46.00	-31.45	Average
8	0.675	6.40	19.75	26.15	56.00	-29.85	QP
9	1.725	0.80	19.84	20.64	46.00	-25.36	Average
10	1.725	8.20	19.84	28.04	56.00	-27.96	QP
11	10.905	8.30	19.57	27.87	50.00	-22.13	Average
12	10.905	18.70	19.57	38.27	60.00	-21.73	QP

AC 120V/60Hz, Neutral

		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.163	8.00	19.83	27.83	55.30	-27.47	Average
2	0.163	23.60	19.83	43.43	65.30	-21.87	QP
3	0.277	5.70	19.82	25.52	50.90	-25.38	Average
4	0.277	17.60	19.82	37.42	60.90	-23.48	QP
5	0.447	12.20	19.75	31.95	46.93	-14.98	Average
6	0.447	24.50	19.75	44.25	56.93	-12.68	QP
7	0.630	-2.60	19.75	17.15	46.00	-28.85	Average
8	0.630	8.20	19.75	27.95	56.00	-28.05	QP
9	1.839	-1.81	19.84	18.03	46.00	-27.97	Average
10	1.839	5.89	19.84	25.73	56.00	-30.27	QP
11	10.125	7.10	19.56	26.66	50.00	-23.34	Average
12	10.125	17.80	19.56	37.36	60.00	-22.64	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24GHz-24.25GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

The system was investigated from 30 MHz to 25GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Over Limit Calculation (For Below 1GHz)

The Factor is calculated by adding Antenna Factor , Cable Loss, and Amplifier Gain. The basic equation is as follows:

$$\text{Factor (dB)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Corrected Amplitude & Margin Calculation (for above 1 GHz)

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249.

Test Data

Environmental Conditions


Temperature:	19.5~21.2℃
Relative Humidity:	51~52 %
ATM Pressure:	101.6~102.0 kPa

The testing was performed by Winnie Yang from 2019-10-30 to 2019-11-20.

Test Mode: Transmitting

Spurious Emission Test:**30MHz-1GHz****Horizontal:**


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low channel of operation in X-axis of orientation** was recorded.)



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	87.42	33.20	-17.23	15.97	40.00	-24.03	200	60	QP
2	107.51	27.50	-13.12	14.38	43.50	-29.12	200	60	QP
3	136.46	33.40	-11.57	21.83	43.50	-21.67	200	240	QP
4	205.68	32.50	-12.15	20.35	43.50	-23.15	200	269	QP
5	256.52	35.20	-11.79	23.41	46.00	-22.59	200	18	QP
6	696.86	23.60	-2.14	21.46	46.00	-24.54	180	364	QP

Vertical:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded.)



	Freq	Read		Limit	Over	APos	TPos	
	MHz	Level	Factor	Level	Line	Limit		Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg
1	45.06	42.60	-14.22	28.38	40.00	-11.62	100	270 QP
2	88.96	43.50	-17.24	26.26	43.50	-17.24	100	219 QP
3	135.98	37.49	-11.54	25.95	43.50	-17.55	100	115 QP
4	207.85	33.61	-12.36	21.25	43.50	-22.25	200	274 QP
5	331.35	29.81	-9.60	20.21	46.00	-25.79	100	13 QP
6	631.69	24.29	-3.40	20.89	46.00	-25.11	200	240 QP

Note:

- 1) Factor (dB) = Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)
- 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2403MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1042.50	---	24.01	200	V	231.0	-12.4	54.00	29.99
1042.50	33.13	---	200	V	231.0	-12.4	74.00	40.87
3140.30	---	31.20	150	V	172.0	-4.1	54.00	22.80
3140.30	41.22	---	150	V	172.0	-4.1	74.00	32.78
4806.00	---	48.70	200	V	202.0	-0.6	54.00	5.30
4806.00	54.56	---	200	V	202.0	-0.6	74.00	19.44
7209.00	---	47.87	200	V	127.0	5.7	54.00	6.13
7209.00	53.61	---	200	V	127.0	5.7	74.00	20.39
13821.40	---	44.95	150	V	279.0	12.3	54.00	29.99
13821.40	54.76	---	150	V	279.0	12.3	74.00	40.87
17704.20	---	46.79	200	V	142.0	14.0	54.00	22.80
17704.20	55.86	---	200	V	142.0	14.0	74.00	32.78

Middle Channel: 2442MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Max Peak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1137.70	---	27.63	200	V	65.0	-11.9	54.00	26.37
1137.70	33.37	---	200	V	65.0	-11.9	74.00	40.63
2927.80	---	30.70	150	H	70.0	-4.7	54.00	23.30
2927.80	40.61	---	150	H	70.0	-4.7	74.00	33.39
4884.00	---	48.43	150	V	210.0	-0.4	54.00	5.57
4884.00	54.43	---	150	V	210.0	-0.4	74.00	19.57
7325.70	---	47.85	200	V	33.0	5.9	54.00	6.15
7325.70	52.43	---	200	V	33.0	5.9	74.00	21.57
11062.30	---	41.72	200	V	278.0	9.8	54.00	12.28
11062.30	52.51	---	200	V	278.0	9.8	74.00	21.49
17581.80	---	48.71	150	H	179.0	14.1	54.00	5.29
17581.80	56.48	---	150	H	179.0	14.1	74.00	17.52

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1256.70	---	24.41	150	V	38.0	-11.3	54.00	29.59
1256.70	33.34	---	150	V	38.0	-11.3	74.00	40.66
4071.90	---	32.68	150	V	213.0	-1.7	54.00	21.32
4071.90	42.61	---	150	V	213.0	-1.7	74.00	31.39
4960.00	---	52.66	150	V	229.0	-0.3	54.00	1.34
4960.00	56.35	---	150	V	229.0	-0.3	74.00	17.65
7440.00	---	44.11	200	V	33.0	6.0	54.00	9.89
7440.00	50.66	---	200	V	33.0	6.0	74.00	23.34
13377.70	---	45.71	200	V	20.0	12.0	54.00	8.29
13377.70	55.17	---	200	V	20.0	12.0	74.00	18.83
17503.60	---	46.53	200	V	96.0	14.3	54.00	7.47
17503.60	56.56	---	200	V	96.0	14.3	74.00	17.44

18GHz-25GHz:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)

Horizontal

Date: 20.NOV.2019 14:01:54

Vertical

Date: 20.NOV.2019 14:33:29

Fundamental Test & Restricted Bands Emissions Test:*(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)*

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Max Peak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)	Degree			
Low Channel: 2403MHz								
2403.00	85.28	---	250.0	H	116.0	2.7	114.00	28.63
2403.00	---	85.05	250.0	H	116.0	2.7	94.00	8.84
2403.00	82.82	---	250.0	V	112.0	2.7	114.00	31.07
2403.00	---	82.73	250.0	V	112.0	2.7	94.00	10.88
2400.00	---	43.99	100.0	H	354.0	2.7	54.00	10.01
2400.00	51.30	---	100.0	H	354.0	2.7	74.00	22.70
Middle Channel: 2442MHz								
2442.00	85.18	---	100.0	H	136.0	3.1	114.00	29.42
2442.00	---	84.61	100.0	H	136.0	3.1	94.00	9.94
2442.00	83.08	---	150.0	V	309.0	3.1	114.00	31.85
2442.00	---	82.32	150.0	V	309.0	3.1	94.00	12.31
High Channel: 2480MHz								
2480.00	84.35	---	150.0	H	314.0	3	114.00	29.81
2480.00	---	83.90	150.0	H	314.0	3	94.00	10.30
2480.00	82.10	---	100.0	V	212.0	3	114.00	32.26
2480.00	---	81.67	100.0	V	212.0	3	94.00	12.58
2483.50	47.95	---	100.0	H	210.0	3	54.00	6.05
2483.50	---	42.26	100.0	H	210.0	3	74.00	31.74

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	20°C~22.4°C
Relative Humidity:	52 %~53 %
ATM Pressure:	101.6 kPa~102.6 kPa


The testing was performed by Winnie Yang from 2019-11-19 to 2019-12-11.

Test Result: Compliant.


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	1.617
Middle	2442	1.323
High	2480	1.323


Low Channel



Middle Channel



High Channel



***** END OF REPORT *****