

Appendix A. Test Data

Duty Cycle						
Band	Frequency (MHz)	On time (ms)	On+off time (ms)	Duty cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
BLE 2M	2402	30.000	30.000	100.000	0.000	0.010
BLR C8	2402	30.000	30.000	100.000	0.000	0.010

Maximum Conducted Output Power Measurement						
Test Mode	Frequency (MHz)	Average Power		Power Limit	RF Power setting in Test Software	Test Software Version
		dBm	W	dBm		
BLE 1M	2402	6.93	0.0049	30.00	8.00	Tera Term
BLE 1M	2440	7.05	0.0051	30.00	8.00	
BLE 1M	2480	6.97	0.0050	30.00	8.00	
BLE 2M	2402	6.93	0.0049	30.00	8.00	
BLE 2M	2440	7.05	0.0051	30.00	8.00	
BLE 2M	2480	6.96	0.0050	30.00	8.00	
BLR C2	2402	6.91	0.0049	30.00	8.00	
BLR C2	2440	7.03	0.0050	30.00	8.00	
BLR C2	2480	6.95	0.0050	30.00	8.00	
BLR C8	2402	6.94	0.0049	30.00	8.00	
BLR C8	2440	7.06	0.0051	30.00	8.00	
BLR C8	2480	6.98	0.0050	30.00	8.00	

Note: The relevant measured result has the offset with cable loss already.

6 dB Bandwidth and 99 % Occupied Bandwidth				
Test mode	Frequency	99 % Occupied Bandwidth	6 dB Bandwidth	6 dB Limit
	(MHz)	(MHz)	(kHz)	(kHz)
BLE 2M	2402	2.060	1222.0000	≥ 500
BLE 2M	2440	2.104	1254.0000	≥ 500
BLE 2M	2480	2.084	1227.0000	≥ 500
BLR C8	2402	1.069	660.7000	≥ 500
BLR C8	2440	1.073	719.8000	≥ 500
BLR C8	2480	1.078	697.2000	≥ 500

Maximum Power Density Measurement			
Test mode	Frequency	Reading	Limit
	(MHz)	(dBm/3 kHz)	(dBm/3 kHz)
BLE 2M	2402	-8.260	≤ 8
BLE 2M	2440	-7.640	≤ 8
BLE 2M	2480	-9.380	≤ 8
BLR C8	2402	1.100	≤ 8
BLR C8	2440	1.360	≤ 8
BLR C8	2480	1.480	≤ 8