

TEST REPORT

EUT Description	WLAN and BT, 2x2 PCIe M.2 1216 SD adapter card
Brand Name	Intel® Wi-Fi AX204
Model Name	AX204D2W
FCC/IC ID	FCC ID: PD9AX204D2 ; IC ID 1000M-AX204D2
Date of Test Start/End	2022-03-14 / 2022-03-30
Features	802.11ax R2, Dual Band, 2x2 Wi-Fi 6 + Bluetooth® 5.2 (see section 5)

Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA
Contact Person	Steven Hackett
Telephone/Fax/ Email	steven.c.hackett@intel.com

Reference Standards	FCC CFR Title 47 Part 15 C RSS-247 issue 2, RSS-Gen issue 5 (see section 1)
---------------------	---

Test Report identification	220225-03.TR04
Revision Control	Rev. 00 This test report revision replaces any previous test report revision (see section 8)

The test results relate only to the samples tested.
Reference to accreditation shall be used only by full reproduction of test report.

Issued by



Digitally signed by Requin
Date: 2022.04.13 15:00:03
+02'00'

Cedric REQUIN
(Test Engineer Lead)

Reviewed by



Digitally signed by
Z.OUACHICHA
Date: 2022.04.13 16:24:09
+02'00'

Zayd OUACHICHA
(Technical Manager)

Intel Corporation S.A.S – WRF Lab
425 rue de Goa – Le Cargo B6 - 06600, Antibes, France
Tel. +33493001400 / Fax +33493001401

Table of Contents

1. Standards, reference documents and applicable test methods	3
2. General conditions, competences and guarantees	3
3. Environmental Conditions	3
4. Test samples	4
5. EUT Features	5
6. Remarks and comments	6
7. Test Verdicts summary	6
7.1. 802.11 B/G/N/AX 2.4GHZ	6
8. Document Revision History	6
Annex A. Test & System Description	7
A.1 MEASUREMENT SYSTEM	7
A.2 TEST EQUIPMENT LIST	10
A.3 MEASUREMENT UNCERTAINTY EVALUATION	12
Annex B. Test Results DTS	13
B.1 TEST CONDITIONS	13
B.2 TEST RESULTS TABLES	14
B.2.1 6dB & 99% Bandwidth	14
B.2.2 Maximum Output Power and antenna gain	17
B.2.3 Power Spectral Density	21
B.2.4 Out-of-band emission (conducted)	25
B.2.5 Radiated spurious emission	26
B.2.6 Out of band emissions - band-edge (conducted)	45
Annex C. Photographs	73
C.1 TEST SETUP	73
C.2 TEST SAMPLE	75

1. Standards, reference documents and applicable test methods

FCC	1. FCC Title 47 CFR part 15 - Subpart C – §15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz. 2019-10-01 Edition 2. FCC Title 47 CFR part 15 - Subpart C – §15.209 Radiated emission limits; general requirements. 2019-10-01 Edition 3. FCC OET KDB 558074 D01 v05r02 - Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules. 4. FCC OET KDB 662911 D01 v02r01 - Emissions Testing of Transmitters with Multiple Outputs in the Same Band. 5. ANSI C63.10-2013 - American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
ISED	1. RSS-247 Issue 2 - Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices. 2. RSS-Gen Issue 5 A1- General Requirements for Compliance of Radio Apparatus. 3. FCC OET KDB 558074 D01 v05r02 - Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules. 4. FCC OET KDB 662911 D01 v02r01 - Emissions Testing of Transmitters with Multiple Outputs in the Same Band. 5. ANSI C63.10-2013 - American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

2. General conditions, competences and guarantees

- ✓ Tests performed under FCC standards identified in section 1 are covered by A2LA accreditation.
- ✓ Tests performed under ISED standards identified in section 1 are covered by Cofrac accreditation.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 laboratory accredited by the American Association for Laboratory Accreditation (A2LA) with the certificate number 3478.01.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an Accredited Test Firm recognized by the FCC, with Designation Number FR0011.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 testing laboratory accredited by the French Committee for Accreditation (Cofrac) with the certificate number 1-6736.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is a Registered Test Site listed by ISED, with ISED #1000Y.
- ✓ Intel WRF Lab declines any responsibility with respect to the identified information provided by the customer and that may affect the validity of results.
- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.

3. Environmental Conditions

- ✓ At the site where the measurements were performed the following limits were not exceeded during the tests:

Temperature	23.0°C ± 1.7°C
Humidity	31.8% ± 13.1%

4. Test samples

Sample	Control #	Description	Model	Serial #	Date of receipt	Note
#01	220225-03.S01	WiFi Module	AX204D2W	C8CB9E88C32C	2022-03-14	Used for 30MHz-1GHz and 18-26GHz Spurious Emissions tests
	200611-01.S09	Adaptor	PowerBy SNJ A4	-	2020-11-30	
	180000-01.S02	Socket	Adapter 1216SD to M.2		2017-08-09	
	220225-03.S07	Microwave Absorber	Eccosorb BSR-1	-	2022-03-14	
	200611-03.S31	Extender	ADEXELEC	-	2020-08-19	
	200615-05.S09	Laptop	Latitude 5401	GVGLK13	2020-06-12	
	210611-02.S13	Antenna	SkyCross	-	2021-07-02	
	210611-02.S14	Antenna	SkyCross	-	2021-07-02	
#02	220225-03.S02	WiFi Module	AX204D2W	C8CB9E88C2EB	2022-03-14	Used for 1GHz-18GHz Spurious Emission tests
	210611-02.S15	Adaptor	PowerBy SNJ A4	-	2021-07-02	
	180001-01.S21	Socket	Socket WsP/ThP /GfP/HrP	-	2021-06-07	
	220225-03.S07	Microwave Absorber	Eccosorb BSR-1	-	2022-03-14	
	220225-03.S23	Extender	ADEXELEC	-	2022-03-14	
	170000-01.S13	Laptop	Latitude E5470	FT6LMC2	2017-05-30	
	210611-02.S11	Antenna	SkyCross	-	2021-07-02	
	210611-02.S12	Antenna	SkyCross	-	2021-07-02	
#3	220225-03.S22	WiFi Module	AX204D2W	C8CB9E88C2D7	2022-03-15	RF Conducted
	180000-01.S01	Adapter 1216SD to M.2	Adapter M2	N/A	2017-08-09	
	170000-01.S18	Laptop	Latitude E5470	4L1BVF2	2019-05-23	
	200611-01.S13	Extender	XVT EXTENDER SNJ A4	-	2020-11-30	

5. EUT Features

The herein information is provided by the customer

Brand Name	Intel® Wi-Fi AX204		
Model Name	AX204D2W		
Software Version	DRTU_01188_99.0.69C		
Driver Version	WiFi: 99.0.70.4		
Prototype / Production	Production		
Supported Radios	802.11b/g/n/ax 2.4GHz (2400.0 – 2483.5 MHz) 802.11a/n/ac/ax 5.2GHz (5150.0 – 5350.0 MHz) 5.6GHz (5470.0 – 5725.0 MHz) 5.8GHz (5725.0 – 5895.0 MHz) Bluetooth 5.2 2.4GHz (2400.0 – 2483.5 MHz)		
Antenna Information	Transmitter	Chain 1 (A) / Aux	Chain 2 (B) / Main
	Manufacturer	SkyCross	Skycross
	Antenna type	PIFA antenna	PIFA antenna
	Part number	N/A	N/A
	Declared antenna gain (dBi)	+3.24	+3.24

6. Remarks and comments

1. No deviations were made from the test methods listed in section 1 of this report
2. Only the worst-case plot per 802.11 mode and test case measurements have been reported excepted for band edge measurements where all plots are reported

7. Test Verdicts summary

The statement of conformity to applicable standards in the table below are based on the measured values, without taking into account the measurement uncertainties.

7.1. 802.11 b/g/n/ax 2.4GHz

FCC part	RSS part	Test name	Verdict
15.247 (a) (2)	RSS-247 Clause 5.2 (a)	6dB Bandwidth	P
15.247 (b) (3)	RSS-247 Clause 5.4 (d)	Maximum output power and E.I.R.P	P
15.247 (e)	RSS-247 Clause 5.2 (b)	Power spectral density	P
15.247 (d) 15.209	RSS-247 Clause 5.5 RSS-Gen A1 Clause 8.9	Out-of-band Emissions (conducted)	P
15.247 (d) 15.209	RSS-247 Clause 5.5 RSS-Gen A1 Clause 8.9	Spurious Emissions (radiated)	P

P: Pass

F: Fail

NM: Not Measured

NA: Not Applicable

8. Document Revision History



Revision #	Modified by	Revision Details
Rev. 00	N.Bui. V.Kaculini	First Issue

Annex A. Test & System Description


A.1 Measurement System

Measurements were performed using the following setups, made in accordance to the general provisions of FCC OET KDB 558074 D01 DTS Meas Guidance.


The DUT was installed in a test fixture and this test fixture is connected to a laptop computer and AC/DC power adapter. The laptop computer was used to configure the EUT to continuously transmit at a specified output power using all different modes and modulation schemes, using the Intel proprietary tool DRTU.




Radiated Setup 1 GHz – 9.5 GHz



Radiated Setup 9.5 GHz - 18 GHz



Radiated Setup 18 GHz – 26 GHz



Sample Calculation

The spurious received voltage $V(\text{dB}\mu\text{V})$ in the spectrum Analyzer is converted to Electric field strength using the transducer factor F corresponding to the Rx path Loss:

$$F(\text{dB/m}) = \text{Rx Antenna Factor (dB/m)} + \text{Cable losses (dB)} - \text{Amplifiers Gain (dBi)}$$

$$E(\text{dB}\mu\text{V}) = V(\text{dB}\mu\text{V}) + F(\text{dB/m})$$

For field strength measurements made at other than the distance at which the applicable limit is specified, the field strength of the emission at the distance specified by the limit is deduced as follows:

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \cdot \log(D_{\text{Meas}}/D_{\text{SpecLimit}})$$

where

$E_{\text{SpecLimit}}$ is the field strength of the emission at the distance specified by the limit, in $\text{dB}\mu\text{V/m}$

E_{Meas} is the field strength of the emission at the measurement distance, in $\text{dB}\mu\text{V/m}$

D_{Meas} is the measurement distance, in m

$D_{\text{SpecLimit}}$ is the distance specified by the limit, in m

A.2 Test Equipment List

Conducted setup

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
134-000	Spectrum Analyzer	FSV30	103308	Rohde & Schwarz	2021-04-21	2023-04-21
018-002	Peak Power Meter	MA24406A	11138	ANRITSU	2021-11-24	2023-11-24
370-000	RF cable 50cm	PE360-50	N/A	PASTERNAK	2022-02-04	2022-08-04
382-000	10dB Attenuator + MH4	N/A	N/A	PASTERNAK	2022-02-04	2022-08-04
349-000	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-D4F8C3	AVTECH	2021-07-30	2023-07-30
413-000	Measurement SW v1.5.4.2	Octopi	N/A	Step AT	N/A	N/A

Radiated Setup #1

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
006-000	Anechoic chamber	FACT 3	5720	ETS Lindgren	2022-01-21	2024-01-21
006-001	Turntable	-	-	ETS Lindgren	N/A	N/A
006-008	Measurement Software v11.30.00	EMC32	100623	Rohde & Schwarz	N/A	N/A
147-000	Spectrum analyzer	FSW43	101847	Rohde & Schwarz	2020-11-02	2022-11-02
006-002	Switch & Positioning	EMC center	00159757	ETS Lindgren	N/A	N/A
006-011	Boresight antenna mast	BAM4.0-P	P/278/2890.01	Maturo	N/A	N/A
006-019	Biconical antenna 30 MHz – 1 GHz	UBAA9115 + BBVU9135 + DGA9552N	0286 + CH 9044	Schwarzbeck	2022-02-01	2024-02-01
006-020	Double Ridged Horn Antenna 1 GHz – 18 GHz	3117	00157734	ETS Lindgren	2021-08-05	2023-08-05
057-000	Horn Antenna 3117 + Amplifier + HPF9.5	3117	00167062+00169546	ETS-Lindgren	2020-06-15	2022-06-15
007-008	Double Horn Ridged antenna + Amplifier	3116C-PA	00169308bis + 00196308	ETS-Lindgren	2021-08-05	2023-08-05
006-059	RF Cable 7.0m	R286304174	20.46.369	Radiall	2022-03-04	2022-09-04
006-051	RF Cable 1.0m	CBL-1.5M-SMSM+	202879	Mini-Circuits	2022-02-02	2022-08-02
006-030	RF Cable 1.2m	UFA147A-0-0480-200200	MFR 64639223720-003	Micro-coax	2022-02-02	2022-08-02
006-034	RF Cable 1.0m	UFA147A	-	Utilflex	2022-02-02	2022-08-02
006-036	RF Cable 1.0m	UFB311A-0-0590-50U50U	MFR 64639 223230-001	Micro-coax	2022-02-02	2022-08-02
006-038	RF Cable 7.0m	R286304009	-	Radiall	2022-02-02	2022-08-02
006-039	RF Cable 2.5m	0500990992500KE	19.23.395	Radiall	2022-02-02	2022-08-02
365-000	Temperature & Humidity logger	RA12E-TH1-RAS	00-80-A3-E1-6E-55	Avtech	2021-03-08	2023-03-08

N/A: Not Applicable

Radiated Setup #2

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
007-000	Anechoic chamber	RFD-FA-100	5996	ETS Lindgren	2021-09-14	2023-09-14
007-002	Turntable	-	-	ETS Lindgren	N/A	N/A
007-003	Antenna Tower	2171B-3.0M	00150123	ETS Lindgren	N/A	N/A
007-006	Switch & Positioner	EMCenter	00151232	ETS Lindgren	N/A	N/A
007-005	Measurement SW, V11.20.00	EMC32	100401	Rohde & Schwarz	N/A	N/A
127-000	Spectrum Analyzer	FSV40	101358	Rohde & Schwarz	2021-01-15	2023-01-15
007-007*	Double Ridge Horn (1-18GHz)	3117	00152266	ETS Lindgren	2020-03-18	2022-03-18
066-000	Double Ridge Horn (1-18GHz)	3117	00103954	ETS Lindgren	2020-06-26	2022-06-26
057-000	Horn Antenna 3117 + Amplifier + HPF9.5	3117	00167062+00169546	ETS-Lindgren	2020-06-15	2022-06-15
007-008	Double Horn Ridged antenna+ Amplifier	3116C-PA	00169308bis 00196308	ETS-Lindgren	2021-08-05	2023-08-05
007-022	RF Cable 1-18GHz, 1.5m	0501050991200GX	19.23.493	Radiall	2022-02-03	2022-08-03
007-020	RF Cable 1-18GHz, 1.2 m	2301761761200PJ	12.22.1104	Radiall	2022-02-03	2022-08-03
007-011	RF Cable 1-18GHz – 6.5m	140-8500-11-51	001	Spectrum	2022-02-03	2022-08-03
007-015	RF Cable 1GHz-18GHz 1.5m	-	-	Spirent	2022-02-03	2022-08-03
007-014	RF Cable 18-40 GHz 6m	R286304009	1747364	Radiall	2022-02-03	2022-08-03
007-023	RF Cable 1m DC-40GHz	PE360-100CM	-	Pasternack	2022-02-03	2022-08-03
007-018	RF Cable 1-9.5GHz 1.2m	0500990991200KE	-	Radiall	2022-02-03	2022-08-03
325-000	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-B9B7C6	Avtech	2022-01-17	2024-01-17

*Item not used during out of cal period

N/A: Not Applicable

Shared Radiated Equipment

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
412-000	DRTU Power finder V2.0	-	-	Intel	NA	NA
139-000	Power Sensor	NRP-Z81	104383	Rohde & Schwarz	2021-04-07	2023-04-07
140-000	Power Sensor	NRP-Z81	104382	Rohde & Schwarz	2020-04-08	2022-04-08

A.3 Measurement Uncertainty Evaluation

The system uncertainty evaluation is shown in the table below with a coverage factor of $k = 2$ to indicate a 95% level of confidence:

Measurement type	Uncertainty	Unit
Timing	± 0.12	%
Power Spectral density	± 1.47	dB
Occupied bandwidth	± 2.07	%
Conducted Power	± 1.03	dB
Conducted Out of band Emission <7 GHz	± 1.67	dB
Radiated tests <1GHz	± 6.07	dB
Radiated tests 1GHz – 26.5 GHz	± 5.92	dB

Annex B. Test Results DTS

The herein test results were performed by:

Test case measurement	Test Peronnel
6dB Bandwidth	V.Kaculini
Maximum output power and E.I.R.P	V.Kaculini
Power spectral density	V.Kaculini
Out-of-band Emissions (conducted)	V.Kaculini
Spurious Emissions (radiated)	K.Khatib, R.Simonini, N.Bui

B.1 Test Conditions

For 802.11b/g modes the EUT can transmit at both CHAIN A and CHAIN B RF outputs individually, but not simultaneously.

For 802.11n20 & 802.11ax20 (20 MHz channel bandwidth), 802.11n40 & 802.11ax40 (40MHz channel bandwidth) modes the EUT can transmit at both CHAIN A and CHAIN B RF outputs individually, and also simultaneously.

The following data rates were selected based on preliminary testing that identified those rates as the worst cases for output power and spurious levels at the band edges:

Transmission	Mode	Bandwidth (MHz)	Worst Case Data Rate
SISO	802.11b	20	1Mbps
	802.11g	20	6Mbps
	802.11n	20	HT0
		40	HT0
	802.11ax	20	HE0
		40	HE0
MIMO	802.11n	20/40	HT8
	802.11ax	20/40	HE0

B.2 Test Results Tables

B.2.1 6dB & 99% Bandwidth

Test limits

FCC part	RSS part	Limits
15.247 (a) (2)	RSS-247 Clause 5.2 (a)	Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test procedure

The conducted setup shown in section *Test & System Description* was used to measure the 6dB & 99% Bandwidth. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Results tables

Mode	Rate	Antenna	Channel	Freq [MHz]	6dB BW [MHz]	99% BW [MHz]
802.11b	1Mbps	SISO A	1	2412	9.08	13.39
			7	2442	9.04	13.39
			11	2462	8.06	13.41
			12	2467	8.54	13.41
			13	2472	9.06	13.37
		SISO B	1	2412	8.57	13.37
			7	2442	9.05	13.34
			11	2462	9.01	13.38
			12	2467	9.02	13.33
			13	2472	9.02	13.43
802.11g	6Mbps	SISO A	1	2412	15.46	16.67
			7	2442	14.94	16.67
			11	2462	15.04	16.67
			12	2467	15.11	16.66
			13	2472	16.36	16.41
		SISO B	1	2412	15.06	16.67
			7	2442	14.38	16.66
			11	2462	15.11	16.65
			12	2467	15.72	16.65
			13	2472	16.35	16.42
802.11n20	HT0	SISO A	1	2412	14.43	17.75
			7	2442	15.30	17.74
			11	2462	14.46	17.74
			12	2467	15.39	17.75
			13	2472	17.61	17.59
		SISO B	1	2412	14.42	17.75
			7	2442	15.04	17.76
			11	2462	15.30	17.72
			12	2467	13.22	17.75
			13	2472	17.59	17.58
	HT8	MIMO A	1	2412	16.23	17.74
			7	2442	15.08	17.76
			11	2462	15.10	17.75
			12	2467	15.09	17.76
		MIMO B	1	2412	15.92	17.74
			7	2442	15.31	17.72
			11	2462	15.62	17.72
			12	2467	15.30	17.75
802.11n40	HT0	SISO A	3	2422	30.90	36.12
			7	2442	31.10	36.11
			9	2452	34.21	36.11
			10	2457	32.66	36.04
			11	2462	36.37	36.25
		SISO B	3	2422	34.72	36.11
			7	2442	31.36	36.09
			9	2452	30.05	36.11
			10	2457	35.09	36.04
			11	2462	36.37	36.25
	HT8	MIMO A	3	2422	27.92	36.13
			7	2442	33.81	36.13
			9	2452	35.10	36.12
			10	2457	35.10	36.04
		MIMO B	11	2462	36.35	36.25
			3	2422	34.46	36.05
			7	2442	35.33	36.01
			9	2452	35.07	36.04
			10	2457	34.18	35.93
			11	2462	36.38	36.19

Max Value

Mode	Rate	Antenna	Channel	Freq [MHz]	RU config.	6dB BW [MHz]	99% BW [MHz]
802.11ax20	HE0	SISO A	1	2412	Full	15.08	18.89
					26/0	2.05	18.53
					52/37	17.02	18.22
					106/53	17.02	18.10
			7	2442	Full	16.58	18.89
					Full	15.09	18.89
					Full	18.33	18.90
			11	2462	Full	18.51	18.73
					26/8	1.98	18.20
					52/40	16.84	18.14
					106/54	16.99	17.81
		SISO B	1	2412	Full	15.02	18.89
					26/0	2.08	18.51
					52/37	16.94	18.37
					106/53	17.10	18.23
			7	2442	Full	15.96	18.89
					Full	15.90	18.87
					Full	16.22	18.89
			11	2462	Full	18.50	18.74
					26/8	2.00	18.25
					52/40	16.87	18.15
					106/54	16.87	18.02
		MIMO A	1	2412	Full	15.16	18.89
					26/0	1.99	18.53
					52/37	16.94	18.35
					106/53	14.62	17.65
			7	2442	Full	16.59	18.90
					Full	16.49	18.91
					Full	16.52	18.87
			11	2462	Full	18.42	18.74
					26/8	1.97	18.19
					52/40	16.90	17.61
					106/54	16.94	17.44
		MIMO B	1	2412	Full	16.08	18.89
					26/0	12.00	18.57
					52/37	17.06	18.25
					106/53	13.58	17.65
			7	2442	Full	15.20	18.89
					Full	16.38	18.89
					Full	15.02	18.88
			11	2462	Full	18.30	18.75
					26/8	1.97	18.23
					52/40	16.87	17.95
					106/54	16.94	17.77
802.11ax40	HE0	SISO A	3	2422	Full	35.12	37.53
					242/61	17.60	18.83
			7	2442	Full	35.90	37.56
					Full	36.53	37.56
			9	2452	Full	36.91	37.52
					Full	37.70	37.60
		SISO B	10	2457	Full	37.62	37.60
					242/62	18.62	18.65
			11	2462	Full	35.47	37.52
					242/61	16.67	18.85
		MIMO A	3	2422	Full	35.50	37.52
					Full	35.07	37.53
			7	2442	Full	35.63	37.53
					Full	37.63	37.60
			9	2452	Full	37.63	37.60
					242/62	18.43	18.64
		MIMO B	10	2457	Full	36.06	37.56
					242/61	17.12	18.84
			11	2462	Full	35.63	37.53
					Full	36.06	37.53
		MIMO B	3	2422	Full	36.48	37.48
					Full	37.81	37.60
			7	2442	242/62	18.54	18.64
					Full	35.54	37.55
			9	2452	242/61	15.65	18.83
					Full	35.14	37.52
			10	2457	Full	35.07	37.55
					Full	35.14	37.45
			11	2462	Full	37.39	37.59
					242/62	18.70	18.67

Max Value

B.2.2 Maximum Output Power and antenna gain

Test limits

	Limits
FCC Part 15.247 (b) (3)	(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.
RSS-247 Clause 5.4 (d)	For DTSSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e). As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

Test procedure

The Maximum Peak Conducted Output Power was measured using a broadband peak power meter methods for 20MHz and 40MHz channel bandwidth as authorized in chapter 2.0 "*Power limits, definitions and device configuration*" of FCC OET KDB 558074 D01

For MIMO mode, according to the measure-and-sum approach defined in FCC OET KDB 662911 D01 - Guidance for Emission Testing of Transmitters with Multiple Outputs in the Same Band, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically in linear power units to determine the total emission level from the device.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

The conducted setup shown in section *Test & System Description* was used to measure the maximum conducted output power. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Results tables:

Maximum peak power are shown in table below with min and max values highlighted. Maximum average output power are shown for indicative purpose only

Mode	Rate	# Ch	Freq [MHz]	Ant	Meas Peak Cond.Power [dBm]	EIRP [dBm]	EIRP [mW]	Peak Cond.Power [mW]	Meas. Avg Cond.Power [dBm]	Max. Avg Cond.Power* [dBm]	EIRP [mW]	Avg Cond.Power [mW]
802.11b	1Mbps	1	2412	SISO A	23.96	27.20	524.81	248.89	20.77	20.77	251.77	119.40
				SISO B	24.05	27.29	535.80	254.10	20.83	20.83	255.27	121.06
		7	2442	SISO A	23.92	27.16	520.00	246.60	20.72	20.72	248.89	118.03
				SISO B	23.97	27.21	526.02	249.46	20.73	20.73	249.46	118.30
		11	2462	SISO A	24.16	27.40	549.54	260.62	20.91	20.91	260.02	123.31
				SISO B	23.90	27.14	517.61	245.47	20.65	20.65	244.91	116.14
		12	2467	SISO A	24.00	27.24	529.66	251.19	20.76	20.76	251.19	119.12
				SISO B	24.05	27.29	535.80	254.10	20.78	20.78	252.35	119.67
		13	2472	SISO A	22.16	25.40	346.74	164.44	18.88	18.88	162.93	77.27
				SISO B	22.12	25.36	343.56	162.93	18.85	18.85	161.81	76.74
802.11g	6Mbps	1	2412	SISO A	27.79	31.03	1267.65	601.17	19.43	19.52	188.89	89.58
				SISO B	27.79	31.03	1267.65	601.17	19.42	19.51	188.46	89.38
		7	2442	SISO A	29.14	32.38	1729.82	820.35	20.80	20.89	258.95	122.81
				SISO B	29.14	32.38	1729.82	820.35	20.73	20.82	254.81	120.84
		11	2462	SISO A	28.67	31.91	1552.39	736.21	20.24	20.33	227.62	107.95
				SISO B	29.12	32.36	1721.87	816.58	20.73	20.82	254.81	120.84
		12	2467	SISO A	26.76	30.00	1000.00	474.24	18.39	18.48	148.67	70.50
				SISO B	27.17	30.41	1099.01	521.19	18.75	18.84	161.52	76.60
		13	2472	SISO A	21.23	24.47	279.90	132.74	13.08	13.17	43.77	20.76
				SISO B	22.94	26.18	414.95	196.79	14.76	14.85	64.45	30.56
802.11n20	HT0	1	2412	SISO A	27.15	30.39	1093.96	518.80	18.85	18.85	161.81	76.74
				SISO B	26.91	30.15	1035.14	490.91	18.57	18.57	151.71	71.94
		7	2442	SISO A	29.31	32.55	1798.87	853.10	20.98	20.98	264.24	125.31
				SISO B	29.11	32.35	1717.91	814.70	20.73	20.73	249.46	118.30
		11	2462	SISO A	27.34	30.58	1142.88	542.00	18.97	18.97	166.34	78.89
				SISO B	28.03	31.27	1339.68	635.33	19.62	19.62	193.20	91.62
		12	2467	SISO A	26.69	29.93	984.01	466.66	18.32	18.32	143.22	67.92
				SISO B	26.67	29.91	979.49	464.52	18.26	18.26	141.25	66.99
		13	2472	SISO A	21.46	24.70	295.12	139.96	13.34	13.34	45.50	21.58
				SISO B	22.95	26.19	415.91	197.24	14.80	14.80	63.68	30.20
	HT8	1	2412	MIMO A	25.09	28.33	680.77	322.85	16.77	16.77	100.23	47.53
				MIMO B	25.54	28.78	755.09	358.10	16.89	16.89	103.04	48.87
				Combined A+B	28.33	31.57	1435.86	680.95	19.84	19.84	203.27	96.40
				MIMO A	24.10	27.34	542.00	257.04	20.71	20.71	248.31	117.76
		7	2442	MIMO B	24.88	28.12	648.63	307.61	20.69	20.69	247.17	117.22
				Combined A+B	27.52	30.76	1190.64	564.65	23.71	23.71	495.49	234.98
		11	2462	MIMO A	25.52	28.76	751.62	356.45	17.15	17.15	109.40	51.88
				MIMO B	26.90	30.14	1032.76	489.78	18.11	18.11	136.46	64.71
				Combined A+B	29.27	32.51	1784.38	846.23	20.67	20.67	245.85	116.59
		12	2467	MIMO A	23.37	26.61	458.14	217.27	14.99	14.99	66.53	31.55
				MIMO B	23.53	26.77	475.34	225.42	14.83	14.83	64.12	30.41
				Combined A+B	26.46	29.70	933.48	442.69	17.92	17.92	130.65	61.96
		13	2472	MIMO A	20.86	24.10	257.04	121.90	12.73	12.73	39.54	18.75
				MIMO B	21.30	24.54	284.45	134.90	12.70	12.70	39.26	18.62
				Combined A+B	24.10	27.34	541.49	256.80	15.73	15.73	78.80	37.37
802.11n40	HT0	3	2422	SISO A	27.79	31.03	1267.65	601.17	19.39	19.39	183.23	86.90
				SISO B	28.04	31.28	1342.76	636.80	19.66	19.66	194.98	92.47
		7	2442	SISO A	28.49	31.73	1489.36	706.32	20.09	20.09	215.28	102.09
				SISO B	29.40	32.64	1836.54	870.96	20.93	20.93	261.22	123.88
		9	2452	SISO A	27.72	30.96	1247.38	591.56	19.35	19.35	181.55	86.10
				SISO B	27.90	31.14	1300.17	616.60	19.45	19.45	185.78	88.10
		10	2457	SISO A	23.34	26.58	454.99	215.77	15.12	15.12	68.55	32.51
				SISO B	23.19	26.43	439.54	208.45	14.97	14.97	66.22	31.41
		11	2462	SISO A	22.29	25.53	357.27	169.43	14.11	14.11	54.33	25.76
				SISO B	22.99	26.23	419.76	199.07	14.83	14.83	64.12	30.41
	HT8	3	2422	MIMO A	26.74	29.98	995.41	472.06	18.31	18.31	142.89	67.76
				MIMO B	26.88	30.12	1028.02	487.53	18.06	18.06	134.90	63.97
				Combined A+B	29.82	33.06	2023.42	959.59	21.20	21.20	277.79	131.74
				MIMO A	23.74	26.98	498.88	236.59	18.48	18.48	148.59	70.47
		7	2442	MIMO B	24.23	27.47	558.47	264.85	18.65	18.65	154.53	73.28
				Combined A+B	27.00	30.24	1057.35	501.44	21.58	21.58	303.12	143.75
		9	2452	MIMO A	26.41	29.65	922.57	437.52	18.00	18.00	133.05	63.10
				MIMO B	26.72	29.96	990.83	469.89	17.93	17.93	130.92	62.09
				Combined A+B	29.58	32.82	1913.40	907.42	20.98	20.98	263.96	125.18
		10	2457	MIMO A	23.28	26.52	448.75	212.81	15.06	15.06	67.61	32.06
				MIMO B	23.41	26.65	462.38	219.28	14.77	14.77	63.24	29.99
				Combined A+B	26.36	29.60	911.13	432.09	17.93	17.93	130.85	62.05
		11	2462	MIMO A	21.00	24.24	265.46	125.89	12.81	12.81	40.27	19.10
				MIMO B	21.42	24.66	292.42	138.68	12.82	12.82	40.36	19.14
				Combined A+B	24.23	27.47	557.88	264.57	15.83	15.83	80.64	38.24

* Duty cycle compensated

Mode	Rate	# Ch	Freq [MHz]	Antenna	RU config	Meas Peak Cond.Power [dBm]	EIRP [dBm]	EIRP [mW]	Peak Cond.Power [mW]	Meas. Avg Cond.Power [dBm]	Max. Avg Cond.Power* [dBm]	EIRP [mW]	Avg Cond.Power [mW]
802.11ax20	HEO	1	2412	SISO A	Full	26.78	30.02	1004.62	476.43	17.70	17.70	124.17	58.88
					26/0	28.68	31.92	1555.97	737.90	19.62	19.62	193.20	91.62
					52/37	29.77	33.01	1999.86	948.42	20.17	20.17	219.28	103.99
					106/53	29.22	32.46	1761.98	835.60	19.78	19.78	200.45	95.06
				SISO B	Full	27.07	30.31	1073.99	509.33	17.95	17.95	131.52	62.37
					26/0	28.38	31.62	1452.11	688.65	19.30	19.30	179.47	85.11
					52/37	29.34	32.58	1811.34	859.01	19.82	19.82	202.30	95.94
					106/53	29.36	32.60	1819.70	862.98	20.00	20.00	210.86	100.00
				MIMO A	Full	25.30	28.54	714.50	338.84	16.17	16.17	87.30	41.40
					26/0	23.24	26.48	444.63	210.86	18.89	18.89	163.31	77.45
					52/37	23.42	26.66	463.45	219.79	18.91	18.91	164.06	77.80
					106/53	23.11	26.35	431.52	204.64	18.77	18.77	158.85	75.34
				MIMO B	Full	25.91	29.15	822.24	389.94	16.69	16.69	98.40	46.67
					26/0	23.86	27.10	512.86	243.22	18.86	18.86	162.18	76.91
					52/37	23.58	26.82	480.84	228.03	19.14	19.14	172.98	82.04
					106/53	23.17	26.41	437.52	207.49	18.49	18.49	148.94	70.63
				Combined A+B	Full	28.63	31.87	1536.74	728.79	19.45	19.45	185.70	88.07
					26/0	26.57	29.81	957.49	454.08	21.89	21.89	325.49	154.36
					52/37	26.51	29.75	944.29	447.82	22.04	22.04	337.04	159.84
					106/53	26.15	29.39	869.04	412.14	21.64	21.64	307.79	145.97
		7	2442	SISO A	Full	24.21	27.45	555.90	263.63	20.88	20.88	258.23	122.46
				SISO B	Full	24.79	28.03	635.33	301.30	20.83	20.83	255.27	121.06
				MIMO A	Full	24.12	27.36	544.50	258.23	20.58	20.58	240.99	114.29
				MIMO B	Full	24.87	28.11	647.14	306.90	20.74	20.74	250.03	118.58
				Combined A+B	Full	27.52	30.76	1191.65	565.13	23.67	23.67	491.03	232.86
		11	2462	SISO A	Full	28.54	31.78	1506.61	714.50	19.40	19.40	183.65	87.10
				SISO B	Full	28.72	31.96	1570.36	744.73	19.53	19.53	189.23	89.74
				MIMO A	Full	23.00	26.24	420.73	199.53	18.07	18.07	135.21	64.12
				MIMO B	Full	23.08	26.32	428.55	203.24	17.92	17.92	130.62	61.94
				Combined A+B	Full	26.05	29.29	849.28	402.76	21.01	21.01	265.82	126.07
		12	2467	SISO A	Full	27.55	30.79	1199.50	568.85	18.37	18.37	144.88	68.71
				SISO B	Full	27.48	30.72	1180.32	559.76	18.33	18.33	143.55	68.08
				MIMO A	Full	24.96	28.20	660.69	313.33	15.80	15.80	80.17	38.02
				MIMO B	Full	25.01	28.25	668.34	316.96	15.71	15.71	78.52	37.24
				Combined A+B	Full	28.00	31.24	1329.04	630.29	18.77	18.77	158.69	75.26
		13	2472	SISO A	Full	23.29	26.53	449.78	213.30	13.72	13.72	49.66	23.55
					26/8	20.43	23.67	232.81	110.41	9.22	9.22	17.62	8.36
					52/40	20.31	23.55	226.46	107.40	9.21	9.21	17.58	8.34
					106/54	19.61	22.85	192.75	91.41	9.24	9.24	17.70	8.39
				SISO B	Full	24.66	27.90	616.60	292.42	15.19	15.19	69.66	33.04
					26/8	20.33	23.57	227.51	107.89	9.03	9.03	16.87	8.00
					52/40	20.19	23.43	220.29	104.47	9.05	9.05	16.94	8.04
					106/54	19.94	23.18	207.97	98.63	9.55	9.55	19.01	9.02
				MIMO A	Full	22.65	25.89	388.15	184.08	13.14	13.14	43.45	20.61
					26/8	18.80	22.04	159.96	75.86	7.73	7.73	12.50	5.93
					52/40	18.71	21.95	156.68	74.30	8.03	8.03	13.40	6.35
					106/54	17.99	21.23	132.74	62.95	7.76	7.76	12.59	5.97
				MIMO B	Full	22.66	25.90	389.05	184.50	13.02	13.02	42.27	20.04
					26/8	18.87	22.11	162.55	77.09	7.73	7.73	12.50	5.93
					52/40	18.67	21.91	155.24	73.62	7.71	7.71	12.45	5.90
					106/54	17.95	21.19	131.52	62.37	7.75	7.75	12.56	5.96
				Combined A+B	Full	25.67	28.91	777.20	368.58	16.09	16.09	85.72	40.65
					26/8	21.85	25.09	322.51	152.95	10.74	10.74	25.01	11.86
					52/40	21.70	24.94	311.91	147.92	10.88	10.88	25.84	12.26
					106/54	20.98	24.22	264.26	125.32	10.77	10.77	25.15	11.93

* Duty cycle compensated

Mode	Rate	# Ch	Freq [MHz]	Antenna	RU config	Meas Peak Cond.P ower [dBm]	EIRP [dBm]	EIRP [mW]	Peak Cond.Power [mW]	Meas. Avg Cond.Po wer [dBm]	Max. Avg Cond.Po wer* [dBm]	EIRP [mW]	Avg Cond.Power [mW]
802.11ax40	HEO	3	2422	SISO A	Full	28.62	31.86	1534.62	727.78	19.29	19.29	179.06	84.92
					242/61	27.06	30.30	1071.52	508.16	18.03	18.03	133.97	63.53
				SISO B	Full	28.78	32.02	1592.21	755.09	19.43	19.43	184.93	87.70
					242/61	27.03	30.27	1064.14	504.66	18.00	18.00	133.05	63.10
				MIMO A	Full	23.43	26.67	464.52	220.29	17.68	17.68	123.59	58.61
					242/61	25.67	28.91	778.04	368.98	16.59	16.59	96.16	45.60
				MIMO B	Full	23.68	26.92	492.04	233.35	18.17	18.17	138.36	65.61
					242/61	25.94	29.18	827.94	392.64	16.80	16.80	100.93	47.86
				Combined A+B	Full	26.57	29.81	956.55	453.64	20.94	20.94	261.95	124.23
					242/61	28.82	32.06	1605.98	761.62	19.71	19.71	197.09	93.47
		7	2442	SISO A	Full	29.29	32.53	1790.61	849.18	20.05	20.05	213.30	101.16
				SISO B	Full	29.79	33.03	2009.09	952.80	20.41	20.41	231.74	109.90
				MIMO A	Full	23.87	27.11	514.04	243.78	18.64	18.64	154.17	73.11
				MIMO B	Full	24.40	27.64	580.76	275.42	18.73	18.73	157.40	74.64
				Combined A+B	Full	27.15	30.39	1094.81	519.20	21.70	21.70	311.57	147.76
		9	2452	SISO A	Full	28.61	31.85	1531.09	726.11	19.28	19.28	178.65	84.72
				SISO B	Full	28.66	31.90	1548.82	734.51	19.34	19.34	181.13	85.90
				MIMO A	Full	23.70	26.94	494.31	234.42	18.13	18.13	137.09	65.01
				MIMO B	Full	23.63	26.87	486.41	230.67	17.71	17.71	124.45	59.02
				Combined A+B	Full	26.68	29.92	980.72	465.10	20.94	20.94	261.54	124.03
		10	2457	SISO A	Full	24.42	27.66	583.45	276.69	15.13	15.13	68.71	32.58
				SISO B	Full	24.30	27.54	567.54	269.15	14.94	14.94	65.77	31.19
				MIMO A	Full	24.18	27.42	552.08	261.82	14.76	14.76	63.10	29.92
				MIMO B	Full	24.28	27.52	564.94	267.92	14.75	14.75	62.95	29.85
				Combined A+B	Full	27.24	30.48	1117.01	529.74	17.77	17.77	126.05	59.78
		11	2462	SISO A	Full	23.49	26.73	470.98	223.36	14.12	14.12	54.45	25.82
					242/62	18.67	21.91	155.24	73.62	9.33	9.33	18.07	8.57
				SISO B	Full	24.31	27.55	568.85	269.77	14.91	14.91	65.31	30.97
					242/62	18.57	21.81	151.71	71.94	9.23	9.23	17.66	8.38
				MIMO A	Full	21.98	25.22	332.66	157.76	12.55	12.55	37.93	17.99
					242/62	17.47	20.71	117.76	55.85	8.07	8.07	13.52	6.41
				MIMO B	Full	22.24	25.48	353.18	167.49	12.64	12.64	38.73	18.37
					242/62	17.45	20.69	117.22	55.59	8.00	8.00	13.30	6.31
				Combined A+B	Full	25.12	28.36	685.84	325.26	15.61	15.61	76.66	36.35
					242/62	20.47	23.71	234.98	111.44	11.05	11.05	26.83	12.72

* Duty cycle compensated

B.2.3 Power Spectral Density

Test limits

FCC part	RSS part	Limits
15.247 (e)	RSS-247 Clause 5.2 (b)	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test procedure

The peak power spectral density level in the fundamental emission was measured using the *Method PKPSD (peak PSD)* according to section 11.10.2 of ANSI C63.10-2013.

For MIMO mode, the *Measure and add $10 \log(N_{ANT})$ dB*, (where N_{ANT} is the number of outputs) technique was used according to the Guidance for Emission Testing of Transmitters with Multiple Outputs in the Same Band FCC OET KDB 662911 D01 Multiple Transmitter Output.

With this technique, spectrum measurements are performed at each output of the device, and the quantity $10 \log(N_{ANT})$ dB is added to each spectrum value before comparing to the emission limit. Number of outputs = 2.

The conducted setup shown in section *Test & System Description* was used to measure the power spectral density. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Results tables

Mode	Rate	Channel	Freq [MHz]	Antenna	PSD Peak [dBm/3kHz]	MIMO Combined +10·log(N _{ant}) [dBm/3kHz]
802.11b	1Mbps	1	2412	SISO A	-1.44	na
				SISO B	-1.39	na
		7	2442	SISO A	-1.52	na
				SISO B	-1.49	na
		11	2462	SISO A	-1.33	na
				SISO B	-1.59	na
		12	2467	SISO A	-1.50	na
				SISO B	-1.45	na
802.11g	6Mbps	1	2412	SISO A	-3.77	na
				SISO B	-2.95	na
		7	2442	SISO A	-2.62	na
				SISO B	-2.37	na
		11	2462	SISO A	-2.61	na
				SISO B	-2.74	na
		12	2467	SISO A	-5.01	na
				SISO B	-4.37	na
802.11n20	HT0	1	2412	SISO A	-4.93	na
				SISO B	-4.42	na
		7	2442	SISO A	-2.47	na
				SISO B	-2.42	na
		11	2462	SISO A	-4.97	na
				SISO B	-4.12	na
		12	2467	SISO A	-5.06	na
				SISO B	-5.94	na
	HT8	13	2472	SISO A	-11.34	na
				SISO B	-9.92	na
		1	2412	MIMO A	-6.24	-3.23
				MIMO B	-5.52	-2.51
		7	2442	MIMO A	-1.60	1.41
				MIMO B	-2.75	0.26
		11	2462	MIMO A	-7.05	-4.04
				MIMO B	-4.66	-1.65
802.11n40	HT0	12	2467	MIMO A	-8.13	-5.12
				MIMO B	-8.09	-5.08
		13	2472	MIMO A	-10.57	-7.56
				MIMO B	-11.35	-8.34
	HT8	3	2422	SISO A	-7.46	na
				SISO B	-7.39	na
		7	2442	SISO A	-6.08	na
				SISO B	-6.34	na
		9	2452	SISO A	-6.83	na
				SISO B	-6.96	na
		10	2457	SISO A	-12.12	na
				SISO B	-10.77	na
	HT8	11	2462	SISO A	-13.24	na
				SISO B	-12.89	na
		3	2422	MIMO A	-8.63	-5.62
				MIMO B	-10.88	-7.87
		7	2442	MIMO A	-8.05	-5.04
				MIMO B	-7.47	-4.46
		9	2452	MIMO A	-8.70	-5.69
				MIMO B	-8.68	-5.67
		10	2457	MIMO A	-11.36	-8.35
				MIMO B	-11.30	-8.29
		11	2462	MIMO A	-15.04	-12.03
				MIMO B	-14.53	-11.52

Mode	Rate	#Ch	Freq[MHz]	Antenna	RU config.	PSD Peak [dBm/3kHz]	MIMO Combined +10·log(N _{ant}) [dBm/3kHz]
802.11ax20	HE0	1	2412	SISO A	Full	-6.46	na
					26/0	3.46	na
					52/37	1.22	na
					106/53	-1.03	na
				SISO B	Full	-6.11	na
					26/0	2.05	na
					52/37	1.03	na
					106/53	-2.22	na
				MIMO A	Full	-7.22	-4.21
					26/0	2.42	5.43
					52/37	-0.18	2.83
					106/53	-2.62	0.39
				MIMO B	Full	-7.77	-4.76
					26/0	3.57	6.58
					52/37	0.33	3.34
					106/53	-2.51	0.50
		7	2442	SISO A	Full	-3.71	na
				SISO B	Full	-3.66	na
				MIMO A	Full	-3.68	-0.67
				MIMO B	Full	-4.20	-1.19
		11	2462	SISO A	Full	-4.63	Na
				SISO B	Full	-4.93	na
				MIMO A	Full	-5.24	-2.23
				MIMO B	Full	-5.77	-2.76
		12	2467	SISO A	Full	-5.73	na
				SISO B	Full	-6.33	na
				MIMO A	Full	-7.63	-4.62
				MIMO B	Full	-8.68	-5.67
		13	2472	SISO A	Full	-11.79	na
					26/8	-7.05	na
					52/40	-9.16	na
					106/54	-12.65	na
				SISO B	Full	-10.27	na
					26/8	-6.71	na
					52/40	-9.48	na
					106/54	-12.67	na
				MIMO A	Full	-11.61	-8.60
					26/8	-8.68	-5.67
					52/40	-10.58	-7.57
					106/54	-13.88	-10.87
				MIMO B	Full	-11.84	-8.83
					26/8	-7.52	-4.51
					52/40	-11.00	-7.99
					106/54	-12.81	-9.80

Mode	Rate	#Ch	Freq[MHz]	Antenna	RU config.	PSD Peak [dBm/3kHz]	MIMO Combined +10·log(N _{ant}) [dBm/3kHz]
802.11ax40	HE0	3	2422	SISO A	Full	-8.38	na
					242/61	-5.69	na
				SISO B	Full	-8.32	na
					242/61	-6.37	na
				MIMO A	Full	-9.00	-5.99
					242/61	-8.07	-5.06
		7	2442	MIMO B	Full	-9.23	-6.22
					242/61	-7.21	-4.20
				SISO A	Full	-7.19	na
				SISO B	Full	-6.33	na
				MIMO A	Full	-9.28	-6.27
				MIMO B	Full	-8.73	-5.72
		9	2452	SISO A	Full	-8.39	Na
				SISO B	Full	-8.16	Na
				MIMO A	Full	-8.50	-5.49
				MIMO B	Full	-9.38	-6.37
		10	2457	SISO A	Full	-12.18	Na
				SISO B	Full	-12.66	Na
				MIMO A	Full	-12.73	-9.72
				MIMO B	Full	-13.11	-10.10
		11	2462	SISO A	Full	-13.79	na
					242/62	-15.63	na
				SISO B	Full	-13.54	na
					242/62	-15.48	na
				MIMO A	Full	-15.73	-12.72
					242/62	-16.89	-13.88
				MIMO B	Full	-15.26	-12.25
					242/62	-16.86	-13.85

B.2.4 Out-of-band emission (conducted)

Test Limits

FCC part	RSS part	Limits																				
15.247 (d)	RSS-247 Clause 5.5	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.																				
15.209	RSS-Gen A1 Clause 8.9	Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a): <table><tr><th>Freq Range (MHz)</th><th>Field Strength (μV/m)</th><th>Field Strength (dBμV/m)</th><th>Meas. Distance (m)</th></tr><tr><td>30-88</td><td>100</td><td>40</td><td>3</td></tr><tr><td>88-216</td><td>150</td><td>43.5</td><td>3</td></tr><tr><td>216-960</td><td>200</td><td>46</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>54</td><td>3</td></tr></table> The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.	Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			

Test procedure

The lower band edge falling in restricted bands was measured using the primary method according to section 11.12.2.5.2 & 11.12.2.4 of ANSI C63.10-2013

The upper band edge was measured using the following methods:

- Integration Method according to 11.13.3 of ANSI C63.10-2013
- Primary Method according 11.12.2.5.2 & 11.12.2.4 of ANSI C63.10-2013

In case of band edge measurements falling in restricted bands, the declared antenna gain is also compensated in the graph.

For band edge measurements falling in restricted bands, the following limits in dBm were applied for the average detector after the conversion from the limits detailed above in dBμV/m, according to FCC 47 CFR part 15 - Subpart C – §15.209(a). The limits in dBm for peak detector are 20dB above the indicated values in the table.

§15.209(a)			Converted values	
Freq Range (MHz)	Distance (m)	Field strength (microvolts/meter)	Field strength (dB microvolts/meter)	Power (dBm)
Above 960	3	500	54.0	-41.2

The conducted setup shown in section *Test & System Description* was used to measure the out-of-band emissions. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Note: for the compliance of the out of band emission measurements, PSD_{Peak} were measured with 100kHz RBW and values are shown just as a reference in section B.2.3.

See Section B.2.6 for the screenshot results.

B.2.5 Radiated spurious emission

Standard references

FCC part	RSS part	Limits			
15.247 (d) 15.209	RSS-247 Clause 5.5 RSS-Gen A1 Clause 8.9	Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):			
		Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)
		30-88	100	40	3
		88-216	150	43.5	3
		216-960	200	46	3
		Above 960	500	54	3
		The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function corresponding to 20 dB above the indicated values in the table.			

Test procedure

The radiated setups shown in section *Test & System Description* were used to measure the radiated spurious emissions. Depending of the frequency range and bands being tested, different antennas and filters were used. The final measurement is done by varying the antenna height from 1 to 4 meters, the EUT azimuth over 360° and for both Vertical and Horizontal polarizations.

The radiated spurious emissions were measured on the worst case configuration selected from the chapter B.2.2 and using the lowest, middle and highest channels.

Test Results**Radiated spurious - 30 MHz – 1 GHz****Radiated Spurious – All modes**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
30.6	31.9	Quasi-Peak	40.0	8.2	V
51.8	32.0	Quasi-Peak	40.0	8.0	V

Note 1: The spurious signals detected do not depend on either the operating channel or the modulation mode.

Radiated spurious – 1 GHz to 26 GHz**802.11b, 1Mbps, Chain A****CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3390.0	57.5	Peak	74.0	16.5	H
3397.5	45.6	Average	54.0	8.4	H
7604.6	53.3	Peak	74.0	20.7	H
7604.6	44.0	Average	54.0	10.0	H
12058.5	51.2	Peak	74.0	22.8	V
12058.5	43.4	Average	54.0	10.6	H
19296.0	39.1	Average	54.0	14.9	H
19296.2	46.7	Peak	74.0	27.3	H
21706.4	49.1	Peak	74.0	24.9	V
21706.8	40.5	Average	54.0	13.5	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
4303.7	48.1	Peak	74.0	25.9	V
4303.7	39.1	Average	54.0	14.8	H
9766.8	46.4	Peak	74.0	27.6	H
9767.8	37.2	Average	54.0	16.8	V
12211.0	50.4	Peak	74.0	23.6	V
12211.0	43.1	Average	54.0	10.9	H
17097.6	41.3	Average	54.0	12.7	H
17100.4	50.3	Peak	74.0	23.7	H
19535.7	47.1	Peak	74.0	26.9	H
19535.9	39.9	Average	54.0	14.1	H

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
4822.6	50.6	Peak	74.0	23.4	H
4823.5	40.7	Average	54.0	13.3	H
5423.0	41.4	Average	54.0	12.6	H
5424.3	50.6	Peak	74.0	23.4	V
5604.7	52.8	Peak	74.0	21.2	H
5604.7	41.9	Average	54.0	12.1	V
7650.4	54.4	Peak	74.0	19.6	H
7650.4	44.0	Average	54.0	10.1	V
11686.4	37.4	Average	54.0	16.6	H
11690.6	47.9	Peak	74.0	26.1	V
17795.5	50.1	Peak	74.0	23.9	H
17824.3	39.8	Average	54.0	14.2	H
19695.8	40.1	Average	54.0	13.9	H
19696.0	48.0	Peak	74.0	26.1	V

802.11b, 1Mbps, Chain B**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1578.0	39.3	Average	54.0	14.7	V
1578.0	49.3	Peak	74.0	24.7	V
4823.0	49.8	Peak	74.0	24.2	V
4823.9	40.9	Average	54.0	13.1	V
9634.1	46.6	Peak	74.0	27.4	V
9647.8	38.8	Average	54.0	15.2	V
12056.6	48.2	Peak	74.0	25.8	H
12061.3	39.1	Average	54.0	14.9	V
19296.0	39.0	Average	54.0	15.0	H
19298.0	46.9	Peak	74.0	27.1	H

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1864.0	53.2	Peak	74.0	20.8	H
1864.0	42.2	Average	54.0	11.8	V
2932.0	55.5	Peak	74.0	18.5	V
2932.0	45.5	Average	54.0	8.5	H
4744.2	50.0	Peak	74.0	24.0	V
4744.6	40.3	Average	54.0	13.7	H
9767.8	46.3	Peak	74.0	27.7	V
9767.8	38.8	Average	54.0	15.2	V
16081.8	49.9	Peak	74.0	24.1	V
16082.8	39.7	Average	54.0	14.3	V
19535.9	48.4	Peak	74.0	25.6	H
19535.9	42.4	Average	54.0	11.6	H
24419.8	48.3	Peak	74.0	25.7	H
24419.8	40.5	Average	54.0	13.5	H

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4455.3	48.9	Peak	74.0	25.1	H
4455.3	39.7	Average	54.0	14.3	V
4774.7	49.1	Peak	74.0	24.9	V
4774.7	40.5	Average	54.0	13.5	H
6124.5	42.9	Average	54.0	11.1	H
6125.0	53.3	Peak	74.0	20.7	V
9847.6	38.9	Average	54.0	15.1	V
9848.5	47.0	Peak	74.0	27.0	H
19695.7	40.8	Average	54.0	13.2	V
19696.0	48.6	Peak	74.0	25.4	H
24619.8	48.2	Peak	74.0	25.8	H
24620.2	40.0	Average	54.0	14.0	H

802.11g, 6Mbps, Chain A**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4409.1	39.8	Average	54.0	14.2	H
4409.1	48.8	Peak	74.0	25.2	H
10008.1	47.7	Peak	74.0	26.3	V
10029.4	37.2	Average	54.0	16.8	V
16380.8	39.8	Average	54.0	14.2	V
16406.7	51.1	Peak	74.0	22.9	H
22713.9	39.8	Average	54.0	14.2	V
22715.4	48.6	Peak	74.0	25.4	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5274.9	50.1	Peak	74.0	23.9	H
5274.9	40.9	Average	54.0	13.1	V
16379.3	50.9	Peak	74.0	23.1	H
16401.5	40.1	Average	54.0	13.9	H
24277.3	39.6	Average	54.0	14.4	H
24278.5	48.5	Peak	74.0	25.5	H

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.0	57.1	Peak	74.0	16.9	V
3399.0	45.7	Average	54.0	8.3	H
16406.7	40.0	Average	54.0	14.0	H
16415.2	51.2	Peak	74.0	22.8	H
21081.0	47.5	Peak	74.0	26.5	H
21081.0	39.8	Average	54.0	14.2	H

802.11g, 6Mbps, Chain B**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	46.2	Average	54.0	7.8	V
3400.0	57.1	Peak	74.0	16.9	H
10098.3	36.8	Average	54.0	17.2	V
10100.7	47.5	Peak	74.0	26.5	V
17796.0	50.9	Peak	74.0	23.1	V
17844.6	39.7	Average	54.0	14.3	V
21091.2	46.9	Peak	74.0	27.1	V
21091.2	39.2	Average	54.0	14.8	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
6029.5	51.6	Peak	74.0	22.4	H
6030.0	42.8	Average	54.0	11.2	H
16396.8	39.7	Average	54.0	14.3	H
16427.5	50.9	Peak	74.0	23.1	H
25600.9	48.0	Peak	74.0	26.0	H
25600.9	39.5	Average	54.0	14.5	H

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
4783.8	41.0	Average	54.0	13.0	H
4784.3	49.6	Peak	74.0	24.4	V
5987.3	52.6	Peak	74.0	21.4	H
5989.9	42.5	Average	54.0	11.5	V
16420.9	39.8	Average	54.0	14.2	H
16431.8	50.7	Peak	74.0	23.3	H
23109.4	47.9	Peak	74.0	26.1	H
23110.2	39.5	Average	54.0	14.5	V

802.11n20, HT0, Chain A**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
3400.0	56.9	Peak	74.0	17.1	H
3400.0	45.7	Average	54.0	8.3	V
12058.0	53.8	Peak	74.0	20.2	V
12058.5	43.5	Average	54.0	10.5	V
24451.3	48.1	Peak	74.0	25.9	V
24453.2	39.7	Average	54.0	14.3	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.5	Peak	74.0	17.5	H
3400.0	45.8	Average	54.0	8.2	H
12203.9	38.4	Average	54.0	15.6	H
12210.1	48.7	Peak	74.0	25.3	H
25819.6	48.1	Peak	74.0	25.9	H
25819.8	39.8	Average	54.0	14.2	V

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3645.3	46.1	Peak	74.0	27.9	V
3645.3	38.2	Average	54.0	15.8	V
12322.0	48.9	Peak	74.0	25.1	H
12322.9	37.8	Average	54.0	16.2	H
21190.0	48.7	Peak	74.0	25.3	H
21190.0	39.6	Average	54.0	14.4	H

802.11n20, HT0, Chain B**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	57.7	Peak	74.0	16.3	V
3400.0	45.9	Average	54.0	8.1	H
12518.9	37.6	Average	54.0	16.4	H
12521.8	47.9	Peak	74.0	26.1	V
24436.4	48.0	Peak	74.0	26.1	V
24437.9	39.7	Average	54.0	14.3	H

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4047.5	48.2	Peak	74.0	25.8	V
4047.9	38.7	Average	54.0	15.3	V
12661.5	48.7	Peak	74.0	25.3	V
12668.6	37.6	Average	54.0	16.4	H
20536.0	47.2	Peak	74.0	26.8	V
20536.2	39.0	Average	54.0	15.0	H

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	58.1	Peak	74.0	15.9	V
3400.0	45.8	Average	54.0	8.2	V
12289.4	48.1	Peak	74.0	25.9	H
12300.3	37.5	Average	54.0	16.5	V
25848.3	39.4	Average	54.0	14.6	V
25848.5	48.0	Peak	74.0	26.0	H

802.11n20, HT0, Chain A+B**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.8	Peak	74.0	17.2	V
3400.0	45.8	Average	54.0	8.2	V
12059.0	40.2	Average	54.0	13.8	V
12064.2	50.3	Peak	74.0	23.7	V
19865.8	46.3	Peak	74.0	27.7	V
19866.6	38.7	Average	54.0	15.3	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.6	Peak	74.0	17.4	V
3400.0	46.0	Average	54.0	8.0	V
12039.1	37.1	Average	54.0	16.9	H
12057.1	48.0	Peak	74.0	25.9	H
25812.3	48.1	Peak	74.0	25.9	V
25812.8	39.5	Average	54.0	14.5	V

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	57.4	Peak	74.0	16.6	V
3399.5	46.0	Average	54.0	8.0	V
12165.2	37.1	Average	54.0	16.9	H
12178.4	48.8	Peak	74.0	25.2	H
23199.9	47.8	Peak	74.0	26.2	H
23200.5	39.0	Average	54.0	15.0	V

802.11ax20, HE0, Chain A**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4412.2	39.9	Average	54.0	14.1	V
4413.5	50.1	Peak	74.0	23.9	H
5277.1	50.2	Peak	74.0	23.8	V
5277.9	41.2	Average	54.0	12.8	H
12383.9	49.8	Peak	74.0	24.2	V
12415.5	38.1	Average	54.0	15.9	H
21632.5	48.2	Peak	74.0	25.8	V
21632.7	41.1	Average	54.0	12.9	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	45.8	Average	54.0	8.2	H
3400.0	57.3	Peak	74.0	16.7	H
12166.6	42.7	Average	54.0	11.3	V
12167.6	51.3	Peak	74.0	22.7	V
21903.0	49.7	Peak	74.0	24.3	V
21904.5	39.5	Average	54.0	14.5	V

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3732.9	38.9	Average	54.0	15.1	H
3732.9	49.7	Peak	74.0	24.3	H
5147.7	49.4	Peak	74.0	24.6	H
5148.1	40.5	Average	54.0	13.4	V
12266.3	50.5	Peak	74.0	23.5	H
12267.7	39.4	Average	54.0	14.6	H
23111.3	39.6	Average	54.0	14.4	V
23114.7	48.6	Peak	74.0	25.4	V

802.11ax20, HE0, Chain B**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4335.0	47.3	Peak	74.0	26.7	H
4335.0	39.2	Average	54.0	14.8	H
5277.5	50.3	Peak	74.0	23.7	H
5277.9	40.9	Average	54.0	13.1	H
12014.1	49.1	Peak	74.0	24.9	V
12017.4	39.4	Average	54.0	14.6	V
25838.5	39.6	Average	54.0	14.4	H
25838.9	49.0	Peak	74.0	24.9	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
4677.5	49.0	Peak	74.0	25.0	H
4680.1	40.4	Average	54.0	13.6	V
12166.6	37.9	Average	54.0	16.1	V
12167.1	48.0	Peak	74.0	25.9	V
25837.8	48.1	Peak	74.0	25.9	V
25837.8	39.5	Average	54.0	14.6	H

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
4648.8	49.9	Peak	74.0	24.1	H
4649.2	40.6	Average	54.0	13.4	V
12267.7	38.1	Average	54.0	15.9	V
12268.6	48.2	Peak	74.0	25.8	H
24380.3	39.6	Average	54.0	14.4	V
24380.7	47.3	Peak	74.0	26.7	V

802.11ax20, HE0, Chain A+B**CH1**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
4807.4	40.9	Average	54.0	13.1	V
4808.2	50.2	Peak	74.0	23.8	V
6502.3	52.0	Peak	74.0	22.0	V
6502.7	43.2	Average	54.0	10.8	H
12016.0	49.2	Peak	74.0	24.8	V
12016.9	39.8	Average	54.0	14.2	V
21631.0	40.1	Average	54.0	13.9	V
21631.6	49.0	Peak	74.0	25.0	V

CH7

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.7	Peak	74.0	17.3	V
3400.0	45.8	Average	54.0	8.2	V
12166.6	48.5	Peak	74.0	25.5	V
12167.6	39.1	Average	54.0	14.9	V
21902.8	48.2	Peak	74.0	25.8	V
21902.8	39.4	Average	54.0	14.6	V

CH11

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5813.4	51.2	Peak	74.0	22.8	H
5813.9	41.8	Average	54.0	12.2	V
12266.8	38.8	Average	54.0	15.2	V
12267.2	48.0	Peak	74.0	26.0	V
19626.9	48.2	Peak	74.0	25.8	H
19627.3	39.4	Average	54.0	14.6	H

802.11n40, HT0, Chain A**CH3F**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.0	45.7	Average	54.0	8.3	H
3399.5	56.0	Peak	74.0	18.0	V
12101.5	49.6	Peak	74.0	24.4	V
12116.1	38.4	Average	54.0	15.6	H
26098.0	38.7	Average	54.0	15.3	H
26098.4	47.5	Peak	74.0	26.5	V

CH6F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	46.3	Average	54.0	7.7	V
3400.0	57.4	Peak	74.0	16.6	V
12148.2	49.2	Peak	74.0	24.8	V
12170.9	39.4	Average	54.0	14.6	V
21479.5	48.1	Peak	74.0	25.9	H
21479.7	39.5	Average	54.0	14.4	H

CH9F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.8	Peak	74.0	17.2	V
3400.0	45.8	Average	54.0	8.2	H
12264.4	49.5	Peak	74.0	24.5	V
12269.6	38.8	Average	54.0	15.2	V
23138.9	46.2	Peak	74.0	27.8	V
23139.1	39.9	Average	54.0	14.1	V

802.11n40, HT0, Chain B**CH3F**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4014.8	39.0	Average	54.0	15.0	H
4015.2	47.9	Peak	74.0	26.1	H
11999.9	37.0	Average	54.0	17.0	V
12016.5	47.6	Peak	74.0	26.4	H
25884.2	39.8	Average	54.0	14.2	V
25886.3	48.5	Peak	74.0	25.5	H

CH6F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.9	Peak	74.0	17.1	H
3400.0	46.0	Average	54.0	8.0	H
12430.6	48.0	Peak	74.0	26.0	V
12438.6	37.2	Average	54.0	16.8	H
23161.2	46.7	Peak	74.0	27.3	V
23161.2	39.8	Average	54.0	14.2	H

CH9F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.6	Peak	74.0	17.4	V
3400.0	45.7	Average	54.0	8.3	H
11957.0	48.1	Peak	74.0	25.9	V
11981.1	37.2	Average	54.0	16.8	V
21184.3	39.5	Average	54.0	14.4	V
21185.0	48.0	Peak	74.0	25.9	H

802.11n40, HT0, Chain A+B**CH3F**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3398.5	57.7	Peak	74.0	16.3	H
3399.5	45.9	Average	54.0	8.1	V
11213.2	51.9	Peak	74.0	22.1	V
11215.1	35.8	Average	54.0	18.2	V
24206.7	48.4	Peak	74.0	25.6	V
24206.7	39.4	Average	54.0	14.7	V

CH6F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	57.1	Peak	74.0	16.9	H
3400.0	45.9	Average	54.0	8.1	V
11947.5	47.7	Peak	74.0	26.3	V
11980.6	36.9	Average	54.0	17.1	H
21497.7	39.6	Average	54.0	14.4	V
21498.4	48.5	Peak	74.0	25.5	V

CH9F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	45.7	Average	54.0	8.3	H
3400.0	56.7	Peak	74.0	17.3	V
12027.3	37.1	Average	54.0	16.9	H
12034.9	48.2	Peak	74.0	25.8	V
25847.0	39.5	Average	54.0	14.5	V
25850.8	49.5	Peak	74.0	24.6	V

802.11ax40, HE0, Chain A**CH3F**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5481.8	50.5	Peak	74.0	23.5	H
5481.8	41.4	Average	54.0	12.6	H
11233.1	36.9	Average	54.0	17.1	V
11240.6	50.0	Peak	74.0	24.0	V
21710.9	39.6	Average	54.0	14.4	V
21711.7	48.6	Peak	74.0	25.4	V

CH6F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.7	Peak	74.0	17.3	V
3400.0	45.6	Average	54.0	8.3	H
11247.7	53.6	Peak	74.0	20.4	V
11248.2	36.6	Average	54.0	17.4	H
12134.5	49.9	Peak	74.0	24.1	H
12136.4	40.6	Average	54.0	13.4	V
24113.4	39.1	Average	54.0	14.9	V
24113.8	47.6	Peak	74.0	26.4	H

CH9F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4480.1	48.6	Peak	74.0	25.4	V
4480.6	39.8	Average	54.0	14.2	H
12212.0	54.7	Peak	74.0	19.3	H
12212.0	48.7	Average	54.0	5.3	H
20958.2	47.1	Peak	74.0	26.9	V
20958.6	39.3	Average	54.0	14.7	H

802.11ax40, HE0, Chain B**CH3F**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	57.3	Peak	74.0	16.7	V
3399.5	45.7	Average	54.0	8.3	H
12059.9	39.1	Average	54.0	14.8	V
12064.2	48.7	Peak	74.0	25.3	V
21715.3	47.4	Peak	74.0	26.6	V
21716.0	39.4	Average	54.0	14.6	V

CH6F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
4278.0	39.6	Average	54.0	14.4	H
4278.4	49.0	Peak	74.0	25.0	V
12134.5	48.1	Peak	74.0	25.9	V
12137.4	37.6	Average	54.0	16.4	V
25014.4	39.1	Average	54.0	14.9	H
25014.8	47.4	Peak	74.0	26.6	V

CH9F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3399.5	57.6	Peak	74.0	16.4	H
3400.0	45.9	Average	54.0	8.1	V
12210.6	37.6	Average	54.0	16.4	V
12213.4	47.6	Peak	74.0	26.4	V
21110.6	48.7	Peak	74.0	25.3	V
21111.0	39.7	Average	54.0	14.3	V

802.11ax40, HE0, Chain A+B**CH3F**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6633.4	43.7	Average	54.0	10.3	V
6634.3	52.4	Peak	74.0	21.6	V
12061.3	40.8	Average	54.0	13.2	V
12062.8	49.9	Peak	74.0	24.1	V
21710.3	39.9	Average	54.0	14.1	V
21712.2	49.2	Peak	74.0	24.8	V


CH6F

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5085.8	49.8	Peak	74.0	24.2	H
5085.8	40.8	Average	54.0	13.2	V
12137.4	49.5	Peak	74.0	24.5	V
12137.4	39.7	Average	54.0	14.3	V
21845.0	49.3	Peak	74.0	24.7	H
21847.5	40.0	Average	54.0	14.0	V

CH9F


Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
3400.0	56.2	Peak	74.0	17.8	H
3400.0	45.7	Average	54.0	8.3	V
12211.5	38.5	Average	54.0	15.5	V
12212.0	49.1	Peak	74.0	24.9	V
19537.2	39.0	Average	54.0	15.0	H
19537.4	46.9	Peak	74.0	27.1	H

B.2.6 Out of band emissions - band-edge (conducted)




Date: 14/MAR/2022 17:16:28

BE-R-LOW, SISO-A, 802.11b-1Mbps, Ch1




BE-NR, SISO-A, 802.11b-1Mbps, Ch1




Date: 14/MAR/2022 17:27:03

BE-R-HIGH, SISO-A, 802.11b-1Mbps, Ch11




Date: 14/MAR/2022 17:27:10

BE-R-HIGH-2MHz, SISO-A, 802.11b-1Mbps, Ch11




BE-R-HIGH, SISO-A, 802.11b-1Mbps, Ch12




Date: 24/MAR/2022 16:24:35


BE-R-HIGH-2MHz, SISO-A, 802.11b-1Mbps, Ch12




BE-R-HIGH, SISO-A, 802.11b-1Mbps, Ch13




BE-R-HIGH-2MHz, SISO-A, 802.11b-1Mbps, Ch13




BE-R-LOW, SISO-A, 802.11g-6Mbps, Ch1




BE-NR, SISO-A, 802.11g-6Mbps, Ch1



BE-R-HIGH, SISO-A, 802.11g-6Mbps, Ch11




BE-R-HIGH-2MHz, SISO-A, 802.11g-6Mbps, Ch11




Date 24/MAR/2022 16:28:17

BE-R-HIGH, SISO-A, 802.11g-6Mbps, Ch12




Date 24/MAR/2022 16:28:24

BE-R-HIGH-2MHz, SISO-A, 802.11g-6Mbps, Ch12



Date 24/MAR/2022 17:02:17

BE-R-HIGH, SISO-A, 802.11g-6Mbps, Ch13




Date 24/MAR/2022 17:02:24

BE-R-HIGH-2MHz, SISO-A, 802.11g-6Mbps, Ch13




Date 15/MAR/2022 21:52:52

BE-R-LOW, SISO-A, 802.11n20-HT0, Ch1




Date 14/MAR/2022 18:40:01

BE-NR, SISO-A, 802.11n20-HT0, Ch1




Date: 14/MAR/2022 18:51:08

BE-R-HIGH, SISO-A, 802.11n20-HT0, Ch11




BE-R-HIGH-2MHz, SISO-A, 802.11n20-HT0, Ch11




Date: 24/MAR/2022 16:30:47

BE-R-HIGH, SISO-A, 802.11n20-HT0, Ch12




Date: 24/MAR/2022 16:30:53

BE-R-HIGH-2MHz, SISO-A, 802.11n20-HT0, Ch12




Date: 24/MAR/2022 16:32:02

BE-R-HIGH, SISO-A, 802.11n20-HT0, Ch13




BE-R-HIGH-2MHz, SISO-A, 802.11n20-HT0, Ch13




Date 24/MAR/2022 16:33:16

BE-R-LOW, SISO-A, 802.11n40-HT0, Ch3




Date 24/MAR/2022 16:33:22

BE-NR, SISO-A, 802.11n40-HT0, Ch3




Date 24/MAR/2022 16:35:32

BE-R-HIGH, SISO-A, 802.11n40-HT0, Ch9




BE-R-HIGH-2MHz, SISO-A, 802.11n40-HT0, Ch9




Date 24/MAR/2022 16:36:44

BE-R-HIGH, SISO-A, 802.11n40-HT0, Ch10




Date 24/MAR/2022 16:36:50

BE-R-HIGH-2MHz, SISO-A, 802.11n40-HT0, Ch10




Date 24MAR2022 16:37:57

BE-R-HIGH, SISO-A, 802.11n40-HT0, Ch11




BE-R-HIGH-2MHz, SISO-A, 802.11n40-HT0, Ch11




Date 14MAR2022 19:00:25

BE-R-LOW, SISO-A, 802.11ax20-HE0, Ch1




Date 14MAR2022 19:00:31


BE-NR, SISO-A, 802.11ax20-HE0, Ch1



BE-R-HIGH, SISO-A, 802.11ax20-HE0, Ch11




BE-R-HIGH-2MHz, SISO-A, 802.11ax20-HE0, Ch11




Date 24MAR2022 16:40:24

BE-R-HIGH, SISO-A, 802.11ax20-HE0, Ch12




Date 24MAR2022 16:40:31

BE-R-HIGH-2MHz, SISO-A, 802.11ax20-HE0, Ch12




Date 24MAR2022 17:13:14

BE-R-HIGH, SISO-A, 802.11ax20-HE0, Ch13




Date 24MAR2022 17:13:14

BE-R-HIGH-2MHz, SISO-A, 802.11ax20-HE0, Ch13




Date 24MAR2022 16:42:52

BE-R-LOW, SISO-A, 802.11ax40-HE0, Ch3




Date 24MAR2022 16:42:53

BE-NR, SISO-A, 802.11ax40-HE0, Ch3




Date 24/MAR/2022 16:45:05

BE-R-HIGH, SISO-A, 802.11ax40-HE0, Ch9




BE-R-HIGH-2MHz, SISO-A, 802.11ax40-HE0, Ch9




Date 24/MAR/2022 16:43:17

BE-R-HIGH, SISO-A, 802.11ax40-HE0, Ch10




Date 24/MAR/2022 16:43:24

BE-R-HIGH-2MHz, SISO-A, 802.11ax40-HE0, Ch10




Date 24/MAR/2022 16:47:30

BE-R-HIGH, SISO-A, 802.11ax40-HE0, Ch11




BE-R-HIGH-2MHz, SISO-A, 802.11ax40-HE0, Ch11




Date: 16.MAR.2022 19:55:20

BE-R-LOW, SISO-B, 802.11b-1Mbps, Ch1




Date: 21.MAR.2022 10:22:07

BE-NR, SISO-B, 802.11b-1Mbps, Ch1




Date: 16.MAR.2022 19:57:30

BE-R-HIGH, SISO-B, 802.11b-1Mbps, Ch11




Date: 16.MAR.2022 19:57:37

BE-R-HIGH-2MHz, SISO-B, 802.11b-1Mbps, Ch11




Date: 21.MAR.2022 10:21:27

BE-R-HIGH, SISO-B, 802.11b-1Mbps, Ch12




Date: 18.MAR.2022 21:58:00


BE-R-HIGH-2MHz, SISO-B, 802.11b-1Mbps, Ch12




BE-R-HIGH, SISO-B, 802.11b-1Mbps, Ch13




BE-R-HIGH-2MHz, SISO-B, 802.11b-1Mbps, Ch13




BE-R-LOW, SISO-B, 802.11g-6Mbps, Ch1




BE-NR, SISO-B, 802.11g-6Mbps, Ch1



BE-R-HIGH, SISO-B, 802.11g-6Mbps, Ch11




BE-R-HIGH-2MHz, SISO-B, 802.11g-6Mbps, Ch11




Date: 18.MAR.2022 22:01:41

BE-R-HIGH, SISO-B, 802.11g-6Mbps, Ch12




Date: 18.MAR.2022 22:01:48

BE-R-HIGH-2MHz, SISO-B, 802.11g-6Mbps, Ch12




Date: 21.MAR.2022 10:41:45

BE-R-HIGH, SISO-B, 802.11g-6Mbps, Ch13




Date: 21.MAR.2022 10:41:51

BE-R-HIGH-2MHz, SISO-B, 802.11g-6Mbps, Ch13




Date: 21.MAR.2022 10:48:40

BE-R-LOW, SISO-B, 802.11n20-HT0, Ch1




Date: 16.MAR.2022 20:33:41

BE-NR, SISO-B, 802.11n20-HT0, Ch1




Date: 21.MAR.2022 12:03:02

BE-R-HIGH, SISO-B, 802.11n20-HT0, Ch11




Date: 21.MAR.2022 12:03:09

BE-R-HIGH-2MHz, SISO-B, 802.11n20-HT0, Ch11




Date: 21.MAR.2022 12:03:00

BE-R-HIGH, SISO-B, 802.11n20-HT0, Ch12




Date: 21.MAR.2022 12:03:03

BE-R-HIGH-2MHz, SISO-B, 802.11n20-HT0, Ch12



Date: 21.MAR.2022 12:11:37

BE-R-HIGH, SISO-B, 802.11n20-HT0, Ch13



Date: 21.MAR.2022 12:11:44

BE-R-HIGH-2MHz, SISO-B, 802.11n20-HT0, Ch13