



Maximum Permissible Exposure Calculations.

The following calculations are based on guidelines published in OET Bulletin 65, Edition 97-01, August 1997: Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields.

	Frequency (GHz)	Wavelength (m)	Near to Far Field Transition (cm)
Lower	2.4000	0.125	~2.0
Upper	2.4835	0.121	~1.9

For a simple case, discounting reflections, equation 4, page 19 gives:

$$\text{Power Density, } S = PG / 4\pi R^2$$

Worst case power input to antenna (P): 67mW.
 Antenna gain: 0 dBi.
 Numeric antenna gain (G): 1.
 General population/ uncontrolled limit (S): 1mW/cm².

Distance from antenna, R, where power density limit is reached is:

$$R = \sqrt{(PG / 4\pi S)}$$

$$R = 2.31 \text{ cm}$$

Notes.

1. The general population/ uncontrolled limit is taken from OET 65, Appendix A Table 1B page 67.

For a worst case prediction of power density, including reflections from nearby surfaces, OET 65 recommends using equation 6, page 20.

$$\text{Power Density } S = PG / \pi R^2$$

Red-M

Neptune House · Mercury Park · Wycombe Lane · Wooburn Green · Bucks · HP10 0HH
Tel: +44 (0)1628 819700 Fax: +44 (0)1628 819701
www.red-m.com



Using the same figures as above the distance from antenna, R, where power density limit is reached is:

$$R = \sqrt{PG / \pi S}$$

$$R = \underline{4.62 \text{ cm.}}$$

Neil Evans

23 May 2003

Red-M (Communications) Ltd.