

CERTIFICATE OF COMPLIANCE

(CLASS B)

CERTIFICATION OF COMPLIANCE is hereby issued to the named Applicant and is VALID ONLY for the equipment identified below:

Date of Tested : Aug. 11. 2001

Applicant's Name : NEWCOMM World CO., LTD.

Applicant's Address : 3RD FL. Songsan Bldg. 381 Songnae-dong, Sosa-gu, PuchonSi
Kyonggi-do, Korea

Manufacturer's Name : NEWCOMM World CO., LTD.

Manufacturer's Address : 3RD FL. Songsan Bldg. 381 Songnae-dong, Sosa-gu, PuchonSi
Kyonggi-do, Korea

Declares that the product

Product Description : LCD Monitor

Brand Name : NEWCOMM

Model Number : TM800

FCC ID : PF5-TM800

Conforms to FCC Rules and Regulations Part 15 Subpart B requirements.

This product herewith complies with the requirements of the FCC Rules and Regulations as listed below:

Part 15.107: Conducted Emissions.

Part 15.109: Radiated Spurious Emissions.

TESTED and CERTIFIED by:

KOREA EMC LABORATORY

352 Youngduk-Ri, Kihung-Eup,
Yongin-Si, Kyunggi-Do,
449-908, KOREA

Date : Aug. 14. 2001

Report No : KEL01I-B011K

Authorized Signature :



M. S. CHO / President

TABLE OF CONTENTS

DESCRIPTION	Page
0. VERIFICATION OF COMPLIANCE	3
1. GENERAL INFORMATION	
1.1 Product Description	4
1.2 Related Submittal(s)/Grant(s)	4
1.3 Tested System Details	4
1.4 System Configuration	4
1.5 General Setup of the test Shield room	5
1.6 Test Facility	5
2. Measurement Procedure	
2.1 System test configuration	6
2.1.1 Video mode Justification	6
2.1.2 EUT Exercise S/W	6
2.2 Special Accessories	6
2.3 Equipment Modification	6
2.4 System Configuration Diagram	6
2.5 Preliminary testing	7
2.6 Shielded Enclosure	7
2.7 Data Reporting Format	7
2.8 Operating Condition	7
2.9 Conditioning of the EUT	7
2.10 Power Line Conducted Emissions	8
2.11 Open field Radiated Emissions Tests	8
3. Measurement Data	
3.1 Conducted Emission Data	9
3.2 Conducted Emission Graph	10
3.3 Radiated Emission Data	11
3.4 Summary	12
4. Labeling Requirement	13
Appendix	
- A : Test set-up Photographs (Conducted and Radiated)	
- B : External Photographs of E.U.T	
- C : Internal Photographs of E.U.T	
- D : FCC ID label location information and sample	
- E : Block Diagram	
- F : User' s Manual	

0 . VERIFICATION OF COMPLIANCE

Equipment Under Test : LCD Monitor

Model Number : TM800

Serial Number : Prototype

Manufacturer : NEWCOMM World CO., LTD.
3RD FL. Songsan Bldg. 381 Songnae-dong, Sosa-gu, Puchon-Shi,
Kyonggi-do, Korea

Type of Test : FCC CLASS B

Report Number : KEL01I-B011K

Date Tested : Aug. 11. 2001

Tested By : S. J. LEE

The results show that the sample equipment tested as described in this reports is in compliance with the CLASS B conducted and radiated emission limits of FCC Rules Part 15, Subpart B.

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The TM800 is a LCD Monitor made by NEWCOMM World CO., LTD. in Korea. Refer to the user's manual for more information.

1.2 Related Submittal(s)/Grant(s)

N/A

1.3 Tested System Details

Type	MODEL NAME	FCC ID	Serial No	Manufacturer
LCD Monitor	TM800	PF5-TM800	Prototype	NEWCOMM World CO., LTD.
PC	Brio BA 600/500		SG95100402	HP
VTR	SV-420		none	SAMSUNG
Keyboard	SKR-1032	GJJSKR-1032	1EAC000237	SEJIN
Mouse	SMB-601	GJJB50PAQ	SKBE020496	SEJIN
Speaker	188825-301		none	COMPAQ
Adapter	LSE9901B1565		2K3100023	LI SHIN International Enterprise Corp.

1.4 System Configuration

Type	Model Name	Serial NO	Manufacturer	Remark
MAIN B/D	DAD114	NONE	NEWCOMM World CO., LTD.	KOREA
LCD	LM220W1	NONE	L.G. PHILIPS LCD	KOREA
CTRL B/D	LM220W1 CTRL	NONE	NEWCOMM World CO., LTD.	KOREA
AMP3A B/D	AMP3A	NONE	NEWCOMM World CO., LTD.	KOREA
LCD B/D	GH008	NONE	NEWCOMM World CO., LTD.	KOREA
ZTR5A B/D	ZTR5A	NONE	NEWCOMM World CO., LTD.	KOREA

1.5 General Set-up of the Test Shielded Room

The EUT was set up in accordance with the suggested configuration given in FCC measurement Procedure ANSI C63.4, 1992. The measurement are performed in the shielded room which dimension is 3.0*7.0*2.5(m). The EUT was placed on a non conductive table which is 1.0*1.5(m), 80cm above an earthed ground plane and is kept at least 1m from any other earthed ground plane except the rear of table top being removed 40cm from a vertical conducting plane.

Power to the EUT was provided through the LISN(KNW-407,Kyoritsu) which has the Impedance vs Frequency Characteristic in accordance with the Fig.1 Impedance Characteristic of LISN. Peripheral equipment required to provide a functional system(support equipment) for EUT testing was powered through another LISN(NSLK8128,Schwarzbeck).

Power to the LISN was filtered to eliminate ambient signal interference. A coaxial type connector which provides a 50 Ohm terminating impedance was provided for the test instrument. The excess length of the power cord was wrapped in the two non metallic pegs attached to the top of the LISN. The two pegs are 9cm high, approximately 2.0cm in diameter and that are spaced 6cm on the center apart.

1.6 Test Facility

Location: Korea EMC Laboratory
352 Yungduck-Ri
Kihung-Eup,Yongin-City
Kyungki-Do,Korea

Site : - 3/10m Open Fielded Radiated
- Indoor Line Conducted Room(Shielded)

The Open Field Radiated and Indoor Line Conducted sites are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4 1992. Korea EMC Lab. was refilled in FCC in 1998.

INSTRUMENTATION

Description	Model	Manufacturer	Serial No.	Last Cal.	Due Cal.
Test Receiver	ESH-2	RodeSchwarz	893268/004	'2001.6.15.	'2002.6.15
Test Receiver	ESVS10	RodeSchwarz	825120/006	'2000.9.29.	'2001.9.29
Test Receiver	ESPC	RodeSchwarz	844006/038	'2001.5.29.	'2002.5.29
L.I.S.N	NSLK8128	Schwarzbeck	8128144	'2000.11.10.	'2001.11.10
L.P. ANT	3146	EMCO	2685	'2001.5.30.	'2002.5.30
Biconical ANT	VHA9103	Schwarzbeck	1271	'2001.5.30.	'2002.5.30
Preamplifier	8447E	H.P	2944A06481	-	-

The calibration of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors are applied in accordance with instruments contained in the manual for the measuring instrument.

2. MEASUREMENT PROCEDURES

2.1 System Test Configuration

2.1.1 Video mode Justification

N/A

2.1.2 EUT Exercise Software


Connect the LCD MONITOR to PC.

On Windows98, under using "H" pattern EMI Test program test displaying it on a monitor.

2.2 Special Accessories

2.3 Equipment Modifications

No equipment modifications were performed during testing.



2.4 System Configuration Diagram

2.5 PRELIMINARY TESTING

It is often valuable to performing preliminary radiated measurements at a closer distance than specified for compliance to determine the emission characteristics of the EUT. At close-in distance, it is easier to determine the spectrum signature of EUT, and if applicable, the EUT configuration that emanate the maximum level of emissions. The data may not be precisely correlatable results.

2.6 SHIELDED ENCLOSURE

To search the Radiated frequency outline of an EUT a shielded screen room may be used. If the shielded room is used for radiated data, the data page will state that the EUT was in a shielded enclosure. All data collected in a screen room for radiated emissions is for frequency outline only. If an EUT is placed in screen room for Line Conducted Data, the data page will show that a screen room was used and data frequencies and levels will be correct and used for test data.

2.7 DATA REPORTING FORMAT

The measurement results expressed in accordance with C63.4 and specified limits where applicable are presented in tabular or graphical form, or alternatively as recorder charts or photographs of a spectrum analyzer display, showing the level vs. frequency.

2.8 OPERATING CONDITIONS

The EUT was operated at the specified load conditions(mechanical and/or electrical)for which it was designed.

2.9 CONDITIONING OF THE EUT

The EUT was operated for a sufficient period of time to approximate normal operating conditions.

2.10 Power line Conducted Emissions

The EUT is set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-1992. The measurements are performed in a 3m x 6m x 2.5m shielded room. A wooden table which height is 80 cm is located at the center of the shielded room; desktop EUTs are placed on top of this table. The rear of the EUT and table are placed 40 cm apart from the shielded room wall. All items on the table (or test-table) were placed at least 10 cm apart each other. Excess EUT power cord is folded back and forth to form a 30 cm by 40 cm bundle. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately in the middle between the ground plane and table. The EUT power cord was plugged into a LISN 80 cm away, while all other devices were plugged into a second LISN, also 80 cm away.

The highest emissions were also analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. On the other hand, the interconnecting cables were moved around the table to maximize the emissions, and the position of the peripheral devices were interchanged to check whether there is any changes in emissions.

2.11 Open field Radiated Emissions Tests

The EUT and support equipment are set up on the turntable in an open field site. Desktop EUTs are set up on a wooden stand (test-table), 80 cm above the ground plane. All items on the table were placed at least 10 cm apart each other. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately between the ground plane and table. The highest emissions were also analyzed, in detail, with the tuned aerial to search the precise amplitude of the emissions. On the other hand, the interconnecting cables were moved around the table and if the highest amplitudes is observed, the EUT is rotated in the horizontal plane while changing the antenna polarization to the vertical plane to maximize the field strength. Once the maximum field strength is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. The position of the peripheral devices are interchanged to check for any changes in emissions. In rare instances, the maximum field strength may occur with the antenna polarized between vertical and horizontal.

3. Measurement Data

3.1 CONDUCTED EMISSION DATA

TEST : LCD Monitor ; TM800

DATE : Aug. 11. 2001

Freq. (MHz)	EUT State	Polarity (H/N)	Level (Q.P) (dBì V)	LIMIT (Q.P) (dBì V)	Margin for(Q.P) (dBì V)
0.466	Refer to Note	N	32.6	48.0	15.4
0.523		N	34.0	48.0	14.0
0.581		H	33.1	48.0	14.9
0.639		H	31.6	48.0	16.4
0.698		H	31.5	48.0	16.5
0.755		H	32.8	48.0	15.2
0.929		H	31.9	48.0	16.1
1.161		H	33.0	48.0	15.0
1.393		N	36.9	48.0	11.1
1.567		N	35.2	48.0	12.8
1.625		N	37.0	48.0	11.0
1.857		N	37.9	48.0	10.1
2.609		N	40.2	48.0	7.8
5.104		N	31.2	48.0	16.8
5.392		H	26.9	48.0	21.1
5.564		H	27.1	48.0	20.9
5.621		H	28.2	48.0	19.8
7.880		H	32.9	48.0	15.1
8.054		H	34.1	48.0	13.9


Notes: Data was transmitted through LCD Monitor after installing network.

The test is implemented in a shielded room in accordance with ANSI C63.4


Test Engineer.



Reviewed by.



3.2 Conducted Emission Graph




Red : HOT LINE, Blue : Neutral LINE
LINE EMISSION GRAPH

3.2 RADIATED EMISSION DATA

TEST : LCD Monitor : TM800

DATE: Aug. 11. 2001

Freq. (MHz)	EUT State	Level (dB μ V/m)	Preamp -Pads (dB μ V/m)	Af (dB μ V/m)	Cl (dB μ V/m)	Hor. /Ver	ha(m) Azimuth	Total Results (dB μ V/m)	Limit (dB μ V/m)	Margin (dB μ V/m)
45.750	Refer to Note	37.53	21.20	13.27	0.9	V	1.0/100	30.5	40.0	9.5
52.276		34.51	21.20	11.39	0.9	V	1.0/90	25.6	40.0	14.4
63.457		41.50	21.00	7.80	0.9	V	1.0/80	29.2	40.0	10.8
78.411		39.09	20.80	6.41	1.1	V	1.0/340	25.8	40.0	14.2
84.932		36.19	20.70	7.01	1.2	V	1.0/340	23.7	40.0	16.3
130.674		26.93	19.90	14.17	1.4	V	1.0/0	22.6	43.5	20.9
140.631		26.47	20.20	14.63	1.6	V	1.0/30	22.5	43.5	21.0
162.357		26.72	20.50	15.58	1.8	V	1.0/120	23.6	43.5	19.9
225.005		26.69	20.40	17.61	2.1	V	1.0/0	26.0	46.0	20.0
359.289		37.06	20.40	14.54	3.1	H	2.3/120	34.3	46.0	11.7
391.956		37.95	20.80	15.75	3.2	H	2.3/120	36.1	46.0	9.9
424.622		36.53	21.20	16.27	3.4	H	2.0/110	35.0	46.0	11.0
457.279		40.39	21.20	16.61	3.7	H	2.0/120	39.5	46.0	6.5
685.923		27.51	21.40	21.59	4.5	H	2.0/90	32.2	46.0	13.8
787.264		29.84	21.10	22.36	4.9	H	2.0/280	36.0	46.0	10.0



Notes: The test is performed in a distance of 3m. Af : Antenna factor, Cl : Cable loss

The test is performed in accordance with ANSI C63.4

Test Engineer.

[Signature]

Reviewed by.

S. G. MOON

3.3 SUMMARY

Company	: NEWCOMM World CO., LTD.		
Equipment Under Test	: LCD Monitor		
Model Number	: TM800	Serial Number: Prototype	
Type of Test	: FCC CLASS B	Passed/Failed: PASSED	

The Equipment Under Test(EUT) was configured and operated in a manner which tends to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling, and physical placement of equipment were simulating the typical application and usage in so far as practicable.

LINE CONDUCTED TEST: An unshielded power cord was used to connect the EUT to a LISN Box which supplied 120VAC/60Hz power. The EUT was tested according to C63.4 test specifications. Line conductance scanned from 450KHz to 30 MHz range on both Line 1(hot side) and Line 2(neutral side). ***The highest emission was observed at 2.609MHz on Line 2 with a margin of 7.8dBuV from the limit.*** All line conductance emissions were within the FCC CLASS B requirements for compliance.

RADIATED TEST: The EUT was placed on a three meter open field test site according to C63.4 test specifications. Preliminary scans ranged from 30MHz to 1GHz in both vertical and horizontal polarizations in all possible modes of operation. The highest six point of emission levels were recorded as data each ranges of limit.

The highest emission was observed at 457.279MHz(Horizontal) with margin of 6.5 dBuV from the limit. All radiated emissions were within the FCC CLASS B requirements for compliance.