

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limit

Limits for general population/Uncontrolled exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm ²]	Averaging Time E ² , H ² or S [minutes]
0.3 - 1.34	614	1.63	(100)	30
1.34 - 30	824/f	2.19/f	(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1 500	--	--	f/1 500	30
1 500 - 100 000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance.

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Max tune up power	: -3.28 dBm (0.469 mW)
Prediction distance	: 20 cm
Predication frequency	: 2 425 MHz
Antenna gain(Max)	: 3.25 dBi (2.113 numeric)
Power density at predication frequency at 20 cm	: 0.000 197 57 mW/cm ²

MPE Limit for	: 1 mW/cm ²
---------------	------------------------

Test Result

The power density level at 20 cm is 0.000 197 57 mW/cm² which is below the uncontrolled exposure limit of 1 mW/cm² at 2 425 MHz to 2 475 MHz.