




The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2020 (FCC) & ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 (IC).

Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that parallel was worst-case orientation; therefore, all final radiated testing was performed with the EUT in parallel.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground for 30 MHz-1 GHz and 1.5 meters for above 1 GHz at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

5. Spectrum analyzer settings for $f < 1$ GHz:

- ① Span = wide enough to fully capture the emission being measured
- ② RBW = 120 kHz
- ③ VBW $\geq$ RBW
- ④ Detector = quasi peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold

6. Spectrum analyzer settings for $f \geq 1$ GHz: Peak

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW ≥ 3 MHz
- ④ Detector = peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold
- ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for $f \geq 1$ GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW $\geq 3 \times$ RBW
- ④ Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40\log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20\log(D_m/D_s)$
 Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. Field strength(dB μ V/m) = Level(dB μ V/m) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

FCC Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (μ V/m)
0.009 ~ 0.490	300	$2400/F(\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

**IC Limit**

According to RSS-Gen, Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits :

Frequency (MHz)	Distance (Meters)	Radiated ($\mu\text{V/m}$)
0.009 ~ 0.490	300	2 400 / F(kHz)
0.490 ~ 1.705	30	24 000 / F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960*	3	500

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

**Duty cycle**


Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T _{on} time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
LE 1 Mbps	2.125	2.500	0.85	85.00	0.71
SISO_802.11n_HT20 (MCS0)	1.338	1.485	0.90	90.10	0.46
MIMO_802.11n_HT20 (MCS8)	0.694	0.841	0.83	82.52	0.81

Duty cycle (Linear) = T_{on} time/Period


DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)





Test results (Below 30 MHz)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	39 (Worst case)




Note.

1. No spurious emission were detected under 30 MHz.



Mode: SISO_802.11n_HT20 (MCS0)_Ant 1
Distance of measurement: 3 meter
Channel: 6 (Worst case)




Note.
1. No spurious emission were detected under 30 MHz.

**Test results (Below 1 000 MHz)**

Mode: LE 1 Mbps

Distance of measurement: 3 meter


Channel: 39 (Worst case)

Horizontal // Vertical**Final Result**

No.	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	59.949	V	40.7	-13.8	26.9	40.0	13.1	110.0	0.0	
2	66.618	H	36.9	-15.7	21.2	40.0	18.8	378.0	59.1	
3	143.975	V	40.2	-17.0	23.2	43.5	20.3	103.0	256.7	
4	149.916	H	43.0	-17.4	25.6	43.5	17.9	192.0	330.3	
5	155.979	V	41.1	-16.9	24.2	43.5	19.3	116.0	209.8	
6	179.986	H	40.1	-15.0	25.1	43.5	18.4	213.0	209.3	
7	179.986	V	43.3	-15.0	28.3	43.5	15.2	134.0	0.0	
8	240.005	H	42.0	-12.2	29.8	46.0	16.2	105.0	104.4	
9	280.018	V	41.1	-11.1	30.0	46.0	16.0	128.0	72.0	
10	680.021	H	32.0	-2.8	29.2	46.0	16.8	103.0	29.8	
11	760.046	H	37.3	-1.2	36.1	46.0	9.9	103.0	287.4	
12	760.046	V	36.4	-1.2	35.2	46.0	10.8	100.0	119.6	



Mode: SISO_802.11n_HT20 (MCS0)_Ant 1
Distance of measurement: 3 meter
Channel: 6 (Worst case)



**Test results (Above 1 000 MHz)**


Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 0


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 000.10	43.36	Peak	V	-8.14	-	35.22	74.00	38.78
2 802.32	45.03	Peak	H	1.84	-	46.87	74.00	27.13
3 203.20	45.78	Peak	V	2.21	-	47.99	74.00	26.01

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 369.06	41.86	Peak	V	0.87	-	42.73	74.00	31.27
2 369.53	41.62	Peak	H	0.88	-	42.50	74.00	31.50





Note.


1. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 20

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 071.29	42.86	Peak	V	-7.72	-	35.14	74.00	38.86
2 848.92	44.62	Peak	H	1.87	-	46.49	74.00	27.51
3 255.70	42.17	Peak	V	2.32	-	44.49	74.00	29.51



Note.

1. Average test would be performed if the peak result were greater than the average limit.




Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 39


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 134.69	42.90	Peak	V	-7.34	-	35.56	74.00	38.44
2 893.71	43.39	Peak	H	1.89	-	45.28	74.00	28.72

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 497.95	41.82	Peak	V	1.35	-	43.17	74.00	30.83
2 497.68	42.05	Peak	H	1.35	-	43.40	74.00	30.60





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Mode: SISO_802.11n_HT20 (MCS0)_Ant 1

Distance of measurement: 3 meter


Channel: 1


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 009.90	53.43	Peak	V	-8.09	-	45.34	74.00	28.66
1 031.70	51.03	Peak	H	-7.96	-	43.07	74.00	30.93
1 097.29	49.36	Peak	H	-7.57	-	41.79	74.00	32.21
1 187.68	51.20	Peak	V	-7.03	-	44.17	74.00	29.83

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 387.49	50.42	Peak	H	0.99	-	51.41	74.00	22.59
2 388.24	44.86	Peak	V	0.99	-	45.85	74.00	28.15





Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Mode: SISO_802.11n_HT20 (MCS0)_Ant 1
Distance of measurement: 3 meter
Channel: 6

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.10	53.17	Peak	V	-8.14	-	45.03	74.00	28.97
1 030.30	51.92	Peak	H	-7.96	-	43.96	74.00	30.04
1 095.09	52.32	Peak	V	-7.58	-	44.74	74.00	29.26
1 496.25	46.88	Peak	H	-4.98	-	41.90	74.00	32.10



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: SISO_802.11n_HT20 (MCS0)_Ant 1
Distance of measurement: 3 meter
Channel: 11


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 009.30	53.17	Peak	V	-8.09	-	45.08	74.00	28.92
1 031.30	51.46	Peak	H	-7.96	-	43.50	74.00	30.50
1 192.28	52.21	Peak	V	-7.00	-	45.21	74.00	28.79
1 494.05	46.28	Peak	H	-5.00	-	41.28	74.00	32.72

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 483.84	44.09	Peak	H	1.31	-	45.40	74.00	28.60
2 487.04	42.29	Peak	V	1.32	-	43.61	74.00	30.39





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Mode: SISO_802.11n_HT20 (MCS0)_Ant 2

Distance of measurement: 3 meter


Channel: 1


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 001.30	53.48	Peak	V	-8.14	-	45.34	74.00	28.66
1 013.50	50.62	Peak	H	-8.06	-	42.56	74.00	31.44
1 188.88	51.76	Peak	V	-7.02	-	44.74	74.00	29.26
1 499.65	46.77	Peak	H	-4.96	-	41.81	74.00	32.19

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 387.56	44.12	Peak	V	0.99	-	45.11	74.00	28.89
2 387.87	50.10	Peak	H	0.99	-	51.09	74.00	22.91





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.