



FCC RADIO TEST REPORT

FCC ID : PGR-WMD3M91QTA
Equipment : CBRS GW WITH DUAL BAND 11AC WIFI AND VOIP
Brand Name : ARRIS
Model Name : NVG558CH
Marketing Name : CBRS GW WITH DUAL BAND 11AC WIFI AND VOIP
Applicant : ARRIS
2500 Walsh Avenue, Santa Clara, California, United States 95051
Manufacturer : ARRIS
2500 Walsh Avenue, Santa Clara, California, United States 95051
Standard : FCC 47 CFR Part 2, 96

The product was received on Jun. 01, 2020 and testing was started from Jun. 01, 2020 and completed on Jul. 06, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applied Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration	8
2.4 Measurement Results Explanation Example	8
2.5 Frequency List of Low/Middle/High Channels.....	9
3 Conducted Test Items.....	10
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power	12
3.3 Peak-to-Average Ratio	13
3.4 EIRP	14
3.5 Occupied Bandwidth	15
3.6 Conducted Band Edge	16
3.7 Conducted Spurious Emission	17
3.8 Frequency Stability	18
4 Radiated Test Items	19
4.1 Measuring Instruments.....	19
4.2 Test Setup	19
4.3 Test Result of Radiated Test.....	20
4.4 Radiated Spurious Emission	21
5 List of Measuring Equipment.....	22
6 Uncertainty of Evaluation	24
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of EIRP and Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FG9O0819-02	01	Initial issue of report	Jul. 16, 2020
FG9O0819-02	02	1. Revise Applicant and Manufacturer's address 2. Revise Antenna information 3. Revise Conducted Setup Photo	Jul. 17, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
3.3	§96.41	Peak-to-Average Ratio	Pass	
3.4	§96.41	Effective Isotropic Radiated Power	Pass	-
3.5	§2.1049 §96.41	Occupied Bandwidth	Reporting only	-
3.6	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	-
3.7	§2.1051 §96.41	Conducted Spurious Emission	Pass	
3.8	§2.1055	Frequency Stability for Temperature & Voltage	Pass	-
4.4	§2.1051 §96.41	Radiated Spurious Emission	Pass	Under limit 0.2 dB at 7400.000 MHz for Internal Antenna Under limit 0.28 dB at 7268.000 MHz for External Antenna

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Vivian Hsu



1 General Description

1.1 Product Feature of Equipment Under Test

LTE

Product Specification subjective to this standard	
Antenna Type/Antenna Gain	Internal CBRS Main Antenna/5.1 dBi Internal CBRS Rx Diversity/5.1 dBi External CBRS Main Antenna/3.5 dBi External CBRS Rx Diversity/3.5 dBi

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH05-HY
Test Engineer	Jacky Wang
Temperature	21.2~23.6℃
Relative Humidity	50~64%

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature	22~26℃
Relative Humidity	58~62%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007



1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 96
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.


2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	48	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	48	-	-	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	48	-	-	v	v	v	v	v	v	v	v		v	v		v
Peak-to-Average Ratio	48	-	-				v	v	v	v	v		v	v	v	v
Conducted Spurious Emission	48	-	-	v	v	v	v	v	v	v	v		v	v	v	v
E.I.R.P	48	-	-	v	v	v	v	v	v	v	v			v	v	v
Frequency Stability	48	-	-		v			v	v	v	v			v	v	v
Radiated Spurious Emission	48	Worst Case												v	v	v
Remark	1. The mark “v ” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$



2.5 Frequency List of Low/Middle/High Channels


LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560.0	3625.0	3690.0
15	Channel	55315	55990	56665
	Frequency	3557.5	3625.0	3692.5
10	Channel	55290	55990	56690
	Frequency	3555.0	3625.0	3695.0
5	Channel	55265	55990	56715
	Frequency	3552.5	3625.0	3697.5

3 Conducted Test Items


3.1 Measuring Instruments

See list of measuring instruments of this test report.


3.1.1 Conducted Output Power



3.1.2 EIRP, Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.3 Frequency Stability



3.1.4 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power

3.2.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio



3.4 EIRP

3.4.1 Description of the EIRP Measurement

The EIRP of mobile transmitters must not exceed 23 dBm /10 megahertz for LTE Band 42 and Band 43, and Band 48.

The testing follows ANSI C63.26-2015 Section 5.2.5.5

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

Device	Maximum EIRP (dBm/10 MHz)
End User Device	23

3.4.2 Test Procedures

The testing follows procedure in Section 5.2 of ANSI C63.26-2015 and KDB 940660 D01 Part 96 Eqpt v02 Section 3.2(b)

Determine the EIRP by adding the effective antenna gain to the measured average conducted power level.

3.5 Occupied Bandwidth

3.5.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.5.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.6 Conducted Band Edge

3.6.1 Description of Conducted Band Edge Measurement

The conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted power of any End User Device emission shall not exceed -25 dBm/MHz. Notwithstanding the emission limits in this paragraph, the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Adjacent Channel Leakage Ratio (ACLR) measurement,

1. The Adjacent Channel Leakage Ratio (ACLR) is the ratio of the average power in the assigned aggregated channel bandwidth to the average power over the equivalent adjacent channel bandwidth.
2. The option ACLR of spectrum analyzer is used and measures the ACLR ratio by setting equivalent channel bandwidth.

The measured ACLR ratio shall be at least 30 dB.

3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

Emission and interference limits: the device satisfies the emission limits specified in Section FCC Part 96.41 e) 1) ii) & e) 2) at the lowest and highest edges of the band, and in the middle of the band.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is -40dBm/MHz.

3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



For radiated emissions above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is -40dBm/MHz



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Base Station (Measure)	Anritsu	MT8821C	62620025341	N/A	Oct. 24, 2019	Jun. 19, 2020~Jul. 06, 2020	Oct. 23, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 15, 2019	Jun. 19, 2020~Jul. 06, 2020	Nov. 14, 2020	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃~90℃	Sep. 02, 2019	Jun. 19, 2020~Jul. 06, 2020	Sep. 01, 2020	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 09, 2019	Jun. 19, 2020~Jul. 06, 2020	Oct. 08, 2020	Conducted (TH05-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#B	1-18GHz	Jan. 14, 2019	Jun. 19, 2020~Jul. 06, 2020	Jan. 13, 2020	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jun. 01, 2020~Jun. 19, 2020	Dec. 25, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	37059 & 01	30MHz~1GHz	Oct. 12, 2019	Jun. 01, 2020~Jun. 19, 2020	Oct. 11, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Nov. 14, 2019	Jun. 01, 2020~Jun. 19, 2020	Nov. 13, 2020	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz~40GHz	Dec. 10, 2019	Jun. 01, 2020~Jun. 19, 2020	Dec. 09, 2020	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2020	Jun. 01, 2020~Jun. 19, 2020	Mar. 24, 2021	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Dec. 20, 2019	Jun. 01, 2020~Jun. 19, 2020	Dec. 19, 2020	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Aug. 06, 2019	Jun. 01, 2020~Jun. 19, 2020	Aug. 05, 2020	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 13, 2019	Jun. 01, 2020~Jun. 19, 2020	Dec. 12, 2020	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Mar. 12, 2020	Jun. 01, 2020~Jun. 19, 2020	Mar. 11, 2021	Radiation (03CH12-HY)
Base Station	Rohde & Schwarz	CMW500	132252	GSM/GPRS/WC DMA/FD-LTE/TD-LTE/MIMO	Aug. 22, 2018	Jun. 01, 2020~Jun. 19, 2020	Aug. 21, 2020	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMB100A	101107	100kHz~40GHz	Aug. 27, 2019	Jun. 01, 2020~Jun. 19, 2020	Aug. 26, 2020	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872.5-6750-18000-40ST	SN2	6.75GHz High Pass Filter	Mar. 18, 2020	Jun. 01, 2020~Jun. 19, 2020	Mar. 17, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 12, 2019	Jun. 01, 2020~Jun. 19, 2020	Dec. 11, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 25, 2020	Jun. 01, 2020~Jun. 19, 2020	Feb. 24, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 25, 2020	Jun. 01, 2020~Jun. 19, 2020	Feb. 24, 2021	Radiation (03CH12-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303B	TP140349	N/A	Oct. 25, 2019	Jun. 01, 2020~ Jun. 19, 2020	Oct. 24, 2020	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 01, 2020~ Jun. 19, 2020	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Jun. 01, 2020~ Jun. 19, 2020	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 01, 2020~ Jun. 19, 2020	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-00098 9	N/A	N/A	Jun. 01, 2020~ Jun. 19, 2020	N/A	Radiation (03CH12-HY)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.24
--	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.62
--	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.06
--	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

<Internal Antenna>

LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	17.35	17.36	16.79
20	1	49		16.87	16.93	16.35
20	1	99		17.38	17.38	16.87
20	50	0		16.97	17.03	16.40
20	50	24		16.93	16.93	16.39
20	50	50		17.07	17.05	16.54
20	100	0		17.04	17.07	16.45
20	1	0	16-QAM	17.82	17.82	17.31
20	1	49		17.46	17.47	16.84
20	1	99		17.87	17.86	17.41
20	50	0		16.95	17.02	16.41
20	50	24		16.90	16.97	16.33
20	50	50		17.06	17.03	16.49
20	100	0		17.03	17.04	16.39
20	1	0	64-QAM	17.62	17.63	16.92
20	1	49		17.16	17.20	16.62
20	1	99		17.73	17.68	17.19
20	50	0		17.08	17.09	16.43
20	50	24		16.96	16.98	16.40
20	50	50		17.09	17.10	16.56
20	100	0		17.11	17.13	16.54
15	1	0	QPSK	15.68	15.74	15.11
15	1	37		16.83	16.91	16.38
15	1	74		15.69	15.73	15.20
15	36	0		16.27	16.29	15.72
15	36	20		16.64	16.67	16.08
15	36	39		16.27	16.32	15.77
15	75	0		16.26	16.35	15.77
15	1	0	16-QAM	16.17	16.25	15.68
15	1	37		17.40	17.47	16.87
15	1	74		16.26	16.28	15.73
15	36	0		16.20	16.30	15.69
15	36	20		16.62	16.65	16.04
15	36	39		16.26	16.31	15.75
15	75	0		16.25	16.34	15.74
15	1	0	64-QAM	15.66	15.72	15.13
15	1	37		16.87	16.92	16.37
15	1	74		15.80	15.81	15.26
15	36	0		16.33	16.38	15.81
15	36	20		16.70	16.77	16.13
15	36	39		16.39	16.44	15.87
15	75	0		16.31	16.37	15.78



LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	15.97	16.15	15.53
10	1	25		16.86	17.03	16.40
10	1	49		16.06	16.15	15.57
10	25	0		16.45	16.55	15.98
10	25	12		16.68	16.74	16.15
10	25	25		16.47	16.58	15.94
10	50	0		16.41	16.56	15.94
10	1	0		16.58	16.63	16.07
10	1	25	16-QAM	17.45	17.56	16.99
10	1	49		16.68	16.67	16.12
10	25	0		16.51	16.55	16.03
10	25	12		16.74	16.82	16.22
10	25	25		16.54	16.57	16.02
10	50	0		16.38	16.50	15.92
10	1	0		16.20	16.25	15.64
10	1	25		17.06	17.17	16.57
10	1	49	64-QAM	16.25	16.34	15.76
10	25	0		16.51	16.61	16.02
10	25	12		16.75	16.87	16.26
10	25	25		16.55	16.65	16.08
10	50	0		16.49	16.60	15.98
5	1	0		16.41	16.50	15.88
5	1	12		16.77	16.93	16.26
5	1	24		16.44	16.47	15.90
5	12	0	QPSK	16.54	16.59	16.03
5	12	7		16.70	16.74	16.14
5	12	13		16.57	16.64	15.98
5	25	0		16.62	16.66	15.98
5	1	0		16.99	17.04	16.40
5	1	12		17.38	17.45	16.75
5	1	24		17.04	17.10	16.42
5	12	0		16.54	16.58	15.94
5	12	7	16-QAM	16.70	16.77	16.08
5	12	13		16.55	16.64	15.99
5	25	0		16.64	16.67	15.97
5	1	0		16.74	16.77	16.11
5	1	12		17.10	17.18	16.56
5	1	24		16.80	16.83	16.17
5	12	0		16.57	16.66	16.01
5	12	7		16.80	16.85	16.16
5	12	13	64-QAM	16.68	16.67	16.01
5	25	0		16.60	16.68	16.02

**<External antenna>**

LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	16.53	17.20	17.04
20	1	49		16.43	16.76	16.68
20	1	99		17.00	17.26	17.26
20	50	0		16.62	16.92	16.79
20	50	24		16.46	16.87	16.72
20	50	50		16.71	16.99	16.96
20	100	0		16.69	16.97	16.83
20	1	0	16-QAM	17.30	17.78	17.61
20	1	49		17.06	17.40	17.29
20	1	99		17.69	17.79	17.80
20	50	0		16.58	16.92	16.70
20	50	24		16.53	16.83	16.67
20	50	50		16.72	16.96	16.93
20	100	0		16.65	16.94	16.83
20	1	0	64-QAM	17.13	17.49	17.30
20	1	49		16.89	17.16	17.01
20	1	99		17.36	17.67	17.61
20	50	0		16.72	16.98	16.80
20	50	24		16.73	16.92	16.77
20	50	50		16.76	17.07	16.99
20	100	0		16.80	16.97	16.92
15	1	0	QPSK	15.29	15.58	15.45
15	1	37		16.50	16.85	16.70
15	1	74		15.37	15.65	15.62
15	36	0		15.89	16.24	16.07
15	36	20		16.34	16.62	16.52
15	36	39		15.91	16.21	16.22
15	75	0		15.97	16.23	16.14
15	1	0	16-QAM	15.86	16.12	15.93
15	1	37		17.12	17.33	17.21
15	1	74		16.00	16.20	16.22
15	36	0		15.86	16.12	16.00
15	36	20		16.25	16.52	16.47
15	36	39		15.96	16.19	16.17
15	75	0		15.93	16.21	16.08
15	1	0	64-QAM	15.59	15.87	15.74
15	1	37		16.90	17.09	17.02
15	1	74		15.75	16.00	15.97
15	36	0		16.01	16.26	16.16
15	36	20		16.43	16.67	16.57
15	36	39		16.10	16.34	16.31
15	75	0		16.06	16.26	16.19



LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	15.74	16.03	15.90
10	1	25		16.60	16.95	16.81
10	1	49		15.78	16.05	16.00
10	25	0		16.15	16.46	16.36
10	25	12		16.40	16.70	16.58
10	25	25		16.22	16.49	16.43
10	50	0		16.19	16.46	16.35
10	1	0	16-QAM	16.29	16.53	16.49
10	1	25		17.24	17.46	17.37
10	1	49		16.37	16.61	16.59
10	25	0		16.18	16.46	16.35
10	25	12		16.38	16.67	16.60
10	25	25		16.20	16.50	16.42
10	50	0		16.17	16.43	16.40
10	1	0	64-QAM	16.08	16.28	16.23
10	1	25		16.99	17.19	17.19
10	1	49		16.16	16.39	16.37
10	25	0		16.24	16.46	16.37
10	25	12		16.47	16.70	16.70
10	25	25		16.34	16.54	16.51
10	50	0		16.24	16.59	16.48
5	1	0	QPSK	16.26	16.55	16.37
5	1	12		16.60	16.91	16.71
5	1	24		16.25	16.58	16.38
5	12	0		16.35	16.68	16.51
5	12	7		16.49	16.79	16.63
5	12	13		16.38	16.70	16.54
5	25	0		16.36	16.68	16.53
5	1	0	16-QAM	16.78	17.05	16.91
5	1	12		17.21	17.52	17.28
5	1	24		16.82	17.10	16.93
5	12	0		16.46	16.73	16.62
5	12	7		16.65	16.86	16.70
5	12	13		16.49	16.78	16.61
5	25	0		16.34	16.65	16.51
5	1	0	64-QAM	16.54	16.85	16.66
5	1	12		17.00	17.22	17.11
5	1	24		16.59	16.92	16.73
5	12	0		16.48	16.73	16.57
5	12	7		16.63	16.90	16.67
5	12	13		16.48	16.77	16.67
5	25	0		16.43	16.76	16.62



LTE Band 48


Peak-to-Average Ratio

Mode	LTE Band 48 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	6.03	5.57	6.58	6.32	PASS
Middle CH	5.80	5.54	6.38	6.26	
Highest CH	5.83	5.48	6.49	6.23	
Mode	LTE Band 48 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	6.09	6.43	-	-	PASS
Middle CH	5.97	6.32	-	-	
Highest CH	6.00	6.17	-	-	




LTE Band 48 / 20MHz / QPSK


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 48 / 20MHz / 16QAM


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB






LTE Band 48 / 20MHz / 64QAM

Lowest Channel / 1RB



Date: 23 JUN 2020 16:15:54

Lowest Channel / Full RB



Date: 23 JUN 2020 16:16:55

Middle Channel / 1RB




Date: 23 JUN 2020 16:17:25

Middle Channel / Full RB




Date: 23 JUN 2020 16:18:39

Highest Channel / 1RB



Date: 23 JUN 2020 16:19:02

Highest Channel / Full RB



Date: 23 JUN 2020 16:19:27


**26dB Bandwidth**

Mode	LTE Band 48 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	5.73	4.89	10.35	9.85	16.03	14.09	19.78	19.34
Middle CH	-	-	-	-	5.51	5.09	10.17	10.25	15.32	14.30	19.30	18.62
Highest CH	-	-	-	-	5.27	5.51	10.59	11.23	15.73	14.15	19.34	19.34
Mode	LTE Band 48 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	5.04	-	10.43	-	14.06	-	20.02	-
Middle CH	-	-	-	-	5.60	-	10.09	-	14.78	-	19.42	-
Highest CH	-	-	-	-	4.80	-	11.35	-	14.75	-	19.70	-




LTE Band 48

Lowest Channel / 5MHz / QPSK




Date: 23 JUN 2020 16:00:36

Lowest Channel / 5MHz / 16QAM




Date: 23 JUN 2020 16:00:48

Middle Channel / 5MHz / QPSK




Date: 23 JUN 2020 16:01:23

Middle Channel / 5MHz / 16QAM




Date: 23 JUN 2020 16:01:35

Highest Channel / 5MHz / QPSK



Date: 23 JUN 2020 16:02:11

Highest Channel / 5MHz / 16QAM




Date: 23 JUN 2020 16:02:24



LTE Band 48

Lowest Channel / 10MHz / QPSK




Date: 23 JUN 2020 16 03:01

Lowest Channel / 10MHz / 16QAM



Date: 23 JUN 2020 16 03:13

Middle Channel / 10MHz / QPSK



Date: 23 JUN 2020 16 03:48

Middle Channel / 10MHz / 16QAM




Date: 23 JUN 2020 16 03:59

Highest Channel / 10MHz / QPSK



Date: 23 JUN 2020 16 04:36

Highest Channel / 10MHz / 16QAM




Date: 23 JUN 2020 16 04:48




LTE Band 48


Lowest Channel / 15MHz / QPSK




Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK




Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK




Highest Channel / 15MHz / 16QAM






LTE Band 48

Lowest Channel / 20MHz / QPSK




Date: 23 JUN 2020 16 07 50

Lowest Channel / 20MHz / 16QAM




Date: 23 JUN 2020 16 08 02

Middle Channel / 20MHz / QPSK




Date: 23 JUN 2020 16 08 37

Middle Channel / 20MHz / 16QAM




Date: 23 JUN 2020 16 08 49

Highest Channel / 20MHz / QPSK



Date: 23 JUN 2020 16 09 25

Highest Channel / 20MHz / 16QAM




Date: 23 JUN 2020 16 09 37




LTE Band 48

Lowest Channel / 5MHz / 64QAM




Date: 23 JUN 2020 16:10:02

Lowest Channel / 10MHz / 64QAM




Date: 23 JUN 2020 16:11:14

Middle Channel / 5MHz / 64QAM




Date: 23 JUN 2020 16:10:25

Middle Channel / 10MHz / 64QAM



Date: 23 JUN 2020 16:11:38

Highest Channel / 5MHz / 64QAM



Date: 23 JUN 2020 16:10:50

Highest Channel / 10MHz / 64QAM




Date: 23 JUN 2020 16:12:02




LTE Band 48


Lowest Channel / 15MHz / 64QAM




Lowest Channel / 20MHz / 64QAM



Middle Channel / 15MHz / 64QAM




Middle Channel / 20MHz / 64QAM



Highest Channel / 15MHz / 64QAM



Highest Channel / 20MHz / 64QAM




**Occupied Bandwidth**

Mode	LTE Band 48 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.50	4.45	9.09	9.01	13.52	13.49	17.90	17.94
Middle CH	-	-	-	-	4.52	4.53	9.11	9.11	13.34	13.46	17.94	17.86
Highest CH	-	-	-	-	4.58	4.52	9.05	9.05	13.31	13.40	17.90	17.98
Mode	LTE Band 48 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.51	-	8.97	-	13.49	-	17.94	-
Middle CH	-	-	-	-	4.53	-	8.93	-	13.37	-	17.90	-
Highest CH	-	-	-	-	4.54	-	9.01	-	13.40	-	17.98	-




LTE Band 48


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK




Highest Channel / 5MHz / 16QAM






LTE Band 48

Lowest Channel / 10MHz / QPSK




Date: 23 JUN 2020 16 02 36

Lowest Channel / 10MHz / 16QAM




Date: 23 JUN 2020 16 02 48

Middle Channel / 10MHz / QPSK




Date: 23 JUN 2020 16 03 25

Middle Channel / 10MHz / 16QAM




Date: 23 JUN 2020 16 03 36

Highest Channel / 10MHz / QPSK



Date: 23 JUN 2020 16 04 11

Highest Channel / 10MHz / 16QAM




Date: 23 JUN 2020 16 04 24




LTE Band 48


Lowest Channel / 15MHz / QPSK




Lowest Channel / 15MHz / 16QAM




Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK




Highest Channel / 15MHz / 16QAM






LTE Band 48


Lowest Channel / 20MHz / QPSK




Lowest Channel / 20MHz / 16QAM




Middle Channel / 20MHz / QPSK




Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK




Highest Channel / 20MHz / 16QAM






LTE Band 48


Lowest Channel / 5MHz / 64QAM




Lowest Channel / 10MHz / 64QAM




Middle Channel / 5MHz / 64QAM




Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM




Highest Channel / 10MHz / 64QAM






LTE Band 48


Lowest Channel / 15MHz / 64QAM




Lowest Channel / 20MHz / 64QAM




Middle Channel / 15MHz / 64QAM




Middle Channel / 20MHz / 64QAM



Highest Channel / 15MHz / 64QAM



Highest Channel / 20MHz / 64QAM






ACLR


LTE Band 48 / 5MHz

QPSK


Lowest Channel / 1RB0



Lowest Channel / 1RBmax



Lowest Channel / FullRB




N/A



LTE Band 48 / 5MHz


QPSK

Middle Channel / 1RB0




Date: 6 JUL 2020 21:21:40

Middle Channel / 1RBmax



Date: 6 JUL 2020 21:25:15

Middle Channel / FullRB



Date: 6 JUL 2020 21:10:05


N/A




LTE Band 48 / 5MHz

QPSK

Highest Channel / 1RB0



Highest Channel / 1RBmax



Highest Channel / FullRB




N/A




LTE Band 48 / 10MHz

QPSK


Lowest Channel / 1RB0



Lowest Channel / 1RBmax



Lowest Channel / FullRB




N/A




LTE Band 48 / 10MHz

QPSK


MiddleChannel / 1RB0



Middle Channel / 1RBmax



Middle Channel / FullRB




N/A



LTE Band 48 / 10MHz


QPSK

Highest Channel / 1RB0




Date: 6 JUL 2020 22:28:18

Highest Channel / 1RBmax



Date: 6 JUL 2020 22:21:34

Highest Channel / FullRB



Date: 6 JUL 2020 22:29:37


N/A




LTE Band 48 / 15MHz

QPSK

Lowest Channel / 1RB0




Lowest Channel / 1RBmax



Lowest Channel / FullRB

N/A







LTE Band 48 / 15MHz

QPSK


Middle Channel / 1RB0



Middle Channel / 1RBmax



Middle Channel / FullRB




N/A




LTE Band 48 / 15MHz

QPSK


Highest Channel / 1RB0



Highest Channel / 1RBmax



Highest Channel / FullRB




N/A




LTE Band 48 / 20MHz

QPSK


Lowest Channel / 1RB0



Lowest Channel / 1RBmax



Lowest Channel / FullRB




N/A



LTE Band 48 / 20MHz


QPSK

Middle Channel / 1RB0




Date: 7 JUL 2020 00:57:11

Middle Channel / 1RBmax



Date: 7 JUL 2020 00:55:51

Middle Channel / FullRB



Date: 7 JUL 2020 01:03:37


N/A



LTE Band 48 / 20MHz


QPSK

Highest Channel / 1RB0




Date: 7 JUL 2020 01:11:55

Highest Channel / 1RBmax



Date: 7 JUL 2020 01:12:15

Highest Channel / FullRB



Date: 7 JUL 2020 01:05:09


N/A



LTE Band 48 / 5MHz


16QAM

Lowest Channel / 1RB0




Date: 6 JUL 2020 20:49:03

Lowest Channel / 1RBmax



Date: 6 JUL 2020 20:54:59

Lowest Channel / FullRB



Date: 6 JUL 2020 20:59:47


N/A



LTE Band 48 / 5MHz


16QAM

Middle Channel / 1RB0




Date: 6 JUL 2020 21:19:08

Middle Channel / 1RBmax



Date: 6 JUL 2020 21:26:37

Middle Channel / FullRB



Date: 6 JUL 2020 21:11:31


N/A



LTE Band 48 / 5MHz


16QAM

Highest Channel / 1RB0




Date: 6 JUL 2020 21:41:55

Highest Channel / 1RBmax



Date: 6 JUL 2020 21:37:35

Highest Channel / FullRB



Date: 6 JUL 2020 21:48:52


N/A




LTE Band 48 / 10MHz

16QAM

Lowest Channel / 1RB0




Lowest Channel / 1RBmax



Lowest Channel / FullRB

N/A







LTE Band 48 / 10MHz

16QAM

MiddleChannel / 1RB0




Middle Channel / 1RBmax



Middle Channel / FullRB

N/A







LTE Band 48 / 10MHz

16QAM


Highest Channel / 1RB0



Highest Channel / 1RBmax



Highest Channel / FullRB




N/A




LTE Band 48 / 15MHz

16QAM


Lowest Channel / 1RB0



Lowest Channel / 1RBmax



Lowest Channel / FullRB




N/A



LTE Band 48 / 15MHz


16QAM

Middle Channel / 1RB0




Date: 6 JUL 2020 23:22:12

Middle Channel / 1RBmax



Date: 6 JUL 2020 23:18:58

Middle Channel / FullRB



Date: 6 JUL 2020 23:28:13


N/A




LTE Band 48 / 15MHz

16QAM


Highest Channel / 1RB0



Highest Channel / 1RBmax



Highest Channel / FullRB




N/A




LTE Band 48 / 20MHz

16QAM


Lowest Channel / 1RB0



Lowest Channel / 1RBmax



Lowest Channel / FullRB




N/A




LTE Band 48 / 20MHz

16QAM


Middle Channel / 1RB0



Middle Channel / 1RBmax



Middle Channel / FullRB




N/A




LTE Band 48 / 20MHz

16QAM


Highest Channel / 1RB0



Highest Channel / 1RBmax



Highest Channel / FullRB




N/A




LTE Band 48 / 5MHz

64QAM

Lowest Channel / 1RB0




Lowest Channel / 1RBmax



Lowest Channel / FullRB

N/A







LTE Band 48 / 5MHz

64QAM


Middle Channel / 1RB0



Middle Channel / 1RBmax



Middle Channel / FullRB




N/A



LTE Band 48 / 5MHz


64QAM

Highest Channel / 1RB0




Date: 6 JUL 2020 21:43:42

Highest Channel / 1RBmax



Date: 6 JUL 2020 21:31:46

Highest Channel / FullRB



Date: 6 JUL 2020 21:45:22


N/A



LTE Band 48 / 10MHz


64QAM

Lowest Channel / 1RB0




Date: 6 JUL 2020 21:58:04

Lowest Channel / 1RBmax



Date: 6 JUL 2020 21:57:18

Lowest Channel / FullRB



Date: 6 JUL 2020 22:03:48

N/A