



EMC Test Data

Client:	Pace Americas, Inc.	Job Number:	J98591
Model:	HR54-700	T-Log Number:	T98678
Contact:	Mark Rieger	Project Manager:	Irene Radamacher
Standard:	FCC 15.247, 15.407	Project Coordinator:	-
		Class:	N/A

Maximum Permissible Exposure / SAR Exclusion

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 8/3/2015

Test Engineer: Mark Hill

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	Yes
---	-----

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Pace Americas, Inc.	Job Number:	J98591
Model:	HR54-700	T-Log Number:	T98678
Contact:	Mark Rieger	Project Manager:	Irene Radamacher
Standard:	FCC 15.247, 15.407	Project Coordinator:	-
		Class:	N/A

FCC MPE Calculation

Use: General
 Antenna: Wifi - 2.4GHz: 3.3dBi; 5Gz: 4.1dBi
 RF4CE: 4.9dBi

Band	Mode	Output Power		Antenna gain (Max)	EIRP		Channels Available	Channels Used	Total EIRP	
		Peak	Average		dBm	W			W	dBm
2412 - 2462	OFDM		22.8	3.3	26.1	0.407	11	-		
2412 - 2462	CCK		20.3	3.3	23.6	0.229				
2425 - 2475	RF4CE		-0.9	4.9	4.0	0.003	1	1	0.003	4.00
5150 - 5250	OFDM		22.2	4.1	26.3	0.427	4	1	0.427	26.30
5250 - 5350	OFDM		21.6	4.1	25.7	0.372	4	-		
5470 - 5725	OFDM		22.2	4.1	26.3	0.427	11	-		
5725 - 5850	OFDM		22.0	4.1	26.1	0.407	5	-		
Totals:								2	0.429	26.33

Worse Case RF Exposure condition: Operation in the UNII1 (or 2c) band + RF4CE

FCC MPE Total

Total EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
429.09	0.085	1.000

Note: Manufacturer stated that the measured powers represent the maximum shipping power, including tolerances.