

FCC - TEST REPORT

Report Number : 68.950.18.0526.01 Date of Issue: March 01, 2019

Model : Buckshot Pro Ultra (OT2351), OT2351-B, OT2351-SB, OT2351-MO

Product Type : Bluetooth Speaker

Applicant : The Ketchum Group, Inc. dba Outdoor Technology

Address : 25231 Paseo De Alicia, Ste. 200 Laguna Hills, CA 92653

Factory : Shenzhen Accolade Sound Technology Co., Ltd.

Address : No.3010 Room, C1 Building, Yitian Industrial Area, Yantian

: Community, Xixiang Street, Bao'an District, Shenzhen, China.

Test Result : **n Positive** **o Negative**

Total pages including
Appendices : 52

TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025. TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH issued reports. This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted Emission.....	10
9.2	Conducted peak output power.....	13
9.3	20 dB bandwidth and 99% Occupied Bandwidth.....	20
9.4	Carrier Frequency Separation	30
9.5	Number of hopping frequencies.....	33
9.6	Dwell Time	35
9.7	Spurious RF conducted emissions.....	38
9.8	Band edge testing	42
9.9	Spurious radiated emissions for transmitter	47
10	Test Equipment List.....	51
11	System Measurement Uncertainty.....	52



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint
Road 2, Nanshan District
Shenzhen 518052
P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 8288 5299

FCC Registration No.: 514049

3 Description of the Equipment Under Test

Product:	Bluetooth Speaker
Model no.:	Buckshot Pro Ultra (OT2351), OT2351-B, OT2351-SB, OT2351-MO
FCC ID:	PGWOT2351
Options and accessories:	USB Cable
Rating:	3.7VDC, 2600mAh(Supplied by Lithium ion rechargeable battery cell) Input:5VDC, 1A (Charged by USB port) Output: 5VDC, 1A
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Bluetooth Speaker operated at 2.4GHz

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2017 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to Public Notice DA 00-705 -Frequency Hopper Spread Spectrum Test Procedure released by FCC on March 30, 2000 and ANSI C63.10-2013.

5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Result	Test Site
§15.207	Conducted emission AC power port	10	N/A	Site 1
§15.247(b)(1)	Conducted peak output power	13	Pass	Site 1
§15.247(e)	Power spectral density*	--	N/A	--
§15.247(a)(2)	6dB bandwidth	--	N/A	--
§15.247(a)(1)	20dB bandwidth and 99% Occupied Bandwidth	20	Pass	Site 1
§15.247(a)(1)	Carrier frequency separation	30	Pass	Site 1
§15.247(a)(1)(iii)	Number of hopping frequencies	33	Pass	Site 1
§15.247(a)(1)(iii)	Dwell Time	35	Pass	Site 1
§15.247(d)	Spurious RF conducted emissions	38	Pass	Site 1
§15.247(d)	Band edge	42	Pass	Site 1
§15.247(d) & §15.209 & §15.205	Spurious radiated emissions for transmitter and receiver	47	Pass	Site 1
§15.203	Antenna requirement	See note 1	Pass	--

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a PCB antenna, which gain is 0dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: PGWOT2351, complies with Section 15.205, 15.209, 15.247 of the FCC Part 15, Subpart C rules.

Buckshot Pro Ultra (OT2351) is a Bluetooth Speaker with Bluetooth function (Only support BDR+EDR). The TX and RX range is 2402MHz-2480MHz.

All models are same except for the appearance colour difference. So the tests were applied on Buckshot Pro Ultra (OT2351), other models are deemed to fulfil the EMC test without further testing.

SUMMARY:

All tests according to the regulations cited on page 5 were.

n - Performed

o - **Not** Performed

The Equipment Under Test

n - **Fulfills** the general approval requirements.

o - **Does not** fulfill the general approval requirements.

Sample Received Date: November 7, 2018

Testing Start Date: November 6, 2018

Testing End Date: December 27, 2018

Reviewed by:



Phoebe Hu
EMC Section Manager

Prepared by:



Mark Chen
EMC Project Engineer

Tested by:




Carry Cai
EMC Test Engineer


7 Test Setups

7.1 Radiated test setups


Below 1GHz




Above 1GHz



7.2 Conducted RF test setups



7.3 AC Power Line Conducted Emission test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Notebook	Lenovo	X220	---

Test software: AppoTech RF Control Kit Test Tool, which used to control the EUT in continues transmitting mode

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power .

9 Technical Requirement

9.1 Conducted Emission

Test Method


1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Product Type : Bluetooth Speaker
 M/N : Buckshot Pro Ultra (OT2351)
 Operating Condition : Charging+ BT Link+ Bright light
 Test Specification : Line
 Comment : 5VDC(Supplies by USB Port)



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.206000	47.28	---	63.37	16.09	L1	10.2
0.302000	42.19	---	60.19	18.00	L1	10.2
0.378000	41.59	---	58.32	16.73	L1	10.3
0.550000	42.29	---	56.00	13.71	L1	10.3
0.658000	40.18	---	56.00	15.82	L1	10.3
0.750000	39.07	---	56.00	16.93	L1	10.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---	---	---

Remark: Correct factor=cable loss + LISN factor

Product Type : Bluetooth Speaker
 M/N : Buckshot Pro Ultra (OT2351)
 Operating Condition : Charging+ BT Link+ Bright light
 Test Specification : Neutral
 Comment : 5VDC(Supplies by USB Port)



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.653500	49.26	---	56.00	6.74	N	10.3
1.302500	47.71	---	56.00	8.29	N	10.3
1.622000	44.62	---	56.00	11.38	N	10.3
1.950500	47.01	---	56.00	8.99	N	10.3
2.598000	45.29	---	56.00	10.71	N	10.3
3.562500	46.64	---	56.00	9.36	N	10.4

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.653500	---	44.22	46.00	1.78	N	10.3
0.653500	47.32	---	56.00	8.68	N	10.3
1.302500	---	45.39	46.00	0.61	N	10.3
1.302500	46.53	---	56.00	9.47	N	10.3
1.950500	---	34.28	46.00	11.72	N	10.3
1.950500	38.45	---	56.00	17.55	N	10.3
3.562500	---	33.69	46.00	12.31	N	10.4
3.562500	40.16	---	56.00	15.84	N	10.4

Remark: Correct factor=cable loss + LISN factor.

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel
RBW > the 20dB bandwidth of the emission being measured, VBW $\geq$ RBW,
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power

Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30




Conducted peak output power

Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	-5.45	Pass
Middle channel 2441MHz	-5.74	Pass
High channel 2480MHz	-5.71	Pass


Low channel 2402MHz



Date: 19 DEC 2018 16:30:28




Middle channel 2441MHz



Date: 19 DEC 2018 16:33:13

High channel 2480MHz




Date: 19 DEC 2018 16:34:51



Bluetooth Mode $\pi/4$ -DQPSK modulation Test Result
Conducted Peak

Frequency MHz	Output Power dBm	Result
Low channel 2402MHz	-6.59	Pass
Middle channel 2441MHz	-6.94	Pass
High channel 2480MHz	-6.94	Pass

Low channel 2402MHz



Date: 19 DEC 2018 16:36:48

Spectrum

Ref Level 30.00 dBm Offset 1.00 dB RBW 3 MHz
 Att 40 dB SWT 1 ms VBW 10 MHz Mode Auto Sweep
 Count 100/100

● 1Pk View

M1[1] -6.94 dBm
 2.4407680 GHz

20 dBm
 10 dBm
 0 dBm
 -10 dBm
 -20 dBm
 -30 dBm
 -40 dBm
 -50 dBm
 -60 dBm

M1

CF 2.441 GHz 691 pts Span 8.0 MHz

Measuring

19.12.2018

Spectrum

Ref Level 30.00 dBm **Offset** 1.00 dB **RBW** 3 MHz **Att** 40 dB **SWT** 1 ms **VBW** 10 MHz **Mode** Auto Sweep

Count 100/100

● IPk View

M1[1] -6.94 dBm 2.4799650 GHz

CF 2.48 GHz 691 pts Span 8.0 MHz


Page 17 of 52



Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	-6.90	Pass
Middle channel 2441MHz	-7.19	Pass
High channel 2480MHz	-7.24	Pass

Low channel 2402MHz



Date: 19 DEC 2018 16:49:26

Spectrum

Ref Level 30.00 dBm **Offset** 1.00 dB **RBW** 3 MHz
Att 40 dB **SWT** 1 ms **VBW** 10 MHz **Mode** Auto Sweep
Count 100/100

● IPk View

M1[1] -7.19 dBm
2.4409420 GHz

20 dBm
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm

CF 2.441 GHz 691 pts Span 8.0 MHz

Spectrum

Ref Level 30.00 dBm Offset 1.00 dB RBW 3 MHz
Att 40 dB SWT 1 ms VBW 10 MHz Mode Auto Sweep
Count 100/100

1Pk View

M1[1] -7.24 dBm
2.4798840 GHz

M1

CF 2.48 GHz 691 pts Span 8.0 MHz

10.12.2018

Page 19 of 52

9.3 20 dB bandwidth and 99% Occupied Bandwidth

Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit [kHz]

N/A





20 dB bandwidth and 99% Occupied Bandwidth

Bluetooth Mode GFSK Modulation test result


Frequency	20 dB Bandwidth	99% Bandwidth	Limit	Result
MHz	kHz	kHz	kHz	
2402	1122	992	--	Pass
2441	1128	992	--	Pass
2480	1122	995	--	Pass

Low channel 2402MHz






Middle channel 2441MHz




Date: 19 DEC 2018 16:33:33




Date: 19 DEC 2018 16:33:44



High channel 2480MHz



Date: 19 DEC 2018 16:35:11



Date: 19 DEC 2018 16:35:22




20 dB bandwidth and 99% Occupied Bandwidth


Bluetooth Mode $\pi/4$ -DQPSK Modulation test result

Frequency	20 dB Bandwidth	99% Bandwidth	Limit	Result
MHz	kHz	kHz	kHz	
2402	1311	1055	--	Pass
2441	1314	1055	--	Pass
2480	1311	1061	--	Pass

Low channel 2402MHz




Date: 19 DEC 2018 16:37:08




Date: 19 DEC 2018 16:37:19



Middle channel 2441MHz




Date: 19 DEC 2018 16:39:28




Date: 19 DEC 2018 16:39:39



High channel 2480MHz



Date: 19 DEC 2018 16:41:26





Date: 19 DEC 2018 16:41:37

20 dB bandwidth and 99% Occupied Bandwidth

Bluetooth Mode 8DPSK Modulation test result


Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1332	1109	--	Pass
2441	1335	1109	--	Pass
2480	1335	1109	--	Pass

Low channel 2402MHz






Middle channel 2441MHz




Date: 19 DEC 2018 16:51:34




Date: 19 DEC 2018 16:51:46



High channel 2480MHz



Date: 19 DEC 2018 16:53:15



Date: 19 DEC 2018 16:53:26

9.4 Carrier Frequency Separation

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, RBW $\geq$ 1% of the span, VBW $\geq$ RBW, Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit kHz
$\geq 25\text{KHz}$ or $2/3$ of the 20 dB bandwidth which is greater

GFSK Modulation Limit

Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	748
2441	752
2480	748




Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.


GFSK Modulation test result

Frequency MHz	Carrier Frequency Separation kHz	Result
2402	1017	Pass
2441	1003	Pass
2480	1003	Pass






Middle channel 2441MHz



High channel 2480MHz



9.5 Number of hopping frequencies

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit
number


≥ 15



Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification. Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
79	Pass



Date: 19 DEC 2018 16:55:17

9.6 Dwell Time

Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Dwell Time

Dwell time

The maximum dwell time shall be 0.4 s.

According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.

The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 79 \text{ [ch]} = 31.6 \text{ [s*ch]}$;


The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 31.6s for DH5 = $1600 / 6 / 79 * 31.6 = 106.67$

Test Result

Modulation	Mode	Reading (us)	Total Hops	Test Result (ms)	Limit (ms)	Result
GFSK	DH5	2980	106.67	317.88	< 400	Pass
$\pi/4$ -DQPSK	2DH5	2990	106.67	318.94	< 400	Pass
8-DPSK	3DH5	2980	106.67	317.88	< 400	Pass


GFSK Modulation



DH5




$\pi/4$ -DQPSK Modulation



2DH5

8-DPSK Modulation



3DH5

9.7 Spurious RF conducted emissions

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.

Limit



Frequency Range MHz	Limit (dBc)
30-25000	-20



Spurious RF conducted emissions


Only the worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.
GFSK Modulation:

Low channel 2402MHz






Middle channel 2441MHz




Date: 19 DEC 2018 16:33:59




Date: 19 DEC 2018 16:34:10



High channel 2480MHz



Date: 19 DEC 2018 16:35:46



Date: 19 DEC 2018 16:35:58

9.8 Band edge testing

Test Method



- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.





GFSK mode: Hopping off







GFSK mode: Hopping on







8DPSK mode: Hopping off





8DPSK mode: Hopping on



9.9 Spurious radiated emissions for transmitter

Test Method

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

For Above 1GHz

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW $\geq$ RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 KHz, VBW $\geq$ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Note:

- 1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($20\log(1/\text{duty cycle})$).
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

Transmitting spurious emission test result as below:

BT3.0 GFSK Modulation 2402MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Correct factor (dB)	Result
30-1000MHz	943.26	33.65	H	46	QP	12.35	-15.2	Pass
	943.26	32.47	V	46	QP	13.53	-15.2	Pass
1000-25000MHz	4804.22*	48.04	H	74	PK	25.96	3.7	Pass
	--	--	H	54	AV	--	--	Pass
	4803.75*	42.50	V	74	PK	32.35	3.7	Pass
	--	--	V	54	AV	--	--	Pass

BT3.0 GFSK Modulation 2441MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Correct factor (dB)	Result
30-1000MHz	--	--	H	43.5	QP	--	--	Pass
	--	--	H	46	QP	--	--	Pass
1000-25000MHz	4880.16*	43.86	H	74	PK	30.14	3.8	Pass
	--	--	H	54	AV	--	--	Pass
	4880.16*	42.14	V	74	PK	31.86	3.8	Pass
	--	--	V	54	AV	--	--	Pass

BT3.0 GFSK Modulation 2480MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Correct factor (dB)	Result
30-1000MHz	--	--	H	43.5	QP	--	--	Pass
	--	--	H	46	QP	--	--	Pass
1000-25000MHz	4959.85*	42.03	H	74	PK	31.97	4.3	Pass
	--	--	H	54	AV	--	--	Pass
	4959.85*	42.65	V	74	PK	31.35	4.3	Pass
	--	--	V	54	AV	--	--	Pass

Remark:

- (1) "*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- (2) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are the noise floor or attenuated more than 10dB below the permissible limits or the field strength is too small to be measured.
- (3) Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss

10 Test Equipment List

List of Test Instruments

Radiated Spurious Emission Test

Description	Manufacturer	Model no.	Serial no.	Cal. due date
Signal Analyzer	Rohde & Schwarz	FSV40	101031	2019-7-6
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	708	2019-7-13
Horn Antenna	Rohde & Schwarz	HF907	102295	2019-7-13
Wideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	12827	2019-7-12
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2019-7-6
Pre-amplifier	Rohde & Schwarz	SCU 40A	100432	2019-7-6
Fully Anechoic Chamber	TDK	8X4X4	--	2020-7-7
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

RF Test System

Description	Manufacturer	Model no.	Serial no.	cal. due date
Signal Analyzer	Rohde & Schwarz	FSV40	101030	2019-7-6

Conducted Emission Test

Description	Manufacturer	Model no.	Serial no.	cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2019-7-6
LISN	Rohde & Schwarz	ENV4200	100249	2019-7-6
LISN	Rohde & Schwarz	ENV432	101318	2019-7-6
LISN	Rohde & Schwarz	ENV216	100326	2019-7-6
ISN	Rohde & Schwarz	ENY81	100177	2019-7-6
ISN	Rohde & Schwarz	ENY81-CA6	101664	2019-7-6
High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-584	2019-6-30
RF Current Probe	Rohde & Schwarz	EZ-17	100816	2019-6-30
Attenuator	Shanghai Huaxiang	TS2-26-3	080928189	2019-7-6
Test software	Rohde & Schwarz	EMC32	Version9.15.00	N/A

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Radiated Spurious Emission 25MHz-3000MHz	Horizontal: 4.80dB; Vertical: 4.87dB;
Radiated Spurious Emission 3000MHz-18000MHz	Horizontal: 4.59dB; Vertical: 4.58dB;
Radiated Spurious Emission 18000MHz-40000MHz	Horizontal: 5.05dB; Vertical: 5.04dB;
Conducted RF test	RF Power Conducted: 1.16dB Frequency test involved: 0.6×10 ⁻⁷ or 1%