


























## 12. Duty cycle

### 12.1. Block diagram of test setup



### 12.2. Limit

Just for Report.

### 12.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.

set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger

- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

- (3) Calculate dwell time follow below formula:


Duty cycle= Pulse's on time / Burst cycle


12.4. Test result

|                    |                         |                |                          |
|--------------------|-------------------------|----------------|--------------------------|
| Test Engineer:     | Haung Yanwen            | Test Site:     | RF Measurement system 4# |
| Ambient Condition: | 24.6-26.1℃,44.2-46.5%RH | Test Date:     | 2026.04.15-2026.04.17    |
| Test Power Supply: | AC 120V                 | Sample Number: | S25101028-006            |

| Test Mode | Antenna | Frequency [MHz] | ON Time [ms] | Period [ms] | Duty Cycle [%] | Duty Cycle Factor [dB] |
|-----------|---------|-----------------|--------------|-------------|----------------|------------------------|
| DH5       | Ant1    | 2402            | 2.90         | 3.76        | 77.13          | 1.13                   |
|           |         | 2441            | 2.89         | 3.75        | 77.07          | 1.13                   |
|           |         | 2480            | 2.89         | 3.75        | 77.07          | 1.13                   |
| 2DH5      | Ant1    | 2402            | 2.89         | 3.75        | 77.07          | 1.13                   |
|           |         | 2441            | 2.89         | 3.75        | 77.07          | 1.13                   |
|           |         | 2480            | 2.89         | 3.75        | 77.07          | 1.13                   |
| 3DH5      | Ant1    | 2402            | 2.89         | 3.75        | 77.07          | 1.13                   |
|           |         | 2441            | 2.90         | 3.75        | 77.33          | 1.12                   |
|           |         | 2480            | 2.89         | 3.76        | 76.86          | 1.14                   |

12.5. Test graphs







## 13. Antenna Requirements

### 13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

### 13.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

## 14. Radiated Emission

### 14.1. Test equipment


Below 1GHz:



| Equipment                                           | Manufacturer      | Model No.             | Serial No.  | Cal Due To | Cal. Interval |
|-----------------------------------------------------|-------------------|-----------------------|-------------|------------|---------------|
| High pass filter                                    | Micro-Tronics     | HPM50102              | DDT-ZC00561 | 2027/02/27 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | Z805UF-NJ-NJ-10M      | DDT-ZC05591 | 2026/10/10 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | Z805UF-NJ-NJ-3M       | DDT-ZC05590 | 2026/10/10 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | JCTB510-NJW-NJW-0.6M  | DDT-ZC04595 | 2026/10/10 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | JCT40P-2.92J-2.92J-1M | DDT-ZC03802 | 2026/10/10 | 1 Year        |
| RF cable                                            | Yuhu Technology   | ZT26S-SMAJ-SMAJ-1M    | DDT-ZC02037 | 2026/10/10 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | JCT40P-2.92J-2.92J-5M | DDT-ZC03800 | 2026/10/10 | 1 Year        |
| Radiation disturbance fully automated test software | Tonscend          | JS32-RE (V5.0.0)      | DDT-ZC02739 | /          | /             |
| Pre-amplifier                                       | SONOMA            | 310N                  | DDT-ZC01969 | 2026/07/06 | 1 Year        |
| Pre-amplifier                                       | COM-POWER         | PAM-840A              | DDT-ZC01693 | 2027/03/05 | 1 Year        |
| Pre-amplifier                                       | COM-POWER         | PAM-118A              | DDT-ZC01293 | 2026/08/10 | 1 Year        |
| EMI TEST RECEIVER                                   | R&S               | ESU26                 | DDT-ZC01909 | 2027/02/27 | 1 Year        |
| Micro-Tronics filters                               | REBES             | BRM50702              | DDT-ZC03242 | /          | /             |
| High pass filter                                    | Micro-Tronics     | HPM50108              | DDT-ZC00560 | 2027/02/27 | 1 Year        |
| High Pass filter                                    | Xi'an Xingbo      | XBLBQ-GTA67           | DDT-ZC02179 | 2027/02/27 | 1 Year        |
| Micro-Tronics filters                               | REBES             | BRM50716              | DDT-ZC03240 | /          | /             |
| Broad-Band Horn Antenna                             | Schwarzbeck       | BBHA 9170             | DDT-ZC00506 | 2027/03/04 | 1 Year        |
| Trilog Broadband Antenna                            | Schwarzbeck       | VULB 9163             | DDT-ZC02050 | 2026/07/25 | 1 Year        |
| Hochgewinn-Hornantenne                              | SCHWARZBECK       | BBHA 9120 D           | DDT-ZC02129 | 2026/08/11 | 1 Year        |
| Active Loop Antenna                                 | Schwarzbeck       | FMZB1519              | DDT-ZC00524 | 2026/08/18 | 1 Year        |
| PSA Series Spectrum Analyzer                        | Agilent           | E4447A                | DDT-ZC00517 | 2027/02/27 | 1 Year        |

Above 1GHz:

| Equipment                                           | Manufacturer      | Model No.             | Serial No.  | Cal Due To | Cal. Interval |
|-----------------------------------------------------|-------------------|-----------------------|-------------|------------|---------------|
| Band Reject Filter Group                            | Tonscend          | JS0806-F              | DDT-ZC05733 | /          | /             |
| Hochgewinn-Hornantenne                              | SCHWARZBECK       | BBHA 9120 D           | DDT-ZC05922 | 2027/01/06 | 1 Year        |
| Broadband Preamplifier                              | HPX               | BP-01G-18G            | DDT-ZC05923 | 2027/01/06 | 1 Year        |
| Pre-amplifier                                       | COM-POWER         | PAM-840A              | DDT-ZC01693 | 2027/03/05 | 1 Year        |
| Broad-Band Horn Antenna                             | Schwarzbeck       | BBHA 9170             | DDT-ZC00506 | 2027/03/04 | 1 Year        |
| Signal & Spectrum analyzer                          | R&S               | FSV40-N               | DDT-ZC04979 | 2026/07/04 | 1 Year        |
| SPECTRUM ANALYZER                                   | R&S               | FSU26                 | DDT-ZC00236 | 2026/07/06 | 1 Year        |
| RF Cable                                            | Tonscend          | 7+1+1+0.5+0.5m        | DDT-ZC05978 | 2027/01/29 | 1 Year        |
| Broad-Band Horn Antenna                             | Schwarzbeck       | BBHA 9170             | DDT-ZC00506 | 2027/03/04 | 1 Year        |
| PSA Series Spectrum Analyzer                        | Agilent           | E4447A                | DDT-ZC00517 | 2027/02/27 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | JCT40P-2.92J-2.92J-1M | DDT-ZC03802 | 2026/10/10 | 1 Year        |
| Radiation disturbance fully automated test software | Tonscend          | JS-RE&RSE (V5.0.0)    | DDT-ZC06466 | /          | /             |

#### 14.2. Block diagram of test setup





### 14.3. Limits

#### (1) FCC 15.205 Restricted frequency band

| MHz               | MHz                 | MHz           | GHz              |
|-------------------|---------------------|---------------|------------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15         |
| 0.495-0.505       | 16.69475-16.69525   | 608-614       | 5.35-5.46        |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75        |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5        |
| 4.1772&4.17775    | 37.5-38.25          | 1435-1626.5   | 9.0-9.2          |
| 4.2072&4.20775    | 73-74.6             | 1645.5-1646.5 | 9.3-9.5          |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7        |
| 6.26775-6.26825   | 108-121.94          | 1718.8-1722.2 | 13.25-13.4       |
| 6.31175-6.31225   | 123-138             | 2200-2300     | 14.47-14.5       |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2       |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4        |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12      |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0        |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8        |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5       |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | ( <sup>2</sup> ) |
| 13.36-13.41       |                     |               |                  |

<sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

<sup>2</sup>Above 38.6

#### RSS-Gen section 8.10 Restricted frequency bands\*

| MHz             | MHz                 | MHz           | GHz         |
|-----------------|---------------------|---------------|-------------|
| 0.090-0.110     | 12.51975-12.52025   | 240-285       | 3.5-4.4     |
| 0.495-0.505     | 12.57675-12.57725   | 322-335.4     | 4.5-5.15    |
| 2.1735-2.1905   | 13.36-13.41         | 399.9-410     | 5.35-5.46   |
| 3.020-3.026     | 16.42-16.423        | 608-614       | 7.25-7.75   |
| 4.125-4.128     | 16.69475-16.69525   | 960-1427      | 8.025-8.5   |
| 4.1772&4.17775  | 16.80425-16.80475   | 1435-1626.5   | 9.0-9.2     |
| 4.2072&4.20775  | 25.5-25.67          | 1645.5-1646.5 | 9.3-9.5     |
| 5.677-5.683     | 37.5-38.25          | 1660-1710     | 10.6-12.7   |
| 6.215-6.218     | 73-74.6             | 1718.8-1722.2 | 13.25-13.4  |
| 6.26775-6.26825 | 74.8-75.2           | 2200-2300     | 14.47-14.5  |
| 6.31175-6.31225 | 108-138             | 2310-2390     | 15.35-16.2  |
| 8.291-8.294     | 149.9-150.05        | 2483.5-2500   | 17.7-21.4   |
| 8.362-8.366     | 156.52475-156.52525 | 2655-2900     | 22.01-23.12 |
| 8.37625-8.38675 | 156.7-156.9         | 3260-3267     | 23.6-24.0   |

|                 |                 |             |            |
|-----------------|-----------------|-------------|------------|
| 8.41425-8.41475 | 162.0125-167.17 | 3332-3339   | 31.2-31.8  |
| 12.29-12.293    | 167.72-173.2    | 3345.8-3358 | 36.43-36.5 |
|                 |                 |             | Above 38.6 |

\* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

| Frequency                | Magnetic field strength (H-Field)<br>( $\mu\text{A/m}$ ) | Measurement distance<br>(m) |
|--------------------------|----------------------------------------------------------|-----------------------------|
| 9 - 490 kHz <sup>1</sup> | 6.37/F (F in kHz)                                        | 300                         |
| 490 - 1705 kHz           | 63.7/F (F in kHz)                                        | 30                          |
| 1.705 - 30 MHz           | 0.08                                                     | 30                          |

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

| FREQUENCY<br>MHz | DISTANCE<br>Meters | FIELD STRENGTHS LIMIT                       |               |
|------------------|--------------------|---------------------------------------------|---------------|
|                  |                    | $\mu\text{V/m}$                             | dBuV/m        |
| 0.009 ~ 0.490    | 300                | 2400/F(kHz)                                 | 67.6-20log(F) |
| 0.490 ~ 1.705    | 30                 | 24000/F(kHz)                                | 87.6-20log(F) |
| 1.705 ~ 30.0     | 30                 | 30                                          | 29.54         |
| 30 ~ 88          | 3                  | 100                                         | 40.0          |
| 88 ~ 216         | 3                  | 150                                         | 43.5          |
| 216 ~ 960        | 3                  | 200                                         | 46.0          |
| 960 ~ 1000       | 3                  | 500                                         | 54.0          |
| Above 1000       | 3                  | 74.0 dBuV/m (Peak)<br>54.0 dBuV/m (Average) |               |

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

## (3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

**14.4. Assistant equipment used for test**

| Assistant equipment | Manufacturer | Model number | Description   | other |
|---------------------|--------------|--------------|---------------|-------|
| Notebook            | Lenovo       | i5-5300U     | Test computer | /     |

**14.5. Test procedure**

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

| Test frequency range | Test antenna used                         | Test antenna distance |
|----------------------|-------------------------------------------|-----------------------|
| 9 kHz - 30 MHz       | Active Loop antenna                       | 3 m                   |
| 30 MHz - 1 GHz       | Trilog Broadband Antenna                  | 3 m                   |
| 1 GHz - 18 GHz       | Double Ridged Horn Antenna (1 GHz-18 GHz) | 3 m                   |
| 18 GHz - 40 GHz      | Horn Antenna (18 GHz-40 GHz)              | 1 m                   |

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)
- (b) Change work frequency or channel of device if practicable.
- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT through three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

| Frequency band   | RBW     |
|------------------|---------|
| 9 kHz - 150 kHz  | 200 Hz  |
| 150 kHz - 30 MHz | 9 kHz   |
| 30 MHz - 1 GHz   | 120 kHz |

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with GFSK,  $\pi/4$ -DQPSK and 8DPSK, the worst case is record and reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

## 14.6. Test result

**PASS.** (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-21

Tested By:

Li Xiongbin

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:59.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC Below 1G BT\1

Memo:

Sample Number:S25101028-006



| Final Data List |             |                  |                     |                 |                 |                |             |          |            |
|-----------------|-------------|------------------|---------------------|-----------------|-----------------|----------------|-------------|----------|------------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable Loss [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1               | 30.190      | 39.32            | 10.46               | 3.78            | 21.26           | 40.00          | 18.74       | QP       | Horizontal |
| 2               | 41.652      | 32.3             | 12.96               | 3.93            | 16.89           | 40.00          | 23.11       | QP       | Horizontal |
| 3               | 109.001     | 30.27            | 12.20               | 4.35            | 14.51           | 43.50          | 28.99       | QP       | Horizontal |
| 4               | 154.445     | 34.41            | 8.99                | 4.62            | 15.67           | 43.50          | 27.83       | QP       | Horizontal |
| 5               | 253.373     | 30.13            | 12.10               | 5.09            | 14.92           | 46.00          | 31.08       | QP       | Horizontal |
| 6               | 373.385     | 29.21            | 15.06               | 5.60            | 17.40           | 46.00          | 28.60       | QP       | Horizontal |

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-21

Tested By:

Li Xiongbín

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:59.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC Below 1G BT\2

Memo:

Sample Number:S25101028-006



| Final Data List |             |                  |                     |                 |                 |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|-----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable Loss [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 34.930      | 45.26            | 11.30               | 3.85            | 28.11           | 40.00          | 11.89       | QP       | Vertical |
| 2               | 37.467      | 44.07            | 12.20               | 3.88            | 27.85           | 40.00          | 12.15       | QP       | Vertical |
| 3               | 41.274      | 41.24            | 12.81               | 3.93            | 25.68           | 40.00          | 14.32       | QP       | Vertical |
| 4               | 119.991     | 40.97            | 9.70                | 4.42            | 22.77           | 43.50          | 20.73       | QP       | Vertical |
| 5               | 186.765     | 32.73            | 9.54                | 4.80            | 14.68           | 43.50          | 28.82       | QP       | Vertical |
| 6               | 287.860     | 33.47            | 13.10               | 5.23            | 19.40           | 46.00          | 26.60       | QP       | Vertical |

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result


Test Date:2026-04-13Tested By:Nan Zhong

Test Mode:TX DH5 2402MHz ModePower Supply:AC 120V/60Hz

Condition:Temp:24.1°C;Humi:46.5%Test Site:4# Fully Anechoic Room

File Path:d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\1

Memo:Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 3603.000    | 56.11           | 30.10               | -44.12          | 42.09          | 74.00          | 31.91       | PK       | Horizontal |
| 2                   | 4803.000    | 51.98           | 32.39               | -42.68          | 41.69          | 74.00          | 32.31       | PK       | Horizontal |
| 3                   | 7311.000    | 50.63           | 36.25               | -41.09          | 45.79          | 74.00          | 28.21       | PK       | Horizontal |
| 4                   | 8208.000    | 50.72           | 37.05               | -40.76          | 47.01          | 74.00          | 26.99       | PK       | Horizontal |
| 5                   | 11010.000   | 48.13           | 38.90               | -38.48          | 48.55          | 74.00          | 25.45       | PK       | Horizontal |
| 6                   | 11685.000   | 47.59           | 38.83               | -37.76          | 48.66          | 74.00          | 25.34       | PK       | Horizontal |

| Final Data List |             |                  |                     |                 |                |                |             |          |            |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1               | 11010.000   | 43.52            | 38.90               | -38.48          | 43.94          | 54.00          | 10.06       | AV       | Horizontal |
| 2               | 11685.000   | 41.41            | 38.83               | -37.76          | 42.48          | 54.00          | 11.52       | AV       | Horizontal |

Note:  
1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\2

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 3601.500    | 58.61           | 30.10               | -44.12          | 44.59          | 74.00          | 29.41       | PK       | Vertical |
| 2                   | 4803.000    | 53.60           | 32.39               | -42.68          | 43.31          | 74.00          | 30.69       | PK       | Vertical |
| 3                   | 7360.500    | 50.04           | 36.29               | -41.01          | 45.32          | 74.00          | 28.68       | PK       | Vertical |
| 4                   | 9066.000    | 49.64           | 38.01               | -40.37          | 47.28          | 74.00          | 26.72       | PK       | Vertical |
| 5                   | 10945.500   | 47.13           | 38.86               | -38.40          | 47.59          | 74.00          | 26.41       | PK       | Vertical |
| 6                   | 11638.500   | 47.93           | 38.84               | -37.75          | 49.02          | 74.00          | 24.98       | PK       | Vertical |

| Final Data List |             |                  |                     |                 |                |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 11638.500   | 44.07            | 38.84               | -37.75          | 45.16          | 54.00          | 8.84        | AV       | Vertical |

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\5

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 3661.500    | 54.29           | 30.19               | -44.17          | 40.31          | 74.00          | 33.69       | PK       | Horizontal |
| 2                   | 4881.000    | 52.66           | 32.55               | -42.72          | 42.49          | 74.00          | 31.51       | PK       | Horizontal |
| 3                   | 7704.000    | 50.24           | 36.56               | -41.01          | 45.79          | 74.00          | 28.21       | PK       | Horizontal |
| 4                   | 8467.500    | 49.84           | 37.36               | -40.58          | 46.62          | 74.00          | 27.38       | PK       | Horizontal |
| 5                   | 11407.500   | 47.30           | 38.86               | -37.81          | 48.35          | 74.00          | 25.65       | PK       | Horizontal |
| 6                   | 12553.500   | 46.77           | 39.30               | -36.70          | 49.37          | 74.00          | 24.63       | PK       | Horizontal |

| Final Data List |             |                  |                     |                 |                |                |             |          |            |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1               | 11407.500   | 43.57            | 38.86               | -37.81          | 44.62          | 54.00          | 9.38        | AV       | Horizontal |
| 2               | 12553.500   | 42.31            | 39.30               | -36.70          | 44.91          | 54.00          | 9.09        | AV       | Horizontal |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\6

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 3661.500    | 57.59           | 30.19               | -44.17          | 43.61          | 74.00          | 30.39       | PK       | Vertical |
| 2                   | 4882.500    | 58.67           | 32.55               | -42.72          | 48.50          | 74.00          | 25.50       | PK       | Vertical |
| 3                   | 7455.000    | 50.72           | 36.36               | -40.84          | 46.24          | 74.00          | 27.76       | PK       | Vertical |
| 4                   | 9370.500    | 49.54           | 38.07               | -39.68          | 47.93          | 74.00          | 26.07       | PK       | Vertical |
| 5                   | 11053.500   | 47.79           | 38.89               | -38.41          | 48.27          | 74.00          | 25.73       | PK       | Vertical |
| 6                   | 12390.000   | 47.69           | 39.15               | -37.10          | 49.74          | 74.00          | 24.26       | PK       | Vertical |

| Final Data List |             |                  |                     |                 |                |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 4882.500    | 56.38            | 32.55               | -42.72          | 46.21          | 54.00          | 7.79        | AV       | Vertical |
| 2               | 11053.500   | 43.73            | 38.89               | -38.41          | 44.21          | 54.00          | 9.79        | AV       | Vertical |
| 3               | 12390.000   | 42.68            | 39.15               | -37.10          | 44.73          | 54.00          | 9.27        | AV       | Vertical |

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2\FCC ABOVE1G BT\3

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                  |                     |                 |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 4345.500    | 51.50            | 31.43               | -42.48          | 40.45          | 74.00          | 33.55       | PK       | Horizontal |
| 2                   | 4959.000    | 55.60            | 32.71               | -42.44          | 45.87          | 74.00          | 28.13       | PK       | Horizontal |
| 3                   | 7620.000    | 50.32            | 36.50               | -41.08          | 45.74          | 74.00          | 28.26       | PK       | Horizontal |
| 4                   | 9316.500    | 49.55            | 38.06               | -39.80          | 47.81          | 74.00          | 26.19       | PK       | Horizontal |
| 5                   | 11929.500   | 47.17            | 38.81               | -37.49          | 48.49          | 74.00          | 25.51       | PK       | Horizontal |
| 6                   | 12688.500   | 46.89            | 39.42               | -36.75          | 49.56          | 74.00          | 24.44       | PK       | Horizontal |

| Final Data List |             |                  |                     |                 |                |                |             |          |            |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1               | 11929.500   | 43.28            | 38.81               | -37.49          | 44.60          | 54.00          | 9.40        | AV       | Horizontal |
| 2               | 12688.500   | 42.15            | 39.42               | -36.75          | 44.82          | 54.00          | 9.18        | AV       | Horizontal |


Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-04-13 **Tested By:** Nan Zhong  
**Test Mode:** TX DH5 2480MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.1°C;Humi:46.5% **Test Site:** 4# Fully Anechoic Room  
**File Path:** d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\4  
**Memo:** Sample number:S25101028-001 Power Setting:NA

**Suspected Data List**

| NO. | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|-----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| 1   | 3720.000    | 53.39            | 30.28               | -44.19          | 39.48          | 74.00          | 34.52       | PK       | Vertical |
| 2   | 4959.000    | 58.21            | 32.71               | -42.44          | 48.48          | 74.00          | 25.52       | PK       | Vertical |
| 3   | 7354.500    | 50.85            | 36.28               | -41.02          | 46.11          | 74.00          | 27.89       | PK       | Vertical |
| 4   | 10645.500   | 48.19            | 38.65               | -38.69          | 48.15          | 74.00          | 25.85       | PK       | Vertical |
| 5   | 12319.500   | 46.89            | 39.09               | -36.84          | 49.14          | 74.00          | 24.86       | PK       | Vertical |
| 6   | 15502.500   | 45.70            | 38.65               | -35.31          | 49.04          | 74.00          | 24.96       | PK       | Vertical |

**Final Data List**

| NO. | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|-----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| 1   | 4959.000    | 56.63            | 32.71               | -42.44          | 46.90          | 54.00          | 7.10        | AV       | Vertical |
| 2   | 10645.500   | 45.32            | 38.65               | -38.69          | 45.28          | 54.00          | 8.72        | AV       | Vertical |
| 3   | 12319.500   | 43.71            | 39.09               | -36.84          | 45.96          | 54.00          | 8.04        | AV       | Vertical |
| 4   | 15502.500   | 42.49            | 38.65               | -35.31          | 45.83          | 54.00          | 8.17        | AV       | Vertical |

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 15. Band Edge Compliance

### 15.1. Test equipment

| Equipment                                           | Manufacturer      | Model No.             | Serial No.  | Cal Due To | Cal. Interval |
|-----------------------------------------------------|-------------------|-----------------------|-------------|------------|---------------|
| Band Reject Filter Group                            | Tonscend          | JS0806-F              | DDT-ZC05733 | /          | /             |
| Hochgewinn-Hornantenne                              | SCHWARZBECK       | BBHA 9120 D           | DDT-ZC05922 | 2027/01/06 | 1 Year        |
| Broadband Preamplifier                              | HPX               | BP-01G-18G            | DDT-ZC05923 | 2027/01/06 | 1 Year        |
| Pre-amplifier                                       | COM-POWER         | PAM-840A              | DDT-ZC01693 | 2027/03/05 | 1 Year        |
| Broad-Band Horn Antenna                             | Schwarzbeck       | BBHA 9170             | DDT-ZC00506 | 2027/03/04 | 1 Year        |
| Signal & Spectrum analyzer                          | R&S               | FSV40-N               | DDT-ZC04979 | 2026/07/04 | 1 Year        |
| SPECTRUM ANALYZER                                   | R&S               | FSU26                 | DDT-ZC00236 | 2026/07/06 | 1 Year        |
| RF Cable                                            | Tonscend          | 7+1+1+0.5+0.5m        | DDT-ZC05978 | 2027/01/29 | 1 Year        |
| Broad-Band Horn Antenna                             | Schwarzbeck       | BBHA 9170             | DDT-ZC00506 | 2027/03/04 | 1 Year        |
| PSA Series Spectrum Analyzer                        | Agilent           | E4447A                | DDT-ZC00517 | 2027/02/27 | 1 Year        |
| RF cable                                            | Zhongke Junchuang | JCT40P-2.92J-2.92J-1M | DDT-ZC03802 | 2026/10/10 | 1 Year        |
| Radiation disturbance fully automated test software | Tonscend          | JS-RE&RSE (V5.0.0)    | DDT-ZC06466 | /          | /             |

15.2. Block diagram of test setup



15.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

15.4. Assistant equipment used for test

| Assistant equipment | Manufacturer | Model number | Description   | other |
|---------------------|--------------|--------------|---------------|-------|
| Notebook            | Lenovo       | i5-5300U     | Test comptuer | /     |

15.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.

15.6. Test result

PASS. (See below detailed test result)

15.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\7

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2370.920    | 44.69           | 27.38               | -28.62          | 43.45          | 74.00          | 30.55       | PK       | Horizontal |
| 2                   | 2390.000    | 41.68           | 27.43               | -28.56          | 40.55          | 74.00          | 33.45       | PK       | Horizontal |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\8

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2389.340    | 46.65           | 27.43               | -28.56          | 45.52          | 74.00          | 28.48       | PK       | Vertical |
| 2                   | 2390.000    | 42.87           | 27.43               | -28.56          | 41.74          | 74.00          | 32.26       | PK       | Vertical |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\9

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 51.52           | 27.70               | -28.53          | 50.69          | 74.00          | 23.31       | PK       | Horizontal |
| 2                   | 2484.034    | 56.23           | 27.70               | -28.53          | 55.40          | 74.00          | 18.60       | PK       | Horizontal |

| Final Data List |             |                  |                     |                 |                |                |             |          |            |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1               | 2483.500    | 46.62            | 27.70               | -28.53          | 45.79          | 54.00          | 8.21        | AV       | Horizontal |
| 2               | 2484.034    | 41.83            | 27.70               | -28.53          | 41.00          | 54.00          | 13.00       | AV       | Horizontal |

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\10

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 55.48           | 27.70               | -28.53          | 54.65          | 74.00          | 19.35       | PK       | Vertical |
| 2                   | 2483.962    | 59.64           | 27.70               | -28.53          | 58.81          | 74.00          | 15.19       | PK       | Vertical |

| Final Data List |             |                  |                     |                 |                |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 2483.500    | 43.20            | 27.70               | -28.53          | 42.37          | 54.00          | 11.63       | AV       | Vertical |
| 2               | 2483.962    | 42.98            | 27.70               | -28.53          | 42.15          | 54.00          | 11.85       | AV       | Vertical |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\11

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2381.210    | 44.19           | 27.41               | -28.59          | 43.01          | 74.00          | 30.99       | PK       | Horizontal |
| 2                   | 2390.000    | 41.73           | 27.43               | -28.56          | 40.60          | 74.00          | 33.40       | PK       | Horizontal |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\12

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2386.190    | 45.22           | 27.42               | -28.57          | 44.07          | 74.00          | 29.93       | PK       | Vertical |
| 2                   | 2390.000    | 42.76           | 27.43               | -28.56          | 41.63          | 74.00          | 32.37       | PK       | Vertical |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\13

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2372.490    | 44.65           | 27.38               | -28.61          | 43.42          | 74.00          | 30.58       | PK       | Horizontal |
| 2                   | 2390.000    | 42.05           | 27.43               | -28.56          | 40.92          | 74.00          | 33.08       | PK       | Horizontal |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\14

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2389.310    | 46.67           | 27.43               | -28.56          | 45.54          | 74.00          | 28.46       | PK       | Vertical |
| 2                   | 2390.000    | 43.25           | 27.43               | -28.56          | 42.12          | 74.00          | 31.88       | PK       | Vertical |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\15

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 62.30           | 27.70               | -28.53          | 61.47          | 74.00          | 12.53       | PK       | Horizontal |
| 2                   | 2483.803    | 62.75           | 27.70               | -28.53          | 61.92          | 74.00          | 12.08       | PK       | Horizontal |

| Final Data List |             |                  |                     |                 |                |                |             |          |            |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1               | 2483.500    | 46.21            | 27.70               | -28.53          | 45.38          | 54.00          | 8.62        | AV       | Horizontal |
| 2               | 2483.803    | 47.31            | 27.70               | -28.53          | 46.48          | 54.00          | 7.52        | AV       | Horizontal |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\16

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 63.70           | 27.70               | -28.53          | 62.87          | 74.00          | 11.13       | PK       | Vertical |
| 2                   | 2483.653    | 66.65           | 27.70               | -28.53          | 65.82          | 74.00          | 8.18        | PK       | Vertical |

| Final Data List |             |                  |                     |                 |                |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 2483.498    | 47.57            | 27.70               | -28.53          | 46.74          | 54.00          | 7.26        | AV       | Vertical |
| 2               | 2483.653    | 48.02            | 27.70               | -28.53          | 47.19          | 54.00          | 6.81        | AV       | Vertical |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\17

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 45.70           | 27.70               | -28.53          | 44.87          | 74.00          | 29.13       | PK       | Horizontal |
| 2                   | 2483.656    | 48.55           | 27.70               | -28.53          | 47.72          | 74.00          | 26.28       | PK       | Horizontal |

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-13

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.1°C;Humi:46.5%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2025 report date\Q25101028-2E\FCC ABOVE1G BT\18

Memo:

Sample number:S25101028-001 Power Setting:NA



| Suspected Data List |             |                 |                     |                 |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 48.33           | 27.70               | -28.53          | 47.50          | 74.00          | 26.50       | PK       | Vertical |
| 2                   | 2483.914    | 50.46           | 27.70               | -28.53          | 49.63          | 74.00          | 24.37       | PK       | Vertical |

| Final Data List |             |                  |                     |                 |                |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 2483.914    | 46.28            | 27.70               | -28.53          | 45.45          | 54.00          | 8.55        | AV       | Vertical |

Note:


- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 16. Power Line Conducted Emissions

### 16.1. Test equipment

| Equipment                   | Manufacturer | Model No. | Serial No.  | Cal Due To | Cal. Interval |
|-----------------------------|--------------|-----------|-------------|------------|---------------|
| EMI Test Receiver           | R&S          | ESCI 3    | DDT-ZC01972 | 2027/02/27 | 1 Year        |
| Two Line V-Network          | R&S          | ENV216    | DDT-ZC00586 | 2026/07/06 | 1 Year        |
| Pulse Limiter               | R&S          | KH43101   | DDT-ZC00747 | 2027/02/27 | 1 Year        |
| Coaxial signal signal cable | H&S          | RG214-5   | DDT-ZC01817 | 2027/02/27 | 1 Year        |
| Conducted Radiated Software | Audix        | e3        | DDT-ZC00562 | /          | /             |
| Two Line V-Network          | R&S          | ENV216    | DDT-ZC02058 | 2026/07/06 | 1 Year        |

### 16.2. Block diagram of test setup



### 16.3. Limits

| Frequency       | Quasi-Peak Level<br>dB(μV) | Average Level<br>dB(μV) |
|-----------------|----------------------------|-------------------------|
| 150 kHz~500 kHz | 66 ~ 56*                   | 56 ~ 46*                |
| 500 kHz~5 MHz   | 56                         | 46                      |
| 5 MHz~30 MHz    | 60                         | 50                      |

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 16.4. Assistant equipment used for test

| Assistant equipment | Manufacturer | Model number | Description   | other |
|---------------------|--------------|--------------|---------------|-------|
| Notebook            | Lenovo       | i5-5300U     | Test computer | /     |

### 16.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

### 16.6. Test result

**PASS. (See below detailed test result)**

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “-----” means Peak detection; “-----” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

## 16.7. Test data

## TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2025 report data\Q25101028\0426 CE.EM6

Test Date : 2026-04-26

Tested By : Jiahao Yang

Power Supply : AC 120V/60Hz


Test Mode : DH5 2480MHz Tx mode

Condition : Temp:25.6°C,Humi:62%

LISN : 2025 2# 216/NEUTRAL

Memo : S251010281-001

Data: 2



| Item   | Freq. | Read Level | LISN Factor | Cable Loss | Pulse Limiter Factor | Result Level | Limit Line | Margin | Detector | Phase   |
|--------|-------|------------|-------------|------------|----------------------|--------------|------------|--------|----------|---------|
| (Mark) | (MHz) | (dBμV)     | (dB)        | (dB)       | (dB)                 | (dBμV)       | (dBμV)     | (dB)   |          |         |
| 1      | 0.21  | 19.57      | 9.49        | 0.05       | 10.20                | 39.31        | 63.36      | 24.05  | QP       | NEUTRAL |
| 2      | 0.21  | 13.34      | 9.49        | 0.05       | 10.20                | 33.08        | 53.36      | 20.28  | Average  | NEUTRAL |
| 3      | 0.56  | 17.30      | 9.48        | 0.11       | 10.33                | 37.22        | 56.00      | 18.78  | QP       | NEUTRAL |
| 4      | 0.56  | 11.72      | 9.48        | 0.11       | 10.33                | 31.64        | 46.00      | 14.36  | Average  | NEUTRAL |
| 5      | 1.29  | 12.94      | 9.49        | 0.19       | 10.40                | 33.02        | 56.00      | 22.98  | QP       | NEUTRAL |
| 6      | 1.29  | 8.02       | 9.49        | 0.19       | 10.40                | 28.10        | 46.00      | 17.90  | Average  | NEUTRAL |
| 7      | 4.57  | 7.50       | 9.53        | 0.24       | 10.27                | 27.54        | 56.00      | 28.46  | QP       | NEUTRAL |
| 8      | 4.57  | 0.91       | 9.53        | 0.24       | 10.27                | 20.95        | 46.00      | 25.05  | Average  | NEUTRAL |
| 9      | 9.97  | 5.63       | 9.62        | 0.27       | 10.14                | 25.66        | 60.00      | 34.34  | QP       | NEUTRAL |
| 10     | 9.97  | -0.54      | 9.62        | 0.27       | 10.14                | 19.49        | 50.00      | 30.51  | Average  | NEUTRAL |
| 11     | 25.19 | 5.53       | 9.94        | 0.38       | 10.31                | 26.16        | 60.00      | 33.84  | QP       | NEUTRAL |
| 12     | 25.19 | 0.34       | 9.94        | 0.38       | 10.31                | 20.97        | 50.00      | 29.03  | Average  | NEUTRAL |

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2025 report data\Q25101028\0426 CE.EM6

Test Date : 2026-04-26

Tested By : Jiahao Yang

Power Supply : AC 120V/60Hz


Test Mode : DH5 2480MHz Tx mode

Condition : Temp:25.6°C,Humi:62%

LISN : 2025 2# 216/LINE

Memo : S251010281-001

Data: 4



| Item<br>(Mark) | Freq.<br>(MHz) | Read<br>Level<br>(dBμV) | LISN<br>Factor<br>(dB) | Cable<br>Loss<br>(dB) | Pulse<br>Limiter<br>Factor<br>(dB) | Result<br>Level<br>(dBμV) | Limit<br>Line<br>(dBμV) | Margin<br>(dB) | Detector | Phase |
|----------------|----------------|-------------------------|------------------------|-----------------------|------------------------------------|---------------------------|-------------------------|----------------|----------|-------|
| 1              | 0.15           | 25.58                   | 9.46                   | 0.05                  | 10.21                              | 45.30                     | 65.82                   | 20.52          | QP       | LINE  |
| 2              | 0.15           | 14.02                   | 9.46                   | 0.05                  | 10.21                              | 33.74                     | 55.82                   | 22.08          | Average  | LINE  |
| 3              | 0.40           | 20.08                   | 9.48                   | 0.09                  | 10.29                              | 39.94                     | 57.86                   | 17.92          | QP       | LINE  |
| 4              | 0.40           | 17.06                   | 9.48                   | 0.09                  | 10.29                              | 36.92                     | 47.86                   | 10.94          | Average  | LINE  |
| 5              | 0.82           | 15.64                   | 9.51                   | 0.15                  | 10.38                              | 35.68                     | 56.00                   | 20.32          | QP       | LINE  |
| 6              | 0.82           | 10.51                   | 9.51                   | 0.15                  | 10.38                              | 30.55                     | 46.00                   | 15.45          | Average  | LINE  |
| 7              | 4.67           | 7.66                    | 9.54                   | 0.24                  | 10.27                              | 27.71                     | 56.00                   | 28.29          | QP       | LINE  |
| 8              | 4.67           | 0.61                    | 9.54                   | 0.24                  | 10.27                              | 20.66                     | 46.00                   | 25.34          | Average  | LINE  |
| 9              | 11.62          | 4.11                    | 9.64                   | 0.29                  | 10.17                              | 24.21                     | 60.00                   | 35.79          | QP       | LINE  |
| 10             | 11.62          | -1.01                   | 9.64                   | 0.29                  | 10.17                              | 19.09                     | 50.00                   | 30.91          | Average  | LINE  |
| 11             | 25.32          | 4.56                    | 9.67                   | 0.38                  | 10.31                              | 24.92                     | 60.00                   | 35.08          | QP       | LINE  |
| 12             | 25.32          | -1.20                   | 9.67                   | 0.38                  | 10.31                              | 19.16                     | 50.00                   | 30.84          | Average  | LINE  |

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## 18. Photos of the EUT

Please refer to DDT-Q25101028-1E appendix I

-----End Report-----