



RADIO TEST REPORT

Applicant	:	Audioengine LLC
Address of Applicant	:	304 Progress Drive, Sherman, TX 75092 United States
Manufacturer	:	Audioengine LLC
Address of Manufacturer	:	304 Progress Drive, Sherman, TX 75092 United States
Equipment under Test	:	Bluetooth audio receiver
Model No.	:	B1
FCC ID	:	PIBB22
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+ Errata to C63.10a-2024
Report No.	:	DDT-RE26061720-2E02
Issue Date	:	2026/09/20
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	6 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result.....	14
4.5.	Test graphs	15
5.	99% Bandwidth	16
5.1.	Block diagram of test setup	16
5.2.	Limits	16
5.3.	Test procedure	16
5.4.	Test result.....	17
5.5.	Test graphs	18
6.	Maximum Peak Output Power.....	19
6.1.	Block diagram of test setup	19
6.2.	Limits	19
6.3.	Test procedure	19
6.4.	Test result.....	20
6.5.	Test graphs	21
7.	Power Spectral Density	22
7.1.	Block diagram of test setup	22
7.2.	Limits	22
7.3.	Test procedure	22
7.4.	Test result.....	23
7.5.	Test graphs	24
8.	Band Edge Compliance (Conducted Method).....	25

8.1.	Block diagram of test setup	25
8.2.	Limits	25
8.3.	Test procedure	25
8.4.	Test result.....	26
8.5.	Test graphs	27
9.	RF Conducted Spurious Emissions.....	28
9.1.	Block diagram of test setup	28
9.2.	Limits	28
9.3.	Test procedure	28
9.4.	Test result.....	29
9.5.	Test graphs	30
10.	Duty Cycle	33
10.1.	Block diagram of test setup	33
10.2.	Limit.....	33
10.3.	Test procedure	33
10.4.	Test result.....	34
10.5.	Test graphs	35
11.	Antenna Requirements.....	36
11.1.	Limit.....	36
11.2.	Result	36
12.	Radiated Emission	37
12.1.	Test equipment.....	37
12.2.	Block diagram of test setup	38
12.3.	Limits	40
12.4.	Assistant equipment used for test	41
12.5.	Test procedure	41
12.6.	Test result.....	42
12.7.	Test data	43
13.	Band Edge Compliance.....	53
13.1.	Test equipment.....	53
13.2.	Block diagram of test setup	53
13.3.	Limits	54
13.4.	Assistant equipment used for test	54
13.5.	Test procedure	54
13.6.	Test result.....	54
13.7.	Test data	55
14.	Power Line Conducted Emissions.....	59
14.1.	Test equipment.....	59

14.2. Block diagram of test setup59

14.3. Limits60

14.4. Assistant equipment used for test60

14.5. Test procedure60

14.6. Test result.....61

14.7. Test data62

15. Test Setup Photograph64

16. Photos of the EUT66

Test Report Declare

Applicant	:	Audioengine LLC
Address of Applicant	:	304 Progress Drive, Sherman, TX 75092 United States
Equipment under Test	:	Bluetooth audio receiver
Model No.	:	B1
Manufacturer	:	Audioengine LLC
Address of Manufacturer	:	304 Progress Drive, Sherman, TX 75092 United States

Test Standard Used:
FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26061720-2E02		
Date of Receipt:	2026/06/25	Date of Test:	2026/07/21 - 2026/08/31

Created: Jacky Huang	Reviewed: Johnson Huang	Approved: Damon Hu
		
2026/09/02	2026/09/20	2026/09/20

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/09/20	Damon Hu

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2)	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3)	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e),	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d)	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 4 7 CFR Part 15 15.247(d)	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a)	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Bluetooth audio receiver
Model Number	: B1
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V
Radio Specification	: Bluetooth LE
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK
Data Rate	: 1 Mbps
Antenna Type	: Rod antenna
Max Antenna Gain (dBi)	: 2.55
Data Rate	: 1 Mbps


Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Line cable	/	/	Length: 108cm
SWITCHING MODE POWER SUPPLY	GOLDEN PROFIT ELECTRONICS LTD	GPE006E-050100-Z	INPUT: AC 100-240V~50/60Hz 0.2A, OUTPUT: 5V/1A

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: BlueTest3.exe, version:3.3.5

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Mode	Setting Tx Power	Channel	Frequency (MHz)
BLE 1M	Default	CH0	2402
	Default	CH19	2440
	Default	CH39	2480

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9\text{ kHz} \leq f < 7\text{ GHz}$);
	3.31 dB ($7\text{ GHz} \leq f < 40\text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
	4.14 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
	4.58 dB (18 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	Cal. Interval
☒ RF Connected Test (RF Measurement System 1#)					
SIGNAL ANALYZER	R&S	FSQ26	101272	2027/02/27	1 Year
Wideband Radio Communication Tester	R&S	CMW500	117491	2027/02/27	1 Year
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY59100192	2027/02/27	1 Year
MXG Vector Signal Generator	Agilent	N5182A	MY47420658	2027/02/27	1 Year
RF Control Unit	Tonscend	JS0806-2	158060010	2027/02/27	1 Year
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/02/27	1 Year
Test Software	Tonscend	JS1120-3	V3.6.21	N/A	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW: 100 kHz

VBW: $\geq [3 \times \text{RBW}]$

Detector Mode: Peak

Sweep time: Auto

Trace mode: Max hold


- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.

4.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.71	2401.64	2402.35	0.5	PASS
		2440	0.71	2439.64	2440.35	0.5	PASS
		2480	0.71	2479.64	2480.35	0.5	PASS

4.5. Test graphs



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold


- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.

5.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001


Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	1.0480	2401.4800	2402.5280	---	---
		2440	1.0480	2439.4800	2440.5280	---	---
		2480	1.0440	2479.4800	2480.5240	---	---

5.5. Test graphs



6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.1.1.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW: $\geq$ DTS bandwidth

VBW: $\geq 3 \times$ RBW

Span: $\geq 3 \times$ RBW

Detector Mode: Peak

Sweep time: Auto

Trace mode: Max hold


- (5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.

6.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0.91	≤30	PASS
		2440	1.45	≤30	PASS
		2480	1.56	≤30	PASS

6.5. Test graphs



7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency:	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span:	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold


- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- (6) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-15.51	≤8.00	PASS
		2440	-14.96	≤8.00	PASS
		2480	-14.82	≤8.00	PASS

7.5. Test graphs



8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span:	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

8.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001


Mode	Frequency [MHz]	Measured Range	Verdict
BLE 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass

8.5. Test graphs



9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency:	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span:	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:


RBW:	100 kHz
VBW:	300 kHz
Span:	Encompass frequency range to be measured
Number of measurement points:	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001

Mode	Frequency [MHz]	Verdict
BLE 1M	2402	Pass
	2440	Pass
	2480	Pass

9.5. Test graphs





BLE_1M_Ant1_2440_1000~26500

Ref 26.8 dBm

Offset 15.4 dB

Alt 20 dB

RBW 100 kHz

VBW 300 kHz

SMF 2.6 s

Marker 2 [T1]

-47.54 dBm


24.416350000 GHz

Marker 1 [T1]

6.73 dBm

2.439600000 GHz

Date: 25. AUG 2026 10: 52: 21



BLE_1M_Ant1_2480_1000~26500

Ref 26.8 dBm

Offset 15.4 dB

Alt 20 dB

RBW 100 kHz

VBW 300 kHz

SMF 2.6 s

Marker 2 [T1]

-46.34 dBm

24.815300000 GHz

Marker 1 [T1]

5.68 dBm

2.479850000 GHz


Start 1 GHz

2.55 GHz/

Stop 26.5 GHz

10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset. set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger


- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

10.4. Test result

Test Engineer:	Guoyuan Lin	Test Site:	RF Measurement System 1#
Ambient Condition:	26℃,30%RH	Test Date:	2026.08.12-2026.08.26
Test Power Supply:	DC 5V	Sample Number:	S26061720-001

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
BLE_1M	Ant1	2402	2.15	2.52	85.32	0.69
		2440	2.15	2.52	85.32	0.69
		2480	2.14	2.50	85.60	0.68

10.5. Test graphs



11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

12. Radiated Emission

12.1. Test equipment



Below 1GHz:



Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2026/10/10	1 Year
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2026/10/10	1 Year
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2026/10/10	1 Year
Radiation disturbance fully automated test software	Tonscend	JS32-RE (V5.0.0)	DDT-ZC02739	/	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2027/06/25	1 Year
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2027/07/10	1 Year
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2027/07/10	1 Year

Above 1GHz:

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/	/
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC05922	2027/01/06	1 Year
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10	1 Year
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25	1 Year
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27	1 Year
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10	1 Year
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/	/
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/	/

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Notebook	Lenovo	i5-5300U	Test computer	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna (1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna (18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

- (b) Change work frequency or channel of device if practicable.
- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage
- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement

produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.


12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-21 **Tested By:** Li Xiongbin
Test Mode: BLE1M 2480MHz TX Mode **Power Supply:** DC 5V
Condition: Temp:20.2°C;Humi:57.1% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2026 report data\Q26061720-1E\FCC Below 1G\5
Memo: Sample Number:S26061720-001



Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	31.977	40.39	10.89	3.81	22.79	40.00	17.21	QP	Horizontal
2	60.061	42.51	12.40	4.06	26.67	40.00	13.33	QP	Horizontal
3	191.943	37.42	9.45	4.83	19.31	43.50	24.19	QP	Horizontal
4	264.074	38.08	12.36	5.14	23.18	46.00	22.82	QP	Horizontal
5	431.709	31.66	15.94	5.81	20.88	46.00	25.12	QP	Horizontal
6	620.334	30.61	18.98	6.45	23.14	46.00	22.86	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-21 **Tested By:** Li Xiongbin
Test Mode: BLE1M 2480MHz TX Mode **Power Supply:** DC 5V
Condition: Temp:20.2°C;Humi:57.1% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2026 report data\Q26061720-1E\FCC Below 1G\6
Memo: Sample Number:S26061720-001

**Final Data List**


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	59.893	46.56	12.39	4.06	30.71	40.00	9.29	QP	Vertical
2	99.924	33.76	11.95	4.30	17.71	43.50	25.79	QP	Vertical
3	166.361	36.13	8.89	4.68	17.33	43.50	26.17	QP	Vertical
4	266.306	32.33	12.40	5.15	17.48	46.00	28.52	QP	Vertical
5	366.383	30.81	15.31	5.57	19.22	46.00	26.78	QP	Vertical
6	465.018	38.5	16.20	5.92	28.05	46.00	17.95	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2402MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\1
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3924.000	49.71	31.65	-40.96	40.40	74.00	33.60	PK	Horizontal
2	4173.900	50.06	31.80	-41.09	40.77	74.00	33.23	PK	Horizontal
3	4804.600	55.49	33.22	-41.30	47.41	74.00	26.59	PK	Horizontal
4	7587.500	48.99	37.18	-39.35	46.82	74.00	27.18	PK	Horizontal
5	11130.300	45.27	39.76	-34.99	50.04	74.00	23.96	PK	Horizontal
6	12214.900	45.48	39.89	-35.30	50.07	74.00	23.93	PK	Horizontal

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11130.300	34.02	39.76	-34.99	38.79	54.00	15.21	AV	Horizontal
2	12214.900	33.41	39.89	-35.30	38.00	54.00	16.00	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2402MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\2
Memo: Sample Number:S26061720-001 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3602.700	53.97	30.41	-40.81	43.57	74.00	30.43	PK	Vertical
2	4170.500	49.83	31.78	-41.07	40.54	74.00	33.46	PK	Vertical
3	4802.900	62.79	33.21	-41.30	54.70	74.00	19.30	PK	Vertical
4	7495.700	49.20	37.10	-39.53	46.77	74.00	27.23	PK	Vertical
5	11104.800	44.74	39.71	-34.92	49.53	74.00	24.47	PK	Vertical
6	12136.700	44.52	39.90	-34.93	49.49	74.00	24.51	PK	Vertical

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4804.062	59.09	33.21	-41.30	51.00	54.00	3.00	AV	Vertical
2	11104.800	34.18	39.71	-34.92	38.97	54.00	15.03	AV	Vertical
3	12136.700	32.59	39.90	-34.93	37.56	54.00	16.44	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX BLE1M 2402MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\3
Memo: Sample Number:S26061720-001 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3857.700	50.18	31.52	-40.89	40.81	74.00	33.19	PK	Horizontal
2	4158.600	50.13	31.73	-41.02	40.84	74.00	33.16	PK	Horizontal
3	4802.900	55.43	33.21	-41.30	47.34	74.00	26.66	PK	Horizontal
4	7388.600	49.27	37.25	-39.72	46.80	74.00	27.20	PK	Horizontal
5	11176.200	45.60	39.85	-35.10	50.35	74.00	23.65	PK	Horizontal
6	12277.800	45.64	39.82	-35.17	50.29	74.00	23.71	PK	Horizontal

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11176.200	33.95	39.85	-35.10	38.70	54.00	15.30	AV	Horizontal
2	12277.800	33.75	39.82	-35.17	38.40	54.00	15.60	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX BLE1M 2402MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLEV4
Memo: Sample Number:S26061720-001 Power Setting:NA

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3602.700	54.64	30.41	-40.81	44.24	74.00	29.76	PK	Vertical
2	3884.900	50.26	31.57	-40.83	41.00	74.00	33.00	PK	Vertical
3	4802.900	63.87	33.21	-41.30	55.78	74.00	18.22	PK	Vertical
4	7556.900	48.78	37.11	-39.41	46.48	74.00	27.52	PK	Vertical
5	11584.200	45.69	39.63	-34.91	50.41	74.00	23.59	PK	Vertical
6	12439.300	45.71	39.74	-34.75	50.70	74.00	23.30	PK	Vertical

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4803.990	59.02	33.21	-41.30	50.93	54.00	3.07	AV	Vertical
2	11584.200	34.98	39.63	-34.91	39.70	54.00	14.30	AV	Vertical
3	12439.300	33.24	39.74	-34.75	38.23	54.00	15.77	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2440MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\5
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3900.200	49.80	31.60	-40.80	40.60	74.00	33.40	PK	Horizontal
2	4163.700	50.92	31.75	-41.04	41.63	74.00	32.37	PK	Horizontal
3	5059.600	50.08	34.00	-40.98	43.10	74.00	30.90	PK	Horizontal
4	7330.800	49.94	37.52	-39.68	47.78	74.00	26.22	PK	Horizontal
5	11135.400	45.98	39.77	-35.00	50.75	74.00	23.25	PK	Horizontal
6	11625.000	46.10	39.58	-35.02	50.66	74.00	23.34	PK	Horizontal

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11135.400	34.69	39.77	-35.00	39.46	54.00	14.54	AV	Horizontal
2	11625.000	36.41	39.58	-35.02	40.97	54.00	13.03	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2440MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\6
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3658.800	54.60	30.54	-41.17	43.97	74.00	30.03	PK	Vertical
2	4122.900	50.32	31.65	-40.86	41.11	74.00	32.89	PK	Vertical
3	4879.400	53.89	33.46	-41.27	46.08	74.00	27.92	PK	Vertical
4	7310.400	48.23	37.64	-39.67	46.20	74.00	27.80	PK	Vertical
5	11154.100	45.66	39.81	-35.05	50.42	74.00	23.58	PK	Vertical
6	12386.600	44.96	39.71	-34.45	50.22	74.00	23.78	PK	Vertical

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11154.100	34.64	39.81	-35.05	39.40	54.00	14.60	AV	Vertical
2	12386.600	35.10	39.71	-34.45	40.36	54.00	13.64	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2480MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\7
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3913.800	50.89	31.63	-40.89	41.63	74.00	32.37	PK	Horizontal
2	4170.500	50.98	31.78	-41.07	41.69	74.00	32.31	PK	Horizontal
3	4949.100	50.01	33.70	-40.95	42.76	74.00	31.24	PK	Horizontal
4	7296.800	49.18	37.71	-39.69	47.20	74.00	26.80	PK	Horizontal
5	11053.800	45.45	39.70	-35.26	49.89	74.00	24.11	PK	Horizontal
6	11934.400	45.80	39.67	-35.17	50.30	74.00	23.70	PK	Horizontal

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11053.800	34.31	39.70	-35.26	38.75	54.00	15.25	AV	Horizontal
2	11934.400	33.78	39.67	-35.17	38.28	54.00	15.72	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2480MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\8
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3720.000	52.75	30.78	-41.35	42.18	74.00	31.82	PK	Vertical
2	4138.200	50.45	31.68	-40.93	41.20	74.00	32.80	PK	Vertical
3	4869.200	51.45	33.44	-41.27	43.62	74.00	30.38	PK	Vertical
4	7250.900	49.39	37.80	-40.10	47.09	74.00	26.91	PK	Vertical
5	11171.100	45.61	39.84	-35.09	50.36	74.00	23.64	PK	Vertical
6	11988.800	45.01	39.78	-34.59	50.20	74.00	23.80	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11171.100	34.20	39.84	-35.09	38.95	54.00	15.05	AV	Vertical
2	11988.800	33.72	39.78	-34.59	38.91	54.00	15.09	AV	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/	/
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC05922	2027/01/06	1 Year
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10	1 Year
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25	1 Year
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27	1 Year
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10	1 Year
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/	/

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Notebook	Lenovo	i5-5300U	Test computer	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.


13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2480MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE15
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	42.56	28.60	-26.14	45.02	74.00	28.98	PK	Horizontal
2	2483.902	49.26	28.60	-26.14	51.72	74.00	22.28	PK	Horizontal

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.902	44.95	28.60	-26.14	47.41	54.00	6.59	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-08-04

Tested By:

Zhong Nan

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.5°C;Humi:56.2%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\16

Memo:

Sample Number:S26061720-001 Power Setting:NA



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	52.07	28.60	-26.14	54.53	74.00	19.47	PK	Vertical
2	2483.956	58.89	28.60	-26.14	61.35	74.00	12.65	PK	Vertical


Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	47.26	28.60	-26.14	49.72	54.00	4.28	AV	Vertical
2	2483.956	46.83	28.60	-26.14	49.29	54.00	4.71	AV	Vertical

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Zhong Nan
Test Mode: TX BLE1M 2402MHz Mode **Power Supply:** Battery
Condition: Temp:23.5°C;Humi:56.2% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\17
Memo: Sample Number:S26061720-001 Power Setting:NA



Suspected Data List

NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2372.090	44.34	28.14	-26.14	46.34	74.00	27.66	PK	Horizontal
2	2390.000	41.81	28.18	-26.15	43.84	74.00	30.16	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-08-04

Tested By:

Zhong Nan

Test Mode:

TX BLE1M 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:23.5°C;Humi:56.2%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26061720-2E\FCC ABOVE 1G BLE\18

Memo:

Sample Number:S26061720-001 Power Setting:NA



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2366.940	44.45	28.13	-26.14	46.44	74.00	27.56	PK	Vertical
2	2390.000	43.81	28.18	-26.15	45.84	74.00	28.16	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Power Line Conducted Emissions

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Three-phase artificial power network	SCHWARZBECK	NSLK 8163	DDT-ZC01572	2027/07/08	1 Year
2-Wire ISN	SCHWARZBECK	NTFM 8131	DDT-ZC01008	2027/06/10	1 Year
Impedance Stablisation Network	Schwarzbeck	ISN S1	DDT-ZC00986	2027/06/10	1 Year
Impedance Stablisation Network	Schwarzbeck	ISN S8	DDT-ZC00987	2027/06/10	1 Year
Impedance Stablisation Network	TESEQ	T8-Cat6	DDT-ZC02057	2027/07/19	1 Year
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2027/06/09	1 Year
CE Cable 1	R&S	ESU8/RF2	DDT-ZC00566	2027/06/21	1 Year
8Line ISN	R&S	ENY81	DDT-ZC00542	2027/06/10	1 Year
Pulse Limiter	SCHWARZBECK	ESH3-Z2	DDT-ZC00539	2027/06/10	1 Year
EMI Test Receiver	R&S	ESCI 3	DDT-ZC00235	2027/06/10	1 Year
Two Line V-Network	R&S	ENV216	DDT-ZC00535	2027/06/14	1 Year
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2027/06/09	1 Year
Conducted & Radiated Software	Audix	e3	DDT-ZC00562	/	/

14.2. Block diagram of test setup



14.3. Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “---” means Peak detection; “---” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

14.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2026 CE Report Data\Q26061720-2E\0831 CE.EM6

Test Date : 2026-08-31

Tested By : Jackey Mao

Power Supply : AC 120V/60Hz


Test Mode : BLE mode

Condition : TEMP:23.7°C, RH:63.0%

LISN : 2026 1# ENV 216/LINE

Memo : S26061720-001

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Margin (dB)	Detector	Phase
1	0.21	3.92	9.58	0.00	9.87	23.37	63.40	40.03	QP	LINE
2	0.21	-12.59	9.58	0.00	9.87	6.86	53.40	46.54	Average	LINE
3	0.92	6.17	9.58	0.01	9.87	25.63	56.00	30.37	QP	LINE
4	0.92	-7.34	9.58	0.01	9.87	12.12	46.00	33.88	Average	LINE
5	1.78	-4.01	9.60	0.01	9.87	15.47	56.00	40.53	QP	LINE
6	1.78	-15.09	9.60	0.01	9.87	4.39	46.00	41.61	Average	LINE
7	4.38	-4.69	9.61	0.01	9.88	14.81	56.00	41.19	QP	LINE
8	4.38	-12.64	9.61	0.01	9.88	6.86	46.00	39.14	Average	LINE
9	6.88	0.09	9.63	0.03	9.88	19.63	60.00	40.37	QP	LINE
10	6.88	-11.24	9.63	0.03	9.88	8.30	50.00	41.70	Average	LINE
11	15.72	-8.87	9.92	0.08	9.92	11.05	60.00	48.95	QP	LINE
12	15.72	-16.16	9.92	0.08	9.92	3.76	50.00	46.24	Average	LINE

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2026 CE Report Data\Q26061720-2E\0831 CE.EM6

Test Date : 2026-08-31

Tested By : Jackey Mao

Power Supply : AC 120V/60Hz


Test Mode : BLE mode

Condition : TEMP:23.7°C, RH:63.0%

LISN : 2026 1# ENV 216/NEUTRAL

Memo : S26061720-001

Data: 8




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Margin (dB)	Detector	Phase
1	0.23	2.94	9.60	0.00	9.87	22.41	62.44	40.03	QP	NEUTRAL
2	0.23	-14.00	9.60	0.00	9.87	5.47	52.44	46.97	Average	NEUTRAL
3	0.93	-0.04	9.59	0.01	9.87	19.43	56.00	36.57	QP	NEUTRAL
4	0.93	-12.95	9.59	0.01	9.87	6.52	46.00	39.48	Average	NEUTRAL
5	1.73	-5.85	9.60	0.01	9.87	13.63	56.00	42.37	QP	NEUTRAL
6	1.73	-15.80	9.60	0.01	9.87	3.68	46.00	42.32	Average	NEUTRAL
7	4.29	-3.65	9.65	0.01	9.88	15.89	56.00	40.11	QP	NEUTRAL
8	4.29	-11.20	9.65	0.01	9.88	8.34	46.00	37.66	Average	NEUTRAL
9	6.88	-0.38	9.68	0.03	9.88	19.21	60.00	40.79	QP	NEUTRAL
10	6.88	-10.84	9.68	0.03	9.88	8.75	50.00	41.25	Average	NEUTRAL
11	15.72	-8.42	10.00	0.08	9.92	11.58	60.00	48.42	QP	NEUTRAL
12	15.72	-15.96	10.00	0.08	9.92	4.04	50.00	45.96	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

15. Test Setup Photograph





16. Photos of the EUT

Please refer to DDT-Q26061720-1E appendix I

-----End Report-----