



Report No.: SZEM200900987603

Page: 1 of 7

RF Exposure Evaluation Report

Application No.: SZEM2009009876CR
Applicant: Airspan Networks Inc
Address of Applicant: 777 Yamato Rd Suite 310, Boca Raton, Florida 33431, United States
Manufacturer: Airspan Networks Inc
Address of Manufacturer: 777 Yamato Rd Suite 310, Boca Raton, Florida 33431, United States
Equipment Under Test (EUT):
EUT Name: B42H/B43L/B48
Model No.: My-Pro-FC-B42H-43L-48-C12-CB
Trademark: Airspan
FCC ID: PIDASPOT5410
47 CFR Part 1.1307
Standards: 47 CFR Part 1.1310
47 CFR Part 2.1091
Date of Receipt: 2020-08-10
Date of Test: 2020-08-10 to 2020-09-29
Date of Issue: 2020-12-16

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-12-16		Original

Authorized for issue by:				
				
		Calvin Weng /Project Engineer		
				
		Eric Fu /Reviewer		





3 Contents

	Page
.....	1
2 VERSION.....	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION	5
4.3 TEST FACILITY.....	5
4.4 DEVIATION FROM STANDARDS.....	5
4.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
5.1.1 Limits.....	6
5.1.2 Test Procedure	6
5.1.3 EUT RF Exposure Evaluation.....	7





4 General Information

4.1 General Description of EUT

Power supply:	Adapter Model NO.: G0720-480-050 Input: 100-240V~50/60Hz, 0.75A Output: 48.0V, 0.5A
Test voltage:	AC 120V, 60Hz
Cable:	AC cable: 0.6m unshielded
Sample Type:	Mobile production
LTE Operation Frequency Band:	48
Frequency range:	3550-3700 MHz
Modulation Type:	UL: QPSK, 16QAM, 64QAM DL: QPSK, 16QAM, 64QAM, 256QAM
LTE Release Version:	R11
LTE Power Class:	Level 3
CA Capability MIMO:	DL 4CC 2X2 MIMO DL 3CC 2X2 MIMO DL 2CC 2X2 MIMO DL 2CC 4X4 MIMO DL 1CC 2X2 MIMO DL 1CC 4X4 MIMO UL 1CC 2X2 MIMO UL 2CC SISO Support Intra-band contiguous/non-contiguous CA and support UL MIMO
Antenna Type:	Panel Antenna Ant 4: RX Ant 3: TX & RX Ant 2: TX & RX Ant 1: RX
Antenna Gain:	18dBi
SIM Card:	This device has only one SIM Card sockets.





4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

For Uncontrolled Environment, the MPE limit of 1500MHz to 100000MHz is 1.0 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.





5.1.3 EUT RF Exposure Evaluation

1) Test Results

For LTE Band 48:

The max tune-up tolerance power Into Antenna & RF Exposure Evaluation Distance:

SISO

Antenna	Max Antenna Gain (dBi)	Max Antenna Gain (Numeric)	Max tune-up tolerance power (dBm)	Max tune-up Tolerance power to Antenna (mW)	Power Density at R = 100 cm (mW/cm ²)	Limit (mW/cm ²)	MPE Ratios	Result
Ant3	18	63.10	24.0	251.19	0.1261	1.0	0.1261	PASS

MIMO

Antenna	Max Antenna Gain (dBi)	Max Antenna Gain (Numeric)	Max tune-up tolerance power (dBm)	Max tune-up Tolerance power to Antenna (mW)	Power Density at R=100 cm (mW/cm ²)	Limit (mW/cm ²)	MPE Ratios	Result
Ant3+2	21.01	126.18	25.0	316.23	0.3175	1.0	0.3175	PASS

Note: Refer to report No. SZEM200900987602 or EUT test Max Conducted Output Power value.

The distance (6th column) calculated from the Fries transmission formula is far greater than 100 cm separation requirement.

Since the SAR Exclusion Threshold Level is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

- End of the Report -

