

**Environmental evaluation and exposure limit according to FCC CFR 47part 1,
§1.1307, §1.1310**

The transceiver is classified as fixed, the calculation was done to confirm a safe distance.

Limit for power density for general population/uncontrolled exposure is $f/1500 \text{ mW/cm}^2$ for 300 -1500 MHz frequency range.

$$\text{Limit} = 866.3\text{MHz} / 1500 = 0.578 \text{ mW/cm}^2$$

The power density $P \text{ (mW/cm}^2\text{)} = P_T / 4\pi r^2$, where

P_T is the transmitted power, which is equal to the peak transmitter output power plus maximum antenna gain. The maximum equivalent isotropically radiated power EIRP is

$$P_T = 46.16 \text{ dBm} + 13.5 \text{ dBi} = 59.66 \text{ dBm} = 924698.2 \text{ mW}, \text{ where}$$

46.16 dBm is the EUT maximum output power,
13.5 dBi – antenna gain.

The minimum safe distance “r”, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{924698.2 / (0.578 \times 4\pi)} = 356.95 \text{ cm}.$$

A warning about a safe distance is contained in the user manual.