

Analysis Report

The Equipment Under Test (EUT) is a portable 2.4GHz Transmitter (controller) operating at the frequency range of 2412.2 - 2472.2MHz with 1 MHz channel spacing.

The EUT is powered by 2*1.5V AA battery. And it is able to control the car to move forward/backward and leftward/rightward.

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength: 94.0dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 97.0dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 1.504\text{mw}$

Conducted power = Radiated Power (EIRP) – Antenna Gain
So;

Conducted Power = 1.504mW.

The SAR Exclusion Threshold Level:

$= 3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$
 $= 3.0 \cdot 5 / \sqrt{2.475} \text{ mW}$
 $= 9.53 \text{ mW}$

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.