

HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.

INT'L STANDARD CERTIFICATION TEAM
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA
TEL : +82 31 639 8518 FAX : +82 31 639 8525 www.hctec.co.kr

CERTIFICATION

Manufacture;

IMAGEQUEST CO., LTD.
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI,
KYOUNKI-DO, 467-701, KOREA

Date of Issue: DECEMBER 3, 2001

Test Report No.: HCT-F01-1201

**Test Site: HYUNDAI CALIBRATION & CERTIFICATION
TECHNOLOGIES CO., LTD.**

FCC ID :

PJIL550B

MODEL / TYPE :

L550B

FCC Rule Part(s):

Part 15 & 2; ET Docket 95-19

Classification:

FCC Class B Peripheral Device (JBP)

Standard(s):

FCC Class B: 1998 (CISPR 22)

Equipment(EUT) Type:

15" LCD Monitor

Max Resolution:

1024X768 (@60KHz/ 75Hz)

Port/ Connector(s):

15-pin D-sub VGA connector


LCD PALEL:

HYUNDAI DISPLAY TECHNOLOGY.INC. (HT15X13-100)

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992.(See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HYUNDAI C-Tech. certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse of 1988,21 U.S.C.853(a).



Report prepared by : Ki-Soo Kim
Manager of EMC Tech. Part



TABLE OF CONTENTS

PAGE

1. GENERAL INFORMATION.....	3
1.1 Product Description.....	3
1.2 Related submittal(s)/Grant(s).....	3
1.3 Tested System Details.....	4
1.4 Test Methodology.....	4
1.5 Test Facility.....	4
2. SYSTEM TEST CONFIGURATION.....	5
2.1 Justification.....	5
2.2 EUT Exercise Software.....	5
2.3 Cable Description.....	6
2.4 Noise Suppression Parts on Cable.....	6
2.5 Equipment Modifications.....	7
2.6 Configuration of Tested System.....	8
3. PRELIMINARY TESTS.....	9
3.1 Power line Conducted Emissions Tests.....	9
3.2 Radiated Emissions Tests.....	9
4. FINAL CONDUCTED AND RADIATED EMISSION TESTS SUMMARY.....	9
4.1 Conducted Emission Tests.....	10
4.2 Radiated Emission Tests.....	11
5. FIELD STRENGTH CALCULATION.....	12
6. LIST OF TEST EQUIPMENT	13

ATTACHMENT A	ID Label / Location Info.
ATTACHMENT B.....	External Photos.
ATTACHMENT C	Block Diagram..
ATTACHMENT D	Test Setup Photos.
ATTACHMENT E	User's Manual.
ATTACHMENT F	Internal Photos.

1. GENERAL INFORMATION

1.1 Product Description

The ImageQuest CO., LTD. Model L550B (referred to as the EUT in this report) is a 15" LCD Monitor HOR. Freq. 60KHz w/max. Resolution of 1024X768 . Product specification information described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	PLASTIC
LIST OF EACH OSC. OR XTAL. FREQ.(FREQ. 1MHz)	12MHz, 20MHz
POWER REQUIREMENT	100-240V AC 60/50Hz 1.0A
NUMBER OF LAYERS	MAIN BOARD 4 LAYER OSD BOARD 1 LAYER POWER BOARD 1 LAYER INVERTER BOARD 4 LAYER
MAX. RESOLUTION	1024X768 (@60KHz/ 75 Hz)
H-SYNC FREQUENCY RANGE	31KHz 60KHz
V-SYNC FREQUENCY RANGE	56Hz 75Hz
LCD TYPE	15" (LCD Type : HT15X13-100)

1.2 Related Submittal(s) / Grant(s)

ORIGINAL SUBMITTAL ONLY

1.3 Tested System Details

The Model names for all equipment, plus descriptions used in the tested system (including inserted cards) are:

DEVICE TYPE	MANUFACTURER	MODEL NUMBER	FCC ID / DoC	CONNECTED TO
MONITOR (EUT)	IMAGEQUEST CO., LTD.	L550B	PJIL550B	HOST
PC(HOST)	H/P	DTPC-17	DoC	N/A
KEY BOARD	H/P	SK-2501-2D-K	GYUR385K	HOST
PRINTER	H/P	HP895C	DoC	HOST
MODEM	3COM CORPORATION	56K FAX MODEM	DoC	HOST
VIDEO CARD	DIAMOND	3D3000	DoC	HOST
MOUSE	H/P	INTELLIMOUSE	DZL211029	HOST

1.4 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4/1992. Radiated testing was performed at an antenna to EUT distance of 10 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, MAEKOK-RI, HOBUP-MYUN, ICHON-SI, KYOUNGKI-DO, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 24, 2000 (Confirmation Number: EA90661)

2.SYSTEM TEST CONFIGURATION

2.1 Justification

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following components and I/O cards inside the E.U.T were used.

DEVICE TYPE	MANUFACTURE	MODEL/PART NUMBER
MAIN BOARD	ImageQuest CO., Ltd.	3041001039
POWER BOARD	C&C TECH CO.,LTD.	3610200087
OSD BOARD	ImageQuest CO., Ltd.	3010700781
INVERTOR BOARD	ImageQuest CO., Ltd.	3610400244
LCD BOARD	Hyundai Display Technology Inc.	HT15X13-100

2.2 EUT exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software, contained on a 3-1/2 inch disc, was inserted into drive A and is auto starting on power-up. Once loaded, the program sequentially exercises each system component in turn. The sequence used is :(1) Display test, (2) RS 232 test (3) Key board test,(4) Printer test,(5) FDD test,(6) HDD test. The complete cycle takes about 20 seconds and is repeated continuously. As the keyboard and mouse are strictly input devices, no data is transmitted to them during test. They are however, continuously scanned for data input activity. The video resolution modes setup and change program was used during the radiated and conducted emission testing.

2.3 Cable Description

The marked "(D)" means the Data Cable and "(P)" means the Power Cable.

	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
MONITOR(EUT)	N	Y	1.8(P), 1.5(D)
PC(HOST)	N	N/A	1.8(P)
PRINTER	N	Y	2.0(P),1.8(D)
KEY BOARD	N/A	Y	2.0(D)
MODEM	N	Y	2.0(P),0.8(D)
MOUSE	N/A	Y	1.8(D)

2.4 Noise Suppression Parts on Cable. (I/O CABLE)

	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
MONITOR(EUT)	Y	BOTH END	Y	BOTH END
PRINTER	N	PC END	Y	BOTH END
KEY BOARD	Y	PC END	Y	PC END
MODEM	Y	PC END	Y	BOTH END
MOUSE	N	N/A	Y	PC END

2.5 Equipment Modifications

N/A


2.6 Configuration of Test system

Line Conducted Test : EUT was connected to LISN, all other supporting equipment were connected to another LISN.

Preliminary Power line Conducted Emission tests were performed by using the procedure in ANSI C63.4/1992 7.2.3 to determine the worse operating conditions.

Radiated Emission Test : Preliminary Radiated Emissions tests were conducted using the procedure in ANSI C63.4/1992 8.3.1.1 to determine the worse operating condition. Final Radiated Emission tests were conducted at 10 meter open area test site.

[Configuration of Tested System]



3. PRELIMINARY TESTS

3.1 AC Power line Conducted Emission Tests

During Preliminary Tests, the following operating mode were investigated

Processor Speed (MHz)	Video Resolution (w/max)	The worst operating condition
Pentium 350 MHz	1024X768 (60KHz/75Hz)	X
	1024X768 (48.4KHz/60Hz)	
	1024X768 (56.5KHz/70Hz)	
	720X400 (31.5KHz/70Hz)	
	800 x 600 (46.7 KHz/75Hz)	
	640 x 480 (31.5KHz/60Hz)	

4.2 Radiated Emission Tests

During Preliminary Tests, the following operating mode were investigated

Processor Speed (MHz)	Video Resolution (w/max)	The worst operating condition
Pentium 350 MHz	1024X768 (60KHz/75Hz)	X
	1024X768 (48.4KHz/60Hz)	
	1024X768 (56.5KHz/70Hz)	
	720X400 (31.5KHz/70Hz)	
	800 x 600 (46.7 KHz/75Hz)	
	640 x 480 (31.5KHz/60Hz)	

Tested by Kyoung-Houn SEO / Engineer

Date : NOVEMBER 19, 2001

4. FINAL CONDUCTED AND RADIATED EMISSION TESTS SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Humidity Level : 39% Temperature : 25
 Limit apply to : CISPR 22
 Type of Tests : CLASS B
 Date : NOVEMBER 27, 2001
 Result : PASSED BY 4.0 dB
 EUT : 15" LCD MONITOR

Operating Condition : 1024X768 (Hf : 60KHz, Vf : 75Hz)
 Detector : CISPR Quasi-Peak (6 dB Bandwidth : 9 KHz)
 CISPR Average(6 dB Bandwidth : 9 KHz)

Line Conducted Emission Tabulated Data

Power Line Conducted Emissions			CISPR 22		
Frequency (MHz)	Amplitude (dBuV)	Conductor	Limit (dBuV)	Margin (dB)	Detector Mode
0.165	61.20	NEUTRAL	65.0	4.0	Quasi-Peak
0.170	49.30	HOT	55.0	5.7	Average
0.165	48.80	NEUTRAL	55.0	6.4	Average
0.185	57.00	NEUTRAL	64.0	7.3	Quasi-Peak

NOET:

1. All video modes and resolutions were investigated and the worst-case emissions are reported
 Other video modes & resolution were tested and found to be in compliance.

Measured by : Kyoung-Houn SEO / Engineer


Date : NOVEMBER 27, 2001

HYUNDAI C-TECH. CO., LTD.
EMC TEST LAB.

EUT: L550B
 Manufacturer: IMAGEQUEST
 Operating Condition:
 Test Site: Shield Room
 Operator:
 Test Specification: CISPR CLASS B
 Comment: N
 Start of Test: 11/27/01 / 10:57:11AM

SCAN TABLE: "EN 55022 V "

Short Description:			EN 55022 Voltage			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	100.0 ms	9 kHz	CABLE LOSS (NEW)
			Average			
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	CABLE LOSS (NEW)
			Average			


MEASUREMENT RESULT: "L550B _fin QP"

11/27/01 11:01AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.165000	61.20	0.5	65	4.0	1	---
0.185000	57.00	0.5	64	7.3	1	---
0.255000	47.80	0.5	62	13.8	1	---
0.275000	46.00	0.5	61	15.0	1	---
0.350000	41.90	0.5	59	17.1	1	---
0.460000	37.00	0.5	57	19.7	1	---
0.860000	39.40	0.5	56	16.6	1	---
0.890000	40.90	0.5	56	15.1	1	---
1.310000	39.00	0.5	56	17.0	1	---
1.405000	39.50	0.5	56	16.5	1	---
2.025000	38.20	0.6	56	17.8	1	---
3.855000	37.50	0.7	56	18.5	1	---
5.415000	38.10	0.9	60	21.9	1	---
5.450000	38.10	0.9	60	21.9	1	---

MEASUREMENT RESULT: "L550B _fin QP"
(continued)

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
7.825000	36.30	1.1	60	23.7	1	---
12.240000	37.30	1.4	60	22.7	1	---
12.425000	37.20	1.4	60	22.8	1	---
12.985000	34.60	1.4	60	25.4	1	---

MEASUREMENT RESULT: "L550B _fin AV"
11/27/01 10:56AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.165000	48.80	0.5	55	6.4	1	---
0.185000	39.50	0.5	54	14.8	1	---
0.250000	36.70	0.5	52	15.0	1	---
0.330000	28.10	0.5	50	21.3	1	---
0.335000	29.20	0.5	49	20.1	1	---
0.425000	22.20	0.6	47	25.2	1	---
0.715000	25.80	0.5	46	20.2	1	---
0.735000	25.40	0.5	46	20.6	1	---
0.830000	28.80	0.5	46	17.2	1	---
1.320000	28.00	0.5	46	18.0	1	---
1.900000	27.10	0.6	46	18.9	1	---
4.145000	27.30	0.8	46	18.7	1	---
5.535000	26.20	1.0	50	23.8	1	---
8.065000	23.40	1.2	50	26.6	1	---
12.125000	22.20	1.4	50	27.8	1	---
12.270000	22.20	1.4	50	27.8	1	---
12.425000	21.80	1.4	50	28.2	1	---
12.435000	21.70	1.4	50	28.3	1	---

HYUNDAI C-TECH. CO., LTD.
EMC TEST LAB.

EUT: L550B
 Manufacturer: IMAGEQUEST
 Operating Condition:
 Test Site: Shield Room
 Operator:
 Test Specification: CISPR CLASS B
 Comment: H
 Start of Test: 11/27/01 / 10:51:47AM

SCAN TABLE: "EN 55022 V"

Short Description:	EN 55022 Voltage	Detector	Meas. Time	IF Bandw.	Transducer
Start Stop Step					
Frequency Width					
150.0 kHz 500.0 kHz 5.0 kHz		MaxPeak	100.0 ms	9 kHz	CABLE LOSS (NEW)
		Average			
500.0 kHz 5.0 MHz 5.0 kHz		MaxPeak	10.0 ms	9 kHz	CABLE LOSS (NEW)
		Average			


MEASUREMENT RESULT: "L550B _fin QP"

11/27/01 10:55AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.160000	58.10	0.5	66	7.3	1	---
0.185000	52.10	0.5	64	12.2	1	---
0.255000	48.90	0.5	62	12.7	1	---
0.275000	44.80	0.5	61	16.2	1	---
0.350000	43.10	0.5	59	15.8	1	---
0.425000	37.90	0.5	57	19.4	1	---
0.875000	41.20	0.5	56	14.8	1	---
1.290000	39.00	0.5	56	17.0	1	---
1.375000	39.60	0.5	56	16.4	1	---
1.795000	37.60	0.6	56	18.4	1	---
1.915000	38.90	0.6	56	17.1	1	---
1.990000	37.60	0.6	56	18.4	1	---
5.315000	37.50	0.9	60	22.5	1	---
7.695000	35.60	1.1	60	24.4	1	---

MEASUREMENT RESULT: "L550B _fin QP"
(continued)

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Line	PE
5.510000	37.70	1.0	60	22.3	1	---
7.705000	37.30	1.1	60	22.7	1	---
7.780000	37.40	1.1	60	22.6	1	---
11.845000	36.30	1.4	60	23.7	1	---

MEASUREMENT RESULT: "L550B _fin AV"
11/27/01 11:01AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Line	PE
0.170000	49.30	0.5	55	5.7	1	---
0.185000	43.20	0.5	54	11.1	1	---
0.255000	36.70	0.5	52	14.9	1	---
0.275000	32.20	0.5	51	18.8	1	---
0.350000	26.40	0.5	49	22.6	1	---
0.425000	22.90	0.5	47	24.4	1	---
0.840000	28.20	0.5	46	17.8	1	---
0.930000	29.30	0.5	46	16.7	1	---
1.345000	28.00	0.5	46	18.0	1	---
1.770000	27.70	0.6	46	18.3	1	---
1.865000	28.10	0.6	46	17.9	1	---
3.855000	26.30	0.7	46	19.7	1	---
5.210000	25.60	0.9	50	24.4	1	---
8.060000	23.30	1.2	50	26.7	1	---
11.955000	24.20	1.4	50	25.8	1	---
12.205000	23.50	1.4	50	26.5	1	---
12.265000	23.50	1.4	50	26.5	1	---
12.370000	22.90	1.4	50	27.1	1	---

4.2 Radiated Emissions Tests

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

Humidity Level : 38 % Temperature : 24
 Limit apply to : CISPR 22
 Type of Tests : CLASS B
 Date : NOVEMBER 23, 2001
 Result : PASSED BY 3.2dB

EUT : 15" LCD MONITOR
 Operating Condition : 1024X768 (Hf : 60 kHz, Vf : 75 Hz)
 Detector : CISPR Quasi-Peak (6 dB Bandwidth : 120 KHz)

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dBuV
66.5	15.11	6.39	1.70	V	23.2	30.0	-6.8
134.0	8.72	14.28	2.50	H	25.5	30.0	-4.5
140.0	9.03	14.57	2.50	V	26.1	30.0	-3.9
147.5	2.92	14.68	2.50	V	20.1	30.0	-9.9
154.2	9.43	14.77	2.60	H	26.8	30.0	-3.2
175.1	8.75	15.05	2.70	V	26.5	30.0	-3.5
200.8	5.12	15.78	3.00	V	23.9	30.0	-6.1
210.2	6.20	16.20	3.20	V	25.6	30.0	-4.4
403.3	12.75	16.55	4.20	H	33.5	37.0	-3.5
525.8	7.65	18.95	5.10	H	31.7	37.0	-5.3
679.8	5.31	22.29	6.00	H	33.6	37.0	-3.4
769.0	1.57	22.73	6.50	V	30.8	37.0	-6.2

NOTE:

- 1.All video modes and resolutions were investigated and the worst-case emissions are reported.
- 2.Other video modes & resolution were tested and found to be in compliance.

Measured by Kyoung-Houn SEO / Engineer

Date : NOVEMBER 23 , 2001

5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dBuV is obtained. The Antenna Factor of 7.4 and a Cable Factor of 1.1 is added. The 30 dBuV/m value was mathematically converted to its corresponding level in uV/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dBuV/m}$$

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(30 \text{ dBuV/m})/20] = 31.6 \text{ uV/m}$$

6. LIST OF TEST EQUIPMENT

<u>TYPE</u>	<u>MANUFACTURE</u>	<u>MODEL</u>	<u>CAL. DATE</u>
EMI Test Receiver	Rohde & Schwarz	ESH3	2001.6.29
EMI Test Receiver	Rohde & Schwarz	ESVP	2001.2.14
EMI Test Receiver	Rohde & Schwarz	ESI40	2001.1.18
EMI Test Receiver	Rohde & Schwarz	ESVS30	2001.6.26
Spectrum Monitor	Rohde & Schwarz	EZM	N.A
Graphic Plotter	Rohde & Schwarz	DOP2	N.A
Printer	Rohde & Schwarz	PDN	N.A
Spectrum Analyzer	H.P	8591EM	2001.7.11
LISN	EMCO	3825/2	2001.7.13
LISN	Rohde & Schwarz	ESH2-Z5	2001.7.14
Amplifier	Hewlett-Packard	8447E	2001.3.2
Dipole Antennas	Rohde & Schwarz	VHAP	2001.6.28
Dipole Antennas	Rohde & Schwarz	UHAP	2001.6.28
Biconical Antenna	Rohde & Schwarz	BBA-9106	2001.6.28
Log-Periodic Antenna	Rohde & Schwarz	UHALP-9107	2001.6.26
Antenna Position Tower	EMCO	1051-12	N.A
Turn Table	EMCO	1060-06	N.A
Line Filter	KEENE	ULW 2X30-60	N.A
Power Analyzer	Voltech	PM 3300	2001.2.20
Reference Network	ImpedanceVoltech	IEC 555	N.A
AC Power Source	PACIFIC	Magnetic Module	N.A
AC Power Source	PACIFIC	360AMX	N.A