

Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-0421/20-01-01 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	PJMLRU3000A
ISED number	6633A-LRU3000A
HVIN (Hardware Version Identification Number)	FE784
PMN (Product Marketing Name)	ID ISC.LRU3000-FCC ID ISC.LRU3500-FCC
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-


This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



cn=Michael Dorongovski, o=CTC Advanced
GmbH, ou=RCE-201118,
email=Michael.Dorongovski@ctcadvanced.co
m, c=DE
2020.12.17 16:05:19 +01'00'

Michael Dorongovski
Lab Manager
Radio Communications



cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-161125,
email=marco.scigliano@ctcadvanced.co
m, c=DE
2020.12.17 17:36:45 +01'00'

Marco Scigliano
Testing Manager
Radio Communications

EUT technologies:

Technologies:	Max. measured power conducted:	Max. antenna gain:	Max. declared EIRP
UHF RFID*	30 dBm	6 dBi	36 dBm

)* for detailed test results see CTC advanced test report 1-0421/20-01-08

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density

P = Power input to the antenna

G = Antenna gain

R = Distance to the center of radiation of the antenna

PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:	SRD	
Frequency (MHz)	902	
PG Declared max power (EIRP)	36	dBm
R Distance	23	cm
S MPE limit for uncontrolled exposure	0.601333333	mW/cm ²
Calculated Power density:	0.5992	mW/cm ²
Calculated percentage of Limit:	99.64%	

This prediction demonstrates the following:

The power density levels for FCC at a distance of 23 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, general limitations for E- and H- Field

Reference levels for general public (uncontrolled environment) exposure to time-varying electric and magnetic fields

According to: RSS 102-ISSUE 05		
Frequency Range (MHz)	Power density (W/m ²)	Reference Period (minutes)
0.003-10	--	Instantaneous*
0.1-10	--	6**
1.1-10	--	6**
10-20	2	6
20-48	$8.944 / f^{0.5}$	6
48-300	1.291	6
300-6000	$0.02619 \times f^{0.6834}$	6
6000-15000	10	6
15000-150000	10	$616000 / f^{1.2}$
150000-300000	$6.67 \times 10^{-5} \times f$	$616000 / f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).		

NOTE:

The resulting Limit for 902 MHz is 2.74W/m²

Prediction: worst case

		UHF RFID	
	Frequency	902	MHz
R	Distance	35	cm
PG	Maximum EIRP	36	dBm
PG	Maximum EIRP	3981.1	mW
S	Power density	2.6	W/m ²
	Exclusion Limit from above:	2.74	W/m ²
	Calculated percentage of Limit:	94.39%	

The power density levels for FCC at a distance of 35 cm are below the maximum levels allowed by regulations.