

May Cheong Toy Products Fty. Ltd.

TEST REPORT

SCOPE OF WORK

RF TESTING-81154(13086/81082)
ADDITIONAL MODELS: SEE PAGE 5

REPORT NUMBER

SZHH01259553-001

ISSUE DATE

August 20, 2018

PAGES

14

DOCUMENT CONTROL NUMBER

FCC 15C_RX_b
© 2017 INTERTEK



May Cheong Toy Products Fty. Ltd.

Application For Certification
FCC ID: PKG81082RC49M

Product Name: 1:24 Formula R/C, asst.

Additional names: 1:24 Radio Control vehicles, Assorted ; 1:24 Licensed R/C Vehicles, Asst. ; 1:24 R/C Asst. ; 1:24 Radio Control vehicles, Assorted ; 1:24 CSRC with working headlights Asst. ; 1:24 CSRC with working headlights Asst. ; 1:24 R/C with stick controller, Asst. ; 1:24 R/C in mailer box pack ; 1:24 H-D Custom RC VW Van Samba ; Radio Control Vehicle 7.5" non-licensed R/C ; 1:14 R/C Formula, asst. ; HD RC Motorcycle - XL 1200N Nightster With Rider 1:24 Ferrari RC - Ferrari SF15-T ; ; 1:24 Red Bull RC - Infiniti Red Bull Racing RB11 ; Radio Control Vehicle 1:24 Formula R/C - Ferrari F138 ; Radio Control Vehicle 1:18 R/C Red Bull Racing RB9 ; Radio Control Vehicle 1:24 R/C Red Bull Racing RB9 ; 1:16 R/C Recon Rover ; Radio Control Vehicle Light Runners R/C, Asst. ; ; Cyklone 360 ; Cyklone 360 ; 1:16 Harley-Davidson Custom RC ; 1:24 R/C in horizontal smaller box, ; 1:10 Badlanders asst. ; Cyklon Twist / Cyklon Twist ; 1:18 Vision GT RC, asst.

Model: 81154(13086/81082)

Additional Models: See page 5

Superregenerative Receiver

Report No.: SZHH01259553-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart B for Superregenerative Receiver, mention 47 CFR [10-1-17]

Prepared and Checked by:

Approved by:

Sign on file
Terry Tang
Senior Engineer

Jimmy Wen
Supervisor
Date: August 20, 2018

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.
-

Intertek Testing Services Shenzhen Ltd. Longhua Branch

1F/2F, Building B, QiaoAn Scientific Technology Park, Shangheng Community, Guanhu Subdistrict,
Longhua District, Shenzhen, P.R. China

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

GENERAL INFORMATION

May Cheong Toy Products Fty. Ltd.

MODEL: 81154(13086/81082)

FCC ID: PKG81082RC49M

Grantee:	May Cheong Toy Products Fty. Ltd.
Grantee Address:	Unit 901-2, 9/F., East Ocean Centre, 98 Granville Road, Tsimshatsui East Kowloon Hong Kong
Contact Person:	Anson Wang
Tel:	(769)8775 3128ext132
Manufacturer:	May Cheong Toy Products Fty. Ltd.
Manufacturer Address:	Unit 901-2, 9/F., East Ocean Centre, 98 Granville Road, Tsimshatsui East Kowloon Hong Kong
Model:	81154(13086/81082)
Type of EUT:	Superregenerative Receiver
Description of EUT:	1:24 Formula R/C, asst.
Serial Number:	N/A
FCC ID :	PKG81082RC49M
Date of Sample Submitted:	May 28, 2018
Date of Test:	August 06, 2018
Report No.:	SZHH01259553-001
Report Date:	August 20, 2018
Environmental Conidtions:	Temperature: +10 to 40°C Humidity: 10 to 90%

SUMMARY OF TEST RESULT

May Cheong Toy Products Fty. Ltd.

MODEL: 81154(13086/81082)

FCC ID: PKG81082RC49M

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenn Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.5	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	N/A
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	N/A
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	N/A
Receiver / Digital Device Radiated Emissions	15.109 / ICES-003	Pass
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

Table of Contents

1.0	<u>General Description</u>	5
1.1	Product Description	5
1.2	Related Submittal(s) Grants	5
1.3	Test Methodology	6
1.4	Test Facility	6
2.0	<u>System Test Configuration</u>	7
2.1	Justification	7
2.2	EUT Exercising Software	7
2.3	Special Accessories	7
2.4	Equipment Modification	7
2.5	Measurement Uncertainty	7
2.6	Support Equipment List and Description	7
3.0	<u>Emission Results</u>	8
3.1	Field Strength Calculation	8
3.2	Radiated Emission Configuration Photograph	9
3.3	Radiated Emission Data	9
4.0	<u>Equipment Photographs</u>	11
5.0	<u>Product Labelling</u>	11
6.0	<u>Technical Specifications</u>	11
7.0	<u>Instruction Manual</u>	11
8.0	<u>Miscellaneous Information</u>	11
8.1	Stabilization Waveform	12
8.2	Discussion of Pulse Desensitization	12
8.3	Calculation of Average Factor	12
8.4	Emissions Test Procedures	13
8.4	Emissions Test Procedures (cont'd)	14
9.0	<u>Equipment List</u>	14

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a receiver for a 1:24 Formula R/C, asst. operating at 49.860MHz. The EUT is powered by two 1.5V AAA batteries. For more detail information pls. refer to the user manual.

The model: 81154 is package numbers which include a transmitter and a receiver, the transmitter model number is 13086, receiver model number is 81082, the additional receiver models: 81051/81052/81053/81054/81055/81057/81058/81059/81061/81062/81063/81064/81065/81066/81067/81068/81073/81074/81077/81078/81079/81082/81086/81091/81126/81142/81087/81088/81089/81159/81185/81186/81090/81160/81501/81502, 81144, 10043/10044, 81251/81252/81253/81254/81255, 81661, 12051/12118, 15961/13086, 82041/82042, 81211/81212/81213/8124/81215/81216 are same as the model: 81082 in hardware and electrical aspect. The difference in appearance and model number serves as marketing strategy.

The Additional Models: 81016/81017/81018/81056/81141/81217/ 83018 (81051/81052/81053/81054/81055/81057/81058/81059/81061/81062/81063/81064/81065/81066/81067/81068/81073/81074/81077/81078/81079/81082/81086/81091/81126/81142/81087/81088/81089/81159/81185/81186/81090/81160/81501/81502); 81681(81144); 81165(10043/10044); 81250(81251/81252/81253/81254/81255); 81660(81661); 81190/81191/81074/81084/81143/81127; 81202(12051/12118); 82066/82086(15961/13086); 82040(82041/82042); 81210(81211/81212/81213/8124/81215/81216) are the same as the Model: 81154(13086/81082) in hardware aspect (circuitry and electrical, mechanical and physical construction), the only differences are the appearance and product name and model no. for trading purpose.

Antenna Type: integral antenna

Type of modulation: Pulse modulation

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is an application for certification of a receiver for the 1:24 Formula R/C, asst., and there has a transmitter which associated with this EUT, has FCC ID: PKG13086RC49M and has been granted.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2013). Radiated Emission measurement was performed in a Semi-anechoic chamber. Preliminary scans were performed in the Semi-anechoic chamber only to determine worst case modes. . For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are Intertek **Testing Services Shenzhen Ltd. Longhua Branch** and located at 1F/2F, Building B, QiaoAn Scientific Technology Park, Shangkeng Community, Guanhu Subdistrict, Longhua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

2.0 System Test Configuration

2.1 Justification.

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2014).

The EUT was powered by two new 1.5V AAA batteries during test.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Exhibit 3.0.

The unit was operated standalone and placed in the centre of the turntable

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the polystyrene turntable, which enabled the Senior Engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it can transmit the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by May Cheong Toy Products Pty. Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description N/A.

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB μ V/m
- RR = RA - AG - AV in dB μ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V/m	
AF = 7.4 dB	RR = 18.0 dB μ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB μ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission at 49.6 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 6.2dB

TEST PERSONNEL:

Sign on file

Terry Tang, Senior Engineer
Typed/Printed Name

August 06, 2018
Date

Applicant: May Cheong Toy Products Fty. Ltd.

Date of Test: August 06, 2018

Model: 81154(13086/81082)

Worst Case Operating Mode:

Receive

Table

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	49.600	42.8	20	11.0	33.8	40.0	-6.2
Vertical	51.060	35.9	20	11.0	26.9	40.0	-13.1
Vertical	51.640	35.5	20	11.0	26.5	40.0	-13.5
Horizontal	49.600	31.6	20	11.0	22.6	40.0	-17.4
Horizontal	51.060	30.7	20	11.0	21.7	40.0	-18.3
Horizontal	51.640	29.6	20	11.0	20.6	40.0	-19.4

NOTES: 1. Quasi Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

8.1 Stabilization Waveform

Previous to the testing, the superregenerative receiver was stabilized as outlined in the test procedure. For the electronic filing, the plot saved with filename: superreg.pdf show the fundamental emission when a signal generator was used to stabilize the receiver. Please note that the antenna was placed as close as possible to the EUT for clear demonstration of the waveform and that accurate readings are not possible from this plot.

8.2 Discussion of Pulse Desensitization

This device is a superregenerative receiver. No desensitization of the measurement equipment is required as the received signals are continuously.

8.3 Calculation of Average Factor

This device is a superregenerative receiver. It is not necessary to apply average factor to the measurement result.

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of superregenerative receivers operating under the Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2014. Superregenerative receivers are stabilized prior to measurement by generating a signal well above the receiver threshold whose frequency is tuned until the emissions stabilize into a line spectrum. The signal is usually generated as CW with a R&S SML03 signal generator and a short whip antenna and is at a level of several hundred to several thousand mV/m. Plots of the stabilized signal will be shown. If a modulated signal is used, it will be noted.

The equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

The frequency range scanned is from 30 MHz to 1000 MHz.

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2014.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

9.0 Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ185-01	EMI Receiver	R&S	ESCI	100547	24-Jan-18	24-Jan-19
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	16-Jan-17	16-Jan-19
SZ062-02	RF Cable	RADIAL	RG 213U	--	2-Jul-18	2-Jan-19
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	11-Mar-18	11-Sep-18
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2-May-18	2-May-19
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	20-Sep-17	20-Sep-18
SZ180-01	Signal Generator	R&S	SML03	--	8-Jun-18	8-Jun-19