



ELECTROMAGNETIC EMISSION COMPLIANCE REPORT

Test report file number : E014R-009

Applicant : AMT CO., LTD.

Address : 5F1. DaeA Venture Bldg., 1594-4, Seocho-Dong, Seocho-Gu, Seoul, 137-070, Korea

Manufacturer : SM Electronics Co., Ltd.

Address : 6Block 1 -14, Jupori, Bongyang-Uep, Jechun-City, Chungbuk, 390-870, Korea

Type of Equipment : Digital Satellite Receiver

FCC ID. : PKJDSR-101PA

Model / Type No. : DSR-101PA

Serial number : N/A

Total page of Report : 19 pages (including this page)

Date of Incoming : January 16, 2001

Date of issue : April 10, 2001

SUMMARY

The equipment complies with the regulation; FCC PART 15 SUBPART B §15.101.

This test report contains only the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Prepared by:

G. W. Lee / Ass. Chief Engineer
EMC Dept.
ONETECH Corp.

Approved by:

S. S. Hong / Managing Director
ONETECH Corp.

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)



CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 RELATED SUBMITTAL(S) / GRANT(S)	5
2.3 TEST SYSTEM DETAILS	6
2.4 TEST METHODOLOGY	6
2.5 TEST FACILITY	6
3. SYSTEM TEST CONFIGURATION	6
3.1 JUSTIFICATION	6
3.2 EUT EXERCISE SOFTWARE	7
3.3 CABLE DESCRIPTION	7
3.4 NOISE SUPPRESSION PARTS ON CABLE	7
3.5 EQUIPMENT MODIFICATIONS	7
3.6 CONFIGURATION OF TEST SYSTEM	8
3.6.1 Line Conducted Test	8
3.6.2 Radiated Emission Test	8
3.6.3 Output Signal Level Test	8
3.6.4 Output Terminal Conducted Spurious Emission test	8
3.6.5 Transfer Switch Isolation Test	9
4. PRELIMINARY TEST	9
4.1 AC POWER LINE CONDUCTED EMISSION TEST	9
4.2 RADIATED EMISSIONS TESTS	9
5. FINAL RESULT OF MEASUREMENT	10
5.1 CONDUCTED EMISSION TEST	10
5.2 RADIATED EMISSION TEST	12
5.3. ANTENNA POWER CONDUCTION DATA	15
5.4 OUTPUT TERMINAL SIGNAL LEVEL TEST	16
5.5 OUTPUT TERMINAL CONDUCTED SPURIOUS EMISSIONS TEST	17
5.6 TRANSFER SWITCH ISOLATION TEST	18

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)



6. FIELD STRENGTH CALCULATION	19
7. LIST OF TEST EQUIPMENT	20



1. VERIFICATION OF COMPLIANCE

APPLICANT : AMT CO., LTD.
ADDRESS : 5F1. DaeA Venture Bldg., 1594-4, Seocho-Dong, Seocho-Gu, Seoul, 137-070, Korea
CONTACT PERSON : Mr. Yong-Jin, Kim / Engineer
TELEPHONE NO : +82-2-3470-1204
FCC ID : PKJDSR-101PA
MODEL NO/NAME : DSR-101PA
SERIAL NUMBER : N/A
DATE : April 10, 2001

DEVICE TYPE	TV INTERFACE DEVICE - UNINTENTIONAL RADIATOR
E.U.T. DESCRIPTION	Digital Satellite Receiver
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	MP-3, ANSI C63.4/1992
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 §15.101
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 METER OPEN AREA TEST SITE

The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The AMT CO., LTD., Model DSR-101PA (referred to as the EUT in this report) is a Digital Satellite Receiver. Product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Metal
LIST OF EACH OSC. OR CRY. FREQ.(FREQ.>=1MHz)	Main Board: 13.5MHz, Front Board: 4MHz, Tuner Board: 60MHz and 4MHz RF Modulator Board: 70MHz
POWER REQUIREMENT	AC110V, 60Hz, 125W
NUMBER OF LAYERS	Front, Tuner and SMPS Board: 2Layers, Main Board: 4Layers RF Modulator Board: 1Layer
TUNER Type NO. / MFR	115-T-7121TP / HYUNDAI
RF MODULATOR Type NO. / MFR	TAMC-H001F / LG
RF INPUT FREQUENCY	950 ~ 2150 MHz
EXTERNAL TERMINALS	LNB-Input/Output, RS232C, RCA Jack(Audio input L/R, Video output and Decoder), RF Input/Output and S-Video

Model Differences:

-. The difference(s) compared to the EUT is as follows: none

2.2 Related Submittal(s) / Grant(s)

Original submittal only

2.3 Test System Details

The model numbers for all the equipments which were used in the tested system is:

Model	Manufacturer	FCC ID	Description	Connected to
DSR-101PA	AMT CO. LTD	PKJDSR-101PA	Digital Satellite Receiver (EUT)	-
CTV-1010XK	Korea Electronics	N/A	TELEVISION	EUT
GHV-S9990	LG Electronics	DoC	VCR	EUT
N/A	-	-	Antenna for TV	EUT

2.4 Test Methodology

The measurement for Radiated Emission, Line Conducted Emission, Output signal levels and Output Terminal Conducted Spurious Emission were performed in accordance with the procedures described in MP-3 and ANSI C63.4/1992. Radiated testing was performed at a distance of 3 meters from EUT to the antenna.

2.5 Test Facility

The open area test site and conducted measurement facilities are located on at 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-080 Korea. Description details of test facilities were submitted to the Commission on January 12, 1999. (Registration Number: 92819)

3. SYSTEM TEST CONFIGURATION

3.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	Q&TECH	N/A	N/A
Front Board	Dong Myoung Circuit	N/A	N/A
Tuner Board	HYUNDAI	N/A	N/A
RF Modulator Board	LG	N/A	N/A
Power Board	Sungwoo Circuit	N/A	N/A

3.2 EUT exercise Software

According to the requirements in Subpart B of Part 15, the measurement is made at each function of the EUT being connected with appropriate cables and peripherals.

This model DSR-101PA has video/audio output terminals in RCA-type plugs, RS232C port for software upgrading, S-Video port, LNB antenna input, RF in/out terminal. Therefore, every measurement was investigated in the operation modes. The LNB input of the EUT was connected to a signal generator directly.

3.3 Cable Description

	Power Cord Shielded (Y/N)	I/O cable Shielded (Y/N)	Length (M)
Digital Satellite Receiver (EUT)	N	-	1.5(P)
TELEVISION	N	N	1.5(P), 1.2(D)
VCR	N	Y	1.5(P), 1.2(D)
Antenna for TV	N/A	N	0.8(D)

* The marked “(D)” means the Data Cable and “(P)” means the Power Cable.

3.4 Noise Suppression Parts on Cable

	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
Digital Satellite Receiver (EUT)	N	N/A	Y	BOTH END
TELEVISION	N	N/A	Y	BOTH END
VCR	N	N/A	Y	BOTH END
Antenna for TV	N	N/A	Y	EUT END

3.5 Equipment Modifications

To achieve compliance to FCC part 15 rules, the following change(s) was made by ONETECH Corp. during compliance testing:

“There was no Modified items during EMI test”

3.6 Configuration of Test System

3.6.1 Line Conducted Test

EUT was connected to LISN, all supporting equipment were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.4/1992 7.2.3 to determine the worse operating conditions.

3.6.2 Radiated Emission Test

Preliminary radiated emission test were conducted using the procedure in ANSI C63.4/1992 8.3.1.1 to determine the worse operating conditions. Final radiated emission test were conducted at 3meter open area test site.

3.6.3 Output Signal Level Test

The output voltage of video carrier frequency at the RF-output terminal of the EUT was measured at 3 and 4 channel connecting directly to a spectrum analyzer with 50ohm input impedance via 75-to-50ohm matching pad. Indicated voltage on screen of measuring instrument was converted to the voltage of 75ohm system.

Data conversion method is as follows.

$$V_{75}[uV] = 10^{(V_r + CF)/20}[uV]$$

here, V_{75} : Voltage at the RF-out terminal of 75ohm in uV,

V_r : Voltage read at analyzer with 50ohm input-impedance in dBuV,

CF : Conversion Factor of the matching pad in dB.

3.6.4 Output Terminal Conducted Spurious Emission test

Any other spectrum at RF-output terminal appearing on frequencies removed by more than 4.6 MHz below or 7.4 MHz above the video carrier frequency of EUT was searched at 3 and 4 channel.

Data conversion method is as follows.

$$V_{75}[uV] = 10^{(V_r + CF)/20}[uV]$$

here, V_{75} : Voltage at the RF-out terminal of 75ohm in uV,

V_r : Voltage read at analyzer with 50ohm input-impedance in dBuV,

CF : Conversion Factor of the matching pad in dB,

3.6.5 Transfer Switch Isolation Test

As a transfer switch was equipped with EUT as an antenna-in, measurement of isolation were made at RF-input terminal with rated input impedance.

The maximum voltage of video carrier frequency of the EUT at the antenna input (RF-in) terminal of the switch was measured for both channels.

Data conversion method is as follows.

$$V_{75}[uV] = 10^{(V_r + CF - PG + AT)/20} [uV]$$

here, V_{75} : Voltage at the RF-out terminal of 75ohm in uV,
 V_r : Voltage read at analyzer with 50ohm input-impedance in dBuV,
 CF : Conversion Factor of the matching pad in dB,
 PG : Gain of pre-amplifier in dB,
 AT: Attenuation of attenuator in dB.

4. PRELIMINARY TEST

4.1 AC Power line Conducted Emission Test

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
CH. 3	X
CH. 4	

4.2 Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated.

Operation Mode	The Worse operating condition (Please check one only)
CH. 3	X
CH. 4	



5. FINAL RESULT OF MEASUREMENT

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level.

5.1 Conducted Emission Test

Humidity Level : 42% Temperature : 22
 Limits apply to : FCC CFR 47, PART 15, SUBPART B
 Type of Test : TV INTERFACE DEVICE
 Result : PASSED BY -4.43 dB at 17.48 MHz.

EUT : Digital Satellite Receiver Date: February 07, 2001
 Operating Condition : CH. 3
 Detector : CISPR QuasiPeak (6 dB Bandwidth: 9 kHz)

Power Line Conducted Emission			FCC CLASS B	
Frequency (MHz)	Amplitude (dBuV)	conductor	Limit (dBuV)	Margin (dB)
0.46	30.60	NEUTRAL	48.00	-17.40
1.12	30.82	NEUTRAL	48.00	-17.18
3.48	39.16	HOT	48.00	-8.84
9.22	42.66	NEUTRAL	48.00	-5.34
17.48	43.57	HOT	48.00	-4.43
29.12	28.49	HOT	48.00	-19.51

Line Conducted Emission Tabulated Data

Measuring by: Young Min, Choi / Project Engineer


This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
 (TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)



This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)



5.2 Radiated Emission Test

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

Humidity Level : 38% Temperature : 18
Limits apply to : FCC CFR 47, PART 15, SUBPART B
Type of Test : TV INTERFACE DEVICE
Result : PASSED BY -2.53 dB at 145.20 MHz

EUT : Digital Satellite Receiver Date: January 16, 2001
Operating Condition : CH. 3
Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)
Distance : 3 Meter

Radiated Emission		Ant Pol.	Correction Factors		Total Amp. (dBuV/m)	FCC CLASS B	
Freq. (MHz)	Amp. (dBuV)		Ant. (dBuV/m)	Cable (dB)		Limit (dBuV/m)	Margin (dB)
124.72	22.10	V	13.18	1.25	36.53	43.50	-6.97
131.56	18.50	V	12.95	1.27	32.72	43.50	-10.78
138.56	23.20	H	12.71	1.30	37.21	43.50	-6.29
145.20	26.60	V	13.04	1.33	40.97	43.50	-2.53
151.96	25.00	V	13.55	1.36	39.91	43.50	-3.59
286.80	12.80	H	14.64	1.94	29.38	46.00	-16.62
293.60	13.00	H	14.94	1.97	29.91	46.00	-16.09
300.00	13.90	H	15.22	2.00	31.12	46.00	-14.88
311.80	16.00	H	15.22	2.07	33.29	46.00	-12.71
378.40	17.90	H	15.55	2.40	35.85	46.00	-10.15
404.60	20.20	H	15.92	2.44	38.56	46.00	-7.44
431.80	23.20	H	16.53	2.50	42.23	46.00	-3.77
486.00	22.60	H	17.91	2.64	43.15	46.00	-2.85

Radiated Emission Tabulated Data

This is the additional radiated emission test due to the local oscillator of the satellite receiver part in the EUT.

The fundamental and 2nd harmonic frequencies of the local oscillator of the satellite receiver part was tested on a near top, middle and bottom tuning frequencies of the EUT according to section 15.31(m) and 15.33(b)(3).

The IF Frequency is 479.5 MHz.

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Freq. to which tuned(MHz)	OSC. Freq (MHz)	Ampl. (dBuV)	Pol.	Ant. (dBuV)	Cable (dB)	Ampl (dBuV/m)	Limit (dBuV/m)	Margin (dB)
950	1429.5	-	H	-	-	-	54.00	-
955	1434.5	-	H	-	-	-	54.00	-
960	1439.4	-	H	-	-	-	54.00	-

*Harmonics RF Radiation

Radiated Emissions				Ant	Correction Factors		Total	FCC Limit	
Freq. to which tuned(MHz)	Ham.	Freq. (MHz)	Ampl. (dBuV)	Pol.	Ant. (dBuV)	Cable (dB)	Ampl (dBuV/m)	Limit (dBuV/m)	Margin (dB)
950	2	2859.0	-	H	-	-	-	54.00	-
955	2	2869.0	-	H	-	-	-	54.00	-
960	2	2878.8	-	H	-	-	-	54.00	-

Remark: There was no found any emission during the above test.



Measuring by: Young Min, Choi / Project Engineer

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)



ONETECH

Testing & Evaluation Lab.

Page 14 of 19

FCC ID. : PKJDSR-101PA

File No. : E014R-009

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)

5.3. Antenna Power conduction Data

This test is the power conduction test at the antenna terminal due to the local oscillator of the satellite receiver part in the EUT.

The fundamental and 2nd harmonic frequencies of the local oscillator were tested on a near top, middle and bottom tuned frequencies of the EUT according to section 15.111(a), 15.31(m) and 15.33(b)(3).

The EUT antenna terminal connected to a resistive termination equal to the impedance specified or employed for the antenna, the power at the antenna terminal at any frequency within the range of measurements specified in section 15.33 shall not exceed 2.0 nanowatts. (2.0 nW = 50.1dBuV)

Operating Condition : Tuning the selected frequency

Detector : Span : 10 MHz SWP : 2 sec
RBW : 100 kHz VBW : 300 kHz

Freq. to which tuned (MHz)	OSC. Freq (MHz)	Measured Value (dBuV)	Imp. Mat. +Ca. Loss (dB)	Total (dBuV)	Limit (dBuV)	Margin (dBuV)
950	1429.5	-	6.0	-	50.10	-
955	1434.5	-	6.0	-	50.10	-
960	1439.4	-	6.0	-	50.10	-

*Harmonics RF Radiation

Freq. to which tuned (MHz)	Har.	OSC. Freq (MHz)	Measured Value (dBuV)	Imp. Mat. +Ca. Loss (dB)	Total (dBuV)	Limit (dBuV)	Margin (dBuV)
950	2	2859.0	-	6.0	-	50.10	-
955	2	2869.0	-	6.0	-	50.10	-
960	2	2878.8	-	6.0	-	50.10	-

Remark: There was no found any emission during the above test.

IF = 479.5MHz.



Measuring by: Young Min, Choi / Project Engineer

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)

5.4 Output Terminal Signal Level Test

The following table shows that the all modes of operation and worst-case emissions were investigated

Humidity Level : 40 %

Temperature : 20

Limits apply to : FCC CFR 47, PART 15, SUBPART B (Section 15.115)

EUT : DIGITAL SATELLITE RECEIVER

Date: January 18, 2001

Detector : SPAN : 10MHz

SWP : 2 sec

RBW : 100kHz

VBW : 300kHz

Output Impedance of RF-Output Terminal: 75ohm


CH	Freq.(MHz)	Reading(dBuV)	M/P Loss(dB)	Signal Level(uV)	Limit(uV)	Margin(dB)
3 (Visual)	61.22	59.8	6.0	1949.80	3000	-3.74
3 (Aural)	65.91	43.0	6.0	281.84	671	-7.53
4 (Visual)	67.21	58.6	6.0	1698.24	3000	-3.94
4 (Aural)	71.69	42.8	6.0	275.4	671	-7.73

MP = Impedance Matching Pad

*Sample Calculation at 61.22MHz = $10^{[(59.8+6.0)/20]} = 1949.8\mu V$

*Margin [dB] = $20 \log (R/L)$ where, R : Signal Level, [uV] or [uV/m],

L : Corresponding Limit, [uV] or [uV/m].



Measuring by: Young Min, Choi / Project Engineer

5.5 Output Terminal Conducted Spurious Emissions Test

The following table shows that frequency range of 30MHz to 1000MHz removed by more than 4.6 MHz below or 7.4 MHz above the video carrier frequency of EUT was investigated at each channel.

Humidity Level : 40 %

Temperature : 20

Limits apply to : FCC CFR 47, PART 15, SUBPART B (Section 15.115)

EUT : DIGITAL SATELLITE RECEIVER

Date: January 18, 2001

Detector : SPAN : 10MHz

SWP : 2 sec

RBW : 100kHz

VBW : 300kHz

Output Impedance of RF-Output Terminal: 75ohm

CH.	Freq. (MHz)	Reading (dBuV)	M/P Loss (dB)	Output Level(uV)	Limit (uV)	Margin (dB)
3	37.35	16.0	6.0	12.59	95	-17.55
	52.50	15.7		12.16		-17.85
	60.05	29.8		61.66		-3.75
	67.65	19.6		19.05		-13.95
	71.00	17.8		15.49		-15.75
	864.40	18.4		16.59		-15.15
4	53.75	14.0	6.0	10.00	95	-19.55
	80.63	12.0		7.94		-21.55
	540.40	12.3		8.22		-21.25
	577.60	13.5		9.44		-20.05
	594.6	16.1		12.74		-17.45
	972.8	10.8		6.92		-22.75

* Sample Calculation at 60.05MHz = $10^{[(29.8 + 6.0)/20]} = 61.66\mu V$

*Margin [dB] = 20 log (R/L) where, R : Output Level, [uV] or [uV/m],

L : Corresponding Limit, [uV] or [uV/m].



Measuring by: Young Min, Choi / Project Engineer

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)

5.6 Transfer Switch Isolation Test

The following table shows that the maximum voltage of video carrier frequency of the EUT at the antenna input (RF-in) terminal of the switch was measured for both channels.

Humidity Level : 55 %

Temperature : 23

Limits apply to : FCC CFR 47, PART 15, SUBPART B (Section 15.115)

EUT : DIGITAL SATELLITE RECEIVER

Date: January 18, 2001

Detector : Span : 1 MHz

SWP : 30 msec

RBW : 10 kHz

VBW : 30 kHz

Output Impedance of RF-Output Terminal: 75ohm

CH.	Freq. (MHz)	Meter Reading (dBuV)	M/P Loss (dB)	Preamp Gain(dB)	Attn. (dB)	Signal Level (uV)	Limit (uV)	Margin (dB)
"It was not observed any emission during the above test"								

Note : To clarify the emissions emanated from RF output terminal the EUT, RF pre-amplifier was utilized.

The gain of pre-amplifier at each frequency measured from the EUT was obtained after sufficient warm-up for stabilization of gain.



Measuring by: Young Min, Choi / Project Engineer



6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

+ Meter reading (dBuV)

+ Cable Loss (dB)

+ Antenna Factor (Loss) (dB/meter)

= Corrected Reading (dBuV/meter)

- Specification Limit (dBuV/meter)

= dB Relative to Spec (+/- dB)

7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESVS 10	827864/005	SEP/00	12MONTH	■
2.	Test receiver	R/S	ESHS10	834467/007	APRIL/00	12MONTH	■
3.	Spectrum analyzer	HP	8568B	3026A0226	SEP/00	12MONTH	■
4.	RF preselector	HP	85685A	3107A01264	SEP/00	12MONTH	■
5.	Quasi-Peak Adapter	HP	85650A	3107A01542	SEP/00	12MONTH	■
6.	Dipole Antenna	EMCO	3121C	9107-745	JUN/00	12MONTH	
7.	Biconical antenna	EMCO	3104C	9109-4441 9109-4443 9109-4444	MAR/01	12MONTH	■
8.	Log Periodic antenna	EMCO	3146	9109-3213 9109-3214 9109-3217	MAR/01	12MONTH	■
9.	LISN	EMCO	3825/2	9109-1867 9109-1869	JUN/00	12MONTH	■
10.	RF Amplifier	HP	8447F	3113A04554	JUN/00	N/A	
11.	Spectrum Analyzer	HP	8591A	3131A02312	APRIL/00	12MONTH	
12.	Computer System	HP	98581C	98543A	N/A	N/A	■
	Hard disk drive		9153C	CMC762Z9153	N/A	N/A	■
13.	Plotter	HP	7475A	30052 22986	N/A	N/A	■
14.	Position Controller	EMCO	1090	9107-1038	N/A	N/A	■
15.	Turn Table	EMCO	1080-1.21	9109-1576	N/A	N/A	■
16.	Antenna Master	EMCO	1070-1	9109-1624	N/A	N/A	■

This report shall not be reproduced except in full without our written approval.

EMC-004 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-

3 1 - 7 6 6 - 2 9 0 4)