



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 22 & 24 Class II Permissive Change

Applicant Name:

Novatel Wireless Inc.
9645 Scranton Road, Suite 205
San Diego, CA 92121-3030
United States

Date of Testing:

September 20 - 21, 2006

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0609140804

FCC ID: PKRNVWES720

APPLICANT: NOVATEL WIRELESS INC.

Application Type: Class II Permissive Change

FCC Classification: PCS Licensed Transmitter (PCB)

FCC Rule Part(s): §2; §22(H), §24(E)

EUT Type: Dual-Band CDMA/EvDO Module

Model(s): ES720

Tx Frequency Range: 824.70 - 848.31MHz (Cell. CDMA) / 1851.25 - 1908.75MHz (PCS CDMA)

Rx Frequency Range: 869.70 - 893.31MHz (Cell. CDMA) / 1931.25 - 1988.75MHz (PCS CDMA)

Max. RF Output Power: 0.275W Conducted (24.40dBm) Cell. CDMA /
0.263W Conducted (24.20dBm) PCS CDMA

Emission Designator(s): 1M28F9W (CDMA/EvDO)

Test Device Serial No.: identical prototype [S/N: N/A]

Class II Permissive Change: Please See Attached Documents

Original Grant Date: 08/07/2006

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is conducted for Part 22 and Part 24.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 1 of 21

TABLE OF CONTENTS

FCC PART 22 & 24 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 MEASUREMENT PROCEDURE	4
1.2 SCOPE	4
1.3 TESTING FACILITY	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
3.0 DESCRIPTION OF TESTS	6
3.1 OCCUPIED BANDWIDTH EMISSION LIMITS	6
3.2 CELLULAR - BASE FREQUENCY BLOCKS	6
3.3 CELLULAR - MOBILE FREQUENCY BLOCKS.....	6
3.4 PCS - BASE FREQUENCY BLOCKS	7
3.5 PCS - MOBILE FREQUENCY BLOCKS	7
3.6 FREQUENCIES	7
3.7 RADIATED SPURIOUS AND HARMONIC EMISSIONS	7
4.0 TEST EQUIPMENT CALIBRATION DATA	8
5.0 SAMPLE CALCULATIONS	9
6.0 TEST RESULTS.....	10
6.1 CONDUCTED OUTPUT POWER	11
6.2 CELLULAR CDMA RADIATED MEASUREMENTS.....	12
6.3 PCS CDMA RADIATED MEASUREMENTS.....	15
7.0 CONCLUSION.....	18
EXHIBIT A - PLOT(S) OF EMISSIONS.....	19
EXHIBIT B – TEST SETUP PHOTOGRAPHS.....	20
EXHIBIT C – INTERNAL/EXTERNAL PHOTOGRAPHS	21

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 2 of 21	



MEASUREMENT REPORT



FCC Part 22 & 24

A. §2.1033 General Information

APPLICANT: Novatel Wireless Inc.
APPLICANT ADDRESS: 9645 Scranton Road, Suite 205
 San Diego, CA 92121-3030
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §22(H), §24(E)
MODEL NAME: ES720
FCC ID: PKRNVWES720
FCC CLASSIFICATION: PCS Licensed Transmitter (PCB)
EMISSION DESIGNATOR(S): 1M28F9W (CDMA/EvDO)
MODE: CDMA / EvDO
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: N/A ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: September 20 - 21, 2006
TEST REPORT S/N: 0609140804

A.1 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 3 of 21

1.0 INTRODUCTION

1.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 1-1). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.





Figure 1-1. Diagram of 3-meter outdoor test range

Deviation from Measurement Procedure.....None

1.2 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.3 Testing Facility



These measurement tests were conducted at PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.

Figure 1-3. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 4 of 21

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Novatel Dual-Band CDMA/EvDO Module** **FCC ID: PKRNVWES720**. The EUT consisted of the following components(s):

Manufacturer / Description	FCC ID	Serial Number
Novatel Dual-Band CDMA/EvDO Module	PKRNVWES720	N/A

Table 2.1. EUT Equipment Description

2.2 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing.

- None


3.0 DESCRIPTION OF TESTS

3.1 Occupied Bandwidth Emission Limits


§2.1049, 22.917(a), 24.238(a)

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

3.2 Cellular - Base Frequency Blocks




3.3 Cellular - Mobile Frequency Blocks



FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 6 of 21

3.4 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

3.5 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

3.6 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

3.7 Radiated Spurious and Harmonic Emissions

§2.1051, 22.917(a), 24.238(a); RSS-129 (8.1.1), RSS-133 (6.5.1)

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 7 of 21	

4.0 TEST EQUIPMENT CALIBRATION DATA

All Test Equipment Calibrations are traceable to the National Institute of Standards and Technology (NIST).

TYPE	MODEL	CAL. DUE DATE	CAL. INTERVAL	SERIAL No.
Microwave Spectrum Analyzer	Agilent E4448A (3Hz-50GHz)	09/19/07	Annual	US42510244
Spectrum Analyzer	HP 8566B (100Hz-22GHz)	12/22/06	Annual	3638A08713
PSG Signal Generator	Agilent E8257D (250kHz-20GHz)	02/11/07	Annual	MY45470194
5 Watt Amplifier	5S1G4 (800MHz-4.2GHz)	N/A	N/A	22332
Wireless Communication Test Set	Agilent 8960 Series 10 E5515C	06/10/07	Annual	6B46110872
Universal Power Meter	Gigatronics 8651A (50MHz-18GHz)	07/28/07	Annual	1834052
Power Sensor	Gigatronics 80701A	04/11/07	Annual	1833460
Quasi-Peak Adapter	HP 85650A	12/22/06	Annual	2043A00301
Preamplifier	HP 8449B (1-26.5GHz)	12/22/06	Annual	3008A00985
Attenuation/Switch Driver	HP 11713A	12/22/06	Annual	N/A
Preselector	HP 85685A (20Hz-2GHz)	12/22/06	Annual	N/A
6dB Res BW Spec. Analyzer Display	OPT 462	12/22/06	Annual	3701A22204
Horn Antenna	EMCO Model 3115 (1-18GHz)	08/25/07	Annual	9704-5182
Horn Antenna	EMCO Model 3116 (18-40GHz)	08/25/07	Annual	9203-2178
EMCO Dipoles (2)	N/A	05/08/07	Annual	00023951
10dB Attenuator	HP 8493B	N/A	N/A	N/A
Bi-Directional Coax Coupler	PE2208-6	N/A	Annual	N/A
Microwave Cables	MicroCoax (1.0-26.5GHz)	02/26/07	Annual	N/A

Table 4.1. Test Equipment

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 8 of 21

5.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 9 of 21	

6.0 TEST RESULTS

Summary

The intentional radiator has been tested in a simulated typical installation to demonstrate compliance with the relevant FCC performance and procedural standards. The radio was transmitting at full power on the specified channels. The channels tested are high, middle and low of the allocated bands. Final system data was gathered in a mode that tended to maximize emissions by varying the orientation of the EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization. This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

Method/System: PCS Licensed Transmitter (PCB)

Mode(s): CDMA / EvDO

FCC Part Section(s)	RSS Section	Test Description	Test Limit	Test Condition	Test Result
TRANSMITTER MODE (TX)					
2.1049, 22.917(a), 24.238(a)	N/A	Occupied Bandwidth	N/A	CONDUCTED	PASS
22.917(a), 24.238(a)	RSS-129 (8.1.1) RSS-133 (6.5.1)	Band Edge / Conducted Spurious Emissions	$< 43 + \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS
2.1046	N/A	Transmitter Conducted Output Power	N/A		PASS
2.1051, 22.917(a), 24.238(a)	RSS-129 (8.1.1) RSS-133 (6.5.1)	Undesirable Emissions	$< 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions	RADIATED	PASS
RECEIVER MODE (RX)					
15.107	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	EN55022	Line Conducted	PASS
15.109	RSS-129 (10(a,d)), RSS-133 (6.7(a,b)), RSS-210 (7.3)	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	$< \text{FCC 15.209 limits or}$ $< \text{RSS-Gen limits [Section 6; Table1]}$	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS
RF EXPOSURE (SAR)					
2.1093	RSS-102	SAR Test or MPE	1.6 W/kg (SAR Limit) 1 mW/cm ² (MPE)	3 Channels	PASS

Table 6-1. Summary of Test Results

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 10 of 21	

6.1 Conducted Output Power

S2.1046

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits. The following procedures were followed according to FCC 3G Measurement Procedures, June 2006.

Output Power Verification

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 6-2 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 6-3 was applied.

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 6-2
Parameters for Max. Power for RC1

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 6-3
Parameters for Max. Power for RC3

Band	Channel	1x EvDO Rev. 0	1x EvDO Rev. 0
		[dBm] (FTAP)	[dBm] (RTAP)
Cellular	1013	24.20	24.40
	384	24.10	24.40
	777	24.20	24.30
PCS	25	24.00	24.10
	600	24.20	24.20
	1175	24.00	24.10

Table 6-4
Maximum Conducted Power Output Table for ES720

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 11 of 21

6.2 Cellular CDMA Radiated Measurements

§2.1051, 22.917(a): RSS-129 (8.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013 (Low)
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.58 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-49.68	6.10	-43.58	V	68.2
2474.10	-66.58	6.70	-59.88	V	84.5
3298.80	-74.48	6.80	-67.68	V	92.3
4123.50	-85.68	6.50	-79.18	V	103.8
4948.20	-84.38	7.00	-77.38	V	102.0

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 12 of 21

Cellular CDMA Radiated Measurements (Cont'd)

§2.1051, 22.917(a); RSS-129 (8.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 37.57 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-48.48	6.10	-42.38	V	67.0
2509.56	-67.08	6.70	-60.38	V	85.0
3346.08	-75.78	6.80	-68.98	V	93.6
4182.60	-85.78	6.50	-79.28	V	103.9
5019.12	-83.78	7.00	-76.78	V	101.4

Table 6-6. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 13 of 21



Cellular CDMA Radiated Measurements (Cont'd)

§2.1051, 22.917(a); RSS-129 (8.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
CHANNEL: 0777 (High)
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) =$ 37.57 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-50.58	6.10	-44.48	V	69.1
2544.93	-68.08	6.70	-61.38	V	86.0
3393.24	-73.08	6.80	-66.28	V	90.9
4241.55	-85.68	6.50	-79.18	V	103.8
5089.86	-83.98	7.00	-76.98	V	101.6

Table 6-7. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 14 of 21

6.3 PCS CDMA Radiated Measurements

§2.1051, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 0025 (Low)
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.13 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-50.83	8.70	-42.13	V	66.3
5553.75	-75.93	9.70	-66.23	V	90.4
7405.00	-66.43	9.90	-56.53	V	80.7
9256.25	-77.43	11.40	-66.03	V	90.2
11107.50	-77.33	12.10	-65.23	V	89.4

Table 6-8. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 15 of 21

PCS CDMA Radiated Measurements (Cont'd)

§2.1051, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 0600 (Mid)
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.13 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-50.33	8.70	-41.63	V	65.8
5640.00	-83.03	9.70	-73.33	V	97.5
7520.00	-67.03	9.90	-57.13	V	81.3
9400.00	-77.23	11.40	-65.83	V	90.0
11280.00	-77.13	12.10	-65.03	V	89.2

Table 6-9. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 16 of 21



PCS CDMA Radiated Measurements (Cont'd)

§2.1051, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz
CHANNEL: 1175 (High)
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) =$ 37.13 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-50.13	8.70	-41.43	V	65.6
5726.25	-82.83	9.70	-73.13	V	97.3
7635.00	-66.73	9.90	-56.83	V	81.0
9543.75	-76.93	11.40	-65.53	V	89.7
11452.50	-76.93	12.10	-64.83	V	89.0

Table 6-10. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO RTAP with "All Up" power control bits.

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 17 of 21



7.0 CONCLUSION

The data collected shows that the **Novatel Dual-Band CDMA/EvDO Module FCC ID: PKRNVWES720** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.


FCC ID: PKRNVWES720	 PCTEST w i r e l e s s	FCC Pt. 22/24 CDMA MEASUREMENT REPORT	 NOVATEL WIRELESS	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 18 of 21	

EXHIBIT A - PLOT(S) OF EMISSIONS



FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 19 of 21	





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 1 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 2 of 12




FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 3 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module		Page 4 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 5 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 6 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 7 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 8 of 12





FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 9 of 12



FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 10 of 12



FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 11 of 12



FCC ID: PKRNVWES720	 PCTEST	FCC Pt. 22/24 CDMA MODE CONDUCTED PLOTS	 NOVATEL WIRELESS.	Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EVDO Module		Page 12 of 12

EXHIBIT B – TEST SETUP PHOTOGRAPHS

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 20 of 21	

EXHIBIT C – INTERNAL/EXTERNAL PHOTOGRAPHS

FCC ID: PKRNVWES720		FCC Pt. 22/24 CDMA MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0609140804	Test Dates: September 20 - 21, 2006	EUT Type: Dual-Band CDMA/EvDO Module	Page 21 of 21	