

18th June 2015

Telecommunication Certification Body
UL Verification Services Ltd
Offices 18-26 Grove House
Lutyens Close
Chineham Court,
Basingstoke
Hampshire
RG24 8AG

RE: Band 14 RN2480 eNode B FCC ID: PKTNODEBBAA MPE Calculation.

To Whom It May Concern,

The General Dynamics Broadband Band 14 RN2480 eNode B is considered to be fixed equipment and intended for operation with separation distances greater than 20cm between the user and the equipment. Therefore the RF Exposure performance can be assessed by a Maximum Permissible Exposure (MPE) calculation using the limits defined in Part 1.1310 Table 1B for the General Population/Uncontrolled Exposure category.

The General Dynamics Broadband Band 14 RN2480 eNode B uses frequency division duplex (FDD) technology in normal operation with a duty cycle of 100%, therefore source based averaging is not applied in the MPE calculation.

MPE Distance Calculation	Channel Size		Units
	5	10	MHz
Antenna Gain	18	18	dBi
Line Loss	0	0	dB
Antenna Gain Ratio	63.09573445	63.0957344	
eNode B Tx Output Power (per branch)	46	46	dBm
Upper Power Tolerance (per branch)	2	2	
Number of Transmitter Branches	2	2	
Total Output Power - all branches	126191.47	126191.47	mW
Maximum EIRP - all branches	7962143.41	7962143.41	mW
Frequency	758	758	MHz
MPE Limit from 1.1310	0.505	0.505	mw/cm ²
Un-controlled/General Public Limit			
Minimum Distance to meet MPE Limit	1119.75	1119.75	cm
(100% Duty Cycle)	440.50	440.50	inches

Table 1: 100% Duty Cycle Calculation

The calculations above show the General Dynamics Broadband Band 14 RN2480 eNode B complies with the un-controlled /General Public limit of $0.505\text{mW}/\text{cm}^2$ at a minimum distance of 11.2m for operation using either 5MHz or 10MHz channel sizes.

Yours Faithfully

A handwritten signature in dark ink, appearing to be 'P Warburg', with a stylized, flowing script.

P Warburg
Principal Engineer
General Dynamics Broadband.