

Marstech Limited

11 Kelfield Street, Etobicoke, Ontario, Canada, M9W 5A1
Telephone (416) 246-1116, Fax (416) 246-1020

Authorized by:
Professional Engineers
Ontario






Engineering &
Administrative



Testing For FCC
Submissions/Verifications

Approved Test Facility



TEST REPORT			
REPORT DATE:	20 November 2001		REPORT NO: 21416D
CONTENTS:	See Table of Contents		
SUBMITTOR:	Mandolyn Electronic Technology Inc. 250 Shields Court, Unit 10B Markham, Ontario L3R 9W7		
SUBJECT:	Model No:	WS10	
	FCC ID:	PLJWS10	
TEST SPECIFICATION:	47 CFR Part 15 Subpart "C" Unintentional Radiators Sections: 15.205, 15.231(b) & (c) NOTE: Tests Conducted Are "Type" Tests.		
DATE SAMPLE RECEIVED:	19 October 2001	DATE TESTED:	06, 16 November 2001
RESULTS:	Equipment tested complies with referenced specification.		
ALTERATIONS:	Alterations required in compliance with referenced specification: <u>433MHz Receiver Module:</u> <u>C3, 2.7pF capacitor was changed to 3.9pF.</u>		
Tested by:			
	Edward Chang	Approved by: CHALL	Robert G. Marshall, P. Eng.
		Date:	Nov 21/01
THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF MARSTECH LIMITED. This report was prepared by Marstech Limited for the account of the "Submitter". The material in it reflects Marstech's judgement in light of the information available to it at the time of preparation. Any use which a Third Party makes of this report, or any reliance on decisions to be made based on it, are the responsibility of such Third Parties. Marstech accepts no responsibility for damages, if any, suffered by any Third Party as a result of decisions made or actions based on this report.			

TECHNICAL REPORT - FCC 2.1033(b)

Applicant

Mandolyn Electronic Technology Inc.
250 Shields Court, Unit 10B
Markham, Ontario
L3R 9W7

FCC Identifier

PLJWS10

Manufacturer

W. H. Mandolyn International Ltd.
Yen Yang Industrial City
Zhang Mu Tou Zhen
Dongguan, China

TABLE OF CONTENTS

<u>Exhibit</u>	<u>Description</u>	<u>FCC Ref.</u>	<u>Page</u>
A	Installation and Operating Instructions Furnished to the User	2.1033(b)(3)	Exhibit A-1
B	Description of Circuit Functions	2.1033(b)(4)	Exhibit B-1
C	Block Diagram Schematic Diagram	2.1033(b)(5)	Exhibit C Exhibit C(1) Exhibit C(2)-1 to -2
D	Report of Measurements Device Measured Test Facility and Equipment Test Results and Methods Test Set-up Photos	2.1033(b)(6)	Exhibit D Exhibit D(1) Exhibit D(2)-1 to -2 Exhibit D(3)-1 to -4 Exhibit D(3)-5
E	Photographs Label Equipment	2.1033(b)(7)	Exhibit E Exhibit E(1) Exhibit E(2)-1 to -3

EXHIBIT D

[FCC Ref. 2.1033(b)(6)]

"Report of Measurements"

EXHIBIT D(1)

DEVICE MEASURED

[FCC Ref. 2.1033(b)(6)]

APPLICANT: Mandolyn Electronic Technology Inc.
250 Shields Court, Unit 10B
Markham, Ontario
L3R 9W7

MANUFACTURER: W. H. Mandolyn International Ltd.
Yen Yang Industrial City
Zhang Mu Tou Zhen
Dongguan, China


FCC IDENTIFIER: PLJWS10

MODEL NUMBERS: WS10

SERIAL NO.: Not Marked

Marstech Limited
11 Kelfield Street
Etobicoke, Ontario
M9W 5A1 CANADA

TECHNICIAN:
Ed Chang


Robert G. Marshall, P. Eng.

Date: Nov 21/01

EXHIBIT D(2)

TEST FACILITY AND EQUIPMENT LIST

FACILITIES

Radiated †@050XANSI C63.4 (FCC OET/55) open field 3 metre test range. This test range is protected from the cold and moisture by a non-conductive enclosure.

EQUIPMENT

Anritsu 2601A Spectrum Analyzer
Advantest R3261A Spectrum Analyzer
Hewlett-Packard RF generator # 8640 B with an 002 doubler
A.H. Systems biconical antenna; 20 MHz to 330 MHz
A.H. Systems log periodic antenna; 300 MHz to 1.8 GHz
Eaton dipole antennas; T1, T2, T3 25 MHz to 1.0 GHz
Roberts dipole antennas; T1, T2, T3 & T4 25 MHz to 1.0 GHz
Compliance Design P950 Preamp (16 dB) ... 25 MHz to 1.0 GHz

NOTE:

The Anritsu 2601A Spectrum Analyzer and the Advantest R3261A Spectrum Analyzer are calibrated annually, and that calibration is directly traceable to the National Research Council of Canada. (NRC)
This equipment is only used by qualified technicians and only for the purpose of EMI measurements.
The three metre test range has been carefully evaluated to the ANSI document C63.4 and will be remeasured for reflections and losses every three years.

SUMMARY OF RESULTS

COMPLIANCE

(yes) (no)

FIELD STRENGTH OF THE CARRIER FREQUENCY

Receiver: 15.231(b) @ 3 Meters
Transmitter

N/A

N/A

BANDWIDTH

Receiver: 15.231(c)
Transmitter

N/A

N/A

TRANSMITTER BAND RESTRICTIONS

Receiver: 15.205(a)
Transmitter

N/A

N/A

SPURIOUS RADIATION LEVELS [EXHIBIT D(3)-4]

Receiver: 15.231(b) 41.37 dB μ V/M @ 3 Meters 421.4 MHz
Transmitter:

(x) ()

N/A

LINE CONDUCTED RADIATION

Receiver:
Transmitter:

N/A

N/A

SPURIOUS RADIATED EMISSIONS

Page 1 of 2

RESULTS

The maximum field strength of any spurious emission or harmonic while receiving was:

Model WS10:

Receiver: **Maximum field strength of 41.37 dB μ V/M at 421.4 MHz.**

TEST CONDITIONS

Equipment Positioning:

Receiver: Laying on its back
Transmitter: N/A

Antenna Polarization: Horizontal

Measurement Bandwidth: 120KHz

Supply Voltage:

Transmitter: N/A
Receiver: Two "AA" batteries

METHODS OF MEASUREMENT

Receiver:

The EUT was placed on a one meter high non-metallic turntable. The EUT was unmodified sample, as supplied by the manufacturer. Power was supplied via a 120 VAC cable fed upward through the centre of a turntable. The EUT was set in the receive mode, and the entire spectrum up to 2,000vMHz was searched for spurious emissions. All emissions were measured and recorded.

The receive frequency was measured using an external unmodulated ambient RF carrier signal, tuned across the wideband of the receiver noise. The unmodulated carrier was emanating from an antenna in the proximity of the receiver. Care was taken so as not to overload the receiver, however the carrier level was varied in amplitude and frequency to obtain the highest level of spurious emissions from the receiver. This external signal was set to cause receiver "quieting" or to cohere the superregenerative receiver and cause single discrete noise components to appear. At this point, the largest emission or single frequency component within this band was measured and recorded.

For each of the above conditions, the turntable was rotated through 360 degrees, while the receiving antenna, at three (3) meters from the EUT, was varied in height from 1 to 4 meters, to find the maximum signal strength. The measured level was converted to a field strength using the antenna correction factors and cable losses.

FIELD STRENGTH OF EMISSIONS

Page 2 of 2

Test Data:Model WS10

Emission Frequency MHz	Meter Reading @3m dB μ V/M	Antenna	Cable and ACF dB	Field Strength dB μ V/M	FCC Limit dB μ V/M	Margin dB	Detector & BW KHz
410.40	22.37	LP H	19.00	41.37	46	-4.63	QP 120
446.00	19.00	LP H	19.00	38.00	46	-8.00	QP 120
800.70	10.00	LP H	28.70	38.70	46	-7.30	QP 120
811.10	10.30	LP H	28.60	38.90	46	-7.10	QP 120
1292.10	9.00	LP V	36.00	45.00	54	-9.10	PK 1000

