


EUT labeling

FCC ID: PM7-IRL2001

The following the labels are for the WPR and the WISI configurations. The Dimensions are in inches.



Dimensions in inches

Description of Label: (This applies to all labels)

1. Minimum Letter Height .047 Inch
2. Facestock: FASSON.U.L. Gloss is a destructible cast-coated high gloss stock.
Basis Weight: 60# per ream +/-10%; (500 sheets 25" X 38")
Caliper: 0.00340 inches +/- 10%
Tensile: MD 26# per inch width; CD 16# per inch width
Tear: MD 55 grams per sheet CD 60 grams per sheet
Stiffness: MD 125 mg CD 65 mg
3. Adhesive: FASSON A351 adhesive is a clear adhesive featuring good initial tack, high shear and minimum cold flow. Suitable for use on a wide variety of substrates,
Type: Solvent Acrylic
Minimum Application Temperature: +45°F
Service Temperature Range: -65°F to +200°F
4. Liner: 40# SCK is a bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance. Used primarily for roll-to-roll label applications
Basis Weight: 41# per ream +/-10% (500 sheets 25" x 36")
Caliper: 0.0025 inches +/-10%
Tensile: MD 35# per inch width
CD 16# per inch width
Tear: MD 35 grams; CD 45 grams
5. Total Construction Caliper: 0.0071 inches +/- 10%
6. Shelf Life: One year when stored at 72°F at 50% RH

WISI Label location



WPR label location

