



AXIS D2122-VE Radar

Label Location and Label drawing



Figure 1: Label Location

AXIS D2122-VE Radar Black

Power in: Power class 8 (IEEE 802.3bt Type 4) PoE: 50-57 VDC / 0.31-0.27 A, max 15.07 W Power out: Power class 6 (IEEE 802.3bt Type 3) PoE: 50-57 VDC / 1.20-1.05A, max 60W CAN ICES (B) / NMB (B) IC: 3919A-D2122VE HVIN: D2122-VE FCC, see manual FCC ID: PNB-AXISD2122-VE IFT: AXAXAX23-44842 U/A: 3050837 ID: AJ	AXIS D2122-VE Radar Black P/N: 03123-001-01 S/N: E82725000000  Axis Communications AB Gränden 1 SE-22369 Lund SWEDEN  R-R-PNB-AXISD2122-VE  IP67 Type 4X Engineered in Sweden    324500612 Country of Origin: POLAND
---	---

P/N: 03123-001-01 S/N: E82725000001  TA-2024/0846 APPROVED UAE -TRA ER32409/24 DA74725/18	 R 005-XXXXXX  CCAB21LPXXXXXXX  ANATEL 10434-23-05509 IFT: AXAXAX23-07984 324500711
--	--

The label size is 40*30.

The diameter of the GITEKI mark is 4 mm.

AXIS D2122-VE Radar White

Power in: Power class 8 (IEEE 802.3bt Type 4) PoE: 50-57 VDC / 0.31-0.27 A, max 15.07 W Power out: Power class 6 (IEEE 802.3bt Type 3) PoE: 50-57 VDC / 1.20-1.05A, max 60W CAN ICES (B) / NMB (B) IC: 3919A-D2122VE HVIN: D2122-VE FCC, see manual FCC ID: PNB-AXISD2122-VE IFT: AXAXAX23-44842 U/A: 3182538 ID: AJ	AXIS D2122-VE Radar White P/N: 03124-001-01 S/N: E82725000001  Axis Communications AB Gränden 1 SE-22369 Lund SWEDEN  R-R-PNB-AXISD2122-VE  IP67 Type 4X Engineered in Sweden    Country of Origin: POLAND 324500612
---	---

P/N: 03124-001-01 S/N: E82725000001  TA-2024/0846 APPROVED UAE -TRA ER32409/24 DA74725/18	 R 005-XXXXXX  CCAB21LPXXXXXXX  ANATEL 10434-23-05509 IFT: AXAXAX23-07984 324500711
--	--

The label size is 40*30.

The diameter of the GITEKI mark is 4 mm.