

FCC Part 90& Part 22 Rules Test Report

Report No.: AGC02931180506FE10

FCC ID : POD-MDUV390
PRODUCT DESIGNATION : DMR Digital Transceiver
BRAND NAME : TYT
MODEL NAME : MD-UV390
CLIENT : TYT ELECTRONICS CO., LTD
DATE OF ISSUE : Nov. 28, 2018
STANDARD(S) : FCC Part 90 Rules
: FCC Part 22 Rules
REPORT VERSION : V 1.2

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jul. 09, 2018	Invalid	Initial Release
V1.1	1 st	Oct. 25, 2018	Invalid	Update the comments.
V1.2	2 nd	Nov. 28, 2018	Valid	Update the comments.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

VERIFICATION OF COMPLIANCE

Applicant:	TYT ELECTRONICS CO., LTD
	Block 39-1, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian, China
Manufacturer:	TYT ELECTRONICS CO., LTD
	Block 39-1, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian, China
Product Designation:	DMR Digital Transceiver
Brand Name:	TYT
Test Model	MD-UV390
Date of Test:	Jun. 28, 2018 to Jul. 09, 2018

WE HEREBY CERTIFY THAT:

The above equipment was tested by Shenzhen Attestation of Global Compliance Science & Technology Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E (2016). The sample tested as described in this report is in compliance with the FCC Rules Part 90 and FCC Rules Part 22 requirements

The test results of this report relate only to the tested sample identified in this report.

Tested by

Steven Zhou

Steven Zhou(Zhou Pengyun) Jul. 09, 2018

Reviewed by

Bart Xie

Bart Xie(Xie Xiaobin) Nov. 28, 2018

Approved by

Forrest Lei

Forrest Lei(Lei Yonggang)
Authorized Officer Nov. 28, 2018

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
1.2 RELATED SUBMITTAL(S) / GRANT (S)	7
1.3 TEST METHODOLOGY	9
1.4 TEST FACILITY	9
1.5 SPECIAL ACCESSORIES	9
1.6 EQUIPMENT MODIFICATIONS	9
2. SYSTEM TEST CONFIGURATION	10
2.1 EUT CONFIGURATION	10
2.2 EUT EXERCISE	10
2.3 GENERAL TECHNICAL REQUIREMENTS	10
2.4 CONFIGURATION OF TESTED SYSTEM	11
3. SUMMARY OF TEST RESULTS	12
4. DESCRIPTION OF TEST MODES	14
5. FREQUENCY TOLERANCE	15
5.1 PROVISIONS APPLICABLE	15
5.2 MEASUREMENT PROCEDURE	15
5.3 TEST SETUP BLOCK DIAGRAM	16
5.4 TEST RESULT	17
6. EMISSION BANDWIDTH	23
6.1 PROVISIONS APPLICABLE	29
6.2 MEASUREMENT PROCEDURE	29
6.3 TEST SETUP BLOCK DIAGRAM	29
6.4 MEASUREMENT RESULT	30
7. UNWANTED RADIATION	54
7.1 PROVISIONS APPLICABLE	54
7.2 MEASUREMENT PROCEDURE	54
7.3 TEST SETUP BLOCK DIAGRAM	55
7.4 MEASUREMENT RESULTS:	56
7.5 EMISSION MASK PLOT	92
8. MODULATION CHARACTERISTICS	117
8.1 PROVISIONS APPLICABLE	117
8.2 MEASUREMENT METHOD	117
8.3 MEASUREMENT RESULT	118

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

9. MAXIMUM TRANSMITTER POWER (CONDUCTED OUTPUT POWER)	133
9.1 PROVISIONS APPLICABLE	136
9.2 TEST PROCEDURE	136
9.3 TEST CONFIGURATION	136
9.4 TEST RESULT	138
9.5 CONDUCT SPURIOUS PLOT	152
10. TRANSMITTER FREQUENCY BEHAVIOR	189
10.1 PROVISIONS APPLICABLE	189
10.2 TEST METHOD	189
10.3 DESCRIBE LIMIT LINE OF TRANSMITTER FREQUENCY BEHAVIOR	190
10.4 MEASURE RESULT	191
11. AUDIO LOW PASS FILTER RESPONSE	192
11.1 LIMITS	193
11.2. METHOD OF MEASUREMENTS	193
11.3 TEST DATA	194
APPENDIX I: PHOTOGRAPHS OF SETUP	196
APPENDIX II: EXTERNAL VIEW OF EUT	197

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **DMR Digital Transceiver** designed for voice/data communication. It is designed by way of utilizing the FM/4FSK modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Data
Hardware Version	UV-V2.1-171109
Software Version	V1.06
Modulation	FM/4FSK
Emission Type	11K0F3E, 7K60FXD, 7K60FXW
Emission Bandwidth	Analog:10.22KHz(5W-12.5 KHz),10.19KHz(1W-12.5 KHz) ---VHF Analog:15.25KHz(5W-25 KHz),15.41KHz(1W-25 KHz) ---VHF Digital: 8.992KHz(5W),9.028 KHz(1W) ---VHF Analog:10.31KHz(5W-12.5 KHz),10.29KHz(1W-12.5 KHz) ---UHF Analog:15.32KHz(5W-25 KHz),15.38KHz(1W-25 KHz) ---UHF Digital:9.001KHz(5W), 9.133KHz(1W) ---UHF
Peak Frequency Deviation	1.98KHz
Audio Frequency Response	11.41 dB
Maximum Transmitter Power	Analog:36.89 dBm(5W-12.5 KHz), 29.89dBm (1W-12.5 KHz) ---VHF Analog:36.89 dBm(5W-25 KHz), 29.89dBm (1W-25 KHz) ---VHF Digital: 36.88 dBm(5W), 29.88dBm (1W) ---VHF Analog:36.88 dBm(5W-12.5 KHz), 29.89dBm (1W-12.5 KHz) ---UHF Analog:36.87 dBm(5W-25 KHz), 29.89dBm (1W-25 KHz) ---UHF Digital: 36.86 dBm(5W), 29.88dBm (1W) ---UHF
Output power Modification	UHF/VHF:1W/5W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)
Data Rate	9600bps/12.5KHz(Channel Spacing)
Antenna Designation	Detachable
Antenna Gain	1.5 dBi
Power Supply	DC 7.4V, 2200mAh (by battery)
Adapter Parameter	INPUT: AC 100V-240V , 50/60Hz , 0.6A OUTPUT: DC 12V , 0.5A
Limiting Voltage	DC 6V-8.51V
Operation Frequency Range and Channel	Frequency Range: 136 MHz to 174 MHz (VHF) 400 MHz to 480 MHz (UHF) Channel Separation: 12.5KHz, 25 KHz(Analog), 12.5KHz(Digital)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

	Bottom Channel: 136.025MHz Middle Channel: 151.85MHz Middle Channel: 155.025MHz Middle Channel: 161.61MHz Top Channel: 173.975MHz	Bottom Channel: 400.025MHz Middle Channel: 453.225MHz Middle Channel: 454.025MHz Top Channel: 479.975MHz
Frequency Tolerance	1.098ppm	

Frequency Range (MHz)	Rated Transmit Power(W)(Conducted)	Transmit Mode/Emission Designator
400-480	1W/5W	11K0F3E(Analog Voice;NB)
400-480	1W/5W	7K60FXD/7K60FXW(9600Data/Digital Voice NB)

Frequency Range (MHz)	Rated Transmit Power(W)(Conducted)	Transmit Mode/Emission Designator
136-174	1/5	11K0F3E(Analog Voice;NB)
136-174	1/5	7K60FXD/7K60FXW(9600Data/Digital Voice NB)

Channel No. (6.25KHz)	Channel No. (12.5KHz)	12.5KHz Channel Spaced 400MHz Band Plan(MHz)
1	1-2	400.025
2		
3	3-4	440.025
4		
5	5-6	479.975
6		

Channel No. (6.25KHz)	Channel No. (12.5KHz)	12.5KHz Channel Spaced 136MHz Band Plan(MHz)
1	1-2	136.025
2		
3	3-4	155.025
4		
5	5-6	173.975
6		

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

Voice –FM Analog (12.5KHz)

Calculation:

Max modulation (M) in kHz : 3.0

Max deviation(D) in kHz:2.5

Constant factor (K): 1(assumed)

$B_n = 2XM + 2XDK = 11.0 \text{ KHz}$

Emission designator: 11K0F3E

9600 Digital Voice/data (12.5KHz)

Calculation:

Data rate in bps(R)=9600

Deviation Peak deviation of carrier(D)=2359.585

Constant factor (K): 1 (default)

$B_n = 3.86D + 1.27RK = 3.86(2359.585) + 0.27(9600)(1) = 11.7 \text{ KHz}$

Emission designator: 11K0FXD

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: POD-MDUV390, filing to comply with Part 2, Part 22, and Part 90 of the Federal Communication Commission rules.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI/TIA-603-E (2016).

1.4 TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012
NVLAP LAB CODE	600153-0
Designation Number	CN5028
FCC Test Firm Registration Number	682566
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0

1.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

For FCC Part 90& Part 22 requirements:

- (1). Section 90.205 & 22.565: RF Output Power
- (2). Section 90.207: Modulation Characteristic
- (3). Section 90.209 & 22.359: Occupied Bandwidth
- (4). Section 90.210 & 22.359: Emission Mask
- (5). Section 90.213 & 22.355: Frequency Tolerance
- (6). Section 90.214: Transient Frequency Behavior

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

2.4 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Model No.	Identifier	Note
1	DMR Digital Transceiver	MD-UV390	FCC ID: POD-MDUV390	EUT

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§90.205 & 22.565	Maximum Transmitter Power	Compliant
§90.207	Modulation Characteristic	Compliant
§90.209& 22.359	Occupied Bandwidth	Compliant
§90.210& 22.359	Emission Mask	Compliant
§90.213& 22.355	Frequency Tolerance	Compliant
§90.214	Transient Frequency Behavior	Compliant

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2018	Jun. 11, 2019
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun. 12, 2018	Jun. 11, 2019
HORN ANTENNA	EM	EM-AH-10180	/	Mar.01, 2018	Feb.29, 2020
SIGNAL GENERATOR	AGILENT	E4421B	122501288	Jun. 12, 2018	Jun. 11, 2019
SIGNAL GENERATOR	R&S	SMT03	A0304261	Jun. 12, 2018	Jun. 11, 2019
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Mar.01, 2018	Feb.29, 2019
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Modulation Domain Analyzer	HP	53310A	3121A02467	May. 17, 2017	May. 18, 2019
Small environmental tester	ESPEC	SH-242	--	Mar.02, 2018	Mar. 01, 2019
RF Communication Test Set	HP	8920B	--	Jun. 20, 2017	Jun. 19, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B	--	Mar.01, 2018	Feb.28, 2019

Note: 8920B can generate audio modulation frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

4. DESCRIPTION OF TEST MODES

RF TEST MODES

The EUT (DMR Digital Transceiver) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

Analog:

No.	TEST MODES	CHANNEL SEPARATION
1	Low Channel	12.5 KHz
2	Middle Channel	12.5 KHz
3	High Channel	12.5 KHz

No.	TEST MODES	CHANNEL SEPARATION
1	Low Channel	25 KHz
2	Middle Channel	25 KHz
3	High Channel	25 KHz

Digital:

No.	TEST MODES	CHANNEL SEPARATION
1	Low Channel	12.5 KHz
2	Middle Channel	12.5 KHz
3	High Channel	12.5 KHz

Note: Only the result of the worst case was recorded in the report.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

5. FREQUENCY TOLERANCE

5.1 PROVISIONS APPLICABLE

- According to FCC §2.1055, § 22.355 and §90.213, the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 KHz channel separation and 0.0001% for 6.25 KHz channel separation.

5.2 MEASUREMENT PROCEDURE

5.2.1 Frequency stability versus environmental temperature


- Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz. Record this frequency as reference frequency.
- Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

5.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 7.4V.
- Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
- Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

5.3 TEST SETUP BLOCK DIAGRAM



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULT
VHF-Analog:

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-**5W-12.5KHz**

Environment Temperature(°C)	Power Supply	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 7.40 V	0.994	0.961	0.576	5
40	DC 7.40 V	0.638	0.395	0.985	
30	DC 7.40 V	0.598	0.626	0.580	
20	DC 7.40 V	0.428	0.755	0.874	
10	DC 7.40 V	0.900	0.385	0.766	
0	DC 7.40 V	0.689	0.335	0.751	
-10	DC 7.40 V	0.621	0.468	0.955	
-20	DC 7.40 V	0.346	0.617	0.712	
-30	DC 7.40 V	0.702	0.792	0.652	
Result	Pass				

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 7.40 V	0.653	0.809	5
40	DC 7.40 V	0.603	0.805	
30	DC 7.40 V	0.717	0.621	
20	DC 7.40 V	0.838	0.502	
10	DC 7.40 V	0.767	0.947	
0	DC 7.40 V	0.920	0.999	
-10	DC 7.40 V	0.997	1.078	
-20	DC 7.40 V	0.780	0.815	
-30	DC 7.40 V	1.097	0.921	
Result	Pass			

 (2) Frequency stability versus input voltage (Battery endpoint is 6V) -**5W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 6.00 V	0.880	0.962	0.884	5
40	DC 6.00 V	0.489	0.556	0.835	
30	DC 6.00 V	0.462	0.547	0.919	
20	DC 6.00 V	0.934	0.712	0.751	
10	DC 6.00 V	0.941	0.930	0.348	
0	DC 6.00 V	0.393	0.594	0.956	
-10	DC 6.00 V	0.434	0.991	0.669	
-20	DC 6.00 V	0.883	0.695	0.689	
-30	DC 6.00 V	0.646	0.806	0.694	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 6.00 V	0.788	1.022	5
40	DC 6.00 V	0.975	0.947	
30	DC 6.00 V	0.681	0.763	
20	DC 6.00 V	0.885	0.612	
10	DC 6.00 V	0.752	0.908	
0	DC 6.00 V	0.828	0.602	
-10	DC 6.00 V	1.089	0.699	
-20	DC 6.00 V	0.670	0.598	
-30	DC 6.00 V	0.529	0.731	
Result	Pass			

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-1W-12.5KHz

Environment	Power Supply	Reference Frequency			Limit:
Temperature(℃)	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 7.40 V	0.308	0.725	0.785	5
40	DC 7.40 V	0.554	0.737	0.613	
30	DC 7.40 V	0.700	0.805	0.677	
20	DC 7.40 V	0.519	0.391	0.777	
10	DC 7.40 V	0.565	0.366	0.606	
0	DC 7.40 V	0.665	0.882	0.719	
-10	DC 7.40 V	0.931	0.994	0.847	
-20	DC 7.40 V	0.653	0.525	0.306	
-30	DC 7.40 V	0.772	0.772	0.336	
Result	Pass				

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 7.40 V	0.827	0.936	5
40	DC 7.40 V	0.659	0.968	
30	DC 7.40 V	0.899	0.757	
20	DC 7.40 V	0.610	0.652	
10	DC 7.40 V	0.974	0.804	
0	DC 7.40 V	0.508	0.833	
-10	DC 7.40 V	0.923	1.065	
-20	DC 7.40 V	1.083	0.961	
-30	DC 7.40 V	0.675	1.062	
Result	Pass			

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

(2) Frequency stability versus input voltage (Battery endpoint is 6V) **-1W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 6.00 V	0.568	0.536	0.327	5
40	DC 6.00 V	0.529	0.557	0.657	
30	DC 6.00 V	0.625	0.654	0.903	
20	DC 6.00 V	0.301	0.755	0.456	
10	DC 6.00 V	0.546	0.979	0.615	
0	DC 6.00 V	0.598	0.651	0.755	
-10	DC 6.00 V	0.821	0.637	0.830	
-20	DC 6.00 V	0.466	0.340	0.627	
-30	DC 6.00 V	0.708	0.519	0.919	
Result	Pass				

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 6.00 V	0.835	0.926	5
40	DC 6.00 V	0.840	0.800	
30	DC 6.00 V	0.511	0.970	
20	DC 6.00 V	0.673	0.835	
10	DC 6.00 V	1.005	0.511	
0	DC 6.00 V	0.659	0.673	
-10	DC 6.00 V	0.668	1.024	
-20	DC 6.00 V	1.084	0.663	
-30	DC 6.00 V	1.010	0.670	
Result	Pass			

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V) **-5W-25KHz**

Environment Temperature(°C)	Power Supply	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 7.40 V	0.802	0.354	0.449	5
40	DC 7.40 V	0.350	0.720	0.922	
30	DC 7.40 V	0.564	0.365	0.643	
20	DC 7.40 V	0.933	0.577	0.568	
10	DC 7.40 V	0.377	0.945	0.420	
0	DC 7.40 V	0.578	0.426	0.887	
-10	DC 7.40 V	0.905	0.632	0.329	
-20	DC 7.40 V	0.386	0.781	0.880	
-30	DC 7.40 V	0.643	0.914	0.845	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 7.40 V	0.979	0.931	5
40	DC 7.40 V	0.336	0.416	
30	DC 7.40 V	0.473	0.972	
20	DC 7.40 V	0.376	0.738	
10	DC 7.40 V	0.742	0.612	
0	DC 7.40 V	0.532	0.737	
-10	DC 7.40 V	0.705	0.760	
-20	DC 7.40 V	0.996	0.489	
-30	DC 7.40 V	0.777	0.584	
Result	Pass			

 (2) Frequency stability versus input voltage (Battery endpoint is 6V) **-5W-25KHz**

Environment Temperature(°C)	Power Supply	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 6.00 V	0.342	0.541	0.926	5
40	DC 6.00 V	0.514	0.976	0.401	
30	DC 6.00 V	0.454	0.734	0.644	
20	DC 6.00 V	0.842	0.305	0.676	
10	DC 6.00 V	0.796	0.334	0.354	
0	DC 6.00 V	0.589	0.682	0.663	
-10	DC 6.00 V	0.655	0.582	0.527	
-20	DC 6.00 V	0.617	0.381	0.529	
-30	DC 6.00 V	0.408	0.484	0.820	
Result	Pass				

Environment Temperature(°C)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 6.00 V	0.809	0.453	5
40	DC 6.00 V	0.850	0.602	
30	DC 6.00 V	0.622	0.971	
20	DC 6.00 V	0.534	0.896	
10	DC 6.00 V	0.500	0.441	
0	DC 6.00 V	0.730	0.551	
-10	DC 6.00 V	0.953	0.633	
-20	DC 6.00 V	0.847	0.883	
-30	DC 6.00 V	0.624	0.865	
Result	Pass			

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-1W-25KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 7.40 V	0.821	0.868	0.330	5
40	DC 7.40 V	0.910	0.485	0.346	
30	DC 7.40 V	0.653	0.812	0.454	
20	DC 7.40 V	0.601	0.476	0.952	
10	DC 7.40 V	0.660	0.418	0.541	
0	DC 7.40 V	0.965	0.530	0.612	
-10	DC 7.40 V	0.673	0.940	0.811	
-20	DC 7.40 V	0.852	0.700	0.682	
-30	DC 7.40 V	0.770	0.562	0.393	
Result	Pass				

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 7.40 V	0.629	0.329	5
40	DC 7.40 V	0.950	0.595	
30	DC 7.40 V	0.582	0.899	
20	DC 7.40 V	0.919	0.616	
10	DC 7.40 V	0.343	0.580	
0	DC 7.40 V	0.926	0.603	
-10	DC 7.40 V	0.948	0.735	
-20	DC 7.40 V	0.592	0.597	
-30	DC 7.40 V	0.896	0.558	
Result	Pass			

(2) Frequency stability versus input voltage (Battery endpoint is 6V) -1W-25KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 6.00 V	0.614	0.988	0.575	5
40	DC 6.00 V	0.825	0.731	0.856	
30	DC 6.00 V	0.349	0.959	0.543	
20	DC 6.00 V	0.361	0.453	0.367	
10	DC 6.00 V	0.433	0.413	0.673	
0	DC 6.00 V	0.647	0.989	0.346	
-10	DC 6.00 V	0.928	0.654	0.785	
-20	DC 6.00 V	0.712	0.556	0.750	
-30	DC 6.00 V	0.955	0.388	0.540	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 6.00 V	0.893	0.849	5
40	DC 6.00 V	0.313	0.578	
30	DC 6.00 V	0.867	0.613	
20	DC 6.00 V	0.877	0.711	
10	DC 6.00 V	0.768	0.387	
0	DC 6.00 V	0.839	0.550	
-10	DC 6.00 V	0.648	0.756	
-20	DC 6.00 V	0.925	0.948	
-30	DC 6.00 V	0.907	0.703	
Result	Pass			

Digital:

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-5W-12.5KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 7.40 V	0.321	0.683	0.697	5
40	DC 7.40 V	0.774	0.665	0.308	
30	DC 7.40 V	0.665	0.590	0.554	
20	DC 7.40 V	0.953	0.604	0.912	
10	DC 7.40 V	0.611	0.985	0.501	
0	DC 7.40 V	0.902	0.494	0.847	
-10	DC 7.40 V	0.599	0.907	0.529	
-20	DC 7.40 V	0.930	0.446	0.315	
-30	DC 7.40 V	0.462	0.366	0.687	
Result	Pass				

Environment Temperature(°C)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 7.40 V	0.345	0.973	5
40	DC 7.40 V	0.418	0.810	
30	DC 7.40 V	0.483	0.305	
20	DC 7.40 V	0.347	0.658	
10	DC 7.40 V	0.709	0.392	
0	DC 7.40 V	0.445	0.340	
-10	DC 7.40 V	0.394	0.942	
-20	DC 7.40 V	0.310	0.582	
-30	DC 7.40 V	0.843	0.543	
Result	Pass			

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

(2) Frequency stability versus input voltage (Battery endpoint is 6V) **-5W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 6.00	0.333	0.873	0.567	5
40	DC 6.00 V	0.935	0.455	0.618	
30	DC 6.00 V	0.593	0.911	0.653	
20	DC 6.00 V	0.409	0.770	0.833	
10	DC 6.00	0.875	0.495	0.643	
0	DC 6.00	0.501	0.450	0.877	
-10	DC 6.00 V	0.332	0.554	0.363	
-20	DC 6.00 V	0.683	0.957	0.678	
-30	DC 6.00 V	0.434	0.390	0.823	
Result	Pass				

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 6.00	0.882	0.651	5
40	DC 6.00	0.472	0.506	
30	DC 6.00	0.540	0.362	
20	DC 6.00	0.695	0.746	
10	DC 6.00	0.917	0.745	
0	DC 6.00	0.803	0.984	
-10	DC 6.00	0.303	0.376	
-20	DC 6.00	0.480	0.452	
-30	DC 6.00	0.754	0.796	
Result	Pass			

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V) **-1W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 7.40 V	0.667	0.515	0.781	5
40	DC 7.40 V	0.986	0.571	0.777	
30	DC 7.40 V	1.054	0.611	0.885	
20	DC 7.40 V	1.021	0.894	0.598	
10	DC 7.40 V	0.591	1.072	0.533	
0	DC 7.40 V	0.832	0.575	0.543	
-10	DC 7.40 V	0.789	0.843	0.637	
-20	DC 7.40 V	0.816	0.591	0.763	
-30	DC 7.40 V	1.027	0.865	0.895	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Environment Temperature(℃)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 7.40 V	0.749	0.977	5
40	DC 7.40 V	0.521	0.547	
30	DC 7.40 V	0.317	0.851	
20	DC 7.40 V	0.319	0.764	
10	DC 7.40 V	0.819	0.401	
0	DC 7.40 V	0.995	0.845	
-10	DC 7.40 V	0.315	0.341	
-20	DC 7.40 V	0.940	0.761	
-30	DC 7.40 V	0.807	0.935	
Result	Pass			

(2) Frequency stability versus input voltage (Battery endpoint is 6V) -1W-12.5KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	136.025MHz	155.025MHz	173.975MHz	ppm
50	DC 6.00	0.415	0.522	0.985	5
40	DC 6.00 V	0.889	0.416	0.561	
30	DC 6.00 V	0.429	0.578	0.446	
20	DC 6.00 V	0.470	0.662	0.599	
10	DC 6.00	0.641	0.672	0.393	
0	DC 6.00	0.350	0.363	0.760	
-10	DC 6.00 V	0.549	0.823	0.452	
-20	DC 6.00 V	0.730	0.739	0.371	
-30	DC 6.00 V	0.386	0.380	0.654	
Result	Pass				

Environment Temperature(°C)	Power Supply	Reference Frequency		Limit:
	(V)	151.85MHz	161.61MHz	ppm
50	DC 6.00	0.761	0.896	5
40	DC 6.00	0.694	0.499	
30	DC 6.00	0.845	0.390	
20	DC 6.00	0.615	0.550	
10	DC 6.00	0.337	0.317	
0	DC 6.00	0.587	0.987	
-10	DC 6.00	0.757	0.530	
-20	DC 6.00	0.496	0.590	
-30	DC 6.00	0.422	0.964	
Result	Pass			

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

UHF:
Analog:

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-**5W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 7.40 V	0.987	0.714	0.660	2.5
40	DC 7.40 V	0.561	0.508	0.986	
30	DC 7.40 V	0.728	0.626	0.656	
20	DC 7.40 V	0.630	0.620	0.670	
10	DC 7.40 V	0.760	0.978	0.549	
0	DC 7.40 V	0.652	0.505	0.584	
-10	DC 7.40 V	0.771	0.838	0.910	
-20	DC 7.40 V	0.782	0.689	0.916	
-30	DC 7.40 V	1.031	0.532	0.821	
Result	Pass				

 (2) Frequency stability versus input voltage (Battery endpoint is 6V) -**5W-12.5KHz**

Environment Temperature(℃)	Power Supply	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 6.00 V	0.854	0.510	0.859	2.5
40	DC 6.00 V	0.417	0.468	0.684	
30	DC 6.00 V	0.355	0.748	0.800	
20	DC 6.00 V	0.345	0.864	0.487	
10	DC 6.00 V	0.828	0.657	0.817	
0	DC 6.00 V	0.933	0.938	0.981	
-10	DC 6.00 V	0.782	0.694	0.524	
-20	DC 6.00 V	0.704	0.345	0.364	
-30	DC 6.00 V	0.676	0.996	0.551	
Result	Pass				

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-**1W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 7.40 V	0.570	0.678	0.682	2.5
40	DC 7.40 V	1.003	1.063	0.553	
30	DC 7.40 V	0.510	0.795	0.565	
20	DC 7.40 V	1.098	0.720	0.553	
10	DC 7.40 V	1.025	0.834	0.757	
0	DC 7.40 V	0.616	0.806	0.741	
-10	DC 7.40 V	0.689	0.707	0.639	
-20	DC 7.40 V	0.565	0.621	0.630	
-30	DC 7.40 V	1.023	0.894	0.552	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

(2) Frequency stability versus input voltage (Battery endpoint is 6V) **-1W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 6.00 V	0.589	0.829	0.582	2.5
40	DC 6.00 V	0.503	0.761	0.928	
30	DC 6.00 V	0.322	0.631	0.950	
20	DC 6.00 V	0.411	0.775	0.336	
10	DC 6.00 V	0.696	0.311	0.345	
0	DC 6.00 V	0.741	0.408	0.548	
-10	DC 6.00 V	0.674	0.875	0.781	
-20	DC 6.00 V	0.537	0.823	0.584	
-30	DC 6.00 V	0.656	0.903	0.756	
Result	Pass				

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V) **-5W-25KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 7.40 V	0.646	0.699	1.050	2.5
40	DC 7.40 V	0.928	0.694	1.061	
30	DC 7.40 V	0.551	0.942	0.696	
20	DC 7.40 V	0.658	0.557	0.586	
10	DC 7.40 V	0.581	0.514	0.941	
0	DC 7.40 V	0.576	0.550	0.997	
-10	DC 7.40 V	0.516	0.921	0.768	
-20	DC 7.40 V	0.582	1.013	0.979	
-30	DC 7.40 V	0.735	0.855	0.777	
Result	Pass				

 (2) Frequency stability versus input voltage (Battery endpoint is 6V) **-5W-25KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 6.00 V	0.305	0.968	0.499	2.5
40	DC 6.00 V	0.926	0.897	0.772	
30	DC 6.00 V	0.302	0.798	0.768	
20	DC 6.00 V	0.498	0.873	0.494	
10	DC 6.00 V	0.894	0.479	0.739	
0	DC 6.00 V	0.576	0.738	0.686	
-10	DC 6.00 V	0.804	0.311	0.793	
-20	DC 6.00 V	0.435	0.881	0.684	
-30	DC 6.00 V	0.939	0.820	0.786	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-1W-25KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 7.40 V	0.802	0.729	0.609	2.5
40	DC 7.40 V	0.701	0.804	0.520	
30	DC 7.40 V	0.705	0.667	0.756	
20	DC 7.40 V	0.714	0.815	0.955	
10	DC 7.40 V	1.036	0.642	0.698	
0	DC 7.40 V	1.060	0.646	0.627	
-10	DC 7.40 V	0.966	0.942	1.005	
-20	DC 7.40 V	0.562	1.033	0.527	
-30	DC 7.40 V	0.888	0.883	0.513	
Result	Pass				

(4) Frequency stability versus input voltage (Battery endpoint is 6V) -1W-25KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 6.00 V	0.586	0.484	0.807	2.5
40	DC 6.00 V	0.559	0.421	0.408	
30	DC 6.00 V	0.402	0.872	0.818	
20	DC 6.00 V	0.802	0.828	0.613	
10	DC 6.00 V	0.598	0.585	0.757	
0	DC 6.00 V	0.547	0.988	0.593	
-10	DC 6.00 V	0.949	0.965	0.352	
-20	DC 6.00 V	0.541	0.723	0.307	
-30	DC 6.00 V	0.618	0.378	0.382	
Result	Pass				

Digital:

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-5W-12.5KHz

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 7.40 V	0.577	0.694	0.765	2.5
40	DC 7.40 V	0.622	0.986	0.710	
30	DC 7.40 V	0.596	1.026	0.936	
20	DC 7.40 V	1.071	0.699	0.914	
10	DC 7.40 V	0.662	0.907	0.739	
0	DC 7.40 V	1.005	0.576	0.755	
-10	DC 7.40 V	0.842	0.593	0.842	
-20	DC 7.40 V	0.849	0.857	0.781	
-30	DC 7.40 V	0.706	0.869	0.997	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

(2) Frequency stability versus input voltage(Battery endpoint is 6V) **-5W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 6.00	0.829	0.650	0.439	2.5
40	DC 6.00 V	0.895	0.447	0.907	
30	DC 6.00 V	0.387	0.740	0.513	
20	DC 6.00 V	0.645	0.319	0.444	
10	DC 6.00	0.948	0.937	0.653	
0	DC 6.00	0.436	0.964	0.581	
-10	DC 6.00 V	0.961	0.468	0.887	
-20	DC 6.00 V	0.305	0.358	0.448	
-30	DC 6.00 V	0.951	0.327	0.712	
Result	Pass				

 (1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)-**1W-12.5KHz**

12) Frequency stability versus input voltage (Supply nominal voltage is 7.15V) 200 Hz/1000 Hz					
Environment	Power	Reference Frequency			Limit:
Temperature(°C)	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 7.40 V	0.672	0.579	0.986	2.5
40	DC 7.40 V	0.788	0.678	0.507	
30	DC 7.40 V	0.601	0.943	0.750	
20	DC 7.40 V	1.097	0.984	1.037	
10	DC 7.40 V	0.804	1.056	0.843	
0	DC 7.40 V	0.922	0.955	0.526	
-10	DC 7.40 V	1.091	0.716	0.568	
-20	DC 7.40 V	0.749	0.528	1.026	
-30	DC 7.40 V	1.045	0.582	1.098	
Result	Pass				

 (2) Frequency stability versus input voltage (Battery endpoint is 6V) **-1W-12.5KHz**

Environment Temperature(℃)	Power	Reference Frequency			Limit:
	(V)	400.025MHz	454.025MHz	479.975MHz	ppm
50	DC 6.00	0.879	0.553	0.988	2.5
40	DC 6.00 V	0.376	0.722	0.596	
30	DC 6.00 V	0.985	0.754	0.440	
20	DC 6.00 V	0.323	0.491	0.588	
10	DC 6.00	0.706	0.824	0.326	
0	DC 6.00	0.733	0.423	0.364	
-10	DC 6.00 V	0.797	0.587	0.606	
-20	DC 6.00 V	0.766	0.979	1.000	
-30	DC 6.00 V	0.520	0.703	0.741	
Result	Pass				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

6. EMISSION BANDWIDTH

6.1 PROVISIONS APPLICABLE


FCC Part 90 & FCC Part 22:

The authorized bandwidth shall be 11.25 KHz for 12.5 KHz channel separation and 6 KHz for 6.25 KHz channel separation.

6.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by 2.5 KHz Sine wave audio signal, The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing).
- 3). Set SPA Center Frequency = fundamental frequency, RBW=100Hz.VBW= 300 Hz, Span =50 KHz.
- 4). Set SPA Max hold. Mark peak, -26 dB.

6.3 TEST SETUP BLOCK DIAGRAM



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.


6.4 MEASUREMENT RESULT

VHF:

Analog:12.5KHz


26 dB Bandwidth Measurement Result			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	10.19KHz	11.25 KHz	Pass
151.850MHz	10.19KHz	11.25 KHz	Pass
161.61MHz	10.19KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (151.850 MHz)-1W



Occupied bandwidth of Middle Channel (161.610 MHz)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

26 dB Bandwidth Measurement Result


Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	10.22KHz	11.25 KHz	Pass
151.850MHz	10.22KHz	11.25 KHz	Pass
161.61MHz	10.19KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (151.850 MHz)-5W



Occupied bandwidth of Middle Channel (161.610 MHz)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Analog:25KHz


26 dB Bandwidth Measurement Result			
Operating Frequency	25 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	15.23KHz	20 KHz	Pass
151.850MHz	15.25KHz	20 KHz	Pass
161.61MHz	15.41KHz	20 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (151.850 MHz)-1W



Occupied bandwidth of Middle Channel (161.610 MHz)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

26 dB Bandwidth Measurement Result


Operating Frequency	25 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	15.21KHz	20 KHz	Pass
151.850MHz	15.21KHz	20 KHz	Pass
161.61MHz	15.25KHz	20 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (151.850 MHz)-5W



Occupied bandwidth of Middle Channel (161.610 MHz)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Digital:

TEST RESULTS


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	8.746KHz	11.25 KHz	Pass
151.850MHz	8.096KHz	11.25 KHz	Pass
161.61 MHz	9.028KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (151.850 MHz)-1W



Occupied bandwidth of Middle Channel (161.610 MHz)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULTS


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	8.421KHz	11.25 KHz	Pass
151.850MHz	8.426KHz	11.25 KHz	Pass
161.610MHz	8.992KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (151.850 MHz)-5W



Occupied bandwidth of Middle Channel (161.610 MHz)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

UHF:

Analog:12.5KHz


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	10.24KHz	11.25 KHz	Pass
453.225MHz	10.23KHz	11.25 KHz	Pass
454.025MHz	10.29KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (Maximum)-1W




Occupied bandwidth of Middle Channel (Maximum)-1W



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	10.27KHz	11.25 KHz	Pass
453.225MHz	10.31KHz	11.25 KHz	Pass
454.025MHz	10.28KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (Maximum)-5W



Occupied bandwidth of Middle Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Analog:25KHz


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	25 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	15.33KHz	20 KHz	Pass
453.225MHz	15.35KHz	20 KHz	Pass
454.025MHz	15.38KHz	20 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (Maximum)-1W




Occupied bandwidth of Middle Channel (Maximum)-1W



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	25 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	15.32KHz	20 KHz	Pass
453.225MHz	15.32KHz	20 KHz	Pass
454.025MHz	15.32KHz	20 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (Maximum)-5W



Occupied bandwidth of Middle Channel (Maximum)-5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Digital:

TEST RESULTS


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	8.454KHz	11.25 KHz	Pass
453.225MHz	9.133KHz	11.25 KHz	Pass
454.025MHz	8.466KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum) -1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (Maximum)-1W



Occupied bandwidth of Middle Channel (Maximum)-1W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULTS


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	8.911KHz	11.25 KHz	Pass
453.225MHz	8.695KHz	11.25 KHz	Pass
454.025MHz	9.001KHz	11.25 KHz	Pass

Occupied bandwidth of Bottom Channel (Maximum) -5W




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Occupied bandwidth of Middle Channel (Maximum)-5W



Occupied bandwidth of Middle Channel (Maximum)-5W



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

7. UNWANTED RADIATION

7.1 PROVISIONS APPLICABLE

8.1.1 According to FCC §2.1049, §22.359 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

Emission Mask D -for 12.5 KHz Channel Separation:

- (1). On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB.
- (2). On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least $7.27(f_d - 2.88 \text{ KHz})$ dB
- (3). On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.

7.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

increase the sensitivity of the measuring receiver.

(14)The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.

(15)The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.



(16)The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.

(17)The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

7.3 TEST SETUP BLOCK DIAGRAM



SUBSTITUTION METHOD: (Radiated Emissions)

Radiated Below 1GHz



Radiated Above 1 GHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.



7.4 MEASUREMENT RESULTS:

Applicable Standard

FCC §2.1053, §22.359 and §90.210

On any frequency removed from the center of the authorized bandwidth by a displacement

Frequency (f_d in KHz) for of more than 12.5 KHz: at least $50+10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.

Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz_{th} and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

Limit: At least $50+10 \log(P) = 50+10 \log(5) = 57$ (dB)—5W

At least $50+10 \log(P) = 50+10 \log(1) = 50$ (dB)—1W

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

VHF:

Analog:

Measurement Result for 12.5 KHz Channel Separation @ 136.025MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	H	0		pass
272.050	H	71.24	57	pass
408.08	H	71.59	57	pass
544.100	H	72.12	57	pass
680.125	H	73.47	57	pass
816.150	H	74.32	57	pass
952.175	H	76.27	57	pass
1088.200	H	81.77	57	pass
1224.225	H	82.29	57	pass
1360.250	H	82.41	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	70.36	57	pass
408.08	V	71.49	57	pass
544.100	V	72.21	57	pass
680.125	V	70.62	57	pass
816.150	V	74.71	57	pass
952.175	V	76.39	57	pass
1088.200	V	75.42	57	pass
1224.225	V	78.37	57	pass
1360.250	V	79.58	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 151.850MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	H	0		pass
303.700	H	69.17	57	pass
455.550	H	70.63	57	pass
607.400	H	70.24	57	pass
759.250	H	73.52	57	pass
911.100	H	76.79	57	pass
1062.950	H	77.35	57	pass
1214.800	H	78.24	57	pass
1366.650	H	81.47	57	pass
1518.500	H	80.26	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	V	0		pass
303.700	V	69.36	57	pass
455.550	V	69.57	57	pass
607.400	V	70.02	57	pass
759.250	V	73.39	57	pass
911.100	V	75.47	57	pass
1062.950	V	78.52	57	pass
1214.800	V	77.69	57	pass
1366.650	V	82.74	57	pass
1518.500	V	81.39	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 155.025MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	H	0		pass
310.050	H	69.57	57	pass
465.075	H	70.19	57	pass
620.100	H	71.53	57	pass
775.125	H	72.78	57	pass
930.150	H	75.18	57	pass
1085.175	H	78.96	57	pass
1240.200	H	73.47	57	pass
1395.225	H	81.22	57	pass
1550.250	H	81.38	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	V	0		pass
310.050	V	69.01	57	pass
465.075	V	69.59	57	pass
620.100	V	71.47	57	pass
775.125	V	74.61	57	pass
930.150	V	76.43	57	pass
1085.175	V	77.58	57	pass
1240.200	V	79.79	57	pass
1395.225	V	80.81	57	pass
1550.250	V	80.23	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 161.610MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	H	0		pass
323.220	H	70.48	57	pass
484.83	H	71.31	57	pass
646.440	H	72.95	57	pass
808.050	H	73.42	57	pass
969.660	H	73.75	57	pass
1131.270	H	75.83	57	pass
1292.880	H	80.45	57	pass
1454.490	H	81.17	57	pass
1616.100	H	80.28	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	V	0		pass
323.220	V	70.62	57	pass
484.83	V	70.78	57	pass
646.440	V	72.62	57	pass
808.050	V	71.43	57	pass
969.660	V	73.84	57	pass
1131.270	V	75.68	57	pass
1292.880	V	74.51	57	pass
1454.490	V	78.75	57	pass
1616.100	V	78.39	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 173.975MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	H	0		pass
347.950	H	70.14	57	pass
521.925	H	71.58	57	pass
695.900	H	72.63	57	pass
869.875	H	75.18	57	pass
1043.850	H	74.29	57	pass
1217.825	H	78.52	57	pass
1391.800	H	77.47	57	pass
1565.775	H	80.16	57	pass
1739.750	H	81.58	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	71.36	57	pass
521.925	V	70.14	57	pass
695.900	V	75.75	57	pass
869.875	V	74.68	57	pass
1043.850	V	76.46	57	pass
1217.825	V	77.29	57	pass
1391.800	V	79.17	57	pass
1565.775	V	80.28	57	pass
1739.750	V	81.63	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 136.025MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	H	0		pass
272.050	H	71.52	50	pass
408.08	H	70.48	50	pass
544.100	H	73.35	50	pass
680.125	H	75.19	50	pass
816.150	H	74.43	50	pass
952.175	H	76.59	50	pass
1088.200	H	79.46	50	pass
1224.225	H	80.17	50	pass
1360.250	H	81.63	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	69.26	50	pass
408.08	V	71.48	50	pass
544.100	V	73.61	50	pass
680.125	V	74.58	50	pass
816.150	V	76.47	50	pass
952.175	V	77.62	50	pass
1088.200	V	78.58	50	pass
1224.225	V	80.14	50	pass
1360.250	V	81.65	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 151.850MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	H	0		pass
303.700	H	69.48	50	pass
455.550	H	70.71	50	pass
607.400	H	71.59	50	pass
759.250	H	72.63	50	pass
911.100	H	75.17	50	pass
1062.950	H	78.89	50	pass
1214.800	H	79.53	50	pass
1366.650	H	81.27	50	pass
1518.500	H	80.85	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.85	V	0		pass
303.7	V	70.26	50	pass
455.55	V	71.18	50	pass
607.4	V	73.96	50	pass
759.25	V	73.47	50	pass
911.1	V	75.52	50	pass
1062.95	V	76.78	50	pass
1214.8	V	77.81	50	pass
1366.65	V	78.34	50	pass
1518.5	V	80.55	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 155.025MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	H	0		pass
310.050	H	69.47	50	pass
465.075	H	70.61	50	pass
620.100	H	71.36	50	pass
775.125	H	73.59	50	pass
930.150	H	76.71	50	pass
1085.175	H	77.25	50	pass
1240.200	H	80.34	50	pass
1395.225	H	81.47	50	pass
1550.250	H	81.62	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	V	0		pass
310.050	V	70.14	50	pass
465.075	V	71.29	50	pass
620.100	V	73.94	50	pass
775.125	V	74.62	50	pass
930.150	V	76.77	50	pass
1085.175	V	75.41	50	pass
1240.200	V	79.86	50	pass
1395.225	V	80.57	50	pass
1550.250	V	81.32	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 161.10MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	H	0		pass
323.220	H	71.74	50	pass
484.830	H	72.32	50	pass
646.440	H	73.57	50	pass
808.050	H	76.41	50	pass
969.660	H	74.68	50	pass
1131.270	H	79.46	50	pass
1292.880	H	78.78	50	pass
1454.490	H	80.91	50	pass
1616.100	H	81.57	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	70.62	50	pass
521.925	V	72.94	50	pass
695.900	V	73.25	50	pass
869.875	V	75.51	50	pass
1043.850	V	76.86	50	pass
1217.825	V	77.47	50	pass
1391.800	V	79.53	50	pass
1565.775	V	81.84	50	pass
1739.750	V	82.36	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 173.975MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	H	0		pass
347.950	H	71.47	50	pass
521.925	H	72.69	50	pass
695.900	H	74.84	50	pass
869.875	H	75.13	50	pass
1043.850	H	76.52	50	pass
1217.825	H	78.47	50	pass
1391.800	H	79.36	50	pass
1565.775	H	80.58	50	pass
1739.750	H	80.94	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	70.69	50	pass
521.925	V	72.47	50	pass
695.900	V	73.36	50	pass
869.875	V	75.78	50	pass
1043.850	V	76.51	50	pass
1217.825	V	77.95	50	pass
1391.800	V	79.47	50	pass
1565.775	V	81.62	50	pass
1739.750	V	82.27	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 25 KHz Channel Separation @ 136.025MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	H	0		pass
272.050	H	71.26	57	pass
408.08	H	71.74	57	pass
544.100	H	72.68	57	pass
680.125	H	73.31	57	pass
816.150	H	74.47	57	pass
952.175	H	76.58	57	pass
1088.200	H	81.62	57	pass
1224.225	H	82.38	57	pass
1360.250	H	82.44	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	70.24	57	pass
408.08	V	71.69	57	pass
544.100	V	72.17	57	pass
680.125	V	70.35	57	pass
816.150	V	74.84	57	pass
952.175	V	76.65	57	pass
1088.200	V	75.74	57	pass
1224.225	V	78.89	57	pass
1360.250	V	79.67	57	pass

Measurement Result for 25 KHz Channel Separation @ 151.850MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	H	0		pass
303.700	H	69.47	57	pass
455.550	H	70.25	57	pass
607.400	H	70.69	57	pass
759.250	H	73.41	57	pass
911.100	H	76.85	57	pass
1062.950	H	77.43	57	pass
1214.800	H	78.69	57	pass
1366.650	H	81.41	57	pass
1518.500	H	80.58	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	V	0		pass
303.700	V	69.63	57	pass
455.550	V	69.14	57	pass
607.400	V	70.58	57	pass
759.250	V	73.49	57	pass
911.100	V	75.23	57	pass
1062.950	V	78.14	57	pass
1214.800	V	77.85	57	pass
1366.650	V	82.74	57	pass
1518.500	V	81.63	57	pass

Measurement Result for 25 KHz Channel Separation @ 155.025MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	H	0		pass
310.050	H	69.47	57	pass
465.075	H	70.62	57	pass
620.100	H	71.14	57	pass
775.125	H	72.58	57	pass
930.150	H	75.37	57	pass
1085.175	H	78.49	57	pass
1240.200	H	73.52	57	pass
1395.225	H	81.47	57	pass
1550.250	H	81.34	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	V	0		pass
310.050	V	69.14	57	pass
465.075	V	69.09	57	pass
620.100	V	71.53	57	pass
775.125	V	74.78	57	pass
930.150	V	76.29	57	pass
1085.175	V	77.11	57	pass
1240.200	V	79.53	57	pass
1395.225	V	80.86	57	pass
1550.250	V	80.74	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 25 KHz Channel Separation @ 161.610MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	H	0		pass
323.220	H	68.25	57	pass
484.83	H	70.31	57	pass
646.440	H	70.52	57	pass
808.050	H	72.61	57	pass
969.660	H	71.51	57	pass
1131.270	H	77.84	57	pass
1292.880	H	82.69	57	pass
1454.490	H	80.36	57	pass
1616.100	H	83.58	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	V	0		pass
323.220	V	68.52	57	pass
484.83	V	69.85	57	pass
646.440	V	70.41	57	pass
808.050	V	70.69	57	pass
969.660	V	72.85	57	pass
1131.270	V	73.64	57	pass
1292.880	V	72.87	57	pass
1454.490	V	75.58	57	pass
1616.100	V	77.26	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 25 KHz Channel Separation @ 173.975MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	H	0		pass
347.950	H	69.26	57	pass
521.925	H	70.86	57	pass
695.900	H	70.35	57	pass
869.875	H	71.92	57	pass
1043.850	H	73.85	57	pass
1217.825	H	75.75	57	pass
1391.800	H	79.79	57	pass
1565.775	H	81.18	57	pass
1739.750	H	82.57	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	70.26	57	pass
521.925	V	70.96	57	pass
695.900	V	72.85	57	pass
869.875	V	76.74	57	pass
1043.850	V	74.68	57	pass
1217.825	V	71.58	57	pass
1391.800	V	78.38	57	pass
1565.775	V	78.65	57	pass
1739.750	V	80.19	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 25 KHz Channel Separation @ 136.025MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	H	0		pass
272.050	H	70.16	50	pass
408.08	H	71.36	50	pass
544.100	H	75.52	50	pass
680.125	H	73.14	50	pass
816.150	H	78.69	50	pass
952.175	H	73.25	50	pass
1088.200	H	77.74	50	pass
1224.225	H	79.63	50	pass
1360.250	H	80.27	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	69.63	50	pass
408.08	V	70.25	50	pass
544.100	V	72.63	50	pass
680.125	V	73.75	50	pass
816.150	V	74.12	50	pass
952.175	V	72.47	50	pass
1088.200	V	77.36	50	pass
1224.225	V	79.57	50	pass
1360.250	V	80.69	50	pass

Measurement Result for 25 KHz Channel Separation @ 151.850MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	H	0		pass
303.700	H	71.26	50	pass
455.550	H	73.35	50	pass
607.400	H	70.17	50	pass
759.250	H	75.36	50	pass
911.100	H	73.51	50	pass
1062.950	H	79.85	50	pass
1214.800	H	75.39	50	pass
1366.650	H	80.51	50	pass
1518.500	H	80.84	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.85	V	0		pass
303.7	V	73.26	50	pass
455.55	V	70.96	50	pass
607.4	V	71.85	50	pass
759.25	V	77.26	50	pass
911.1	V	79.74	50	pass
1062.95	V	73.62	50	pass
1214.8	V	78.28	50	pass
1366.65	V	79.39	50	pass
1518.5	V	80.45	50	pass

Measurement Result for 25 KHz Channel Separation @ 155.025MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	H	0		pass
310.050	H	69.24	50	pass
465.075	H	70.63	50	pass
620.100	H	72.17	50	pass
775.125	H	73.25	50	pass
930.150	H	76.84	50	pass
1085.175	H	77.16	50	pass
1240.200	H	80.55	50	pass
1395.225	H	81.34	50	pass
1550.250	H	81.04	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	V	0		pass
310.050	V	70.53	50	pass
465.075	V	71.47	50	pass
620.100	V	73.86	50	pass
775.125	V	74.18	50	pass
930.150	V	76.62	50	pass
1085.175	V	75.74	50	pass
1240.200	V	79.09	50	pass
1395.225	V	80.43	50	pass
1550.250	V	81.17	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 25 KHz Channel Separation @ 161.10MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	H	0		pass
323.220	H	71.63	50	pass
484.830	H	72.12	50	pass
646.440	H	73.63	50	pass
808.050	H	76.74	50	pass
969.660	H	74.86	50	pass
1131.270	H	79.18	50	pass
1292.880	H	78.53	50	pass
1454.490	H	80.96	50	pass
1616.100	H	81.47	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	70.42	50	pass
521.925	V	72.39	50	pass
695.900	V	73.41	50	pass
869.875	V	75.85	50	pass
1043.850	V	76.71	50	pass
1217.825	V	77.53	50	pass
1391.800	V	79.47	50	pass
1565.775	V	81.95	50	pass
1739.750	V	82.43	50	pass

Measurement Result for 25 KHz Channel Separation @ 173.975MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	H	0		pass
347.950	H	71.47	50	pass
521.925	H	72.63	50	pass
695.900	H	74.24	50	pass
869.875	H	75.78	50	pass
1043.850	H	76.43	50	pass
1217.825	H	78.14	50	pass
1391.800	H	79.02	50	pass
1565.775	H	80.66	50	pass
1739.750	H	80.17	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	70.15	50	pass
521.925	V	72.74	50	pass
695.900	V	73.96	50	pass
869.875	V	75.43	50	pass
1043.850	V	76.25	50	pass
1217.825	V	77.75	50	pass
1391.800	V	79.41	50	pass
1565.775	V	81.58	50	pass
1739.750	V	82.43	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Digital:

Measurement Result for 12.5 KHz Channel Separation @ 136.025MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	H	0		pass
272.050	H	69.68	57	pass
408.08	H	71.14	57	pass
544.100	H	76.53	57	pass
680.125	H	72.89	57	pass
816.150	H	74.24	57	pass
952.175	H	75.73	57	pass
1088.200	H	81.01	57	pass
1224.225	H	80.28	57	pass
1360.250	H	81.45	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	71.43	57	pass
408.08	V	70.15	57	pass
544.100	V	72.69	57	pass
680.125	V	73.74	57	pass
816.150	V	74.43	57	pass
952.175	V	75.12	57	pass
1088.200	V	78.88	57	pass
1224.225	V	80.17	57	pass
1360.250	V	80.09	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 151.850MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	H	0		pass
303.700	H	70.63	57	pass
455.55	H	71.25	57	pass
607.400	H	73.17	57	pass
759.250	H	72.47	57	pass
911.100	H	74.56	57	pass
1062.950	H	75.34	57	pass
1214.800	H	81.25	57	pass
1366.650	H	80.48	57	pass
1518.500	H	81.46	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	V	0		pass
303.700	V	71.59	57	pass
455.55	V	70.31	57	pass
607.400	V	72.17	57	pass
759.250	V	72.25	57	pass
911.100	V	74.56	57	pass
1062.950	V	75.74	57	pass
1214.800	V	77.96	57	pass
1366.650	V	79.24	57	pass
1518.500	V	81.43	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 155.025MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	H	0		pass
310.050	H	71.36	57	pass
465.075	H	71.47	57	pass
620.100	H	72.89	57	pass
775.125	H	75.16	57	pass
930.150	H	76.52	57	pass
1085.175	H	78.74	57	pass
1240.200	H	79.81	57	pass
1395.225	H	80.25	57	pass
1550.250	H	80.17	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	V	0		pass
310.050	V	69.48	57	pass
465.08	V	70.52	57	pass
620.100	V	71.18	57	pass
775.125	V	70.62	57	pass
930.150	V	71.47	57	pass
1085.175	V	75.59	57	pass
1240.200	V	77.34	57	pass
1395.225	V	78.79	57	pass
1550.250	V	80.24	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 161.61MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	H	0		pass
323.220	H	70.42	57	pass
484.83	H	71.69	57	pass
646.440	H	72.14	57	pass
808.050	H	71.52	57	pass
969.660	H	73.47	57	pass
1131.270	H	77.39	57	pass
1292.880	H	80.48	57	pass
1454.490	H	81.73	57	pass
1616.100	H	80.61	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	V	0		pass
323.220	V	71.42	57	pass
484.83	V	70.61	57	pass
646.440	V	71.56	57	pass
808.050	V	72.14	57	pass
969.660	V	73.78	57	pass
1131.270	V	76.52	57	pass
1292.880	V	77.13	57	pass
1454.490	V	81.52	57	pass
1616.100	V	81.89	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 173.975MHz-5W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	H	0		pass
347.950	H	71.29	57	pass
521.925	H	71.47	57	pass
695.900	H	73.53	57	pass
869.875	H	74.24	57	pass
1043.850	H	75.16	57	pass
1217.825	H	76.81	57	pass
1391.800	H	79.57	57	pass
1565.775	H	82.29	57	pass
1739.750	H	80.43	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	71.84	57	pass
521.925	V	72.19	57	pass
695.900	V	74.47	57	pass
869.875	V	73.63	57	pass
1043.850	V	75.24	57	pass
1217.825	V	76.18	57	pass
1391.800	V	77.43	57	pass
1565.775	V	80.19	57	pass
1739.750	V	79.47	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 136.025MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	H	0		pass
272.050	H	68.53	50	pass
408.08	H	69.15	50	pass
544.100	H	73.84	50	pass
680.125	H	74.71	50	pass
816.150	H	75.26	50	pass
952.175	H	75.47	50	pass
1088.200	H	77.38	50	pass
1224.225	H	79.41	50	pass
1360.250	H	80.69	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	71.15	50	pass
408.08	V	72.69	50	pass
544.100	V	74.47	50	pass
680.125	V	75.43	50	pass
816.150	V	78.19	50	pass
952.175	V	77.51	50	pass
1088.200	V	78.85	50	pass
1224.225	V	80.17	50	pass
1360.250	V	81.22	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 151.850MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	H	0		pass
303.700	H	69.53	50	pass
455.55	H	72.89	50	pass
607.400	H	73.47	50	pass
759.250	H	75.36	50	pass
911.100	H	75.21	50	pass
1062.950	H	76.47	50	pass
1214.800	H	76.52	50	pass
1366.650	H	78.78	50	pass
1518.500	H	81.43	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
151.850	V	0		pass
303.700	V	71.43	50	pass
455.55	V	72.29	50	pass
607.400	V	73.14	50	pass
759.250	V	75.78	50	pass
911.100	V	74.23	50	pass
1062.950	V	76.53	50	pass
1214.800	V	75.74	50	pass
1366.650	V	81.86	50	pass
1518.500	V	80.71	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 155.025MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	H	0		pass
310.050	H	69.46	50	pass
465.075	H	71.23	50	pass
620.100	H	72.61	50	pass
775.125	H	75.42	50	pass
930.150	H	75.59	50	pass
1085.175	H	78.14	50	pass
1240.200	H	78.58	50	pass
1395.225	H	81.47	50	pass
1550.250	H	80.36	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.025	V	0		pass
310.050	V	69.47	50	pass
465.075	V	72.36	50	pass
620.100	V	73.82	50	pass
775.125	V	75.95	50	pass
930.150	V	77.24	50	pass
1085.175	V	76.46	50	pass
1240.200	V	79.25	50	pass
1395.225	V	81.74	50	pass
1550.250	V	82.11	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 161.610MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	H	0		pass
323.220	H	69.53	50	pass
484.83	H	71.26	50	pass
646.440	H	73.45	50	pass
808.050	H	74.74	50	pass
969.660	H	75.58	50	pass
1131.270	H	76.63	50	pass
1292.880	H	76.15	50	pass
1454.490	H	78.53	50	pass
1616.100	H	81.78	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/H)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
161.610	V	0		pass
323.220	V	71.48	50	pass
484.83	V	72.16	50	pass
646.440	V	74.75	50	pass
808.050	V	74.43	50	pass
969.660	V	76.13	50	pass
1131.270	V	75.06	50	pass
1292.880	V	76.48	50	pass
1454.490	V	79.51	50	pass
1616.100	V	80.46	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Measurement Result for 12.5 KHz Channel Separation @ 173.975MHz-1W

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	H	0		pass
347.950	H	69.65	50	pass
521.925	H	69.71	50	pass
695.900	H	71.36	50	pass
869.875	H	73.15	50	pass
1043.850	H	76.74	50	pass
1217.825	H	77.62	50	pass
1391.800	H	78.24	50	pass
1565.775	H	79.38	50	pass
1739.750	H	80.61	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	69.47	50	pass
521.925	V	70.53	50	pass
695.900	V	72.18	50	pass
869.875	V	75.53	50	pass
1043.850	V	76.24	50	pass
1217.825	V	78.18	50	pass
1391.800	V	79.69	50	pass
1565.775	V	81.78	50	pass
1739.750	V	80.81	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

UHF:

Analog:

TEST RESULTS--5W
Measurement Result for 12.5 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	H	0		pass
800.050	H	68.47	57	pass
1200.075	H	69.36	57	pass
1600.100	H	71.28	57	pass
2000.125	H	72.14	57	pass
2400.150	H	75.85	57	pass
2800.175	H	77.46	57	pass
3200.200	H	79.89	57	pass
3600.225	H	78.71	57	pass
4000.250	H	81.59	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	70.15	57	pass
1200.075	V	72.36	57	pass
1600.100	V	71.42	57	pass
2000.125	V	75.78	57	pass
2400.150	V	76.95	57	pass
2800.175	V	75.63	57	pass
3200.200	V	77.74	57	pass
3600.225	V	79.13	57	pass
4000.250	V	80.28	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 454.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	H	0		pass
908.050	H	67.43	57	pass
1362.075	H	70.59	57	pass
1816.100	H	70.24	57	pass
2270.125	H	74.39	57	pass
2724.150	H	75.48	57	pass
3178.175	H	79.16	57	pass
3632.200	H	78.78	57	pass
4086.225	H	81.63	57	pass
4540.250	H	81.78	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	V	0		pass
908.050	V	70.16	57	pass
1362.075	V	71.84	57	pass
1816.100	V	74.62	57	pass
2270.125	V	73.18	57	pass
2724.150	V	74.42	57	pass
3178.175	V	75.96	57	pass
3632.200	V	79.34	57	pass
4086.225	V	78.58	57	pass
4540.250	V	81.14	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 479.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	H	0		pass
959.950	H	67.25	57	pass
1439.925	H	68.35	57	pass
1919.900	H	69.61	57	pass
2399.875	H	71.26	57	pass
2879.850	H	72.24	57	pass
3359.825	H	75.35	57	pass
3839.800	H	76.42	57	pass
4319.775	H	79.62	57	pass
4799.750	H	81.15	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	V	0		pass
959.950	V	67.84	57	pass
1439.925	V	69.36	57	pass
1919.900	V	70.44	57	pass
2399.875	V	71.16	57	pass
2879.850	V	73.52	57	pass
3359.825	V	78.47	57	pass
3839.800	V	80.63	57	pass
4319.775	V	80.24	57	pass
4799.750	V	81.87	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULTS--1W
Measurement Result for 12.5 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	H	0		pass
800.050	H	70.46	50	pass
1200.075	H	71.85	50	pass
1600.100	H	73.16	50	pass
2000.125	H	75.36	50	pass
2400.150	H	76.74	50	pass
2800.175	H	77.29	50	pass
3200.200	H	78.63	50	pass
3600.225	H	80.24	50	pass
4000.250	H	81.09	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	70.69	50	pass
1200.075	V	71.42	50	pass
1600.100	V	73.26	50	pass
2000.125	V	74.34	50	pass
2400.150	V	75.18	50	pass
2800.175	V	76.52	50	pass
3200.200	V	77.49	50	pass
3600.225	V	79.84	50	pass
4000.250	V	80.39	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 454.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	H	0		pass
908.050	H	70.24	50	pass
1362.075	H	70.59	50	pass
1816.100	H	74.43	50	pass
2270.125	H	74.84	50	pass
2724.150	H	76.63	50	pass
3178.175	H	75.21	50	pass
3632.200	H	76.52	50	pass
4086.225	H	79.47	50	pass
4540.250	H	81.63	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	V	0		pass
908.050	V	68.25	50	pass
1362.075	V	69.48	50	pass
1816.100	V	70.39	50	pass
2270.125	V	73.51	50	pass
2724.150	V	76.74	50	pass
3178.175	V	78.83	50	pass
3632.200	V	79.13	50	pass
4086.225	V	80.28	50	pass
4540.250	V	80.42	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 479.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	H	0		pass
959.950	H	70.63	50	pass
1439.925	H	71.74	50	pass
1919.900	H	73.26	50	pass
2399.875	H	75.92	50	pass
2879.850	H	76.13	50	pass
3359.825	H	78.27	50	pass
3839.800	H	79.35	50	pass
4319.775	H	80.18	50	pass
4799.750	H	81.69	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	V	0		pass
959.950	V	70.46	50	pass
1439.925	V	71.32	50	pass
1919.900	V	72.19	50	pass
2399.875	V	74.28	50	pass
2879.850	V	76.47	50	pass
3359.825	V	77.62	50	pass
3839.800	V	78.47	50	pass
4319.775	V	79.28	50	pass
4799.750	V	80.11	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULTS--5W
Measurement Result for 25 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	H	0		pass
800.050	H	68.25	57	pass
1200.075	H	69.24	57	pass
1600.100	H	71.18	57	pass
2000.125	H	72.69	57	pass
2400.150	H	75.85	57	pass
2800.175	H	77.18	57	pass
3200.200	H	79.74	57	pass
3600.225	H	78.29	57	pass
4000.250	H	81.13	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	70.16	57	pass
1200.075	V	72.28	57	pass
1600.100	V	71.84	57	pass
2000.125	V	75.31	57	pass
2400.150	V	76.71	57	pass
2800.175	V	75.42	57	pass
3200.200	V	77.69	57	pass
3600.225	V	79.24	57	pass
4000.250	V	80.49	57	pass

Measurement Result for 25 KHz Channel Separation @ 454.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	H	0		pass
908.050	H	67.26	57	pass
1362.075	H	70.68	57	pass
1816.100	H	70.85	57	pass
2270.125	H	74.24	57	pass
2724.150	H	75.86	57	pass
3178.175	H	79.39	57	pass
3632.200	H	78.75	57	pass
4086.225	H	81.42	57	pass
4540.250	H	81.89	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	V	0		pass
908.050	V	70.14	57	pass
1362.075	V	72.38	57	pass
1816.100	V	74.12	57	pass
2270.125	V	73.15	57	pass
2724.150	V	74.29	57	pass
3178.175	V	75.28	57	pass
3632.200	V	79.85	57	pass
4086.225	V	78.96	57	pass
4540.250	V	81.25	57	pass

Measurement Result for 25 KHz Channel Separation @ 479.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	H	0		pass
959.950	H	68.24	57	pass
1439.925	H	68.74	57	pass
1919.900	H	69.35	57	pass
2399.875	H	70.53	57	pass
2879.850	H	73.46	57	pass
3359.825	H	78.38	57	pass
3839.800	H	79.61	57	pass
4319.775	H	80.48	57	pass
4799.750	H	80.68	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	V	0		pass
959.950	V	67.63	57	pass
1439.925	V	69.12	57	pass
1919.900	V	70.77	57	pass
2399.875	V	71.96	57	pass
2879.850	V	73.85	57	pass
3359.825	V	78.96	57	pass
3839.800	V	80.68	57	pass
4319.775	V	80.26	57	pass
4799.750	V	81.63	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULTS--1W
Measurement Result for 25 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	H	0		pass
800.050	H	70.26	50	pass
1200.075	H	71.89	50	pass
1600.100	H	73.85	50	pass
2000.125	H	75.96	50	pass
2400.150	H	76.18	50	pass
2800.175	H	77.88	50	pass
3200.200	H	78.92	50	pass
3600.225	H	80.42	50	pass
4000.250	H	81.59	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	70.15	50	pass
1200.075	V	71.36	50	pass
1600.100	V	73.85	50	pass
2000.125	V	74.12	50	pass
2400.150	V	75.36	50	pass
2800.175	V	76.74	50	pass
3200.200	V	77.52	50	pass
3600.225	V	79.89	50	pass
4000.250	V	80.15	50	pass

Measurement Result for 25 KHz Channel Separation @ 454.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	H	0		pass
908.050	H	70.23	50	pass
1362.075	H	70.42	50	pass
1816.100	H	72.65	50	pass
2270.125	H	74.91	50	pass
2724.150	H	76.28	50	pass
3178.175	H	75.47	50	pass
3632.200	H	76.85	50	pass
4086.225	H	79.92	50	pass
4540.250	H	81.35	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	V	0		pass
908.050	V	68.52	50	pass
1362.075	V	69.69	50	pass
1816.100	V	70.28	50	pass
2270.125	V	73.39	50	pass
2724.150	V	76.47	50	pass
3178.175	V	78.83	50	pass
3632.200	V	79.06	50	pass
4086.225	V	80.62	50	pass
4540.250	V	80.78	50	pass

Measurement Result for 25 KHz Channel Separation @ 479.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	H	0		pass
959.950	H	70.41	50	pass
1439.925	H	71.89	50	pass
1919.900	H	73.35	50	pass
2399.875	H	75.28	50	pass
2879.850	H	76.71	50	pass
3359.825	H	78.59	50	pass
3839.800	H	79.35	50	pass
4319.775	H	80.05	50	pass
4799.750	H	81.63	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	V	0		pass
959.950	V	70.62	50	pass
1439.925	V	71.17	50	pass
1919.900	V	72.52	50	pass
2399.875	V	74.86	50	pass
2879.850	V	76.88	50	pass
3359.825	V	78.29	50	pass
3839.800	V	78.71	50	pass
4319.775	V	79.32	50	pass
4799.750	V	80.15	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Digital:

TEST RESULTS-5W
Measurement Result for 12.5 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	H	0		pass
800.050	H	70.24	57	pass
1200.075	H	71.52	57	pass
1600.100	H	72.16	57	pass
2000.125	H	74.19	57	pass
2400.150	H	75.84	57	pass
2800.175	H	77.06	57	pass
3200.200	H	78.71	57	pass
3600.225	H	79.86	57	pass
4000.250	H	80.22	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	70.24	57	pass
1200.075	V	71.86	57	pass
1600.100	V	72.12	57	pass
2000.125	V	75.89	57	pass
2400.150	V	76.74	57	pass
2800.175	V	75.53	57	pass
3200.200	V	78.03	57	pass
3600.225	V	79.91	57	pass
4000.250	V	80.66	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 454.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	H	0		pass
908.050	H	70.74	57	pass
1362.075	H	71.52	57	pass
1816.100	H	74.16	57	pass
2270.125	H	74.58	57	pass
2724.150	H	76.34	57	pass
3178.175	H	77.25	57	pass
3632.200	H	79.63	57	pass
4086.225	H	81.85	57	pass
4540.250	H	80.42	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	V	0		pass
908.050	V	70.32	57	pass
1362.075	V	71.19	57	pass
1816.100	V	72.74	57	pass
2270.125	V	73.35	57	pass
2724.150	V	75.11	57	pass
3178.175	V	74.15	57	pass
3632.200	V	77.28	57	pass
4086.225	V	78.74	57	pass
4540.250	V	81.06	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 479.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	H	0		pass
959.950	H	71.36	57	pass
1439.925	H	70.24	57	pass
1919.900	H	73.71	57	pass
2399.875	H	75.53	57	pass
2879.850	H	78.09	57	pass
3359.825	H	77.34	57	pass
3839.800	H	79.19	57	pass
4319.775	H	79.86	57	pass
4799.750	H	80.24	57	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	V	0		pass
959.950	V	71.63	57	pass
1439.925	V	72.62	57	pass
1919.900	V	74.68	57	pass
2399.875	V	75.49	57	pass
2879.850	V	76.38	57	pass
3359.825	V	77.96	57	pass
3839.800	V	78.46	57	pass
4319.775	V	79.82	57	pass
4799.750	V	80.19	57	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULTS-1W
Measurement Result for 12.5 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	H	0		pass
800.050	H	70.03	50	pass
1200.075	H	71.24	50	pass
1600.100	H	72.74	50	pass
2000.125	H	73.25	50	pass
2400.150	H	74.68	50	pass
2800.175	H	75.71	50	pass
3200.200	H	76.58	50	pass
3600.225	H	78.62	50	pass
4000.250	H	79.74	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	70.54	50	pass
1200.075	V	71.81	50	pass
1600.100	V	74.35	50	pass
2000.125	V	75.08	50	pass
2400.150	V	76.41	50	pass
2800.175	V	78.83	50	pass
3200.200	V	81.74	50	pass
3600.225	V	80.36	50	pass
4000.250	V	81.47	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 454.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	H	0		pass
908.050	H	70.65	50	pass
1362.075	H	72.14	50	pass
1816.100	H	73.85	50	pass
2270.125	H	76.47	50	pass
2724.150	H	75.39	50	pass
3178.175	H	77.85	50	pass
3632.200	H	78.12	50	pass
4086.225	H	81.38	50	pass
4540.250	H	80.74	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
454.025	V	0		pass
908.050	V	69.36	50	pass
1362.075	V	71.84	50	pass
1816.100	V	70.27	50	pass
2270.125	V	72.52	50	pass
2724.150	V	74.87	50	pass
3178.175	V	76.62	50	pass
3632.200	V	77.14	50	pass
4086.225	V	78.01	50	pass
4540.250	V	81.59	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 479.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	H	0		pass
959.950	H	70.62	50	pass
1439.925	H	71.14	50	pass
1919.900	H	74.87	50	pass
2399.875	H	76.23	50	pass
2879.850	H	77.61	50	pass
3359.825	H	78.54	50	pass
3839.800	H	79.69	50	pass
4319.775	H	80.74	50	pass
4799.750	H	82.28	50	pass

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
479.975	V	0		pass
959.950	V	69.63	50	pass
1439.925	V	71.71	50	pass
1919.900	V	72.05	50	pass
2399.875	V	74.69	50	pass
2879.850	V	75.27	50	pass
3359.825	V	76.48	50	pass
3839.800	V	77.79	50	pass
4319.775	V	78.62	50	pass
4799.750	V	80.13	50	pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

7.5 EMISSION MASK PLOT


The detailed procedure employed for Emission Mask measurements are specified as following:

- The transmitter shall be modulated by a 2.5 kHz audio signal,
- The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz.

VHF:


Analog:

The Worst Emission Mask for (136.025MHz) of 12.5 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (136.025MHz) of 12.5 KHz channel Separation (5W)




The Worst Emission Mask for (151.85MHz) of 12.5 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (151.85MHz) of 12.5 KHz channel Separation (5W)




The Worst Emission Mask for (161.61MHz) of 12.5 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (161.61MHz) of 12.5 KHz channel Separation (5W)




The Worst Emission Mask for (173.975MHz) of 12.5 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (173.975MHz) of 12.5 KHz channel Separation (5W)




The Worst Emission Mask for (136.025MHz) of 25 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (136.025MHz) of 25 KHz channel Separation (5W)




The Worst Emission Mask for (151.85MHz) of 25 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (151.85MHz) of 25 KHz channel Separation (5W)




The Worst Emission Mask for (161.61MHz) of 25 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (161.61MHz) of 25 KHz channel Separation (5W)




The Worst Emission Mask for (173.975MHz) of 25 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask for (173.975MHz) of 25 KHz channel Separation (5W)




Digital:

The Worst Emission Mask D for (136.025MHz) of 12.5 KHz channel Separation (1W)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

The Worst Emission Mask D for (136.025MHz) of 12.5 KHz channel Separation (5W)



The Worst Emission Mask D for (151.85MHz) of 12.5 KHz channel Separation (1W)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.