

# FCC Test Report

**FCC ID** : PPQ-3509R38BT  
**Equipment** : 802.11a/b/g/n 2Tx2R + BT5.0 USB WLAN Module  
**Brand Name** : LITE-ON  
**Model Name** : WCBN3509R(38BT)  
**Applicant** : Lite-On Technology Corp.  
Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City  
23585, Taiwan, R.O.C  
**Manufacturer** : LITE-ON TECHNOLOGY (Changzhou) CO., LTD  
A9 Building, No.88 Yanghu Road, Wujin Hi-Tech  
Industrial Development Zone, Changzhou City, Jiangsu  
Province 213100 China  
**Standard** : 47 CFR FCC Part 15.247

The product was received on Oct. 24, 2019, and testing was started from Oct. 31, 2019 and completed on Nov. 27, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

## Table of Contents

|                                                                                       |           |
|---------------------------------------------------------------------------------------|-----------|
| <b>HISTORY OF THIS TEST REPORT .....</b>                                              | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                                                   | <b>4</b>  |
| <b>1 GENERAL DESCRIPTION .....</b>                                                    | <b>5</b>  |
| 1.1 Information.....                                                                  | 5         |
| 1.2 Testing Applied Standards .....                                                   | 8         |
| 1.3 Testing Location Information .....                                                | 8         |
| 1.4 Measurement Uncertainty .....                                                     | 9         |
| <b>2 TEST CONFIGURATION OF EUT.....</b>                                               | <b>10</b> |
| 2.1 Test Condition .....                                                              | 10        |
| 2.2 Test Channel Mode .....                                                           | 10        |
| 2.3 The Worst Case Measurement Configuration.....                                     | 11        |
| 2.4 Support Equipment.....                                                            | 12        |
| 2.5 Test Setup Diagram .....                                                          | 13        |
| <b>3 TRANSMITTER TEST RESULT .....</b>                                                | <b>15</b> |
| 3.1 AC Power-line Conducted Emissions .....                                           | 15        |
| 3.2 20dB Bandwidth and Carrier Frequency Separation.....                              | 17        |
| 3.3 Maximum Conducted Output Power .....                                              | 18        |
| 3.4 Number of Hopping Frequencies and Hopping Bandedge .....                          | 19        |
| 3.5 Time of Occupancy (Dwell Time) .....                                              | 20        |
| 3.6 Emissions in Non-restricted Frequency Bands .....                                 | 21        |
| 3.7 Emissions in Restricted Frequency Bands.....                                      | 22        |
| <b>4 TEST EQUIPMENT AND CALIBRATION DATA.....</b>                                     | <b>25</b> |
| <b>APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS</b>                  |           |
| <b>APPENDIX B. TEST RESULTS OF 20DB BANDWIDTH AND CARRIER FREQUENCY SEPARATION</b>    |           |
| <b>APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER</b>                     |           |
| <b>APPENDIX D. TEST RESULTS OF NUMBER OF HOPPING FREQUENCIES AND HOPPING BANDEDGE</b> |           |
| <b>APPENDIX E. TEST RESULTS OF TIME OF OCCUPANCY (DWELL TIME)</b>                     |           |
| <b>APPENDIX F. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS</b>        |           |
| <b>APPENDIX G. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS</b>            |           |
| <b>APPENDIX H. TEST PHOTOS</b>                                                        |           |
| <b>PHOTOGRAPHS OF EUT V01</b>                                                         |           |



## History of this test report

[illegible]

## Summary of Test Result

| Report Clause | Ref. Std. Clause | Test Items                                         | Result (PASS/FAIL) | Remark |
|---------------|------------------|----------------------------------------------------|--------------------|--------|
| 1.1.2         | 15.203           | Antenna Requirement                                | PASS               | -      |
| 3.1           | 15.207           | AC Power-line Conducted Emissions                  | PASS               | -      |
| 3.2           | 15.247(a)        | 20dB Bandwidth                                     | PASS               | -      |
| 3.2           | 15.247(a)        | Carrier Frequency Separation                       | PASS               | -      |
| 3.3           | 15.247(b)        | Maximum Conducted Output Power                     | PASS               | -      |
| 3.4           | 15.247(a)        | Number of Hopping Frequencies and Hopping Bandedge | PASS               | -      |
| 3.5           | 15.247(a)        | Time of Occupancy (Dwell Time)                     | PASS               | -      |
| 3.6           | 15.247(d)        | Emissions in Non-restricted Frequency Bands        | PASS               | -      |
| 3.7           | 15.247(d)        | Emissions in Restricted Frequency Bands            | PASS               | -      |

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and explanations:**

None

**Reviewed by: Sam Tsai**

**Report Producer: Kate Lo**

# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

| Frequency Range (MHz) | Bluetooth Version | Ch. Frequency (MHz) | Channel Number |
|-----------------------|-------------------|---------------------|----------------|
| 2400-2483.5           | BR / EDR          | 2402-2480           | 0-78 [79]      |

| Band          | Mode          | BWch (MHz) | Nant |
|---------------|---------------|------------|------|
| 2.4-2.4835GHz | BT-BR(1Mbps)  | 1          | 1TX  |
| 2.4-2.4835GHz | BT-EDR(2Mbps) | 1          | 1TX  |
| 2.4-2.4835GHz | BT-EDR(3Mbps) | 1          | 1TX  |

Note:

- Bluetooth BR uses a GFSK (1Mbps).
- Bluetooth EDR uses a combination of  $\pi/4$ -DQPSK (2Mbps) and 8DPSK (3Mbps).
- Bluetooth BR/EDR uses as a system using FHSS modulation.
- BWch is the nominal channel bandwidth.

### 1.1.2 Antenna Information

| Ant. | Brand  | Model Name             | Antenna Type | Connector | Support | Remark  |
|------|--------|------------------------|--------------|-----------|---------|---------|
| 1    | HONGBO | 290-10569              | PIFA         | I-Pex     | 2.4G+5G | Group 1 |
| 2    | HONGBO | 290-10569              | PIFA         | I-Pex     | 2.4G+5G |         |
| 3    | HONGBO | 290-10569              | PIFA         | I-Pex     | BT      |         |
| 4    | PSA    | RFMTA401030IML<br>B702 | PIFA         | I-Pex     | 2.4G+5G | Group 2 |
| 5    | PSA    | RFMTA401030IML<br>B702 | PIFA         | I-Pex     | 2.4G+5G |         |
| 6    | PSA    | RFMTA401030IML<br>B702 | PIFA         | I-Pex     | BT      |         |
| 7    | HONGBO | 290-10843              | PIFA         | I-Pex     | 2.4G+5G | Group 3 |
| 8    | HONGBO | 290-10843              | PIFA         | I-Pex     | 2.4G+5G |         |
| 9    | HONGBO | 290-10843              | PIFA         | I-Pex     | BT      |         |
| 10   | PSA    | RFMTA401050IML<br>B706 | PIFA         | I-Pex     | 2.4G+5G | Group 4 |
| 11   | PSA    | RFMTA401050IML<br>B706 | PIFA         | I-Pex     | 2.4G+5G |         |
| 12   | PSA    | RFMTA401050IML<br>B706 | PIFA         | I-Pex     | BT      |         |

| Ant. | Brand  | Model Name             | Antenna Type | Connector | Support | Remark  |
|------|--------|------------------------|--------------|-----------|---------|---------|
| 13   | HONGBO | 290-10844              | PIFA         | I-Pex     | 2.4G+5G | Group 5 |
| 14   | HONGBO | 290-10844              | PIFA         | I-Pex     | 2.4G+5G |         |
| 15   | HONGBO | 290-10844              | PIFA         | I-Pex     | BT      |         |
| 16   | PSA    | RFMTA401080IML<br>B704 | PIFA         | I-Pex     | 2.4G+5G | Group 6 |
| 17   | PSA    | RFMTA401080IML<br>B704 | PIFA         | I-Pex     | 2.4G+5G |         |
| 18   | PSA    | RFMTA401080IML<br>B704 | PIFA         | I-Pex     | BT      |         |
| 19   | PSA    | RFMTA340730IML<br>B305 | PIFA         | I-Pex     | 2.4G+5G | Group 7 |
| 20   | PSA    | RFMTA340715IML<br>B302 | PIFA         | I-Pex     | 2.4G+5G |         |
| 21   | PSA    | RFMTA340715IML<br>B305 | PIFA         | I-Pex     | BT      |         |

| Ant. | Port | Gain (dBi) |      |      | Remark  |
|------|------|------------|------|------|---------|
|      |      | 2.4G       | 5G   | BT   |         |
| 1    | 1    | 3.74       | 3.8  | -    | Group 1 |
| 2    | 2    | 3.74       | 3.8  | -    |         |
| 3    | 3    | -          | -    | 3.74 |         |
| 4    | 1    | 3.74       | 3.8  | -    | Group 2 |
| 5    | 2    | 3.74       | 3.8  | -    |         |
| 6    | 3    | -          | -    | 3.74 |         |
| 7    | 1    | 3.05       | 1.59 | -    | Group 3 |
| 8    | 2    | 3.05       | 1.59 | -    |         |
| 9    | 3    | -          | -    | 3.05 |         |
| 10   | 1    | 3.05       | 1.59 | -    | Group 4 |
| 11   | 2    | 3.05       | 1.59 | -    |         |
| 12   | 3    | -          | -    | 3.05 |         |
| 13   | 1    | 2.38       | 1.49 | -    | Group 5 |
| 14   | 2    | 2.38       | 1.49 | -    |         |
| 15   | 3    | -          | -    | 2.38 |         |
| 16   | 1    | 1.72       | 1.25 | -    | Group 6 |
| 17   | 2    | 1.72       | 1.25 | -    |         |
| 18   | 3    | -          | -    | 1.72 |         |

| Ant. | Port | Gain (dBi) |      |      | Remark  |
|------|------|------------|------|------|---------|
|      |      | 2.4G       | 5G   | BT   |         |
| 19   | 1    | -0.5       | 3.28 | -    | Group 7 |
| 20   | 2    | -1.68      | 3.08 | -    |         |
| 21   | 3    | -          | -    | -0.5 |         |

Note 1: The EUT has twenty one antennas.

Note 2: EUT can match with above antennas for using. Group 1 was used to perform the worst configuration and result of that was recorded as the final test result.

**For 2.4GHz function:**

For IEEE 802.11 b/g/n mode (2TX/2RX)

Port 1 and Port 2 could transmit/receive simultaneously.

**For BT function:**

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Port 3 could transmit/receive.

**For 5GHz function:**

For IEEE 802.11 a/n mode (2TX/2RX)

Port 1 and Port 2 could transmit/receive simultaneously.

### 1.1.3 EUT Information

| Operational Condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                               |                                         |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------|--|
| EUT Power Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | From host system(NB)                                                          |                                         |  |
| EUT Function                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <input checked="" type="checkbox"/> Point-to-multipoint                       | <input type="checkbox"/> Point-to-point |  |
| AFH Function                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <input checked="" type="checkbox"/> Non-AFH                                   | <input checked="" type="checkbox"/> AFH |  |
| <p>Note.</p> <p><b>Non-AFH:</b> DH5 Packet permit maximum <math>1600 / 79 / 6 = 3.37</math> hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times <math>3.37 \times 1.185 = 4</math> within 1.185 seconds.</p> <p><b>AFH:</b> DH5 Packet permit maximum <math>800 / 20 / 6 = 6.67</math> hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times <math>13.33 \times 8 = 106.6</math> within 8 seconds.</p> <p>Under the above conditions, Non-AFH Mode configuration was found to be the worst case and measured during the test.</p> |                                                                               |                                         |  |
| Type of EUT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                               |                                         |  |
| <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Stand-alone                                                                   |                                         |  |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Combined (EUT where the radio part is fully integrated within another device) |                                         |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Combined Equipment - Brand Name / Model No.:                                  | ...                                     |  |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Plug-in radio (EUT intended for a variety of host systems)                    |                                         |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Host System - Brand Name / Model No.:                                         | ...                                     |  |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Other:                                                                        |                                         |  |

### 1.1.4 Mode Test Duty Cycle

| Mode          | DC    | DCF(dB) | T(s)   | VBW(Hz) $\geq 1/T$ |
|---------------|-------|---------|--------|--------------------|
| BT-BR(1Mbps)  | 0.575 | 2.4     | 2.876m | 1k                 |
| BT-EDR(2Mbps) | 0.576 | 2.4     | 2.88m  | 1k                 |
| BT-EDR(3Mbps) | 0.577 | 2.39    | 2.883m | 1k                 |

Note. If DC < 0.98, the DCF was added while measuring Output power and PSD.

## 1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ KDB 558074 D01 v05r02
- ♦ ANSI C63.10-2013
- ♦ KDB 414788 D01 v01r01

## 1.3 Testing Location Information

| Testing Location                           |        |                                                                              |                      |
|--------------------------------------------|--------|------------------------------------------------------------------------------|----------------------|
| <input checked="" type="checkbox"/>        | HWA YA | ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)    |                      |
|                                            |        | TEL : 886-3-327-3456                                                         | FAX : 886-3-327-0973 |
| Test site Designation No. TW1190 with FCC. |        |                                                                              |                      |
| <input type="checkbox"/>                   | JHUBEI | ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) |                      |
|                                            |        | TEL : 886-3-656-9065                                                         | FAX : 886-3-656-9085 |
| Test site Designation No. TW0006 with FCC. |        |                                                                              |                      |

| Test Condition | Test Site No. | Test Engineer | Test Environment            | Test Date                   |
|----------------|---------------|---------------|-----------------------------|-----------------------------|
| RF Conducted   | TH06-HY       | Tim           | 23~25°C /<br>61~67%         | 03/Nov/2019~<br>20/Nov/2019 |
| Radiated       | 03CH03-HY     | Justin        | 18.7~24.3°C /<br>53.8~61.2% | 31/Oct/2019~<br>20/Nov/2019 |
| AC Conduction  | CO04-HY       | Edward        | 20.9~22.1°C /<br>60.4~64.2% | 04/Nov/2019~<br>27/Nov/2019 |

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

| Test Items                           | Uncertainty | Remark                   |
|--------------------------------------|-------------|--------------------------|
| Conducted Emission (150kHz ~ 30MHz)  | 3.54 dB     | Confidence levels of 95% |
| Radiated Emission (9kHz ~ 30MHz)     | 1.6 dB      | Confidence levels of 95% |
| Radiated Emission (30MHz ~ 1,000MHz) | 4.3 dB      | Confidence levels of 95% |
| Radiated Emission (1GHz ~ 18GHz)     | 3.9 dB      | Confidence levels of 95% |
| Radiated Emission (18GHz ~ 40GHz)    | 3.5 dB      | Confidence levels of 95% |
| Conducted Emission                   | 1.3 dB      | Confidence levels of 95% |
| Temperature                          | 0.7 °C      | Confidence levels of 95% |
| Humidity                             | 4 %         | Confidence levels of 95% |

## 2 Test Configuration of EUT

### 2.1 Test Condition

| RF Conducted | Abbreviation | Remark |
|--------------|--------------|--------|
| TnomVnom     | Tnom         | 20°C   |
| -            | Vnom         | 5V     |

### 2.2 Test Channel Mode

|                       |                     |
|-----------------------|---------------------|
| Test Software Version | WCN_Combo_Tool 1747 |
|-----------------------|---------------------|

| Mode          | PowerSetting |
|---------------|--------------|
| BT-BR(1Mbps)  | -            |
| 2402MHz       | 7            |
| 2441MHz       | 7            |
| 2480MHz       | 7            |
| BT-EDR(2Mbps) | -            |
| 2402MHz       | 7            |
| 2441MHz       | 7            |
| 2480MHz       | 7            |
| BT-EDR(3Mbps) | -            |
| 2402MHz       | 7            |
| 2441MHz       | 7            |
| 2480MHz       | 7            |

## 2.3 The Worst Case Measurement Configuration

| The Worst Case Mode for Following Conformance Tests |                                                          |
|-----------------------------------------------------|----------------------------------------------------------|
| <b>Tests Item</b>                                   | AC power-line conducted emissions                        |
| <b>Condition</b>                                    | AC power-line conducted measurement for line and neutral |
| <b>Operating Mode</b>                               | CTX                                                      |
| 1                                                   | USB mode                                                 |

| The Worst Case Mode for Following Conformance Tests |                                                                                                                                                                                                                        |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tests Item</b>                                   | 20dB Bandwidth<br>Carrier Frequency Separation<br>Maximum Conducted Output Power<br>Number of Hopping Frequencies<br>Hopping Bandedge<br>Time of Occupancy (Dwell Time)<br>Emissions in Non-restricted Frequency Bands |
| <b>Test Condition</b>                               | Conducted measurement at transmit chains                                                                                                                                                                               |

| The Worst Case Mode for Following Conformance Tests |                                                                                                                                                                                                                                                     |                                                                                      |                                                                                       |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Tests Item</b>                                   | Emissions in Restricted Frequency Bands                                                                                                                                                                                                             |                                                                                      |                                                                                       |
| <b>Test Condition</b>                               | Radiated measurement<br>If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type. |                                                                                      |                                                                                       |
| <b>Operating Mode &lt; 1GHz</b>                     | CTX                                                                                                                                                                                                                                                 |                                                                                      |                                                                                       |
| 1                                                   | USB mode                                                                                                                                                                                                                                            |                                                                                      |                                                                                       |
| <b>Operating Mode &gt; 1GHz</b>                     | CTX                                                                                                                                                                                                                                                 |                                                                                      |                                                                                       |
| <b>Orthogonal Planes of EUT</b>                     | <b>X Plane</b>                                                                                                                                                                                                                                      | <b>Y Plane</b>                                                                       | <b>Z Plane</b>                                                                        |
|                                                     |                                                                                                                                                                  |  |  |
| <b>Worst Planes of EUT</b>                          |                                                                                                                                                                                                                                                     |                                                                                      | V                                                                                     |

| The Worst Case Mode for Following Conformance Tests                                |                                    |
|------------------------------------------------------------------------------------|------------------------------------|
| <b>Tests Item</b>                                                                  | Simultaneous Transmission Analysis |
| <b>Operating Mode</b>                                                              | CTX                                |
| 1                                                                                  | WLAN 2.4GHz+Bluetooth              |
| 2                                                                                  | WLAN 5GHz+Bluetooth                |
| Refer to Sporton Test Report No.: FA9O2329 for Co-location RF Exposure Evaluation. |                                    |

## 2.4 Support Equipment


| Support Equipment – RF Conducted |                |            |            |        |
|----------------------------------|----------------|------------|------------|--------|
| No.                              | Equipment      | Brand Name | Model Name | FCC ID |
| 1                                | Notebook       | DELL       | E5410      | DoC    |
| 2                                | Adapter for NB | DELL       | HA65NM130  | DoC    |
| 3                                | Fixture        | LITE-ON    | TB001      | -      |


Note: Support equipment No.3 was provided by customer.

| Support Equipment –AC Conduction and Radiated Emission |           |            |            |        |
|--------------------------------------------------------|-----------|------------|------------|--------|
| No.                                                    | Equipment | Brand Name | Model Name | FCC ID |
| 1                                                      | Notebook  | DELL       | E4300      | -      |
| 2                                                      | Adapter   | DELL       | LA90PM111  | -      |
| 3                                                      | Fixture   | LITE-ON    | TB001      | -      |

Note: Support equipment No.3 was provided by customer.

## 2.5 Test Setup Diagram



**Test Setup Diagram - Radiated Test**


| Item | Connection     | Shielded | Length(m) | Remark |
|------|----------------|----------|-----------|--------|
| 1    | AC Power Cable | No       | 1.8       | -      |
| 2    | DC Power Cable | No       | 2.0       | -      |
| 3    | USB Cable      | No       | 0.1       | -      |
| 4    | Fixture Cable  | No       | 0.05      | -      |
| 5    | Antenna cable  | No       | 0.3       | -      |
| 6    | Antenna cable  | No       | 0.3       | -      |
| 7    | Antenna cable  | No       | 0.3       | -      |

### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

| AC Power-line Conducted Emissions Limit                  |            |           |
|----------------------------------------------------------|------------|-----------|
| Frequency Emission (MHz)                                 | Quasi-Peak | Average   |
| 0.15-0.5                                                 | 66 - 56 *  | 56 - 46 * |
| 0.5-5                                                    | 56         | 46        |
| 5-30                                                     | 60         | 50        |
| Note 1: * Decreases with the logarithm of the frequency. |            |           |


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

| Test Method                                                                   |
|-------------------------------------------------------------------------------|
| ▪ Refer as ANSI C63.10-2013, clause 6.2 foray power-line conducted emissions. |

### 3.1.4 Test Setup



### 3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

## 3.2 20dB Bandwidth and Carrier Frequency Separation

### 3.2.1 20dB Bandwidth and Carrier Frequency Separation Limit

| 20dB Bandwidth and Carrier Frequency Separation Limit for Frequency Hopping Systems |                                                                                                                                               |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>2400-2483.5 MHz Band:</li> </ul>             |                                                                                                                                               |
|                                                                                     | <ul style="list-style-type: none"> <li><math>N \geq 75</math> and <math>ChS \geq MAX</math> (20 dB bandwidth, 25 kHz).</li> </ul>             |
|                                                                                     | <ul style="list-style-type: none"> <li><math>75 &gt; N \geq 15</math> and <math>ChS \geq MAX</math> (20 dB bandwidth 2/3, 25 kHz).</li> </ul> |
| <b>N:</b> Number of Hopping Frequencies; <b>ChS:</b> Hopping Channel Separation     |                                                                                                                                               |


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

| Test Method                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 6.9.2 for 20 dB bandwidth measurement.</li> </ul>              |
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 7.8.2 for carrier frequency separation measurement.</li> </ul> |

### 3.2.4 Test Setup



### 3.2.5 Test Result of 20dB Bandwidth

Refer as Appendix B

### 3.2.6 Test Result of Carrier Frequency Separation

Refer as Appendix B

### 3.3 Maximum Conducted Output Power

#### 3.3.1 Maximum Conducted Output Power Limit

| Maximum Conducted Output Power Limit                                    |                                                                                                           |
|-------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>2400-2483.5 MHz Band:</li> </ul> |                                                                                                           |
|                                                                         | <ul style="list-style-type: none"> <li><math>N \geq 75</math>; Power 30dBm; EIRP 36dBm</li> </ul>         |
|                                                                         | <ul style="list-style-type: none"> <li><math>75 &gt; N \geq 15</math>; Power 21dBm; EIRP 27dBm</li> </ul> |
| N: Number of Hopping Frequencies                                        |                                                                                                           |


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.3.3 Test Procedures

| Test Method                                                                                                             |
|-------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 7.8.5 for output power measurement.</li> </ul> |

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

### 3.4 Number of Hopping Frequencies and Hopping Bandedge

#### 3.4.1 Number of Hopping Frequencies Limit

| Number of Hopping Frequencies Limit                                     |                                                                                                                                               |
|-------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>2400-2483.5 MHz Band:</li> </ul> |                                                                                                                                               |
|                                                                         | <ul style="list-style-type: none"> <li><math>N \geq 75</math> and <math>ChS \geq MAX</math> (20 dB bandwidth, 25 kHz).</li> </ul>             |
|                                                                         | <ul style="list-style-type: none"> <li><math>75 &gt; N \geq 15</math> and <math>ChS \geq MAX</math> (20 dB bandwidth 2/3, 25 kHz).</li> </ul> |
| N: Number of Hopping Frequencies; ChS : Hopping Channel Separation      |                                                                                                                                               |

#### 3.4.2 Hopping Bandedge Limit

Refer clause 3.6.1 and clause 3.7.1


#### 3.4.3 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.4 Test Procedures

| Test Method                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 7.8.3 for number of hopping frequencies measurement.</li> </ul> |
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 7.8.6 for hopping frequencies Bandedge measurement.</li> </ul>  |

#### 3.4.5 Test Setup



#### 3.4.6 Test Result of Number of Hopping Frequencies

Refer as Appendix D

#### 3.4.7 Test Result of Number of Hopping Frequencies Bandedge

Refer as Appendix D

### 3.5 Time of Occupancy (Dwell Time)

#### 3.5.1 Time of Occupancy (Dwell Time) Limit

| Time of Occupancy (Dwell Time) Limit for Frequency Hopping Systems      |                                                                                                                            |
|-------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>2400-2483.5 MHz Band:</li> </ul> |                                                                                                                            |
|                                                                         | <ul style="list-style-type: none"> <li><math>N \geq 75</math>; 0.4s in <math>N \times 0.4</math> period</li> </ul>         |
|                                                                         | <ul style="list-style-type: none"> <li><math>75 &gt; N \geq 15</math>; 0.4s in <math>N \times 0.4</math> period</li> </ul> |
| N: Number of Hopping Frequencies                                        |                                                                                                                            |


#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures

| Test Method                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 7.8.4 for dwell time measurement.</li> </ul>                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>Bluetooth ACL packets can be 1, 3, or 5 time slots. Following as dwell time. Operate DH5 at maximum dwell time and maximum duty cycle.</li> </ul> |                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                                                                                                                                                                                          | <ul style="list-style-type: none"> <li>The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is <math>5/1600</math> seconds, or 3.125ms. DH5 Packet permit maximum <math>1600 / 79 / 6 = 3.37</math> hops per second in each channel.</li> </ul> |

#### 3.5.4 Test Setup



#### 3.5.5 Test Result of Time of Occupancy (Dwell Time)

Refer as Appendix E

### 3.6 Emissions in Non-restricted Frequency Bands

#### 3.6.1 Emissions in Non-restricted Frequency Bands Limit

| Un-restricted Band Emissions Limit                                                                                                                                                                                                                                                                                                            |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| RF output power procedure                                                                                                                                                                                                                                                                                                                     | Limit (dB) |
| Peak output power procedure                                                                                                                                                                                                                                                                                                                   | 20         |
| Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level. |            |


#### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.6.3 Test Procedures

| Test Method                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 7.8.8 for unwanted emissions into non-restricted bands.</li> </ul> |

#### 3.6.4 Test Setup



#### 3.6.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix F

### 3.7 Emissions in Restricted Frequency Bands

#### 3.7.1 Emissions in Restricted Frequency Bands Limit

| Restricted Band Emissions Limit |                       |                         |                      |
|---------------------------------|-----------------------|-------------------------|----------------------|
| Frequency Range (MHz)           | Field Strength (uV/m) | Field Strength (dBuV/m) | Measure Distance (m) |
| 0.009~0.490                     | 2400/F(kHz)           | 48.5 - 13.8             | 300                  |
| 0.490~1.705                     | 24000/F(kHz)          | 33.8 - 23               | 30                   |
| 1.705~30.0                      | 30                    | 29                      | 30                   |
| 30~88                           | 100                   | 40                      | 3                    |
| 88~216                          | 150                   | 43.5                    | 3                    |
| 216~960                         | 200                   | 46                      | 3                    |
| Above 960                       | 500                   | 54                      | 3                    |

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


#### 3.7.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.7.3 Test Procedures

| Test Method |                                                                                                                                                                                                         |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|             | ▪ The average emission levels shall be measured in [hopping duty factor].                                                                                                                               |
|             | ▪ Refer as ANSI C63.10; clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.                             |
|             | ▪ For the transmitter unwanted emissions shall be measured using following options below:                                                                                                               |
|             | ▪ Refer as ANSI C63.10, clause 4.1.4.2.1 QP value.                                                                                                                                                      |
|             | ▪ Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak.                                                                                                                                    |
|             | ▪ Refer as ANSI C63.10, clause 4.1.4.2.4 average value of hopping pulsed emissions.                                                                                                                     |
|             | ▪ KDB 414788 Open-Field Test Sites and Chamber Correlation Justification.                                                                                                                               |
|             | ▪ Based on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in regulations; however, an attempt should be made to avoid making measurements in the near field. |
|             | ▪ Open-field site and chamber correlation testing had been performed and chamber measured test result is the worst case test result.                                                                    |

### 3.7.4 Test Setup





### 3.7.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

### 3.7.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix G

## 4 Test Equipment and Calibration Data

### Instrument for AC Conduction

| Instrument                           | Manufacturer | Model No.   | Serial No. | Spec.               | Calibration Date | Calibration Due Date |
|--------------------------------------|--------------|-------------|------------|---------------------|------------------|----------------------|
| EMC Receiver                         | R&S          | ESR3        | 102052     | 9kHz~3.6GHz         | 09/Apr/2019      | 08/Apr/2020          |
| LISN                                 | R&S          | ENV216      | 101295     | 9kHz~30MHz          | 08/Nov/2018      | 07/Nov/2019          |
| LISN                                 | R&S          | ENV216      | 101295     | 9kHz ~ 30MHz        | 04/Nov/2019      | 05/Nov/2020          |
| RF Cable-CON                         | MTJ          | RG142       | CB002-CO   | 9kHz~200MHz         | 12/Sep/2019      | 11/Sep/2020          |
| AC POWER                             | APC          | AFC-11005G  | F310050055 | 47Hz~63Hz<br>5~300V | NCR              | NCR                  |
| Impuls<br>Begrenzer Pulse<br>Limiter | SCHWARZBECK  | VTSD 9561-F | 9561-F041  | 9kHz~30MHz          | 24/Sep/2019      | 23/Sep/2020          |

NCR : Non-Calibration Require

### Instrument for Radiated Test

| Instrument                             | Manufacturer   | Model No.                | Serial No.          | Spec.              | Calibration Date | Calibration Due Date |
|----------------------------------------|----------------|--------------------------|---------------------|--------------------|------------------|----------------------|
| 3m Semi<br>Anechoic<br>Chamber         | SIDT FRANKONIA | SAC-3M                   | 03CH03-HY           | 30MHz ~ 1GHz<br>3m | 30/Aug/2019      | 29/Aug/2020          |
| 3m Semi<br>Anechoic<br>Chamber         | SIDT FRANKONIA | SAC-3M                   | 03CH03-HY           | 1GHz ~ 18GHz<br>3m | 30/Aug/2019      | 29/Aug/2020          |
| Amplifier                              | HP             | 8447D                    | 2944A08033          | 10kHz ~ 1.3GHz     | 22/Apr/2019      | 21/Apr/2020          |
| EMI Test<br>Receiver                   | R&S            | ESR3                     | 102052              | 9kHz ~ 3.6GHz      | 09/Apr/2019      | 08/Apr/2020          |
| Bilog Antenna &<br>5db Attenuator      | SCHAFFNER/MTJ  | CBL6112D /<br>MTJ6102-05 | 2678 / 001          | 30MHz ~ 2GHz       | 06/Jul/2019      | 05/Jul/2020          |
| Microwave<br>System<br>Preamplifier    | KEYSIGHT       | 83017A                   | MY53270196          | 1GHz ~ 26.5GHz     | 09/Sep/2019      | 08/Sep/2020          |
| Signal Analyzer                        | R&S            | FSV40                    | 101500              | 10Hz ~ 40GHz       | 15/Aug/2019      | 14/Aug/2020          |
| RF Cable-R03m                          | Jye Bao        | RG142                    | CB021               | 9kHz ~ 1GHz        | 22/Mar/2019      | 21/Mar/2020          |
| RF CABLE 6m                            | HUBER+SUHNER   | SUOFLEX 104              | SN 805801/4         | 1GHz ~ 40GHz       | 21/Mar/2019      | 20/Mar/2020          |
| RF CABLE                               | HUBER+SUHNER   | SUOFLEX 104              | 802378/4            | 1 GHz ~ 18 GHz     | 04/Jul/2019      | 03/Jul/2020          |
| Broadband Horn<br>Antenna              | SCHWARZBECK    | BBHA 9170                | BBHA9170<br>339     | 18GHz ~ 40GHz      | 19/Apr/2019      | 18/Apr/2020          |
| Double Ridged<br>Guide Horn<br>Antenna | SCHWARZBECK    | BBHA 9120 D              | BBHA 9120 D<br>1531 | 1GHz ~ 18GHz       | 09/Mar/2019      | 08/Mar/2020          |
| Preamplifier                           | MITEQ          | TTA1840-35-HG            | 1864481             | 18GHz ~ 40GHz      | 05/Aug/2019      | 04/Aug/2020          |


**Instrument for Conducted Test**

| Instrument                     | Manufacturer | Model No. | Serial No.    | Spec.        | Calibration Date | Calibration Due Date |
|--------------------------------|--------------|-----------|---------------|--------------|------------------|----------------------|
| Signal Analyzer                | R&S          | FSV 40    | 101029        | 10KHz~40GHz  | 01/Oct/2019      | 30/Sep/2020          |
| SMB100A<br>Signal<br>Generator | R&S          | SMB100A03 | 181147        | 100kHz~40GHz | 12/Nov/2018      | 10/Nov/2020          |
| Pulse Power<br>Sensor          | Anritsu      | MA2411B   | 1027452       | 300MHz~40GHz | 14/Mar/2019      | 13/Mar/2020          |
| Power Meter                    | Anritsu      | ML2495A   | 1124009       | 300MHz~40GHz | 14/Mar/2019      | 13/Mar/2020          |
| CABLE 0.2m                     | HUBER        | MY37960/4 | RF Cable - 17 | 30MHz~18G    | 10/Jan/2019      | 09/Jan/2020          |
| CABLE 0.2m                     | HUBER        | MY37960/4 | RF Cable - 17 | 30MHz~18G    | 10/Jan/2019      | 09/Jan/2020          |
| CABLE 0.5m                     | HUBER        | MY37963/4 | RF Cable - 22 | 30MHz~18G    | 10/Jan/2019      | 09/Jan/2020          |

### AC Power-line Conducted Emissions Result

|                    |          |             |         |
|--------------------|----------|-------------|---------|
| Operating Mode     | 1        | Power Phase | Neutral |
| Operating Function | USB Mode |             |         |

04/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Factor<br>(dB) | Condition | Comment | Raw<br>(dBuV) | LISN<br>(dB) | CL<br>(dB) | AT<br>(dB) |  |  |  |
|------|--------------|-----------------|-----------------|----------------|----------------|-----------|---------|---------------|--------------|------------|------------|--|--|--|
| QP   | 162.429k     | 32.14           | 65.33           | -33.19         | 19.48          | Neutral   | -       | 12.66         | 9.60         | 0.01       | 9.87       |  |  |  |
| AV   | 162.429k     | 26.38           | 55.33           | -28.95         | 19.48          | Neutral   | -       | 6.90          | 9.60         | 0.01       | 9.87       |  |  |  |
| QP   | 443.732k     | 27.64           | 56.99           | -29.35         | 19.48          | Neutral   | -       | 8.16          | 9.59         | 0.01       | 9.88       |  |  |  |
| AV   | 443.732k     | 26.78           | 46.99           | -20.21         | 19.48          | Neutral   | -       | 7.30          | 9.59         | 0.01       | 9.88       |  |  |  |
| QP   | 881.649k     | 25.89           | 56.00           | -30.11         | 19.49          | Neutral   | -       | 6.40          | 9.59         | 0.02       | 9.88       |  |  |  |
| AV   | 881.649k     | 20.78           | 46.00           | -25.22         | 19.49          | Neutral   | -       | 1.29          | 9.59         | 0.02       | 9.88       |  |  |  |
| QP   | 1.717M       | 33.03           | 56.00           | -22.97         | 19.53          | Neutral   | -       | 13.50         | 9.61         | 0.03       | 9.89       |  |  |  |
| AV   | 1.717M       | 31.06           | 46.00           | -14.94         | 19.53          | Neutral   | "Worst" | 11.53         | 9.61         | 0.03       | 9.89       |  |  |  |
| QP   | 5.898M       | 21.37           | 60.00           | -38.63         | 19.58          | Neutral   | -       | 1.79          | 9.64         | 0.05       | 9.89       |  |  |  |
| AV   | 5.898M       | 18.56           | 50.00           | -31.44         | 19.58          | Neutral   | -       | -1.02         | 9.64         | 0.05       | 9.89       |  |  |  |
| QP   | 10.093M      | 21.75           | 60.00           | -38.25         | 19.63          | Neutral   | -       | 2.12          | 9.67         | 0.07       | 9.89       |  |  |  |
| AV   | 10.093M      | 18.64           | 50.00           | -31.36         | 19.63          | Neutral   | -       | -0.99         | 9.67         | 0.07       | 9.89       |  |  |  |

### AC Power-line Conducted Emissions Result

|                    |          |             |      |
|--------------------|----------|-------------|------|
| Operating Mode     | 1        | Power Phase | Line |
| Operating Function | USB Mode |             |      |

04/11/2019



| Type | Freq (Hz) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Factor (dB) | Condition | Comment | Raw (dBuV) | LISN (dB) | CL (dB) | AT (dB) |  |  |  |
|------|-----------|--------------|--------------|-------------|-------------|-----------|---------|------------|-----------|---------|---------|--|--|--|
| QP   | 251.653k  | 30.05        | 61.70        | -31.65      | 19.48       | Line      | -       | 10.57      | 9.60      | 0.01    | 9.87    |  |  |  |
| AV   | 251.653k  | 25.60        | 51.70        | -26.10      | 19.48       | Line      | -       | 6.12       | 9.60      | 0.01    | 9.87    |  |  |  |
| QP   | 426.418k  | 30.32        | 57.32        | -27.00      | 19.48       | Line      | -       | 10.84      | 9.59      | 0.01    | 9.88    |  |  |  |
| AV   | 426.418k  | 28.99        | 47.32        | -18.33      | 19.48       | Line      | -       | 9.51       | 9.59      | 0.01    | 9.88    |  |  |  |
| QP   | 855.72k   | 24.80        | 56.00        | -31.20      | 19.50       | Line      | -       | 5.30       | 9.60      | 0.02    | 9.88    |  |  |  |
| AV   | 855.72k   | 23.00        | 46.00        | -23.00      | 19.50       | Line      | -       | 3.50       | 9.60      | 0.02    | 9.88    |  |  |  |
| QP   | 1.7M      | 31.94        | 56.00        | -24.06      | 19.54       | Line      | -       | 12.40      | 9.62      | 0.03    | 9.89    |  |  |  |
| AV   | 1.7M      | 30.15        | 46.00        | -15.85      | 19.54       | Line      | "Worst" | 10.61      | 9.62      | 0.03    | 9.89    |  |  |  |
| QP   | 5.611M    | 23.92        | 60.00        | -36.08      | 19.58       | Line      | -       | 4.34       | 9.64      | 0.05    | 9.89    |  |  |  |
| AV   | 5.611M    | 20.03        | 50.00        | -29.97      | 19.58       | Line      | -       | 0.45       | 9.64      | 0.05    | 9.89    |  |  |  |
| QP   | 7.792M    | 25.58        | 60.00        | -34.42      | 19.61       | Line      | -       | 5.97       | 9.66      | 0.06    | 9.89    |  |  |  |
| AV   | 7.792M    | 22.06        | 50.00        | -27.94      | 19.61       | Line      | -       | 2.45       | 9.66      | 0.06    | 9.89    |  |  |  |

**Summary**

| Mode          | Max-N dB<br>(Hz) | Max-OBW<br>(Hz) | ITU-Code | Min-N dB<br>(Hz) | Min-OBW<br>(Hz) |
|---------------|------------------|-----------------|----------|------------------|-----------------|
| 2.4-2.4835GHz | -                | -               | -        | -                | -               |
| BT-BR(1Mbps)  | 921.25k          | 879.56k         | 880KF1D  | 915k             | 879.56k         |
| BT-EDR(2Mbps) | 1.284M           | 1.183M          | 1M18G1D  | 1.26M            | 1.182M          |
| BT-EDR(3Mbps) | 1.265M           | 1.188M          | 1M19G1D  | 1.264M           | 1.186M          |

**Max-N dB** = Maximum 20dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

**Min-N dB** = Minimum 20dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


**Result**

| Mode             | Result | Limit<br>(Hz) | Port 1-N dB<br>(Hz) | Port 1-OBW<br>(Hz) |
|------------------|--------|---------------|---------------------|--------------------|
| BT-BR(1Mbps)     | -      | -             | -                   | -                  |
| 2402MHz_TnomVnom | Pass   | Inf           | 915k                | 879.56k            |
| 2441MHz_TnomVnom | Pass   | Inf           | 918.75k             | 879.56k            |
| 2480MHz_TnomVnom | Pass   | Inf           | 921.25k             | 879.56k            |
| BT-EDR(2Mbps)    | -      | -             | -                   | -                  |
| 2402MHz_TnomVnom | Pass   | Inf           | 1.26M               | 1.182M             |
| 2441MHz_TnomVnom | Pass   | Inf           | 1.28M               | 1.183M             |
| 2480MHz_TnomVnom | Pass   | Inf           | 1.284M              | 1.182M             |
| BT-EDR(3Mbps)    | -      | -             | -                   | -                  |
| 2402MHz_TnomVnom | Pass   | Inf           | 1.264M              | 1.186M             |
| 2441MHz_TnomVnom | Pass   | Inf           | 1.264M              | 1.188M             |
| 2480MHz_TnomVnom | Pass   | Inf           | 1.265M              | 1.188M             |


**Port X-N dB** = Port X 20dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

**BT-BR(1Mbps)**
**2402MHz**
**EBW**

04/11/2019



**BT-BR(1Mbps)**
**2441MHz**
**EBW**

04/11/2019




**BT-BR(1Mbps)**
**EBW**
**2480MHz**

04/11/2019



**BT-EDR(2Mbps)**
**EBW**
**2402MHz**

04/11/2019




**BT-EDR(2Mbps)**
**EBW**
**2441MHz**

04/11/2019



**BT-EDR(2Mbps)**
**EBW**
**2480MHz**

04/11/2019




**BT-EDR(3Mbps)**
**EBW**
**2402MHz**

04/11/2019


**BT-EDR(3Mbps)**
**EBW**
**2441MHz**

04/11/2019




## BT-EDR(3Mbps)

2480MHz

EBW

04/11/2019





**Summary**

| Mode          | Max-Space<br>(Hz) | Min-Space<br>(Hz) |
|---------------|-------------------|-------------------|
| 2.4-2.4835GHz | -                 | -                 |
| BT-BR(1Mbps)  | 1.002M            | 999k              |
| BT-EDR(2Mbps) | 1.002M            | 1.002M            |
| BT-EDR(3Mbps) | 1.002M            | 999k              |

## Result

| Mode             | Result | Fl<br>(Hz) | Fh<br>(Hz) | Ch.Space<br>(Hz) | Limit<br>(Hz) |
|------------------|--------|------------|------------|------------------|---------------|
| BT-BR(1Mbps)     | -      | -          | -          | -                | -             |
| 2402MHz_TnomVnom | Pass   | 2.402155G  | 2.403157G  | 1.002M           | 609.39k       |
| 2441MHz_TnomVnom | Pass   | 2.441157G  | 2.442156G  | 999k             | 611.8875k     |
| 2480MHz_TnomVnom | Pass   | 2.479155G  | 2.480156G  | 1.0005M          | 613.5525k     |
| BT-EDR(2Mbps)    | -      | -          | -          | -                | -             |
| 2402MHz_TnomVnom | Pass   | 2.402157G  | 2.403159G  | 1.002M           | 839.16k       |
| 2441MHz_TnomVnom | Pass   | 2.441157G  | 2.442159G  | 1.002M           | 852.48k       |
| 2480MHz_TnomVnom | Pass   | 2.479155G  | 2.480157G  | 1.002M           | 855.144k      |
| BT-EDR(3Mbps)    | -      | -          | -          | -                | -             |
| 2402MHz_TnomVnom | Pass   | 2.402157G  | 2.403156G  | 999k             | 841.824k      |
| 2441MHz_TnomVnom | Pass   | 2.441155G  | 2.442157G  | 1.002M           | 841.824k      |
| 2480MHz_TnomVnom | Pass   | 2.479155G  | 2.480157G  | 1.002M           | 842.49k       |

## BT-BR(1Mbps)

2.402G/2.403GHz

## Channel Separation



## BT-BR(1Mbps)

2.441G/2.442GHz

## Channel Separation



## BT-BR(1Mbps)

2.48G/2.479GHz

## Channel Separation




## BT-EDR(2Mbps)

2.402G/2.403GHz

## Channel Separation

04/11/2019




## BT-EDR(2Mbps)

2.441G/2.442GHz

## Channel Separation

04/11/2019




## BT-EDR(2Mbps)

2.48G/2.479GHz

## Channel Separation

04/11/2019




## BT-EDR(3Mbps)

2.402G/2.403GHz

## Channel Separation

04/11/2019




## BT-EDR(3Mbps)

2.441G/2.442GHz

## Channel Separation

04/11/2019




## BT-EDR(3Mbps)

2.48G/2.479GHz

## Channel Separation

04/11/2019





**Summary**

| Mode          | Power<br>(dBm) | Power<br>(W) |
|---------------|----------------|--------------|
| 2.4-2.4835GHz | -              | -            |
| BT-BR(1Mbps)  | 7.86           | 0.00611      |
| BT-EDR(2Mbps) | 10.52          | 0.01127      |
| BT-EDR(3Mbps) | 10.88          | 0.01225      |

**Result**

| Mode             | Result | Gain<br>(dBi) | Power<br>(dBm) | Power Limit<br>(dBm) |
|------------------|--------|---------------|----------------|----------------------|
| BT-BR(1Mbps)     | -      | -             | -              | -                    |
| 2402MHz_TnomVnom | Pass   | 3.74          | 6.80           | 21.00                |
| 2441MHz_TnomVnom | Pass   | 3.74          | 7.49           | 21.00                |
| 2480MHz_TnomVnom | Pass   | 3.74          | 7.86           | 21.00                |
| BT-EDR(2Mbps)    | -      | -             | -              | -                    |
| 2402MHz_TnomVnom | Pass   | 3.74          | 9.37           | 21.00                |
| 2441MHz_TnomVnom | Pass   | 3.74          | 10.03          | 21.00                |
| 2480MHz_TnomVnom | Pass   | 3.74          | 10.52          | 21.00                |
| BT-EDR(3Mbps)    | -      | -             | -              | -                    |
| 2402MHz_TnomVnom | Pass   | 3.74          | 9.74           | 21.00                |
| 2441MHz_TnomVnom | Pass   | 3.74          | 10.48          | 21.00                |
| 2480MHz_TnomVnom | Pass   | 3.74          | 10.88          | 21.00                |

**DG** = Directional Gain; **Port X** = Port X output power



**Summary**

| Mode          | Power<br>(dBm) | Power<br>(W) |
|---------------|----------------|--------------|
| 2.4-2.4835GHz | -              | -            |
| BT-BR(1Mbps)  | 7.43           | 0.00553      |
| BT-EDR(2Mbps) | 7.52           | 0.00565      |
| BT-EDR(3Mbps) | 7.47           | 0.00558      |

### Result

| Mode             | Result | Gain<br>(dBi) | Power<br>(dBm) | Power Limit<br>(dBm) |
|------------------|--------|---------------|----------------|----------------------|
| BT-BR(1Mbps)     | -      | -             | -              | -                    |
| 2402MHz_TnomVnom | Pass   | 3.74          | 6.26           | 21.00                |
| 2441MHz_TnomVnom | Pass   | 3.74          | 6.97           | 21.00                |
| 2480MHz_TnomVnom | Pass   | 3.74          | 7.43           | 21.00                |
| BT-EDR(2Mbps)    | -      | -             | -              | -                    |
| 2402MHz_TnomVnom | Pass   | 3.74          | 6.41           | 21.00                |
| 2441MHz_TnomVnom | Pass   | 3.74          | 7.12           | 21.00                |
| 2480MHz_TnomVnom | Pass   | 3.74          | 7.52           | 21.00                |
| BT-EDR(3Mbps)    | -      | -             | -              | -                    |
| 2402MHz_TnomVnom | Pass   | 3.74          | 6.40           | 21.00                |
| 2441MHz_TnomVnom | Pass   | 3.74          | 7.05           | 21.00                |
| 2480MHz_TnomVnom | Pass   | 3.74          | 7.47           | 21.00                |

**DG** = Directional Gain; **Port X** = Port X output power



**Summary**

| Mode          | Max-Hop No |
|---------------|------------|
| 2.4-2.4835GHz | -          |
| BT-BR(1Mbps)  | 79         |
| BT-EDR(2Mbps) | 79         |
| BT-EDR(3Mbps) | 79         |

**Result**


| Mode             | Result | Hopping No | Limit |
|------------------|--------|------------|-------|
| BT-BR(1Mbps)     | -      | -          | -     |
| 2441MHz_TnomVnom | Pass   | 79         | 15    |
| BT-EDR(2Mbps)    | -      | -          | -     |
| 2441MHz_TnomVnom | Pass   | 79         | 15    |
| BT-EDR(3Mbps)    | -      | -          | -     |
| 2441MHz_TnomVnom | Pass   | 79         | 15    |

**BT-BR(1Mbps)**

**2441MHz**

**Hopping Ch**

04/11/2019



Port 1 

Hopping No  
79

Span  
83.5MHz

RBW  
100kHz

VBW  
300kHz

Sweep  
200ms

Detector  
Peak


| Hopping No | Limit |
|------------|-------|
| 79         | 15    |

**BT-BR(1Mbps)**

**2441MHz**

**Hopping Ch Bandedge (Non-restricted Band)**

04/11/2019



Port 1 

Span  
120MHz

RBW  
100kHz

VBW  
300kHz

Sweep  
200ms

Detector  
Peak


| Limit(dBm) | Ref(Hz)  | Ref(dBm) | BE-l(Hz)  | BE-l(dBm) | BE-h(Hz) | BE-h(dBm) |
|------------|----------|----------|-----------|-----------|----------|-----------|
| -13.23     | 2.47816G | 6.77     | 2.399965G | -50.56    | 2.48785G | -51.58    |

### BT-BR(1Mbps)

2441MHz

### Hopping Ch Bandedge (Restricted Band)

04/11/2019




### BT-EDR(2Mbps)

2441MHz

### Hopping Ch

04/11/2019




## BT-EDR(2Mbps)

2441MHz

## Hopping Ch Bandedge (Non-restricted Band)

04/11/2019




## BT-EDR(2Mbps)

2441MHz

## Hopping Ch Bandedge (Restricted Band)


04/11/2019



### BT-EDR(3Mbps) 2441MHz

### Hopping Ch


04/11/2019



### BT-EDR(3Mbps) 2441MHz


### Hopping Ch Bandedge (Non-restricted Band)

04/11/2019



**BT-EDR(3Mbps)****2441MHz****Hopping Ch Bandedge (Restricted Band)**

04/11/2019





**Summary**

| Mode          | Max-Dwell<br>(s) |
|---------------|------------------|
| 2.4-2.4835GHz | -                |
| BT-BR(1Mbps)  | 306.7948m        |
| BT-EDR(2Mbps) | 86.4526m         |
| BT-EDR(3Mbps) | 54.366m          |

**Result**

| Mode             | Result | Period<br>(s) | Dwell<br>(s) | Limit<br>(s) | Tx On<br>(s) |
|------------------|--------|---------------|--------------|--------------|--------------|
| BT-BR(1Mbps)     | -      | -             | -            | -            | -            |
| 2441MHz_TnomVnom | Pass   | 31.6          | 306.7948m    | 400m         | 2.878m       |
| BT-EDR(2Mbps)    | -      | -             | -            | -            | -            |
| 2441MHz_TnomVnom | Pass   | 31.6          | 86.4526m     | 400m         | 811u         |
| BT-EDR(3Mbps)    | -      | -             | -            | -            | -            |
| 2441MHz_TnomVnom | Pass   | 31.6          | 54.366m      | 400m         | 510u         |

## BT-BR(1Mbps)

2441MHz

04/11/2019

Port1 


Ch Freq  
2.441GHz

RBW  
300kHz

VBW  
1MHz

Sweep Time  
8ms

TX Time  
2.878ms



non AFH Mode

| Period(s) | Dwell(s)  | Limit(s) | Tx On(s) |
|-----------|-----------|----------|----------|
| 31.6      | 306.7948m | 400m     | 2.878m   |

AFH Mode

| Period(s) | Dwell(s)  | Limit(s) | Tx On(s) |
|-----------|-----------|----------|----------|
| 8         | 153.3974m | 400m     | 2.878m   |

## BT-EDR(2Mbps)

2441MHz

04/11/2019

Port1 


Ch Freq  
2.441GHz

RBW  
300kHz

VBW  
1MHz

Sweep Time  
8ms

TX Time  
811us



non AFH Mode

| Period(s) | Dwell(s) | Limit(s) | Tx On(s) |
|-----------|----------|----------|----------|
| 31.6      | 86.4526m | 400m     | 811u     |

AFH Mode


| Period(s) | Dwell(s) | Limit(s) | Tx On(s) |
|-----------|----------|----------|----------|
| 8         | 43.2263m | 400m     | 811u     |

## BT-EDR(3Mbps)

2441MHz

## Dwell

04/11/2019



**Summary**

| Mode          | Result | Ref<br>(Hz) | Ref<br>(dBm) | Limit<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Port |
|---------------|--------|-------------|--------------|----------------|--------------|----------------|--------------|----------------|--------------|----------------|--------------|----------------|------|
| 2.4-2.4835GHz | -      | -           | -            | -              | -            | -              | -            | -              | -            | -              | -            | -              | -    |
| BT-BR(1Mbps)  | Pass   | 2.40196G    | 5.21         | -14.79         | 711.69M      | -55.20         | 2.4G         | -48.96         | 2.48482G     | -53.01         | 17.49141G    | -40.57         | 1    |
| BT-EDR(2Mbps) | Pass   | 2.402G      | 4.21         | -15.79         | 2.09608G     | -54.65         | 2.39993G     | -50.53         | 2.48463G     | -52.87         | 24.88461G    | -40.14         | 1    |
| BT-EDR(3Mbps) | Pass   | 2.40213G    | 5.99         | -14.01         | 2.12479G     | -54.39         | 2.39994G     | -50.92         | 2.48421G     | -52.90         | 23.33393G    | -40.39         | 1    |

**Result**


| Mode             | Result | Ref<br>(Hz) | Ref<br>(dBm) | Limit<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Freq<br>(Hz) | Level<br>(dBm) | Port |
|------------------|--------|-------------|--------------|----------------|--------------|----------------|--------------|----------------|--------------|----------------|--------------|----------------|------|
| BT-BR(1Mbps)     | -      | -           | -            | -              | -            | -              | -            | -              | -            | -              | -            | -              | -    |
| 2402MHz_TnomVnom | Pass   | 2.40196G    | 5.21         | -14.79         | 711.69M      | -55.20         | 2.4G         | -48.96         | 2.48482G     | -53.01         | 17.49141G    | -40.57         | 1    |
| 2441MHz_TnomVnom | Pass   | 2.441G      | 5.92         | -14.08         | 2.14374G     | -54.53         | 2.39951G     | -52.85         | 2.48424G     | -52.98         | 23.22698G    | -40.26         | 1    |
| 2480MHz_TnomVnom | Pass   | 2.48008G    | 6.25         | -13.75         | 953.82M      | -55.47         | 2.39983G     | -53.82         | 2.48362G     | -51.47         | 23.27201G    | -40.90         | 1    |
| BT-EDR(2Mbps)    | -      | -           | -            | -              | -            | -              | -            | -              | -            | -              | -            | -              | -    |
| 2402MHz_TnomVnom | Pass   | 2.402G      | 4.21         | -15.79         | 2.09608G     | -54.65         | 2.39993G     | -50.53         | 2.48463G     | -52.87         | 24.88461G    | -40.14         | 1    |
| 2441MHz_TnomVnom | Pass   | 2.44117G    | 6.80         | -13.20         | 2.14226G     | -54.68         | 2.39847G     | -53.82         | 2.48458G     | -52.96         | 23.32267G    | -40.41         | 1    |
| 2480MHz_TnomVnom | Pass   | 2.48016G    | 7.00         | -13.00         | 2.00669G     | -55.03         | 2.39925G     | -53.64         | 2.48529G     | -52.03         | 23.31423G    | -40.19         | 1    |
| BT-EDR(3Mbps)    | -      | -           | -            | -              | -            | -              | -            | -              | -            | -              | -            | -              | -    |
| 2402MHz_TnomVnom | Pass   | 2.40213G    | 5.99         | -14.01         | 2.12479G     | -54.39         | 2.39994G     | -50.92         | 2.48421G     | -52.90         | 23.33393G    | -40.39         | 1    |
| 2441MHz_TnomVnom | Pass   | 2.44117G    | 6.64         | -13.36         | 2.05908G     | -54.40         | 2.39841G     | -52.87         | 2.48471G     | -52.97         | 23.2692G     | -39.76         | 1    |
| 2480MHz_TnomVnom | Pass   | 2.48008G    | 6.49         | -13.51         | 2.14226G     | -54.90         | 2.39804G     | -53.19         | 2.48466G     | -51.18         | 23.41273G    | -40.54         | 1    |

BT-BR(1Mbps)


CSE NdB

2402MHz

04/11/2019



Port1



RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak


| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.40196G | 5.21     | -14.79     | 711.69M  | -55.20     | 2.4G     | -48.96     | 2.48482G | -53.01     | 17.49141G | -40.57     | 1    |

BT-BR(1Mbps)


CSE NdB

2441MHz

04/11/2019



Port1



RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

| Ref(Hz) | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|---------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.441G  | 5.92     | -14.08     | 2.14374G | -54.53     | 2.39951G | -52.85     | 2.48424G | -52.98     | 23.22698G | -40.26     | 1    |



## BT-BR(1Mbps)

2480MHz

CSE NdB

04/11/2019

Port1



RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.48008G | 6.25     | -13.75     | 953.82M  | -55.47     | 2.39983G | -53.82     | 2.48362G | -51.47     | 23.27201G | -40.90     | 1    |



## BT-EDR(2Mbps)

2402MHz

CSE NdB

04/11/2019

Port1



RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak


| Ref(Hz) | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|---------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.402G  | 4.21     | -15.79     | 2.09608G | -54.65     | 2.39993G | -50.53     | 2.48463G | -52.87     | 24.88461G | -40.14     | 1    |

## BT-EDR(2Mbps)


CSE NdB

2441MHz

04/11/2019



Port1

RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak


| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.44117G | 6.80     | -13.20     | 2.14226G | -54.68     | 2.39847G | -53.82     | 2.48458G | -52.96     | 23.32267G | -40.41     | 1    |

## BT-EDR(2Mbps)


CSE NdB

2480MHz

04/11/2019



Port1

RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.48016G | 7.00     | -13.00     | 2.00669G | -55.03     | 2.39925G | -53.64     | 2.48529G | -52.03     | 23.31423G | -40.19     | 1    |



## BT-EDR(3Mbps)

2402MHz

CSE NdB

04/11/2019

Port1

RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.40213G | 5.99     | -14.01     | 2.12479G | -54.39     | 2.39994G | -50.92     | 2.48421G | -52.90     | 23.33393G | -40.39     | 1    |



## BT-EDR(3Mbps)

2441MHz

CSE NdB

04/11/2019

Port1

RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|----------|------------|------|
| 2.44117G | 6.64     | -13.36     | 2.05908G | -54.40     | 2.39841G | -52.87     | 2.48471G | -52.97     | 23.2692G | -39.76     | 1    |



BT-EDR(3Mbps)

2480MHz

CSE NdB

04/11/2019

Port1



RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

| Ref(Hz)  | Ref(dBm) | Limit(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz) | Level(dBm) | Freq(Hz)  | Level(dBm) | Port |
|----------|----------|------------|----------|------------|----------|------------|----------|------------|-----------|------------|------|
| 2.48008G | 6.49     | -13.51     | 2.14226G | -54.90     | 2.39804G | -53.19     | 2.48466G | -51.18     | 23.41273G | -40.54     | 1    |



**Summary**

| Mode          | Result | Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comments |
|---------------|--------|------|--------------|-------------------|-------------------|----------------|-------------|------------|----------------|---------------|----------|
| 2.4-2.4835GHz | -      | -    | -            | -                 | -                 | -              | -           | -          | -              | -             | -        |
| BT-BR(1Mbps)  | Pass   | PK   | 103.72M      | 41.64             | 43.50             | -1.86          | 3           | Horizontal | 0              | 1.00          | -        |


**Result**

| Mode         | Result | Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comments |
|--------------|--------|------|--------------|-------------------|-------------------|----------------|-------------|------------|----------------|---------------|----------|
| BT-BR(1Mbps) | -      | -    | -            | -                 | -                 | -              | -           | -          | -              | -             | -        |
| 2441MHz_USB  | Pass   | PK   | 95.96M       | 36.05             | 43.50             | -7.45          | 3           | Vertical   | 360            | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 103.72M      | 33.69             | 43.50             | -9.81          | 3           | Vertical   | 360            | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 229.82M      | 26.59             | 46.00             | -19.41         | 3           | Vertical   | 360            | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 480.08M      | 32.34             | 46.00             | -13.66         | 3           | Vertical   | 360            | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 724.52M      | 32.20             | 46.00             | -13.80         | 3           | Vertical   | 360            | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 837.04M      | 31.55             | 46.00             | -14.45         | 3           | Vertical   | 360            | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 103.72M      | 41.64             | 43.50             | -1.86          | 3           | Horizontal | 0              | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 264.74M      | 33.68             | 46.00             | -12.32         | 3           | Horizontal | 0              | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 293.84M      | 34.79             | 46.00             | -11.21         | 3           | Horizontal | 0              | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 315.18M      | 33.07             | 46.00             | -12.93         | 3           | Horizontal | 0              | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 344.28M      | 32.89             | 46.00             | -13.11         | 3           | Horizontal | 0              | 1.00          | -        |
| 2441MHz_USB  | Pass   | PK   | 482.02M      | 34.70             | 46.00             | -11.30         | 3           | Horizontal | 0              | 1.00          | -        |

# BT-BR(1Mbps)

## 2441MHz\_USB

02/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| PK   | 95.96M       | 36.05             | 43.50             | -7.45          | -10.64         | 3           | Vertical  | 360            | 1.00          | -       | 46.69         | 15.27      | 1.48       | 27.39      |
| PK   | 103.72M      | 33.69             | 43.50             | -9.81          | -9.42          | 3           | Vertical  | 360            | 1.00          | -       | 43.11         | 16.40      | 1.55       | 27.37      |
| PK   | 229.82M      | 26.59             | 46.00             | -19.41         | -9.14          | 3           | Vertical  | 360            | 1.00          | -       | 35.73         | 15.31      | 2.37       | 26.82      |
| PK   | 480.08M      | 32.34             | 46.00             | -13.66         | -1.60          | 3           | Vertical  | 360            | 1.00          | -       | 33.94         | 22.65      | 3.52       | 27.77      |
| PK   | 724.52M      | 32.20             | 46.00             | -13.80         | 0.85           | 3           | Vertical  | 360            | 1.00          | -       | 31.35         | 24.46      | 4.43       | 28.04      |
| PK   | 837.04M      | 31.55             | 46.00             | -14.45         | 2.35           | 3           | Vertical  | 360            | 1.00          | -       | 29.20         | 25.28      | 4.84       | 27.77      |

# BT-BR(1Mbps)

## 2441MHz\_USB

02/11/2019



| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| PK   | 103.72M      | 41.64             | 43.50             | -1.86          | -9.42          | 3           | Horizontal | 0              | 1.00          | -       | 51.06         | 16.40      | 1.55       | 27.37      |
| PK   | 264.74M      | 33.68             | 46.00             | -12.32         | -5.65          | 3           | Horizontal | 0              | 1.00          | -       | 39.33         | 18.52      | 2.56       | 26.73      |
| PK   | 293.84M      | 34.79             | 46.00             | -11.21         | -5.81          | 3           | Horizontal | 0              | 1.00          | -       | 40.60         | 18.18      | 2.72       | 26.71      |
| PK   | 315.18M      | 33.07             | 46.00             | -12.93         | -5.36          | 3           | Horizontal | 0              | 1.00          | -       | 38.43         | 18.61      | 2.82       | 26.79      |
| PK   | 344.28M      | 32.89             | 46.00             | -13.11         | -4.86          | 3           | Horizontal | 0              | 1.00          | -       | 37.75         | 19.14      | 2.95       | 26.95      |
| PK   | 482.02M      | 34.70             | 46.00             | -11.30         | -1.60          | 3           | Horizontal | 0              | 1.00          | -       | 36.30         | 22.65      | 3.53       | 27.78      |



**Summary**

| Mode          | Result | Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comments |
|---------------|--------|------|--------------|-------------------|-------------------|----------------|-------------|------------|----------------|---------------|----------|
| 2.4-2.4835GHz | -      | -    | -            | -                 | -                 | -              | -           | -          | -              | -             | -        |
| BT-BR(1Mbps)  | Pass   | PK   | 2.3896G      | 61.27             | 74.00             | -12.73         | 3           | Horizontal | 157            | 1.71          | -        |


**Result**

| Mode         | Result | Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comments |
|--------------|--------|------|--------------|-------------------|-------------------|----------------|-------------|------------|----------------|---------------|----------|
| BT-BR(1Mbps) | -      | -    | -            | -                 | -                 | -              | -           | -          | -              | -             | -        |
| 2402MHz      | Pass   | AV   | 2.3574G      | 36.87             | 54.00             | -17.13         | 3           | Vertical   | 151            | 1.59          | -        |
| 2402MHz      | Pass   | AV   | 2.402G       | 76.14             | Inf               | -Inf           | 3           | Vertical   | 151            | 1.59          | -        |
| 2402MHz      | Pass   | PK   | 2.3574G      | 59.37             | 74.00             | -14.63         | 3           | Vertical   | 151            | 1.59          | -        |
| 2402MHz      | Pass   | PK   | 2.402G       | 98.64             | Inf               | -Inf           | 3           | Vertical   | 151            | 1.59          | -        |
| 2402MHz      | Pass   | AV   | 2.3896G      | 38.77             | 54.00             | -15.23         | 3           | Horizontal | 157            | 1.71          | -        |
| 2402MHz      | Pass   | AV   | 2.4018G      | 80.39             | Inf               | -Inf           | 3           | Horizontal | 157            | 1.71          | -        |
| 2402MHz      | Pass   | PK   | 2.3896G      | 61.27             | 74.00             | -12.73         | 3           | Horizontal | 157            | 1.71          | -        |
| 2402MHz      | Pass   | PK   | 2.4018G      | 102.89            | Inf               | -Inf           | 3           | Horizontal | 157            | 1.71          | -        |
| 2402MHz      | Pass   | AV   | 4.80408G     | 29.69             | 54.00             | -24.31         | 3           | Vertical   | 163            | 2.63          | -        |
| 2402MHz      | Pass   | PK   | 4.80408G     | 52.19             | 74.00             | -21.81         | 3           | Vertical   | 163            | 2.63          | -        |
| 2402MHz      | Pass   | AV   | 4.80398G     | 33.48             | 54.00             | -20.52         | 3           | Horizontal | 238            | 2.29          | -        |
| 2402MHz      | Pass   | PK   | 4.80386G     | 55.98             | 74.00             | -18.02         | 3           | Horizontal | 238            | 2.29          | -        |
| 2441MHz      | Pass   | AV   | 2.3798G      | 36.50             | 54.00             | -17.50         | 3           | Vertical   | 161            | 1.73          | -        |
| 2441MHz      | Pass   | AV   | 2.441G       | 76.37             | Inf               | -Inf           | 3           | Vertical   | 161            | 1.73          | -        |
| 2441MHz      | Pass   | AV   | 2.4978G      | 36.74             | 54.00             | -17.26         | 3           | Vertical   | 161            | 1.73          | -        |
| 2441MHz      | Pass   | PK   | 2.3798G      | 59.00             | 74.00             | -15.00         | 3           | Vertical   | 161            | 1.73          | -        |
| 2441MHz      | Pass   | PK   | 2.441G       | 98.87             | Inf               | -Inf           | 3           | Vertical   | 161            | 1.73          | -        |
| 2441MHz      | Pass   | PK   | 2.4978G      | 59.24             | 74.00             | -14.76         | 3           | Vertical   | 161            | 1.73          | -        |
| 2441MHz      | Pass   | AV   | 2.3474G      | 36.77             | 54.00             | -17.23         | 3           | Horizontal | 168            | 1.49          | -        |
| 2441MHz      | Pass   | AV   | 2.441G       | 81.17             | Inf               | -Inf           | 3           | Horizontal | 168            | 1.49          | -        |
| 2441MHz      | Pass   | AV   | 2.4842G      | 37.04             | 54.00             | -16.96         | 3           | Horizontal | 168            | 1.49          | -        |
| 2441MHz      | Pass   | PK   | 2.3474G      | 59.27             | 74.00             | -14.73         | 3           | Horizontal | 168            | 1.49          | -        |
| 2441MHz      | Pass   | PK   | 2.441G       | 103.67            | Inf               | -Inf           | 3           | Horizontal | 168            | 1.49          | -        |
| 2441MHz      | Pass   | PK   | 2.4842G      | 59.54             | 74.00             | -14.46         | 3           | Horizontal | 168            | 1.49          | -        |
| 2441MHz      | Pass   | AV   | 4.88193G     | 27.49             | 54.00             | -26.51         | 3           | Vertical   | 225            | 1.39          | -        |
| 2441MHz      | Pass   | PK   | 4.88193G     | 49.99             | 74.00             | -24.01         | 3           | Vertical   | 225            | 1.39          | -        |
| 2441MHz      | Pass   | AV   | 4.88209G     | 30.51             | 54.00             | -23.49         | 3           | Horizontal | 154            | 1.48          | -        |
| 2441MHz      | Pass   | PK   | 4.88209G     | 53.01             | 74.00             | -20.99         | 3           | Horizontal | 154            | 1.48          | -        |
| 2480MHz      | Pass   | AV   | 2.4802G      | 76.41             | Inf               | -Inf           | 3           | Vertical   | 163            | 1.71          | -        |
| 2480MHz      | Pass   | AV   | 2.4872G      | 37.40             | 54.00             | -16.60         | 3           | Vertical   | 163            | 1.71          | -        |
| 2480MHz      | Pass   | PK   | 2.4802G      | 98.91             | Inf               | -Inf           | 3           | Vertical   | 163            | 1.71          | -        |
| 2480MHz      | Pass   | PK   | 2.4872G      | 59.90             | 74.00             | -14.10         | 3           | Vertical   | 163            | 1.71          | -        |
| 2480MHz      | Pass   | AV   | 2.4798G      | 80.19             | Inf               | -Inf           | 3           | Horizontal | 177            | 1.52          | -        |
| 2480MHz      | Pass   | AV   | 2.4874G      | 36.82             | 54.00             | -17.18         | 3           | Horizontal | 177            | 1.52          | -        |
| 2480MHz      | Pass   | PK   | 2.4798G      | 102.69            | Inf               | -Inf           | 3           | Horizontal | 177            | 1.52          | -        |
| 2480MHz      | Pass   | PK   | 2.4874G      | 59.32             | 74.00             | -14.68         | 3           | Horizontal | 177            | 1.52          | -        |
| 2480MHz      | Pass   | AV   | 4.96019G     | 28.33             | 54.00             | -25.67         | 3           | Vertical   | 171            | 2.65          | -        |
| 2480MHz      | Pass   | PK   | 4.96019G     | 50.83             | 74.00             | -23.17         | 3           | Vertical   | 171            | 2.65          | -        |
| 2480MHz      | Pass   | AV   | 4.96006G     | 30.90             | 54.00             | -23.10         | 3           | Horizontal | 153            | 1.43          | -        |
| 2480MHz      | Pass   | PK   | 4.96006G     | 53.40             | 74.00             | -20.60         | 3           | Horizontal | 153            | 1.43          | -        |

## BT-BR(1Mbps)

### 2402MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 2.3574G      | 36.87             | 54.00             | -17.13         | 31.64          | 3           | Vertical  | 151            | 1.59          | -       | 5.23          | 27.67      | 3.97       | -          |
| AV   | 2.402G       | 76.14             | Inf               | -Inf           | 31.51          | 3           | Vertical  | 151            | 1.59          | -       | 44.63         | 27.50      | 4.01       | -          |
| PK   | 2.3574G      | 59.37             | 74.00             | -14.63         | 31.64          | 3           | Vertical  | 151            | 1.59          | -       | 27.73         | 27.67      | 3.97       | -          |
| PK   | 2.402G       | 98.64             | Inf               | -Inf           | 31.51          | 3           | Vertical  | 151            | 1.59          | -       | 67.13         | 27.50      | 4.01       | -          |

## BT-BR(1Mbps)

### 2402MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 2.3896G      | 38.77             | 54.00             | -15.23         | 31.54          | 3           | Horizontal | 157            | 1.71          | -       | 7.23          | 27.54      | 4.00       | -          |
| AV   | 2.4018G      | 80.39             | Inf               | -Inf           | 31.51          | 3           | Horizontal | 157            | 1.71          | -       | 48.88         | 27.50      | 4.01       | -          |
| PK   | 2.3896G      | 61.27             | 74.00             | -12.73         | 31.54          | 3           | Horizontal | 157            | 1.71          | -       | 29.73         | 27.54      | 4.00       | -          |
| PK   | 2.4018G      | 102.89            | Inf               | -Inf           | 31.51          | 3           | Horizontal | 157            | 1.71          | -       | 71.38         | 27.50      | 4.01       | -          |

## BT-BR(1Mbps)

### 2402MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 4.80408G     | 29.69             | 54.00             | -24.31         | 7.47           | 3           | Vertical  | 163            | 2.63          | -       | 22.22         | 31.10      | 5.78       | 29.41      |
| PK   | 4.80408G     | 52.19             | 74.00             | -21.81         | 7.47           | 3           | Vertical  | 163            | 2.63          | -       | 44.72         | 31.10      | 5.78       | 29.41      |

# BT-BR(1Mbps)

01/11/2019

## 2402MHz\_TX




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 4.80398G     | 33.48             | 54.00             | -20.52         | 7.47           | 3           | Horizontal | 238            | 2.29          | -       | 26.01         | 31.10      | 5.78       | 29.41      |
| PK   | 4.80386G     | 55.98             | 74.00             | -18.02         | 7.47           | 3           | Horizontal | 238            | 2.29          | -       | 48.51         | 31.10      | 5.78       | 29.41      |

## BT-BR(1Mbps)

### 2441MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 2.3798G      | 36.50             | 54.00             | -17.50         | 31.57          | 3           | Vertical  | 161            | 1.73          | -       | 4.93          | 27.58      | 3.99       | -          |
| AV   | 2.441G       | 76.37             | Inf               | -Inf           | 31.46          | 3           | Vertical  | 161            | 1.73          | -       | 44.91         | 27.42      | 4.04       | -          |
| AV   | 2.4978G      | 36.74             | 54.00             | -17.26         | 31.40          | 3           | Vertical  | 161            | 1.73          | -       | 5.34          | 27.30      | 4.10       | -          |
| PK   | 2.3798G      | 59.00             | 74.00             | -15.00         | 31.57          | 3           | Vertical  | 161            | 1.73          | -       | 27.43         | 27.58      | 3.99       | -          |
| PK   | 2.441G       | 98.87             | Inf               | -Inf           | 31.46          | 3           | Vertical  | 161            | 1.73          | -       | 67.41         | 27.42      | 4.04       | -          |
| PK   | 2.4978G      | 59.24             | 74.00             | -14.76         | 31.40          | 3           | Vertical  | 161            | 1.73          | -       | 27.84         | 27.30      | 4.10       | -          |

## BT-BR(1Mbps)

### 2441MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 2.3474G      | 36.77             | 54.00             | -17.23         | 31.67          | 3           | Horizontal | 168            | 1.49          | -       | 5.10          | 27.71      | 3.96       | -          |
| AV   | 2.441G       | 81.17             | Inf               | -Inf           | 31.46          | 3           | Horizontal | 168            | 1.49          | -       | 49.71         | 27.42      | 4.04       | -          |
| AV   | 2.4842G      | 37.04             | 54.00             | -16.96         | 31.42          | 3           | Horizontal | 168            | 1.49          | -       | 5.62          | 27.33      | 4.09       | -          |
| PK   | 2.3474G      | 59.27             | 74.00             | -14.73         | 31.67          | 3           | Horizontal | 168            | 1.49          | -       | 27.60         | 27.71      | 3.96       | -          |
| PK   | 2.441G       | 103.67            | Inf               | -Inf           | 31.46          | 3           | Horizontal | 168            | 1.49          | -       | 72.21         | 27.42      | 4.04       | -          |
| PK   | 2.4842G      | 59.54             | 74.00             | -14.46         | 31.42          | 3           | Horizontal | 168            | 1.49          | -       | 28.12         | 27.33      | 4.09       | -          |

# BT-BR(1Mbps)

## 2441MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 4.88193G     | 27.49             | 54.00             | -26.51         | 7.64           | 3           | Vertical  | 225            | 1.39          | -       | 19.85         | 31.18      | 5.83       | 29.37      |
| PK   | 4.88193G     | 49.99             | 74.00             | -24.01         | 7.64           | 3           | Vertical  | 225            | 1.39          | -       | 42.35         | 31.18      | 5.83       | 29.37      |

# BT-BR(1Mbps)

## 2441MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 4.88209G     | 30.51             | 54.00             | -23.49         | 7.65           | 3           | Horizontal | 154            | 1.48          | -       | 22.86         | 31.18      | 5.84       | 29.37      |
| PK   | 4.88209G     | 53.01             | 74.00             | -20.99         | 7.65           | 3           | Horizontal | 154            | 1.48          | -       | 45.36         | 31.18      | 5.84       | 29.37      |

# BT-BR(1Mbps)

## 2480MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 2.4802G      | 76.41             | Inf               | -Inf           | 31.42          | 3           | Vertical  | 163            | 1.71          | -       | 44.99         | 27.34      | 4.08       | -          |
| AV   | 2.4872G      | 37.40             | 54.00             | -16.60         | 31.42          | 3           | Vertical  | 163            | 1.71          | -       | 5.98          | 27.33      | 4.09       | -          |
| PK   | 2.4802G      | 98.91             | Inf               | -Inf           | 31.42          | 3           | Vertical  | 163            | 1.71          | -       | 67.49         | 27.34      | 4.08       | -          |
| PK   | 2.4872G      | 59.90             | 74.00             | -14.10         | 31.42          | 3           | Vertical  | 163            | 1.71          | -       | 28.48         | 27.33      | 4.09       | -          |

# BT-BR(1Mbps)

## 2480MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 2.4798G      | 80.19             | Inf               | -Inf           | 31.42          | 3           | Horizontal | 177            | 1.52          | -       | 48.77         | 27.34      | 4.08       | -          |
| AV   | 2.4874G      | 36.82             | 54.00             | -17.18         | 31.42          | 3           | Horizontal | 177            | 1.52          | -       | 5.40          | 27.33      | 4.09       | -          |
| PK   | 2.4798G      | 102.69            | Inf               | -Inf           | 31.42          | 3           | Horizontal | 177            | 1.52          | -       | 71.27         | 27.34      | 4.08       | -          |
| PK   | 2.4874G      | 59.32             | 74.00             | -14.68         | 31.42          | 3           | Horizontal | 177            | 1.52          | -       | 27.90         | 27.33      | 4.09       | -          |

## BT-BR(1Mbps)

### 2480MHz\_TX

01/11/2019




| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|-----------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 4.96019G     | 28.33             | 54.00             | -25.67         | 7.93           | 3           | Vertical  | 171            | 2.65          | -       | 20.40         | 31.38      | 5.89       | 29.34      |
| PK   | 4.96019G     | 50.83             | 74.00             | -23.17         | 7.93           | 3           | Vertical  | 171            | 2.65          | -       | 42.90         | 31.38      | 5.89       | 29.34      |

## BT-BR(1Mbps)

### 2480MHz\_TX

01/11/2019



| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Factor<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | Raw<br>(dBuV) | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|----------------|-------------|------------|----------------|---------------|---------|---------------|------------|------------|------------|
| AV   | 4.96006G     | 30.90             | 54.00             | -23.10         | 7.93           | 3           | Horizontal | 153            | 1.43          | -       | 22.97         | 31.38      | 5.89       | 29.34      |
| PK   | 4.96006G     | 53.40             | 74.00             | -20.60         | 7.93           | 3           | Horizontal | 153            | 1.43          | -       | 45.47         | 31.38      | 5.89       | 29.34      |