RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C
INDUSTRY CANADA RSS-247

Test Standard	**FCC Part 15.247 and IC RSS-247 issue 2**
FCC ID	**PPQ-WCBN3507R**
ISED No.	**4491A-WCBN3507R**
Product name	**802.11a/b/g/n/ac 2Tx2R+BT V4.2LE USB Combo Module**
Brand Name	**LITE-ON**
Model No.	**WCBN3507R**
Test Result	**Pass**

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.
The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.(Wugu Laboratory)

Testing Laboratory
1309

Approved by:

Sam Chuang
Manager

Tested by:

Kevin Kuo
Engineer

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	December 7, 2017	Initial Issue	ALL	Allison Chen

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Table of contents

1. GENERAL INFORMATION 4
1.1 EUT INFORMATION 4
1.2 EUT CHANNEL INFORMATION 5
1.3 ANTENNA INFORMATION 5
1.4 MEASUREMENT UNCERTAINTY 6
1.5 FACILITIES AND TEST LOCATION 7
1.6 INSTRUMENT CALIBRATION 7
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT 8
2. TEST SUMMERY 9
3. DESCRIPTION OF TEST MODES 10
3.1 THE WORST MODE OF OPERATING CONDITION 10
3.2 THE WORST MODE OF MEASUREMENT 11
3.3 EUT DUTY CYCLE 12
4. TEST RESULT 13
4.1 AC POWER LINE CONDUCTED EMISSION 13
4.2 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16
4.3 OUTPUT POWER MEASUREMENT 18
4.4 POWER SPECTRAL DENSITY 20
4.5 CONDUCTED BAND EDGE AND SPURIOUS EMISSION 22
4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION 26
APPENDIX 1 - PHOTOGRAPHS OF EUT

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	LITE-ON Technology Corp. Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C
Manufacturer	LITE-ON TECHNOLOGY (Changzhou) CO., LTD A9 Building,No.88 Yanghu Road, Wujin Hi-Tech Industrial Development Zone ,Changzhou City,Jiangsu Province 213100 China
Equipment	802.11a/b/g/n/ac 2Tx2R+BT V4.2LE USB Combo Module
Model No.	WCBN3507R
Model Discrepancy	N/A
Trade Name	LITE-ON
Received Date	November 29, 2017
Date of Test	November 30 ~ December 4, 2017
Output Power (W)	BLE : 0.0044 (EIRP : 0.0103)
Power Supply	Powered from host device: DC 5V
H/W Version	V01
F/W Version	JEDI.MT76x2

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.2 EUT CHANNEL INFORMATION

Frequency Range	2402MHz-2480MHz
Modulation Type	GFSK for BLE-1Mbps
Number of channel	40 Channels

Remark:
Refer as ANSI 63.10:2013 clause 5.6.1 Table 4 and RSS-GEN Table A1 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	**Number of frequencies**	**Location in frequency range of operation**
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type: ☒ PIFA ☐ PCB ☐ Dipole ☐ Coils

Antenna Gain

Brand	P/N	Type	Cable length	Peak Gain	Worst case
HongBo	290-10569	PIFA	300mm	3.74dBi	V

1. Power Directional Gain: 3.74
2. Power Density Directional Gain: 3.74

Other antenna information:

Brand	P/N	Type	Cable length	Peak Gain
HongBo	290-10310	PIFA	500mm	2.85dBi
Walsin	RFMTA401032IMLB702	PIFA	320mm	3.16dBi
Walsin	RFMTA401080IMLB701	PIFA	800mm	1.85dBi
Walsin	RFMTA401082IMLB701	PIFA	820mm	1.72dBi

Notes:
1. Power Directional Gain: 10LOG(((10^(Ant1/10)+10^(Ant2/10))/2))
2. Power Density Directional Gain: 10LOG(((10^(Ant1/10)+10^(Ant2/10))/2))+10log(NTX/NSS)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 1.4003
RF output power, conducted	+/- 1.1372
Power density, conducted	+/- 1.4003
3M Semi Anechoic Chamber / 30M~200M	+/- 4.0138
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9483
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5975
3M Semi Anechoic Chamber / 8G~18G	+/- 2.6112
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7389
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9683
3M Semi Anechoic Chamber / 40G~60G	+/- 1.8509
3M Semi Anechoic Chamber / 60G~75G	+/- 1.9869
3M Semi Anechoic Chamber / 75G~110G	+/- 2.9651
3M Semi Anechoic Chamber / 110G~170G	+/- 2.7807
3M Semi Anechoic Chamber / 170G~220G	+/- 3.6437
3M Semi Anechoic Chamber / 220G~325G	+/- 4.2982

***Remark**:*
1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Eric Lee	
Radiation	Kevin Kuo	
RF Conducted	Eric Lee	

Remark: *The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.*

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
Power Meter	Anritsu	ML2495A	1033009	04/11/2017	04/10/2018
Power Sensor	Anritsu	MA2411B	917072	07/03/2017	07/02/2018
Spectrum Analyzer	R&S	FSV 40	101073	10/02/2017	10/01/2018
Thermostatic/Hrgrosatic Chamber	GWINSTEK	GTC-288MH-CC	TH160402	05/23/2017	05/22/2018
Directional Coupler	Agilent	87301D	MY44350252	07/25/2017	07/24/2018
SUCOFLEX Cable	HUBER SUHNER	SUCOFLEX 104PEA	25157	07/31/2017	07/30/2018
Divider	Solvang Technology	2-18GHz 4Way	STI08-0015	07/26/2017	07/25/2018

3M 966 Chamber Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
Bilog Antenna	Sunol Sciences	JB3	A030105	06/20/2017	06/19/2018
Horn Antenna	EMCO	3117	00055165	02/20/2017	02/19/2018
Pre-Amplifier	EMCI	EMC 012635	980151	08/01/2017	07/31/2018
Pre-Amplifier	EMEC	EM330	060609	06/07/2017	06/06/2018
Spectrum Analyzer	Agilent	E4446A	US42510252	11/26/2017	11/25/2018
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R

AC Conducted Emissions Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
LISN	R&S	ENV216	101054	05/18/2017	05/17/2018
LISN	SCHWARZBECK	NSLK 8127	8127-541	02/14/2017	02/13/2018
EMI Test Receiver	R&S	ESCI	100064	05/17/2017	05/16/2018

Remark: *Each piece of equipment is scheduled for calibration once a year.*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
	N/A				

Support Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
1	NB(H)	Acer	Aspire 4320 series	N/A	QDS-BRCM1018

1.8 Test methodology and applied standards

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 558074 D01 v04, RSS-247 Issue 2 and RSS-GEN Issue 4

.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

2. TEST SUMMERY

FCC Standard Section	IC Standard Section	Report Section	Test Item	Result
15.203	-	1.2	Antenna Requirement	Pass
15.207(a)	RSS-GEN 8.8	4.1	AC Conducted Emission	Pass
15.247(a)(2)	RSS-247(5.2)(a)	4.2	6 dB Bandwidth	Pass
-	RSS-GEN 6.6	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)	RSS-247(5.4)(d)	4.3	Output Power Measurement	Pass
15.247(e)	RSS-247(5.2)(b)	4.4	Power Spectral Density	Pass
15.247(d)	RSS-247(5.5)	4.5	Conducted Band Edge	Pass
15.247(d)	RSS-247(5.5)	4.5	Conducted Emission	Pass
15.247(d)	RSS-GEN 8.9, 8.10	4.6	Radiation Band Edge	Pass
15.247(d)	RSS-GEN 8.9, 8.10	4.6	Radiation Spurious Emission	Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	BT4.0 Mode (1Mbps)
Test Channel Frequencies	1.Lowest Channel : 2402MHz 2.Middle Channel : 2440MHz 3.Highest Channel : 2480MHz

Remark:
1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.
.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Voltage/Hz	5V
Test Mode	Mode 1:EUT power by Host System
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Band edge, Emission for Unwanted and Fundamental
Voltage/Hz	5V
Test Mode	Mode 1:EUT power by Host System
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☒ Placed in fixed position at Z-Plane (H-Plane)
Worst Polarity	☐ Horizontal ☒ Vertical

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Voltage/Hz	5V
Test Mode	Mode 1:EUT power by Host System
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:
1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis, X, Y, Z and two polarity, Horizontal and Vertical for radiated measurement. The worst case (Z-Plane and Vertical) were recorded in this report
3. For below 1G, AC power line conducted emission and radiation emission were performed the EUT transmit at the highest output power channel as worse case.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3.3 EUT DUTY CYCLE

Duty Cycle				
Configuration	TX ON (ms)	TX ALL (ms)	Duty Cycle (%)	Duty Factor(dB)
BLE	0.4900	0.6400	76.56%	1.16

BLE



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI 63.10:2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Data

Test Mode:	Mode 1	Temp/Hum	24(℃)/ 50%RH
Test Voltage:	120Vac / 60Hz	Test Date	December 1, 2017
Phase:	Line	Test Engineer	Eric Lee



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1740	35.69	13.64	0.05	35.74	13.69	64.77	54.77	-29.03	-41.08	Pass
0.1980	47.55	34.77	0.05	47.60	34.82	63.69	53.69	-16.09	-18.87	Pass
0.2700	39.17	26.98	0.05	39.22	27.03	61.12	51.12	-21.90	-24.09	Pass
0.3380	33.35	24.53	0.05	33.40	24.58	59.25	49.25	-25.85	-24.67	Pass
0.6260	30.52	21.14	0.06	30.58	21.20	56.00	46.00	-25.42	-24.80	Pass
15.7100	37.66	34.16	0.24	37.90	34.40	60.00	50.00	-22.10	-15.60	Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	Mode 1	Temp/Hum	24(℃)/ 50%RH
Test Voltage:	120Vac / 60Hz	Test Date	November 30, 2017
Phase:	Neutral	Test Engineer	Eric Lee



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBu)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1620	54.20	21.98	0.12	54.32	22.10	65.36	55.36	-11.04	-33.26	Pass
0.2100	49.73	22.12	0.12	49.85	22.24	63.21	53.21	-13.36	-30.97	Pass
0.2380	48.47	17.15	0.12	48.59	17.27	62.17	52.17	-13.58	-34.90	Pass
0.2620	48.27	23.03	0.12	48.39	23.15	61.37	51.37	-12.98	-28.22	Pass
0.3100	45.10	19.92	0.13	45.23	20.05	59.97	49.97	-14.74	-29.92	Pass
0.3340	44.47	26.57	0.13	44.60	26.70	59.35	49.35	-14.75	-22.65	Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.2 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

4.2.1 Test Limit

According to §15.247(a)(2) and RSS-247 section 5.2(a)

6 dB Bandwidth ：

Limit	Shall be at least 500kHz

Occupied Bandwidth(99%) ： For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as KDB 558074 D01 v04, section 8.1 and ANSI 63.10:2013 clause 6.9.2 & 6.9.3.

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth and 99% Bandwidth.
4. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



4.2.4 Test Result

Test mode: BLE mode / 2402-2480 MHz				
Channel	**Frequency (MHz)**	**OBW(99%) (MHz)**	**6dB BW (MHz)**	**6dB limit (kHz)**
Low	2402	1.0419	0.7173	>500
Mid	2440	1.0332	0.7130	
High	2480	1.0376	0.7217	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Data

BLE mode

Low CH



Date: 4.DEC.2017 18:26:03

Mid CH



Date: 4.DEC.2017 18:24:22

High CH



Date: 4.DEC.2017 18:28:03

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b) and RSS-247 section 5.4(d)

Peak output power：

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	☒ Antenna not exceed 6 dBi：30dBm ☐ Antenna with DG greater than 6 dBi [Limit = 30 – (DG – 6)] ☐ Point-to-point operation

Average output power：For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as KDB 558074 D01 v04, section 9.1.2.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.3.4 Test Result

Peak output power：

BLE Mode								
Config.	**CH**	**Freq. (MHz)**	**PK Power (dBm)**	**EIRP PK Power (dBm)**	**PK Power (W)**	**EIRP PK Power (W)**	**FCC/IC Limit (dBm)**	**FCC/IC Limit (dBm)**
BLE Data rate: 1Mbps	0	2402	6.39	10.13	0.0044	0.0103	30	36
	19	2440	5.62	9.36	0.0036	0.0086		
	39	2480	5.76	9.50	0.0038	0.0089		

Average output power：

BLE Mode			
Config.	**CH**	**Freq. (MHz)**	**AV Power (dBm)**
BLE Data rate: 1Mbps	0	2402	5.61
	19	2440	5.09
	39	2480	5.12

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.4 POWER SPECTRAL DENSITY

4.4.1 Test Limit

According to §15.247(e) and RSS-247 section 5.2(b)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	☒ Antenna not exceed 6 dBi：8dBm ☐ Antenna with DG greater than 6 dBi [Limit = 8 – (DG – 6)] ☐ Point-to-point operation：

4.4.2 Test Procedure

Test method Refer as KDB 558074 D01 v04, Section 10.2

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 30kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

4.4.3 Test Setup



4.4.4 Test Result

Test mode: BLE mode / 2402-2480 MHz			
Channel	**Frequency (MHz)**	**PSD (dBm)**	**IC/FCC limit (dBm)**
Low	2402	-15.23	8
Mid	2440	-14.52	
High	2480	-15.14	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Data

BLE mode

Low CH



Date: 4.DEC.2017 18:29:27

Mid CH



Date: 4.DEC.2017 18:35:45

High CH



Date: 4.DEC.2017 18:42:21

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.5 CONDUCTED BAND EDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d) and RSS-247 section 5.5

In any 100 kHz bandwidth outside the authorized frequency band,

Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.5.2 Test Procedure

Test method Refer as KDB 558074 D01 v04, Section 11.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.

2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.

3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.5.4 Test Result

Test Data

BLE mode Low CH

Reference Level of PSD in 100kHz



Date: 4.DEC.2017 18:30:41

Band Edge



Date: 4.DEC.2017 18:21:28

Spurious Emission 30MHz-25GHz



Date: 4.DEC.2017 18:32:48

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

BLE mode Mid CH	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

BLE mode High CH

Reference Level of PSD in 100kHz



Date: 4.DEC.2017 18:43:10

Band Edge



Date: 4.DEC.2017 18:44:00

Spurious Emission 30MHz-25GHz



Date: 4.DEC.2017 18:45:18

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:
Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.6.2 Test Procedure

Test method Refer as KDB 558074 D01 v04, Section 12.1.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9KHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

4. No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

5. The SA setting following：

(1) Below 1G：RBW = 100kHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G：

(2.1) For Peak measurement：RBW = 1MHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2.2) For Average measurement：RBW = 1MHz, VBW

˙If Duty Cycle ≥ 98%, VBW=10Hz.

˙If Duty Cycle < 98%, VBW=1/T.

Configuration	Duty Cycle (%)	T(ms)	1/T (kHz)	VBW Setting
BLE	77%	0.4900	2.041	2.2K

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.6.3 Test Setup

9kHz ~ 30MHz



30MHz ~ 1GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1 GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.6.4 Test Result

Band Edge Test Data

Test Mode:	BLE Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage:	120Vac / 60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.786	54.60	-2.99	51.61	74.00	-22.39	peak
2	2401.800	104.66	-2.95	101.71	-	-	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Average	Test Voltage:	120Vac / 60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2384.664	41.25	-2.99	38.26	54.00	-15.74	AVG
2	2402.004	103.79	-2.95	100.84	-	-	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage:	120Vac / 60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.758	103.71	-2.70	101.01	-	-	peak
2	2484.678	54.14	-2.69	51.45	74.00	-22.55	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Average	Test Voltage:	120Vac / 60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.004	102.81	-2.70	100.11	-	-	AVG
2	2483.776	42.79	-2.69	40.10	54.00	-13.90	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1G Test Data

Test Mode:	BLE Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 4, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak and Average	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804.000	39.18	4.34	43.52	74.00	-30.48	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 4, 2017
Polarize	Horizontal	Test Engineer	Kevin Kuo
Detector	Peak and Average	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804.000	39.69	4.34	44.03	74.00	-29.97	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 4, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak and Average	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4880.000	38.59	4.48	43.07	74.00	-30.93	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 4, 2017
Polarize	Horizontal	Test Engineer	Kevin Kuo
Detector	Peak and Average	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4880.000	38.20	4.48	42.68	74.00	-31.32	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 4, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak and Average	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4960.000	40.16	4.61	44.77	74.00	-29.23	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BLE High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 4, 2017
Polarize	Horizontal	Test Engineer	Kevin Kuo
Detector	Peak and Average	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4960.000	38.44	4.61	43.05	74.00	-30.95	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Below 1G Test Data

Test Mode:	BT Mode	Temp/Hum	24(℃)/ 33%RH
Test Item	30MHz-1GHz	Test Date	December 2, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak and Quasi-peak	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
105.6600	47.84	-17.56	30.28	43.52	-13.24	QP
199.7500	40.57	-15.32	25.25	43.52	-18.27	peak
309.3600	45.54	-13.87	31.67	46.02	-14.35	peak
399.5700	41.40	-11.40	30.00	46.02	-16.02	peak
499.4800	33.55	-8.50	25.05	46.02	-20.97	peak
732.2800	34.92	-4.50	30.42	46.02	-15.60	peak

Note: *No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	BT Mode	Temp/Hum	24(℃)/ 33%RH
Test Item	30MHz-1GHz	Test Date	November 30, 2017
Polarize	Horizontal	Test Engineer	Kevin Kuo
Detector	Peak and Quasi-peak	Test Voltage:	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
132.8200	47.35	-15.35	32.00	43.52	-11.52	peak
199.7500	41.61	-15.32	26.29	43.52	-17.23	peak
257.9500	42.64	-15.59	27.05	46.02	-18.97	peak
460.6800	29.34	-9.36	19.98	46.02	-26.04	peak
708.0300	34.89	-4.80	30.09	46.02	-15.93	peak
764.2900	29.20	-4.03	25.17	46.02	-20.85	peak

Note: *No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.