RADIO TEST REPORT
FCC 47 CFR PART 15 SUBPART C
INDUSTRY CANADA RSS-247

Test Standard	**FCC Part 15.247 + IC RSS-247 issue 2**
FCC ID	**PPQ-WCBN3507R12**
Reference FCC ID	**PPQ-WCBN3507R**
ISED No.	**4491A-WCBN3507R12**
Reference ISED No.	**4491A-WCBN3507R**
Brand name	**LITE-ON**
Product name	**802.11a/b/g/n/ac 2Tx2R USB WLAN Module**
Model No.	**WCBN3507R(12)**
Test Result	**Pass**

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.
The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Testing Laboratory
1309

Approved by:

Sam Chuang
Manager

Tested by:

Jerry Chuang
Engineer

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Revision History

Rev.	Issue Date	Revisions	Revised By
00	December 18, 2017	Initial Issue	May Lin

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Table of contents

1. GENERAL INFORMATION 4
1.1 EUT INFORMATION 4
1.2 EUT CHANNEL INFORMATION 5
1.3 ANTENNA INFORMATION 5
1.4 MEASUREMENT UNCERTAINTY 6
1.5 FACILITIES AND TEST LOCATION 7
1.6 INSTRUMENT CALIBRATION 7
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT 8
1.8 TEST METHODOLOGY AND APPLIED STANDARDS 8
2. TEST SUMMERY 9
3. DESCRIPTION OF TEST MODES 10
3.1 THE WORST MODE OF OPERATING CONDITION 10
3.2 THE WORST MODE OF MEASUREMENT 11
4. EUT DUTY CYCLE 12
5. TEST RESULT 13
5.1 AC POWER LINE CONDUCTED EMISSION 13
5.2 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16
5.3 OUTPUT POWER MEASUREMENT 24
5.4 POWER SPECTRAL DENSITY 27
5.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION 35
5.6 RADIATION BANDEDGE AND SPURIOUS EMISSION 54
6. SUMMERY OF THE SPOT CHECK FOR UNLICENSED BANDS 100
APPENDIX 1 - PHOTOGRAPHS OF EUT

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	LITE-ON Technology Corp. Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C
Manufacturer	LITE-ON TECHNOLOGY (Changzhou) CO., LTD A9 Building, No.88 Yanghu Road, Wujin Hi-Tech Industrial Development Zone, Changzhou City, Jiangsu Province 213100 China
Equipment	802.11a/b/g/n/ac 2Tx2R USB WLAN Module
Model Name	WCBN3507R(12)
Model Discrepancy	N/A
Received Date	November 29, 2017
Date of Test	November 30 ~ December 14, 2017
Output Power(W)	IEEE 802.11b mode: 0.0914 (EIRP: 0.2163) IEEE 802.11g mode: 0.2600 (EIRP: 0.6152) IEEE 802.11n HT 20 MHz mode: 0.1524 (EIRP: 0.3606) IEEE 802.11n HT 40 MHz mode: 0.1327 (EIRP: 0.3141)
Power Supply	Powered from host device: DC 5V
HW Version	V01
FW Version	JEDI.MT76x2

Remark:
1.The WLAN hardware of this device are identical to the implementation in PPQ-WCBN3507R.
2.The Product Equality Declaration document includes detailed information about the changes between the devices.
3.This test report data was reused from FCC ID: PPQ-WCBN3507R, we has been verified through appropriate spot checks to demonstrate compliance for this device as shown in the Section 6.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT 20: 2412MHz ~ 2462MHz 802.11n HT 40: 2422MHz ~ 2452MHz
Modulation Type	1. IEEE 802.11b mode: CCK 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT 20 MHz mode : OFDM 4. IEEE 802.11n HT 40 MHz mode : OFDM
Bandwidth	1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT 20 MHz mode : 11 Channels 4. IEEE 802.11n HT 40 MHz mode : 7 Channels

Remark:
Refer as ANSI 63.10:2013 clause 5.6.1 Table 4 and RSS-GEN Table A1 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	**Number of frequencies**	**Location in frequency range of operation**
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type ☒ PIFA ☐ PCB ☐ Dipole ☐ Coils

Antenna Gain

Brand	P/N	Type	Cable length	Peak Gain	Worst case
HongBo	290-10569	PIFA	300mm	3.74dBi	V

1. Power Directional Gain: 3.74
2. Power Density Directional Gain: 3.74

Other antenna information:

Brand	P/N	Type	Cable length	Peak Gain
HongBo	290-10310	PIFA	500mm	3.60dBi
Walsin	RFMTA401032IMLB702	PIFA	320mm	2.6dBi
Walsin	RFMTA401080IMLB701	PIFA	800mm	1.72dBi
Walsin	RFMTA401082IMLB701	PIFA	820mm	1.62dBi

Notes:
1. Power Directional Gain: 10LOG(((10^(Ant1/10)+10^(Ant2/10))/2))
2. Power Density Directional Gain: 10LOG(((10^(Ant1/10)+10^(Ant2/10))/2))+10log(NTX/NSS)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

Remark:
1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at *No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)*

Test site	Test Engineer	Remark
AC Conduction Room	Eric Lee	-
Radiation	Jerry Chuang	-
RF Conducted	Jerry Chuang	-

Remark: *The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.*

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
Power Meter	Anritsu	ML2495A	1033009	04/11/2017	04/10/2018
Power Sensor	Anritsu	MA2411B	917072	07/03/2017	07/02/2018
Spectrum Analyzer	R&S	FSV 40	101073	10/02/2017	10/01/2018
Thermostatic/Hrgrosatic Chamber	GWINSTEK	GTC-288MH-CC	TH160402	05/23/2017	05/22/2018
Directional Coupler	Agilent	87301D	MY44350252	07/25/2017	07/24/2018
SUCOFLEX Cable	HUBER SUHNER	SUCOFLEX 104PEA	25157	07/31/2017	07/30/2018
Divider	Solvang Technology	2-18GHz 4Way	STI08-0015	07/26/2017	07/25/2018

3M 966 Chamber Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
Bilog Antenna	Sunol Sciences	JB3	A030105	06/20/2017	06/19/2018
Horn Antenna	EMCO	3117	00055165	02/20/2017	02/19/2018
Pre-Amplifier	EMCI	EMC 012635	980151	08/01/2017	07/31/2018
Pre-Amplifier	EMEC	EM330	060609	06/07/2017	06/06/2018
Spectrum Analyzer	Agilent	E4446A	US42510252	11/26/2017	11/25/2018
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R

AC Conducted Emissions Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
LISN	R&S	ENV216	101054	05/18/2017	05/17/2018
LISN	SCHWARZBECK	NSLK 8127	8127-541	02/14/2017	02/13/2018
EMI Test Receiver	R&S	ESCI	100064	05/17/2017	05/16/2018

Remark: *Each piece of equipment is scheduled for calibration once a year.*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
	N/A				

Support Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
1	NB(H)	Acer	Aspire 4320 series	N/A	QDS-BRCM1018

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 662911 D01 v02 r01, KDB 558074 D01 V04, RSS-247 Issue 2 and RSS-GEN Issue 4.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

2. TEST SUMMERY

FCC Standard Section	IC Standard Section	Report Section	Test Item	Result
15.203	-	1.2	Antenna Requirement	Pass
15.207(a)	RSS-GEN 8.8	4.1	AC Conducted Emission	Pass
15.247(a)(2)	RSS-247(5.2)(a)	4.2	6 dB Bandwidth	Pass
-	RSS-GEN 6.6	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)	RSS-247(5.4)(d)	4.3	Output Power Measurement	Pass
15.247(e)	RSS-247(5.2)(b)	4.4	Power Spectral Density	Pass
15.247(d)	RSS-247(5.5)	4.5	Conducted Band Edge	Pass
15.247(d)	RSS-247(5.5)	4.5	Conducted Emission	Pass
15.247(d)	RSS-GEN 8.9, 8.10	4.6	Radiation Band Edge	Pass
15.247(d)	RSS-GEN 8.9, 8.10	4.6	Radiation Spurious Emission	Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b mode :1Mbps IEEE 802.11g mode :6Mbps IEEE 802.11n HT20 mode :MCS0 IEEE 802.11n HT40 mode :MCS0
Test Channel Frequencies	**IEEE 802.11b mode :** 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz **IEEE 802.11g mode :** 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz **IEEE 802.11n HT20 mode :** 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz **IEEE 802.11n HT40 mode :** 1. Lowest Channel : 2422MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2452MHz
Operation Transmitter	IEEE 802.11b mode :1T1R IEEE 802.11g mode :1T1R IEEE 802.11n HT20 mode : 2T2R IEEE 802.11n HT40 mode : 2T2R

Remark:
1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Voltage/Hz	DC 5V
Test Mode	Mode 1: EUT power by Host System.
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Band edge, Emission for Unwanted and Fundamental
Voltage/Hz	DC 5V
Test Mode	Mode 1: EUT power by Host System.
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☒ Placed in fixed position at Z-Plane (H-Plane)
Worst Polarity	☐ Horizontal ☒ Vertical

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Voltage/Hz	DC 5V
Test Mode	Mode 1: EUT power by Host System.
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:
1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis, X, Y, Z and two polarity, Horizontal and Vertical for radiated measurement. The worst case (Z-Plane and Vertical) were recorded in this report
3. For below 1G, AC power line conducted emission and radiation emission were performed the EUT transmit at the highest output power channel as worse case.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4. EUT DUTY CYCLE

Duty Cycle				
Configuration	TX ON (ms)	TX ALL (ms)	Duty Cycle (%)	Duty Factor(dB)
802.11b	8.7700	8.9000	98.54%	0.06
802.11g	1.5000	1.6700	89.82%	0.47
802.11n HT20	1.4200	1.5600	91.03%	0.41
802.11n HT40	0.7200	0.8800	81.82%	0.87

802.11b



802.11g



802.11n HT20



802.11n HT40



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5. TEST RESULT

5.1 AC POWER LINE CONDUCTED EMISSION

5.1.1 Test Limit

According to §15.207(a)(2) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

5.1.2 Test Procedure

Test method Refer as ANSI 63.10:2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

5.1.3 Test Setup



5.1.4 Test Result

Pass.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Data

Test Mode:	Mode 1	Temp/Hum	24(℃)/ 50%RH
Test Voltage:	120Vac / 60Hz	Test Date	2017/12/01
Phase:	Line	Test Engineer	Eric Lee



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1740	35.69	13.64	0.05	35.74	13.69	64.77	54.77	-29.03	-41.08	Pass
2	0.1980	47.55	34.77	0.05	47.60	34.82	63.69	53.69	-16.09	-18.87	Pass
3	0.2700	39.17	26.98	0.05	39.22	27.03	61.12	51.12	-21.90	-24.09	Pass
4	0.3380	33.35	24.53	0.05	33.40	24.58	59.25	49.25	-25.85	-24.67	Pass
5	0.6260	30.52	21.14	0.06	30.58	21.20	56.00	46.00	-25.42	-24.80	Pass
6	15.7100	37.66	34.16	0.24	37.90	34.40	60.00	50.00	-22.10	-15.60	Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode:	Mode 1	Temp/Hum	24(℃)/ 50%RH
Test Voltage:	120Vac / 60Hz	Test Date	2017/12/01
Phase:	Neutral	Test Engineer	Eric Lee



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1620	54.20	21.98	0.12	54.32	22.10	65.36	55.36	-11.04	-33.26	Pass
2	0.2100	49.73	22.12	0.12	49.85	22.24	63.21	53.21	-13.36	-30.97	Pass
3	0.2380	48.47	17.15	0.12	48.59	17.27	62.17	52.17	-13.58	-34.90	Pass
4	0.2620	48.27	23.03	0.12	48.39	23.15	61.37	51.37	-12.98	-28.22	Pass
5	0.3100	45.10	19.92	0.13	45.23	20.05	59.97	49.97	-14.74	-29.92	Pass
6	0.3340	44.47	26.57	0.13	44.60	26.70	59.35	49.35	-14.75	-22.65	Pass

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.2 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

5.2.1 Test Limit

According to §15.247(a)(2) and RSS-247 section 5.2(a),

6 dB Bandwidth ：

Limit	Shall be at least 500kHz

Occupied Bandwidth(99%) ： For reporting purposes only.

5.2.2 Test Procedure

Test method Refer as KDB 558074 D01 V04, Section 8.1 and ANSI 63.10:2013 clause 6.9.2,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth and 99% Bandwidth.
4. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

5.2.3 Test Setup



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.2.4 Test Result

Test mode: IEEE 802.11b mode / 2412-2462 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2412	12.2431	-	10.0435	-	≥500
Mid	2437	12.2431	-	10.0435	-	
High	2462	12.1562	-	10.0435	-	

Test mode: IEEE 802.11g mode / 2412-2462 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2412	16.5846	-	16.3043	-	≥500
Mid	2437	16.5846	-	16.3043	-	
High	2462	16.5846	-	16.3043	-	

Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2412	17.5832	17.5832	16.9565	17.0435	≥500
Mid	2437	17.6266	17.6700	17.0343	17.0870	
High	2462	17.6266	17.5832	17.0435	17.5217	

Test mode: IEEE 802.11n HT 40 MHz mode / 2422-2452 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2422	36.2373	36.0057	35.478	35.13	>500
Mid	2437	36.2373	36.1215	35.362	35.13	
High	2452	36.2373	36.1215	35.246	35.13	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Data

IEEE 802.11b mode- chain 0

Low CH



Date: 1.DEC.2017 09:45:39

Mid CH



Date: 1.DEC.2017 10:06:30

High CH



Date: 1.DEC.2017 10:36:31

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 mode- chain 1

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 mode- chain 1

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.3 OUTPUT POWER MEASUREMENT

5.3.1 Test Limit

According to §15.247(b) and RSS-247 section 5.4(d),

Peak output power：

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm) and the e.i.r.p. shall not exceed 4Watt(36 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	☒ Antenna not exceed 6 dBi：30dBm ☐ Antenna with DG greater than 6 dBi： [Limit = 30 – (DG – 6)] ☐ Point-to-point operation：

Average output power：For reporting purposes only.

5.3.2 Test Procedure

Test method Refer as KDB 558074 D01 V04, Section 9.1.2.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

5.3.3 Test Setup



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.3.4 Test Result

Peak output power：

Wifi 2.4G													
Config	CH	Freq. (MHz)	power set		PK Power(dBm)		PK Total Power (dBm)	PK Total Power (W)	EIRP PK Total Power (dBm)	EIRP PK Total Power (W)	DG (dBi)	Limit (dBm)	EIRP Limit (dBm)
			chain0	chain1	chain0	chain1							
IEEE 802.11b Data rate: 1Mbps	Low	2412	20	-	19.61	-	19.61	0.0914	23.35	0.2163	3.74	30	36
	Mid	2437	1F	-	19.24	-	19.24	0.0839	22.98	0.1986			
	High	2462	1F	-	19.22	-	19.22	0.0836	22.96	0.1977			
IEEE 802.11g Data rate: 6Mbps	Low	2412	20	-	24.14	-	24.14	0.2594	27.88	0.6138			
	Mid	2437	20	-	24.12	-	24.12	0.2582	27.86	0.6109			
	High	2462	20	-	24.15	-	24.15	0.2600	27.89	0.6152			
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	1D	1D	17.64	17.27	20.47	0.1114	24.21	0.2636			
	Mid	2437	20	20	19.01	18.62	21.83	0.1524	25.57	0.3606			
	High	2462	1E	1E	18.20	18.12	21.17	0.1309	24.91	0.3097			
IEEE 802.11n HT40 Data rate: MCS0	Low	2422	19	19	15.03	14.36	17.72	0.0592	21.46	0.1400			
	Mid	2437	21	21	18.26	18.17	21.23	0.1327	24.97	0.3141			
	High	2452	18	18	13.58	13.46	16.53	0.0450	20.27	0.1064			

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Average output power：

Wifi 2.4G					
Config	CH	Freq. (MHz)	AV Power(dBm)		AV Total Power (dBm)
			chain0	chain1	
IEEE 802.11b Data rate: 1Mbps	Low	2412	16.94	-	16.94
	Mid	2437	16.76	-	16.76
	High	2462	16.73	-	16.73
IEEE 802.11g Data rate: 6Mbps	Low	2412	15.93	-	15.93
	Mid	2437	15.85	-	15.85
	High	2462	15.91	-	15.91
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	14.33	14.08	17.22
	Mid	2437	15.77	15.30	18.55
	High	2462	14.63	14.57	17.61
IEEE 802.11n HT40 Data rate: MCS0	Low	2422	11.82	11.45	14.65
	Mid	2437	15.14	15.03	18.10
	High	2452	10.75	10.69	13.73

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.4 POWER SPECTRAL DENSITY

5.4.1 Test Limit

According to §15.247(e) and RSS-247 section 5.2(b),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	☒ Antenna not exceed 6 dBi：8dBm ☐ Antenna with DG greater than 6 dBi： [Limit = 8 – (DG – 6)] ☐ Point-to-point operation：

5.4.2 Test Procedure

Test method Refer as KDB 558074 D01 V04, Section 10.2

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 30kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

5.4.3 Test Setup



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.4.4 Test Result

Test mode: IEEE 802.11b mode / 2412-2462 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PSSD (dBm)**	**Limit (dBm)**
Low	2412	-6.07	-	-6.07	8
Mid	2437	-8.02	-	-8.02	
High	2462	-6.70	-	-6.70	

Test mode: IEEE 802.11g mode / 2412-2462 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PSSD (dBm)**	**Limit (dBm)**
Low	2412	-7.98	-	-7.98	8
Mid	2437	-8.26	-	-8.26	
High	2462	-7.54	-	-7.54	

Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PSSD (dBm)**	**Limit (dBm)**
Low	2412	-11.53	-11.42	-8.46	8
Mid	2437	-10.63	-9.54	-7.04	
High	2462	-10.97	-11.54	-8.24	

Test mode: IEEE 802.11n HT 40 MHz mode / 2422-2452 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PSSD (dBm)**	**Limit (dBm)**
Low	2422	-15.64	-20.59	-14.43	8
Mid	2437	-11.48	-12.08	-8.76	
High	2452	-19.51	16.09	16.09	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Data

IEEE 802.11b mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 mode- chain 1

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 mode- chain 0

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 mode- chain 1

Low CH



Mid CH



High CH



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

5.5.1 Test Limit

According to §15.247(d) and RSS-247 section 5.5,

In any 100 kHz bandwidth outside the authorized frequency band,

Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

5.5.2 Test Procedure

Test method Refer as KDB 662911 D01 v02 r01, KDB 558074 D01 V04, Section 11.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.

2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.

3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. f the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

5.5.3 Test Setup



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.5.4 Test Result

Test Data

IEEE 802.11b mode Low CH chain 0	
Reference Level of PSD in 100kHz	**Band Edge**
	
Spurious Emission 30MHz-25GHz	
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11b mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11b mode High CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode Low CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode High CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT20 mode Low CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT20 mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 mode High CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT20 mode Low CH chain 1

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT20 mode Mid CH chain 1	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 mode High CH chain 1

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT40 mode Low CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT40 mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 mode High CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT40 mode Low CH chain 1

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11 n HT40 mode Mid CH chain 1	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 mode High CH chain 1

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

5.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency	Field Strength (microvolts/m)	Measurement Distance (metres)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.6.2 Test Procedure

Test method Refer as KDB 662911 D01 v02 r01, KDB 558074 D01 V04, Section 12.1.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

4. The SA setting following：

(1) Below 1G：RBW = 100kHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G：

(2.1) For Peak measurement：RBW = 1MHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2.2) For Average measurement：RBW = 1MHz, VBW

˙If Duty Cycle ≥ 98%, VBW=10Hz.

˙If Duty Cycle < 98%, VBW=1/T.

Configuration	Duty Cycle (%)	T(ms)	1/T (kHz)	VBW Setting
802.11b	99%	8.7700	-	10Hz
802.11g	90%	1.5000	0.667	680Hz
802.11n HT20	91%	1.4200	0.704	750Hz
802.11n HT40	82%	0.7200	1.389	1.5kHz

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.6.3 Test Setup

9kHz ~ 30MHz



30MHz ~ 1GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1 GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.6.4 Test Result

Band Edge Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	72.03	-2.98	69.05	74.00	-4.95	peak
2413.488	115.85	-2.90	112.95	-	-	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b Low CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	51.06	-2.98	48.08	54.00	-5.92	AVG
2414.720	111.78	-2.90	108.88	-	-	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2463.500	115.44	-2.75	112.69	-	-	peak
2483.900	72.15	-2.69	69.46	74.00	-4.54	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b High CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2459.200	111.23	-2.76	108.47	-	-	AVG
2486.800	48.25	-2.68	45.57	54.00	-8.43	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	71.81	-2.98	68.83	74.00	-5.17	peak
2412.144	110.95	-2.91	108.04	-	-	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g Low CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	53.87	-2.98	50.89	54.00	-3.11	AVG
2410.240	100.56	-2.92	97.64	-	-	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2460.400	113.06	-2.76	110.30	-	-	peak
2484.100	72.68	-2.69	69.99	74.00	-4.01	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g High CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	November 30, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2461.000	103.03	-2.76	100.27	-	-	AVG
2483.500	53.19	-2.69	50.50	54.00	-3.50	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2389.632	73.76	-2.98	70.78	74.00	-3.22	peak
2409.792	111.72	-2.92	108.80	-	-	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 Low CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	55.16	-2.98	52.18	54.00	-1.82	AVG
2413.376	101.57	-2.90	98.67	-	-	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2462.000	112.09	-2.76	109.33	-	-	peak
2483.900	75.00	-2.69	72.31	74.00	-1.69	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 High CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2461.300	100.77	-2.76	98.01	-	-	AVG
2483.500	54.36	-2.69	51.67	54.00	-2.33	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	73.99	-2.98	71.01	74.00	-2.99	peak
2414.412	104.70	-2.90	101.80	-	-	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 Low CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.000	56.08	-2.98	53.10	54.00	-0.90	AVG
2427.612	94.58	-2.86	91.72	-	-	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2456.840	109.15	-2.78	106.37	-	-	peak
2489.480	74.35	-2.67	71.68	74.00	-2.32	peak

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 High CH	Temperature:	24(℃)/ 33%RH
Test Item	Band Edge	Test Date	December 12, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2450.480	99.81	-2.79	97.02	-	-	AVG
2483.500	56.47	-2.69	53.78	54.00	-0.22	AVG

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Below 1G Test Data

Test Mode	Mode 1	Temp/Hum	24(℃)/ 33%RH
Test Item	30MHz-1GHz	Test Date	December 2, 2017
Polarize	Vertical	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
240.4900	50.91	-16.12	34.79	46.02	-11.23	peak
345.2500	44.90	-13.09	31.81	46.02	-14.21	peak
499.4800	33.39	-8.50	24.89	46.02	-21.13	peak
703.1800	36.64	-4.85	31.79	46.02	-14.23	peak
719.6700	39.26	-4.65	34.61	46.02	-11.41	peak
960.2300	36.69	-1.08	35.61	54.00	-18.39	peak

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	Mode 1	Temp/Hum	24(℃)/ 33%RH
Test Item	30MHz-1GHz	Test Date	December 2, 2017
Polarize	Horizontal	Test Engineer	Kevin Kuo
Detector	Peak	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB	Remark
110.5100	43.64	-16.69	26.95	43.52	-16.57	peak
240.4900	39.46	-16.12	23.34	46.02	-22.68	peak
257.9500	40.87	-15.59	25.28	46.02	-20.74	peak
480.0800	34.90	-8.94	25.96	46.02	-20.06	peak
500.4500	35.21	-8.48	26.73	46.02	-19.29	peak
960.2300	32.98	-1.08	31.90	54.00	-22.10	peak

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4827.000	43.96	4.38	48.34	74.00	-25.66	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4827.000	42.05	4.38	46.43	74.00	-27.57	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4876.000	45.36	4.47	49.83	74.00	-24.17	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4876.000	43.92	4.47	48.39	74.00	-25.61	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4925.000	44.67	4.55	49.22	74.00	-24.78	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11b High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4925.000	44.91	4.55	49.46	74.00	-24.54	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4827.000	41.41	4.38	45.79	74.00	-28.21	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4827.000	39.59	4.38	43.97	74.00	-30.03	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4876.000	44.96	4.47	49.43	74.00	-24.57	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4876.000	40.27	4.47	44.74	74.00	-29.26	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4925.000	43.50	4.55	48.05	74.00	-25.95	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11g High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4925.000	42.10	4.55	46.65	74.00	-27.35	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4820.000	48.45	4.36	52.81	74.00	-21.19	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4827.000	44.36	4.38	48.74	74.00	-25.26	Peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4869.000	49.81	4.45	54.26	74.00	-19.74	peak
4869.000	39.00	4.45	43.45	54.00	-10.55	AVG
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4876.000	45.69	4.47	50.16	74.00	-23.84	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4925.000	46.50	4.55	51.05	74.00	-22.95	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4918.000	43.36	4.55	47.91	74.00	-26.09	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4848.000	41.31	4.43	45.74	74.00	-28.26	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4844.000	37.88	4.41	42.29	74.00	-31.71	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4876.000	49.86	4.47	54.33	74.00	-19.67	peak
4876.000	41.95	4.47	46.42	54.00	-7.58	AVG
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 5, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4869.000	45.61	4.45	50.06	74.00	-23.94	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Vertical	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4904.000	39.43	4.51	43.94	74.00	-30.06	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	24(℃)/ 33%RH
Test Item	Harmonic	Test Date	December 13, 2017
Polarize	Horizontal	Test Engineer	Jerry Chuang
Detector	Peak and Average	Test Voltage	120Vac / 60Hz



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4904.000	38.64	4.51	43.15	74.00	-30.85	peak
N/A						

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6. SUMMERY OF THE SPOT CHECK FOR UNLICENSED BANDS

Report	Test Item	Channel	Measured Frequency	PPQ-WCBN3507R		PPQ-WCBN3507R12		Gap (dB)	
				Peak	Average	Peak	Average	Peak	Average
DTS (20MHz)	Band edge	1	2390.000	109.33	98.67	106.17	95.75	3.16	2.92
	RSE	11	9846.000	52.81	-	50.64	-	2.17	-
DTS (40MHz)	Band edge	3	2389.464	106.37	97.02	106.9	96.01	-0.53	1.01
	RSE	6	11020.000	45.74	-	45.4	-	0.34	-

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.