

Radio Exposure Evaluation Report

FCC ID : PPQ-WCBN3509R
Equipment : Wireless LAN Module
Brand Name : LITEON
Model Name : WCBN3509R, WCBN3509R(AU)
Applicant : LITE-ON TECHNOLOGY CORP.
Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City
23585, Taiwan, R.O.C
Manufacturer : LITE-ON TECHNOLOGY (Changzhou) CO., LTD
A9 Building, No.88 Yanghu Road, Wujin Hi-Tech
Industrial Development Zone, Changzhou City, Jiangsu
Province 213100 China
Standard : 47 CFR Part 2.1091

The product was received on Aug. 12, 2019, and testing was started from Aug. 22, 2019 and completed on Aug. 22, 2019. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091, KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
1 General Description	5
1.1 EUT General Information	5
1.2 Table for Multiple Listing	5
1.3 Table for Permissive Change	5
1.4 Testing Location	6
2 Maximum Permissible Exposure	7
2.1 Limit of Maximum Permissible Exposure	7
2.2 MPE Calculation Method	7
2.3 Calculated Result and Limit.....	8

Photographs of EUT V02



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Sam Tsai

Report Producer: Debby Hung

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

1.2 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
WCBN3509R	All the models are identical, the difference are "chip model name" and "software".
WCBN3509R(AU)	

Note: The Model Name WCBN3509R(AU) configuration was pretested and found to be the worst case and measured during the test.

1.3 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA980219-01

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Master SKU was added 2. Antenna was added (For Limit Module Master DFS)	The MPE was evaluated, and the test result of original test report was found to be the worst case scenario.



1.4 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
☒ Hsinhua	ADD: No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)	
(TAF: 3785)	TEL: 886-3-327-3456	FAX: 886-3-327-0973
Test site Designation No. TW1190 with FCC.		
☐ Wen 33rd.St.	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)	
(TAF: 3785)	TEL: 886-3-318-0787	FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.		

Laboratory number TAF 3785 is a spin-off from the original Laboratory number TAF 1190.

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

2.4GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D	3.74	21.18	24.92	0.50	25.42	0.34834	20	0.06930	1.00000
2.4G;D1D	3.74	22.99	26.73	0.50	27.23	0.52845	20	0.10513	1.00000

5GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
5.2G;D1D	3.80	22.28	26.08	0.50	26.58	0.45499	20	0.09052	1.00000
5.3G;D1D	3.80	22.17	25.97	0.50	26.47	0.44361	20	0.08825	1.00000
5.6G;D1D	3.80	22.57	26.37	0.50	26.87	0.48641	20	0.09677	1.00000
5.8G;D1D	3.80	21.27	25.07	0.50	25.57	0.36058	20	0.07174	1.00000

Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;BT-LE	3.74	7.48	11.22	0.50	11.72	0.01486	20	0.00296	1.00000
2.4G;BT-BR	3.74	7.53	11.27	0.50	11.77	0.01503	20	0.00299	1.00000
2.4G;BT-EDR	3.74	7.51	11.25	0.50	11.75	0.01496	20	0.00298	1.00000

**Bluetooth+WLAN 2.4GHz**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D	3.74	22.99	26.73	0.50	27.23	0.52845	20	0.10513	1.00000	0.10513
2.4G;BT-BR	3.74	7.53	11.27	0.50	11.77	0.01503	20	0.00299	1.00000	0.00299
									Sum Ratio	0.10812
									Ratio Limit	1

Bluetooth+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
5.6G;D1D	3.80	22.57	26.37	0.50	26.87	0.48641	20	0.09677	1.00000	0.09677
2.4G;BT-BR	3.74	7.53	11.27	0.50	11.77	0.01503	20	0.00299	1.00000	0.00299
									Sum Ratio	0.09976
									Ratio Limit	1

————THE END————