

# RF Exposure Evaluation Report

**Equipment** : 802.11 a/b/g/n/ac 2T2R+BT V4.2LE combo module  
**Brand Name** : LITE-ON  
**Model No.** : WCBN3510A  
**FCC ID** : PPQ-WCBN3510A  
**Standard** : 47 CFR Part 2.1091  
**Applicant** : LITE-ON Technology Corp.  
Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City  
23585, Taiwan, R.O.C  
**Manufacturer** : LITE-ON TECHNOLOGY (Changzhou) CO., LTD  
A9 Building, No.88 Yanghu Road, Wujin Hi-Tech  
Industrial Development Zone, Changzhou City,  
Jiangsu Province 213100 China

The product sample received on Nov. 27, 2017 and completely tested on Dec. 14, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Kevin Liang / Assistant Manager





## **TABLE OF CONTENTS**

|                               |                                             |          |
|-------------------------------|---------------------------------------------|----------|
| <b>1</b>                      | <b>GENERAL DESCRIPTION .....</b>            | <b>4</b> |
| 1.1                           | EUT General Information .....               | 4        |
| 1.2                           | Testing Location .....                      | 4        |
| <b>2</b>                      | <b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>   | <b>5</b> |
| 2.1                           | Limit of Maximum Permissible Exposure ..... | 5        |
| 2.2                           | MPE Calculation Method .....                | 5        |
| 2.3                           | Calculated Result and Limit.....            | 6        |
| <b>PHOTOGRAPHS OF EUT V01</b> |                                             |          |

## REVISION HISTORY

[illegible]

# 1 General Description

## 1.1 EUT General Information

| RF General Information |                                                  |                                                  |                                                                                                                                      |
|------------------------|--------------------------------------------------|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation Mode        | Frequency Range (MHz)                            | Operating Frequency (MHz)                        | Modulation Type                                                                                                                      |
| 2.4GHz WLAN            | 2400-2483.5                                      | 2412-2462                                        | 802.11b: DSSS (DBPSK, DQPSK, CCK)<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |
| 5GHz WLAN              | 5150-5250<br>5250-5350<br>5470-5725<br>5725-5850 | 5180-5240<br>5260-5320<br>5500-5700<br>5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)                                      |
| Bluetooth              | 2400-2483.5                                      | 2402-2480                                        | BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK)<br>LE: DSSS (GFSK)                                                                    |

## 1.2 Testing Location

| Testing Location                           |        |                                                                              |                      |
|--------------------------------------------|--------|------------------------------------------------------------------------------|----------------------|
| <input checked="" type="checkbox"/>        | HWA YA | ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)    |                      |
|                                            |        | TEL : 886-3-327-3456                                                         | FAX : 886-3-327-0973 |
| Test site Designation No. TW1190 with FCC. |        |                                                                              |                      |
| <input type="checkbox"/>                   | JHUBEI | ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) |                      |
|                                            |        | TEL : 886-3-656-9065                                                         | FAX : 886-3-656-9085 |
| Test site Designation No. TW0006 with FCC. |        |                                                                              |                      |

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6                                                                |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f <sup>2</sup> )*                 | 6                                                                |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6                                                                |
| 300-1500              | -                                 | -                                 | F/300                                    | 6                                                                |
| 1500-100,000          | -                                 | -                                 | 5                                        | 6                                                                |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30                                                               |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f <sup>2</sup> )*                   | 30                                                               |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30                                                               |
| 300-1500              | -                                 | -                                 | F/1500                                   | 30                                                               |
| 1500-100,000          | -                                 | -                                 | 1.0                                      | 30                                                               |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

| Mode       | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>EIRP<br>(dBm) | Tune-up<br>EIRP<br>(W) | Distance<br>(cm) | S<br>(mW/cm <sup>2</sup> ) | S Limit<br>(mW/cm <sup>2</sup> ) | Ratio<br>(S/Limit) |
|------------|-------------|----------------|---------------|-------------------|--------------------------|------------------------|------------------|----------------------------|----------------------------------|--------------------|
| 2.4G;D1D   | 3.52        | 25.74          | 29.26         | 0.50              | 29.76                    | 0.94624                | 20               | 0.18825                    | 1.00000                          | 0.18825            |
| 2.4G;BT-BR | 3.52        | 11.94          | 15.46         | 0.50              | 15.96                    | 0.03945                | 20               | 0.00785                    | 1.00000                          | 0.00785            |
|            |             |                |               |                   |                          |                        |                  |                            | Sum Ratio                        | 0.1961             |
|            |             |                |               |                   |                          |                        |                  |                            | Ratio Limit                      | 1                  |

| Mode       | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>EIRP<br>(dBm) | Tune-up<br>EIRP<br>(W) | Distance<br>(cm) | S<br>(mW/cm <sup>2</sup> ) | S Limit<br>(mW/cm <sup>2</sup> ) | Ratio<br>(S/Limit) |
|------------|-------------|----------------|---------------|-------------------|--------------------------|------------------------|------------------|----------------------------|----------------------------------|--------------------|
| 5.8G;D1D   | 4.18        | 26.57          | 30.75         | 0.50              | 31.25                    | 1.33352                | 20               | 0.2653                     | 1.00000                          | 0.2653             |
| 2.4G;BT-BR | 3.52        | 11.94          | 15.46         | 0.50              | 15.96                    | 0.03945                | 20               | 0.00785                    | 1.00000                          | 0.00785            |
|            |             |                |               |                   |                          |                        |                  |                            | Sum Ratio                        | 0.27315            |
|            |             |                |               |                   |                          |                        |                  |                            | Ratio Limit                      | 1                  |