

**IEEE C95.1 2005
KDB 447498 D01 V06
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091**

RF EXPOSURE REPORT

For

WLAN + BT Combo Module

Model: WCBN4511R

Trade Name: LITE-ON

Issued to

**Lite-On Technology Corp.
Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C**

Issued by

**Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
<http://www.ccsrf.com>
service@ccsrf.com
Issued Date: July 29, 2016**



Testing Laboratory
1309

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 29, 2016	Initial Issue	ALL	Doris Chu
01	August 26, 2016	1. Added section 6.	P.9	Doris Chu

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	4
2. LIMIT	5
3. EUT SPECIFICATION.....	5
4. TEST RESULTS.....	7
5. MAXIMUM PERMISSIBLE EXPOSURE	8
6. SIMULTANEOUS TRANSMISSION SAR ANALYSIS	9

1. TEST RESULT CERTIFICATION

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
IEEE C95.1 2005 KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted

Approved by:



Miller Lee
Manager
Compliance Certification Services Inc.

Test by:



Doris Chu
Report coordinator
Compliance Certification Services Inc.

2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

3. EUT SPECIFICATION

EUT	WLAN + BT Combo Module
Model	WCBN4511R
Trade Name	LITE-ON
Model Discrepancy	N/A
Frequency band (Operating)	☒ Bluetooth 2.1 + EDR / 4.0: 2402 MHz ~ 2480 MHz 802.11b/g/n HT20: 2412MHz ~ 2462MHz 802.11n HT40: 2422MHz ~ 2452MHz 802.11a/n HT20: 5180MHz ~ 5700MHz / 5745MHz ~ 5825MHz 802.11n HT40: 5190MHz ~ 5670MHz / 5755MHz ~ 5795MHz 802.11ac VHT80: 5210MHz ~ 5290MHz / 5530 MHz ~ 5775MHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)

Antenna Specification	BT Walsin / RFMTA400536IMAB301 PIFA Antenna / Gain: 3.79dBi 2.4G LITE-ON / WCBN4511R PIFA Antenna ANT-L: Gain: 2.54dBi ANT-R: Gain: 0.93dBi 5G LITE-ON / WCBN4511R PIFA Antenna ANT-L: Gain: 2.94dBi ANT-R: Gain: 3.35dBi BT: Antenna Gain : 3.79 dBi (Numeric gain: 2.39) Worst 2.4GHz: Antenna Gain : 2.54 dBi (Numeric gain: 1.79) Worst 5GHz: Antenna Gain : 3.35 dBi (Numeric gain: 2.16) Worst 2.4GHz: Directional gain = 2.54 dBi +10log (2) = 5.55 dBi (Numeric gain: 3.59) 5GHz: Directional gain = 3.35 dBi +10log (2) = 6.36 dBi (Numeric gain: 4.33)
Maximum Average output power	Bluetooth Mode : 8.22 dBm (6.637 mW) IEEE 802.11b Mode: 19.06 dBm (80.538 mW) IEEE 802.11g Mode: 19.55 dBm (90.157 mW) IEEE 802.11n HT 20 Mode: 18.85 dBm (76.736 mW) IEEE 802.11n HT 40 Mode: 13.53 dBm (22.542 mW) IEEE 802.11a Mode: 19.05 dBm (80.353 mW) IEEE 802.11n HT20 Mode: 18.58 dBm (72.111 mW) IEEE 802.11n HT40 Mode: 18.66 dBm (73.451 mW) IEEE 802.11ac VHT80 Mode: 14.26 dBm (26.669 mW)
Maximum Tune up Power	Bluetooth Mode : 9.50 dBm (8.913 mW) IEEE 802.11b Mode: 20.50 dBm (112.202 mW) IEEE 802.11g Mode: 21.00 dBm (125.893 mW) IEEE 802.11n HT 20 Mode: 20.00 dBm (100.000 mW) IEEE 802.11n HT 40 Mode: 15.00 dBm (31.623 mW) IEEE 802.11a Mode: 20.50 dBm (112.202 mW) IEEE 802.11n HT20 Mode: 20.00 dBm (100.000 mW) IEEE 802.11n HT40 Mode: 20.00 dBm (100.000 mW) IEEE 802.11ac VHT80 Mode: 15.50 dBm (35.481 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

4. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
40	2441	8.913	2.39	20	0.0042	1

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	112.202	3.59	20	0.0802	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	125.893	3.59	20	0.0899	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	100.000	3.59	20	0.0714	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	31.623	3.59	20	0.0226	1

IEEE 802.11a mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
116	5580	112.202	4.33	20	0.0967	1

IEEE 802.11a HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
157	5785	100.000	4.33	20	0.0862	1

IEEE 802.11a HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
110	5550	100.000	4.33	20	0.0862	1

IEEE 802.11ac VHT80 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
58	5290	35.481	4.33	20	0.0306	1

6. SIMULTANEOUS TRANSMISSION SAR ANALYSIS

Both of the BT and WLAN can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

BT+WIFI

Therefore, the worst-case situation is $0.0042 / 1 + 0.0967 / 1 = 0.1009$, which is less than "1".