

CHARGING STATION

MODEL: W1-UC166-OMK1ER

MFG: LITEON

IN/OUT: 208-240VAC, 1Ø, 60Hz, MAX. 48A

TEMP. : -30°C~50°C

ENCLOSURE: TYPE 4. FOR INDOOR OR OUTDOOR USE.

MFGDT:

S/N:

THIS DEVICE CONTAINS

FCC ID: PPQ202008EG91NAXD IC: 4491A-021EG91NAXD

FCC ID: PPQ1LYW131 IC: 4491A-L1LYW131

FCC ID: PPQRYORR2L IC: 4491A-RYORR2L



EVSE
E354962
FACTORY ID:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

CAN ICES-3(B) / NMB-3(B)

MADE IN TAIWAN

CHARGING STATION

MODEL: W1-UC168-OMF1FR

MFG: LITEON

IN/OUT: 208-240VAC, 1Ø, 60HZ, MAX. 48A

TEMP. : -30°C~50°C

ENCLOSURE: TYPE 4. FOR INDOOR OR OUTDOOR USE.

MFGDT:

S/N:

THIS DEVICE CONTAINS

FCC ID: PPQLILYW131

IC:4491A-LILYW131

FCC ID: PPRYORR2L

IC:4491A-RYORR2L



EVSE

E354962

FACTORY ID:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

CAN ICES-3(B) / NMB-3(B)

MADE IN TAIWAN

CHARGING STATION

MODEL: W1-UC168-OMF1FO

MFG: LITEON

IN/OUT: 208-240VAC, 1Ø, 60Hz, MAX. 48A

TEMP. : -30°C~50°C

ENCLOSURE: TYPE 4. FOR INDOOR OR OUTDOOR USE.

MFGDT:

S/N:

THIS DEVICE CONTAINS

FCC ID: PPQLIYW131

IC:4491A-LIYW131



EVSE

E354962

FACTORY ID:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

CAN ICES-3(B) / NMB-3(B)

MADE IN TAIWAN