

CHARGING STATION

Model: EX-1193-M

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A

Type: Type 3R Enclosure

Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
FOR INDOOR OR OUTDOOR USE.
MADE IN TAIWAN.
CAN ICES-3(B) / NMB-3(B)



LISTED
EVSE
E354962

This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQ202008EG91NAXD
Contains FCC ID: PPQLILYW131
Contains FCC ID: PPQRYORR2L
Contains IC: 4491A-021EG91NAXD
Contains IC: 4491A-LILYW131
Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-E

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A

Type: Type 3R Enclosure

Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
FOR INDOOR OR OUTDOOR USE.
MADE IN TAIWAN.
CAN ICES-3(B) / NMB-3(B)



LISTED
EVSE
E354962

This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
Contains FCC ID: PPQRYORR2L
Contains IC: 4491A-LILYW131
Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-T

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A

Type: Type 3R Enclosure

Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
FOR INDOOR OR OUTDOOR USE.
MADE IN TAIWAN.
CAN ICES-3(B) / NMB-3(B)



LISTED
EVSE
E354962

This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
Contains IC: 4491A-LILYW131

CHARGING STATION

Model: EX-1193-M-48

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A

Type: Type 3R Enclosure

Temp: -35°C~55°C

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
FOR INDOOR OR OUTDOOR USE.
MADE IN TAIWAN.
CAN ICES-3(B) / NMB-3(B)



LISTED
EVSE
E354962

This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQ202008EG91NAXD
Contains FCC ID: PPQLILYW131
Contains FCC ID: PPQRYORR2L
Contains IC: 4491A-021EG91NAXD
Contains IC: 4491A-LILYW131
Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-E-48

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A

Type: Type 3R Enclosure

Temp: -35°C~55°C

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
FOR INDOOR OR OUTDOOR USE.
MADE IN TAIWAN.
CAN ICES-3(B) / NMB-3(B)



LISTED
EVSE
E354962

This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
Contains FCC ID: PPQRYORR2L
Contains IC: 4491A-LILYW131
Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-T-48

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A

Type: Type 3R Enclosure

Temp: -35°C~55°C

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
FOR INDOOR OR OUTDOOR USE.
MADE IN TAIWAN.
CAN ICES-3(B) / NMB-3(B)



LISTED
EVSE
E354962

This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
Contains IC: 4491A-LILYW131