

CHARGING STATION

Model: EX-1193-1
 In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A
 Enclosure Type: Type 3R
 Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A
 Date:
 SN:

FOR USE WITH ELECTRIC VEHICLES.
 VENTILATION NOT REQUIRED.
 FOR INDOOR OR OUTDOOR USE.
 MADE IN TAIWAN.
 CAN ICES-3(B) / NMB-3(B)



FCC ID: xxxxxxxx
 FCC ID: xxxxxxxx
 FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQ201707BG96
 Contains FCC ID: PPQLILYW131
 Contains FCC ID: PPQRYORR2L
 Contains IC: 4491A-201709BG96
 Contains IC: 4491A-LILYW131
 Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-5
 In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A
 Enclosure Type: Type 3R
 Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A
 Date:
 SN:

FOR USE WITH ELECTRIC VEHICLES.
 VENTILATION NOT REQUIRED.
 FOR INDOOR OR OUTDOOR USE.
 MADE IN TAIWAN.
 CAN ICES-3(B) / NMB-3(B)



FCC ID: xxxxxxxx
 FCC ID: xxxxxxxx
 FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
 Contains FCC ID: PPQRYORR2L
 Contains IC: 4491A-LILYW131
 Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-3
 In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A
 Enclosure Type: Type 3R
 Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A
 Date:
 SN:

FOR USE WITH ELECTRIC VEHICLES.
 VENTILATION NOT REQUIRED.
 FOR INDOOR OR OUTDOOR USE.
 MADE IN TAIWAN.
 CAN ICES-3(B) / NMB-3(B)



FCC ID: xxxxxxxx
 FCC ID: xxxxxxxx
 FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
 Contains IC: 4491A-LILYW131

CHARGING STATION

Model: EX-1193-1-48
 In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A
 Enclosure Type: Type 3R
 Temp: -35°C~55°C
 Date:
 SN:

FOR USE WITH ELECTRIC VEHICLES.
 VENTILATION NOT REQUIRED.
 FOR INDOOR OR OUTDOOR USE.
 MADE IN TAIWAN.
 CAN ICES-3(B) / NMB-3(B)



FCC ID: xxxxxxxx
 FCC ID: xxxxxxxx
 FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQ201707BG96
 Contains FCC ID: PPQLILYW131
 Contains FCC ID: PPQRYORR2L
 Contains IC: 4491A-201709BG96
 Contains IC: 4491A-LILYW131
 Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-5-48
 In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A
 Enclosure Type: Type 3R
 Temp: -35°C~55°C
 Date:
 SN:

FOR USE WITH ELECTRIC VEHICLES.
 VENTILATION NOT REQUIRED.
 FOR INDOOR OR OUTDOOR USE.
 MADE IN TAIWAN.
 CAN ICES-3(B) / NMB-3(B)



FCC ID: xxxxxxxx
 FCC ID: xxxxxxxx
 FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
 Contains FCC ID: PPQRYORR2L
 Contains IC: 4491A-LILYW131
 Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-3-48
 In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A
 Enclosure Type: Type 3R
 Temp: -35°C~55°C
 Date:
 SN:

FOR USE WITH ELECTRIC VEHICLES.
 VENTILATION NOT REQUIRED.
 FOR INDOOR OR OUTDOOR USE.
 MADE IN TAIWAN.
 CAN ICES-3(B) / NMB-3(B)



FCC ID: xxxxxxxx
 FCC ID: xxxxxxxx
 FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQLILYW131
 Contains IC: 4491A-LILYW131