

RF Exposure Report

Report No.: MFBHTZ-WTW-P22090089

FCC ID: PPQLILYW131

Test Model: W1-UC168-0MK1ER

Series Model: W1-UC168-0MF1FR, W1-UC168-0MF1F0

Received Date: Sep. 16, 2022

Date of Evaluation: Feb. 20, 2023

Issued Date: Mar. 02, 2023

Applicant: LITE-ON Technology Corp.

Address: Bldg. C, 90, Chien 1 Rd., Chung-Ho, New Taipei City 23585, Taiwan
(R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration /
Designation Number: 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Description of EUT.....	5
2.5 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
MFBHTZ-WTW-P22090089	Original Release	Mar. 02, 2023

1 Certificate of Conformity

Product: AC charging station

Brand: LITEON

Test Model: W1-UC168-0MK1ER

Series Model: W1-UC168-0MF1FR, W1-UC168-0MF1F0

Sample Status: Engineering Sample

Applicant: LITE-ON Technology Corp.

Date of Evaluation: Feb. 20, 2023

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Gina Liu, **Date:** Mar. 02, 2023
Gina Liu / Specialist

Approved by : Jeremy Lin, **Date:** Mar. 02, 2023
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 ANTENNA DESCRIPTION OF EUT

The antenna information is listed as below.

Brand	Antenna Type	Connector	Antenna Gain (dBi)		
			2400	2450	2500
Auden	Dipole	I-PEX	2.2	2.6	3.0

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2.5 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max PK. Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	2412-2462	21.50	3.0	20	0.056	1.00

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	1850-1910	24.00	2.7	26.70	20	0.093	1.00
WCDMA IV	1710-1755	24.00	2	26.00	20	0.079	1.00
WCDMA V	824-849	24.00	1.9	25.90	20	0.077	0.55
LTE 2	1850-1910	24.50	2.7	27.20	20	0.104	1.00
LTE 4	1710-1755	24.50	2	26.50	20	0.089	1.00
LTE 5	824-849	24.50	1.9	26.40	20	0.087	0.55
LTE 12	699-716	24.50	1.9	26.40	20	0.087	0.47
LTE 13	777-787	24.50	1.7	26.20	20	0.083	0.52
LTE 25	1850-1915	25.00	2.7	27.70	20	0.117	1.00
LTE Band 26 (Part 22)	824.7-848.3	25.00	1.9	26.90	20	0.097	0.54
LTE Band 26 (Part 90)	814.7-823.3	25.00	1.9	26.90	20	0.097	0.54

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.
3. The max. power is Tune-up Power.
4. WLAN 2.4G & WWAN & NFC technology can transmit at same time.
5. The EUT contains certified WWAN module with FCC ID: PPQ202008EG91NAXD and NFC module with FCC ID: PPQRYORR2L.

Frequency (MHz)	Field Strength (dBuV/m@3m)	Max. Power (mW)	Min. test separation distance (mm)	SAR test exclusion calculation value ^(NOTE)	1-g extremity SAR test exclusion thresholds	Result
13.56	66.2	0.00125	5	0.00125	1107.433774	Pass

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Calculate SAR test exclusion thresholds from condition “3” formulas.
3. Field Strength (dBuV/m@3m) = Field Strength (dBuV/m@30m) + 40*log(30/3).
4. Max Power (dBm) = Field Strength of Fundamental (dBuV/m@3m) – 95.23,
Max Power (mW) = $10^{(\text{Max power (dBm)}/10)}$

Conclusion:

Both of the WLAN 2.4GHz and WWAN can transmit simultaneously, the formula of calculated the MPE is:

$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$\text{WLAN 2.4GHz} + \text{WWAN} + \text{NFC} = 0.056/1 + 0.087/0.47 + 0.00125/1107.433774 = 0.241$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---