

# RF Exposure Evaluation Report

**Report No.:** 2505R15120EB-A1

**Applicant:** Whirlpool Microwave Products Development Limited.

**Address:** 17th Fl, Elite Centre, 22 Hung To Rd, Kwun Tong, Hong Kong

**Product Name:** Household microwave oven

**Product Model:** MMMF8030P

**Multiple Models:** JMHF730R

**Trade Mark:** MAYTAG, JennAir

**FCC ID:** PR4FLUSHP2MT

**Standards:** 47 CFR §1.1310

KDB 447498 D01 General RF Exposure Guidance v06

**Test Date:** 2025-03-12

**Test Result:** Complied

**Report Date:** 2025-04-17

**Reviewed by:** Ryan Zhang

**Approved by:** Jacob Kong

Ryan Zhang  
Project Engineer

Jacob Kong  
Manager

## Prepared by:

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen,  
Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

## Announcement

1. This test report shall not be reproduced except in full, without the written approval of World Alliance Testing & Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
4. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

## Revision History

| Version No. | Issued Date | Description |
|-------------|-------------|-------------|
| 00          | 2025-04-17  | CIIPC       |

## Contents

|          |                                     |          |
|----------|-------------------------------------|----------|
| <b>1</b> | <b>General Information .....</b>    | <b>4</b> |
| 1.1      | Client Information .....            | 4        |
| 1.2      | Product Description of EUT .....    | 4        |
| 1.3      | Laboratory Location.....            | 4        |
| <b>2</b> | <b>RF Exposure Evaluation .....</b> | <b>5</b> |
| 2.1      | Standard .....                      | 5        |
| 2.2      | Result.....                         | 6        |

# 1 General Information

## 1.1 Client Information

|               |                                                          |
|---------------|----------------------------------------------------------|
| Applicant:    | Whirlpool Microwave Products Development Limited.        |
| Address:      | 17th Fl, Elite Centre,22 Hung To Rd,Kwun Tong, Hong Kong |
| Manufacturer: | Whirlpool Microwave Products Development Limited.        |
| Address:      | 17th Fl, Elite Centre,22 Hung To Rd,Kwun Tong, Hong Kong |

## 1.2 Product Description of EUT

The EUT is Household microwave oven operate on 2450MHz ISM frequency Band.

|                                           |                                        |
|-------------------------------------------|----------------------------------------|
| Sample Serial Number                      | 2ZK0-1 (assigned by WATC)              |
| Sample Received Date                      | 2025-03-11                             |
| Sample Status                             | Good Condition                         |
| Operating Frequency Range                 | 2450MHz±50.0 MHz                       |
| Power Supply                              | AC 120V/60Hz                           |
| Microwave Rated Input Power <sup>#</sup>  | 1800W                                  |
| Microwave Rated Output Power <sup>#</sup> | 950W                                   |
| Modification                              | Sample No Modification by the test lab |

## 1.3 Laboratory Location

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: [qa@watc.com.cn](mailto:qa@watc.com.cn)

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

## 2 RF Exposure Evaluation

### 2.1 Standard

According to §1.1310, radio frequency devices shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Table 1 to § 1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                           | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|-----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(i) Limits for Occupational/Controlled Exposure</b>          |                               |                               |                                     |                          |
| 0.3–3.0                                                         | 614                           | 1.63                          | *(100)                              | ≤6                       |
| 3.0–30                                                          | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | <6                       |
| 30–300                                                          | 61.4                          | 0.163                         | 1.0                                 | <6                       |
| 300–1,500                                                       |                               |                               | f/300                               | <6                       |
| 1,500–100,000                                                   |                               |                               | 5                                   | <6                       |
| <b>(ii) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3–1.34                                                        | 614                           | 1.63                          | *(100)                              | <30                      |
| 1.34–30                                                         | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | <30                      |
| 30–300                                                          | 27.5                          | 0.073                         | 0.2                                 | <30                      |
| 300–1,500                                                       |                               |                               | f/1500                              | <30                      |
| 1,500–100,000                                                   |                               |                               | 1.0                                 | <30                      |

f = frequency in MHz. \* = Plane-wave equivalent power density.

#### Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

## 2.2 Result

| Radio     | Frequency (MHz) | Maximum Conducted Power including Tune-up Tolerance |        | Antenna Gain |           | Min. test separation distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Verdict |
|-----------|-----------------|-----------------------------------------------------|--------|--------------|-----------|------------------------------------|-------------------------------------|---------------------------------|---------|
|           |                 | (dBm)                                               | (mW)   | (dBi)        | (numeric) |                                    |                                     |                                 |         |
| 2.4G WLAN | 2412-2462       | 22.0                                                | 158.49 | 4.2          | 2.63      | 20                                 | 0.0829                              | 1.0                             | Pass    |
| BT        | 2402-2480       | 3.0                                                 | 2.0    | 4.2          | 2.63      | 20                                 | 0.0005                              | 1.0                             | Pass    |
| BLE       | 2402-2480       | 0                                                   | 1.0    | 4.2          | 2.63      | 20                                 | 0.0010                              | 1.0                             | Pass    |

*Note: The device contains a certified Wi-Fi module (Model: RIGEL, FCC ID: 2AC7Z-RIGEL), the Maximum Conducted Power including Tune-up Tolerance and Antenna Gain in above table was refer from the module report.*

For microwave oven, refer report 2505R08116EA-A1, the maximum tested microwave leakage is 0.1mW/cm<sup>2</sup>, the limit is 1.0mW/cm<sup>2</sup>

Simultaneously transmit Consideration:

Microwave Oven + Wi-Fi module

The ratio=0.0829/1.0+0.1/1.0=0.1829<1

**Result: Complied.**

**---End of Report---**