



ETS Dr.GenZ Taiwan PS Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

Accredited Testing Laboratory



A2LA Cert.No.: 2300.01

PTCRB Accredited Type Certification Test House

FCC

TEST - REPORT

FCC Part 15C for IEEE 802.11 g device

FCC ID: PRL-IWE3300

Test report no.: W6M20605-7003-C-2

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	NOTES	3
1.2	TESTING LABORATORY	4
1.2.1	Location	4
1.2.2	Details of accreditation status	4
1.3	DETAILS OF APPROVAL HOLDER	4
1.4	APPLICATION DETAILS	4
1.5	GENERAL INFORMATION OF TEST ITEM	5
1.6	TEST STANDARDS	6
2	TECHNICAL TEST	7
2.1	SUMMARY OF TEST RESULTS	7
2.2	TEST ENVIRONMENT	7
2.3	TEST EQUIPMENT LIST	8
3	TEST RESULTS (ENCLOSURE).....	12
3.1	PEAK OUTPUT POWER (TRANSMITTER)	13
3.2	EQUIVALENT ISOTROPIC RADIATED POWER	14
3.2.1	Transmitter	14
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	14
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS.....	15
3.5	SPURIOUS EMISSIONS (TX)	16
3.6	MINIMUM 6 DB BANDWIDTH	20
3.7	PEAK POWER SPECTRAL DENSITY.....	21
3.8	RADIATED EMISSIONS FROM RECEIVER SECTION OF TRANSCEIVER.....	22
3.9	POWER LINE CONDUCTED EMISSION	26
	APPENDIX.....	28
	APPENDIX A.....	29
	APPENDIX B.....	30
	APPENDIX C.....	31
	APPENDIX D.....	32
	APPENDIX E	33
	APPENDIX F	34
	APPENDIX G.....	35
	APPENDIX H.....	36

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

The test sample is able to work according to IEEE 802.11 g.

This report is related to FCC Part 15 C (OFDM device).

Tester:

July 04, 2006

Jay Chaing



Date

ETS-Lab.


Name

Signature

Technical responsibility for area of testing:

July 04, 2006

Steven Chuang



Date

ETS

Name

Signature

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company
ETS Dr.Genx Taiwan PS Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

PTCRB Accredited Type Certification Test House

1.3 Details of approval holder

Name	: Interepoch Technology, Inc.
Street	: 6F., No.1, Alley 1, Lane 235, Pao-Chiao Rd., Hsin-Tien City,
Town	: Taipei Hsien
Country	: Taiwan, R.O.C.
Telephone	: +886-2-8665-0305
Fax	: +886-2-8665-0306

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

1.4 Application details

Date of receipt of application : May.29, 2006
Date of receipt of test item : Jun.02, 2006
Date of test : from Jun.03, 2006 to Jun.14, 2006

1.5 General information of Test item

Type of test item : High Power Wireless Access Point
Model Number : IWE3300
Brand Name : ./.

Hardware : IWE3300
Software : 2.6.5.4394
Serial number : ./.
Photos : see Annex

Technical data

Frequency band : 2.4 GHz – 2.4835 GHz
Frequency (ch A) : 2.412 GHz
Frequency (ch B) : 2.437 GHz
Frequency (ch C) : 2.462 GHz
Number of Channels : 11
Operation modes : duplex
Modulation Type : DSSS/OFDM

Fixed point-to-point operation: ☐ Yes / ☒ No
Type of Antenna : Antenna 2.4G + R-SMA CONNECTOR
Antenna gain of Antenna : 3.3 dBi

Power supply	Adaptor	Input	: 100 - 240 VAC(ac/dc adaptor)
		Output	: 5 VDC
	POE	Input	: 100 - 240 VAC(ac/dc adaptor)
		Output	: 48 VDC

Emission designator : 16M7W7D

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Host device: none

Classification :

Fixed Device	☒
Mobile Device (Human Body distance > 20cm)	☐
Portable Device (Human Body distance < 20cm)	☐

Transmitter

Unom

Power (ch A) : Conducted: 24.00dBm
Power (ch B) : Conducted: 23.67dBm
Power (ch C) : Conducted: 23.81dBm

Manufacturer:

(if different from applicant)

Name : ./.
Street : ./.
Town : ./.
Country : ./.

Additional information: The sample is using WLAN technology according IEEE 802.11 b/g. For this report the function according IEEE 802.11g is considered only. The scheme for frequency generation, spectrum spreading, receiver parameters, synchronization procedure, and other parameters are determined by the mentioned standard above.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART B / SUBPART C § 15.247 : September 2005

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	:	23 °C
Relative humidity content	:	20 ... 75 %
Air pressure	:	86 ... 103 kPa
Power supply	Adaptor	Input : 100 - 240 VAC(ac/dc adaptor)
		Output : 5 VDC
	POE	Input : 100 - 240 VAC(ac/dc adaptor)
		Output : 48 VDC
Extreme conditions parameters	:	--

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2005/10/27	2006/10/26
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY	None	None	T-POWER	Function Test	
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2005/10/25	2006/10/24
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2005/10/21	2006/10/20
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2004/11/11	2006/11/10
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS-MESSWANDLER-ZANGE	2005/10/24	2007/10/23
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2005/8/18	2006/8/17
ETSTW-CS 001	SIGNAL GENERATOR	SMX	849254/003	R&S	2005/10/14	2006/10/13
ETSTW-CS 002	COUPLING AND DECOUPLING NETWORK	CDN S751	19263	SCHAFFNER	2005/10/14	2006/10/13
ETSTW-CS 003	COUPLING AND DECOUPLING NETWORK	CDN T400	19820	SCHAFFNER	2005/10/14	2006/10/13
ETSTW-CS 004	COUPLING AND DECOUPLING NETWORK	CDN M016	20053	SCHAFFNER	2005/10/27	2006/10/26
ETSTW-CS 005	RF Power Amplifier	100A250A	306547	AR	2005/10/14	2006/10/13
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2005/10/14	2007/10/13
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2005/10/24	2006/10/23
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2005/10/29	2006/10/30
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2005/10/16	2006/10/15
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	2006/5/4	2008/5/3
ETSTW-RE 018	ANTENNA	AT4560	27212	AR	2004/11/8	2007/11/7
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2005/10/14	2006/10/13
ETSTW-RE 022	AMPLIFIER	8447D	2944A09837	Agilent	2005/10/14	2006/10/13
ETSTW-RE 026	Open Area Test Site	10m	None	ETS	NSA Measurement	
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	2004/6/30	2007/6/29
ETSTW-RE 028	Log-Periodic DipoleArray Antenna	3148	34429	EMCO	2006/5/26	2008/5/25
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2006/5/26	2008/5/25
ETSTW-RE 030	Double-Ridged Waveguide Horn Antenna	3117	35224	EMCO	2006/5/3	2008/5/2
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2005/10/17	2006/10/16
ETSTW-RE 033	4CH 1GHz 5GS/s DSO	WAVERUNNER 6100A	LCRY0604P14508	LeCory	2005/8/11	2006/8/10
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2005/10/17	2006/10/16
ETSTW-RE 037	Log-Periodic DipoleArray Antenna	3148	00034546	EMCO	2004/11/18	2006/11/17
ETSTW-RE 038	Log-Periodic DipoleArray Antenna	3148	00034547	EMCO	2004/11/18	2006/11/17
ETSTW-RE 039	Biconical Antenna	3110B	41760	EMCO	2004/11/18	2006/11/17
ETSTW-RE 040	Biconical Antenna	3110B	41761	EMCO	2004/11/18	2006/11/17
ETSTW-RE 042	ANTENNA	HK116	100172	R&S	2005/1/14	2007/1/13
ETSTW-RE 043	ANTENNA	HL223	100166	R&S	2006/5/8	2008/5/7
ETSTW-RE 044	ANTENNA	HL050	100094	R&S	2006/5/29	2008/5/28
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2005/3/22	2008/3/21
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2005/5/19	2007/5/18
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2005/9/6	2006/9/5
ETSTW-EMI 001	HARMONICS 1000	HAR1000-1P	93	EMC-PARTNER	2005/9/12	2006/9/11

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

ETSTW-EMS 001	Clamp BASELSTRASSE 160 CH-4242 LAUFEN	CN-EFT1000	354	EMC-PARTNER	2004/11/2	2006/11/1
ETSTW-EMS 002	Frequency Converter	YF-6020	0308014	T-POWER	Function Test	
ETSTW-EMS 003	EMC Immunity Test System	TRA2000IN6	579	EMC-PARTNER	2005/10/27	2006/10/26
ETSTW-EMS 004	ESD generator minizap	ESD2000	016	EMC-PARTNER	2005/10/27	2006/10/26
ETSTW-EMS 005	Attenautor (50Ω)	VERI50	051	EMC-PARTNER	2004/8/31	2006/8/30
ETSTW-EMS 006	Attenautor (1 KΩ)	VERI1K	019	EMC-PARTNER	2004/10/21	2006/10/20
ETSTW-EMS 008	Safety Test Solutions	ELT-400	E-0039	Narda	2005/5/4	2007/5/3
ETSTW-EMS 009	Magnetic Field Antenna	MF1000-1	104	EMC-PARTNER	2004/12/3	2007/12/2
ETSTW-EMS 010	Coupling De-coupling Network	CDN-UTP8	014	EMC-PARTNER	2005/9/1	2008/8/31
ETSTW-EMS 011	Calibration Fixture	F-2031-CF-23MM	451	FCC	2005/8/11	2007/8/11
ETSTW-EMS 012	EM Injection Clamp	F-2031-23MM	476	FCC	2005/8/11	2007/8/10
ETSTW-RS 003	RF Power Amplifier	30S1G3	306933	AR	Function Test	
ETSTW-RS 004	RF Power Amplifier	150W1000	307009	AR	2005/10/21	2006/10/20
ETSTW-RS 005	Electric Field Probe Type 8.3	EMR-20	BN 2244/20	Narda	2005/9/7	2007/9/6
ETSTW-RS 006	SIGNAL GENERATOR	SML03	101551	R&S	2005/10/21	2006/10/20
ETSTW-GSM 01	SIM Simulator	IT3	B2004-50106	ORGA	2005/9/15	2006/9/14
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	103489	R&S	2005/11/15	2006/11/14
ETSTW-GSM 03	Agilent 8960 Test Set 1	E5515C	GB44052675	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 04	Agilent 8960 Test Set 2	E5515C	GB44052665	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 05	Agilent 8960 Test Set 3	E5515C	GB44052652	Agilent	2004/7/17	2006/7/16
ETSTW-GSM 06	Agilent 8960 Test Set 4	E5515C	GB44052684	Agilent	2004/7/16	2006/7/15
ETSTW-GSM 07	Agilent 8960 Test Set 5	E5515C	GB44052658	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 08	Agilent 8960 Test Set 6	E5515C	GB44052666	Agilent	2004/7/16	2006/7/15
ETSTW-GSM 09	Controller PC	Dell GX 270	700F61J	Dell	Function Test	
ETSTW-GSM 10	Combiner Wessex / Anite	B4605/100	053	Wessex / Anite	2004/7/14	2006/7/13
ETSTW-GSM 11	GSM 850,900,1800,1900 Test system	TS8950G		R&S	2005/11/1	2006/10/31
ETSTW-GSM 12	Acoustical Calibrator	4231	2463874	Brüel&Kjær	2005/10/31	2006/10/30
ETSTW-GSM 13	Conditioning Amplifier	2690--0S2	2437856	Brüel&Kjær		
ETSTW-GSM 14	Telephone Test Head	4602B	2465324	Brüel&Kjær		
ETSTW-GSM 15	Mouth Simulator	4227	2462516	Brüel&Kjær		
ETSTW-GSM 16	TEMP.&HUMIDITY CHAMBER	GTH-120-40-1P-U	MAA0501002	GIANT FORCE	2005/12/29	2006/12/28
ETSTW-GSM 18	AUDIO ANALYZER	UPL16	100173	R&S	2005/10/29	2006/10/28
ETSTW-GSM 24	Vibration Testing System	VS-100V	5494	Vibration	2005/12/20	2006/12/19

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Dr.Genx Taiwan PS Co., Ltd. at the registered open field test site located at No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.) The Registration Number: 930600.

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANTENNA & GROUND:

This unit uses Antenna 2.4G+R-SMA CONNECTOR. (see photos)

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	☒	☒	☐
Equivalent radiated Power	15.247(b)(3)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(c)	☒	☒	☐
Band Edge Measurement	15.247(c)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(d)	☒	☒	☐
Radiated Emission from Digital Part And Receiver L.O.	15.109	☒	☒	☐
Power Line Conducted Emission	15.207	☒	☒	☐

The follows is intended to leave blank.

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
		[dBm]	[dBm]	[dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	24.00	23.67	23.81
Measurement uncertainty		< 3 dB		

Test condition $T_{nom} = 23^{\circ}\text{C}$, $V_{nom} = 120 \text{ V}$	Signal Field strength TX highest power mode dB $\mu\text{V/m}$
Frequency [MHz]	
2412	110.68
Measurement uncertainty	< 3 dB

Remarks: The diagrams for the field strength measurements are included in Appendix.

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to-point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 055

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

EIRP = 24.00dBm + 3.3dBi

= 27.30dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

3.2.1 Transmitter

Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules § 15.247, subpart C, section b.

3.3 RF Exposure Compliance Requirements

The test sample is a WLAN access point intended for fixed installation.

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4\pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain G = AG-D

Item	Unit	Value	Remarks
P	mW	251.1886	Peak value
D	dB		
AG	dBi	2.2	
G		3.3	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.16537	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1,0

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 1000 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency $\leq$ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 100Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of DSSS Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

No duty cycle correction was added to the reading.

$54.0\text{dB } \mu\text{V/m} + 20 \text{ dB} = 74 \text{ dB } \mu\text{V/m}$

Remarks: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 017

ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 042, ETSTW-RE 043

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz:

Max. reading – 20 dB

$110.68\text{dB } \mu\text{V/m} - 20\text{ dB} = 90.68\text{dB } \mu\text{V/m}$

Guidance on Measurement of DSSS Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. Reading-20dB+20dB(because Peak detector is used)

$90.68\text{dB } \mu\text{V/m}$

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

No duty cycle correction was added to the reading

$110.68\text{dB } \mu\text{V/m} - 20\text{ dB} = 90.68\text{dB } \mu\text{V/m}$

Remarks: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 017
ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 042 ETSTW-RE 043

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Duty-Cycle Correction Factor".

Summary table with radiated data of the test plots

Low Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	QP	PK	AV	PK	AV		
H	2390	52.78	36.16	2.05	54.83	38.21	74	54	19.17	15.79	271	284
	4817.635	44.89	--	2.25	47.14	--	--	54	--	6.86	216	164
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	265.731	22.67	--	14.22	36.89	--	--	46	--	9.11	223	331
	499.799	27.23	--	19.81	47.04	--	90.68	--	--	45.7	85	261
	125.05	24.74	--	13.88	38.62	--	--	43.52	--	4.9	322	292

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	AV	PK	AV	PK	AV		
V	2332.124	51.79	39.16	2.09	53.88	41.25	74	54	20.12	12.75	177	208
	2492.262	54.77	--	-1.44	53.33	--	--	54	--	13.38	198	272
	2390	69.63	51.27	2.05	71.68	53.32	74	54	2.32	0.68	188	262
	4817.635	45.84	--	2.25	48.09	--	--	54	--	5.91	205	132
	9643.286	37.48	--	10.67	48.15	--	90.68	--	--	44.59	318	156
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	265.731	19.91	--	14.22	34.13	--	--	46	--	11.87	276	260
	499.799	23.13	--	19.81	42.94	--	90.68	--	--	49.8	179	265
	125.05	26.8	--	13.88	40.68	--	--	43.52	--	2.84	291	208
	133.226	--	28.59	14.22	--	42.81	--	43.52	--	0.71	288	194

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Middle Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	QP	PK	AV	PK	AV		
H	2489.71	48.31	--	-1.39	46.92	--	--	54	--	7.08	198	342
	4873.747	55.66	--	4.81	48.62	--	--	54	--	5.38	267	155
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	265.731	23.04	--	14.22	37.26	--	--	40	--	2.74	227	327
	499.799	27.63	--	19.81	47.44	--	90.68	--	--	43.24	88	263
	125.05	23.94	--	13.88	37.82	--	--	43.52	--	5.7	308	299

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	AV	PK	AV	PK	AV		
V	2358.897	52.79	40.7	2.07	54.86	42.77	74	54	19.14	11.23	180	265
	2384.068	53.04	40.07	2.08	55.12	42.15	74	54	18.88	11.85	177	256
	2489.584	56.07	43.05	-1.39	54.68	41.66	74	54	19.32	12.34	195	277
	4873.747	42.56	--	4.81	47.37	--	--	54	--	6.63	2.44	149
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	265.731	19.31	--	14.22	33.53	--	--	46	--	12.47	284	262
	499.799	23.46	--	19.81	43.27	--	90.68	--	--	47.41	178	269
	125.05	26.53	--	13.88	40.41	--	--	43.52	--	3.11	288	212
	133.226	29.18	27.99	14.22	--	42.21	--	43.52	--	0.12	296	198

High Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	QP	PK	AV	PK	AV		
H	7385.49	49.33	32.43	6.29	55.62	38.72	74	54	18.38	15.28	267	378
	4929.859	41.93	--	4.35	46.28	--	--	54	--	7.72	287	363
	2483.5	62.42	48.92	-1.09	61.33	47.83	74	54	12.67	6.17	256	278
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	265.731	22.91	--	14.22	37.13	--	--	46	--	8.87	228	327
	499.799	27.07	--	19.81	46.88	--	90.68	--	--	45.8	89	286
	125.05	23.6	--	13.88	37.48	--	--	43.52	--	6.04	315	287

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	AV	PK	AV	PK	AV		
V	2378.937	52.75	41.07	2.08	54.83	43.15	74	54	19.17	10.85	179	215
	2483.5	70.41	53.87	-1.09	69.32	52.78	74	54	4.68	1.22	191	265
	4921.843	43.44	--	4.35	47.79	--	--	54	--	6.21	211	143
	7386.492	47.82	33.48	6.29	54.11	39.77	74	54	19.89	14.23	188	294
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	265.731	19.52	--	14.22	33.74	--	--	46	--	12.26	288	254
	499.799	23.04	--	19.81	42.85	--	90.68	--	--	47.38	178	271
	125.05	27.18	--	13.88	41.06	--	--	43.52	--	2.46	281	277
	133.226	--	28.34	14.22	--	42.56	--	43.52	--	0.96	291	196

- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Corrected Reading + Correction Factor
 3. Detector function in the form : P = Peak, QP = Quasi Peak, AV = Average

Freq. – Frequency Range:

- 1: 30 - 200 MHz
- 2: 200 - 1000 MHz
- 3: 1 - 4 GHz
- 4: 4 - 8 GHz
- 5: 8 - 12 GHz
- 6: 12 - 17 GHz
- 7: 17 - 26.5 GHz

All not in the table noted test results are more than 20 dB below the relevant limits.

All other not noted test polts do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 017

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

3.6 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.

Test conditions		6 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{\text{nom}} = 23^{\circ}\text{C}$	$V_{\text{nom}} = 120 \text{ V}$	16.538 MHz	16.506MHz	16.538 MHz
Measurement uncertainty			< 10 Hz	

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 055

Comment: see attached diagram

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

3.7 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.

The Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, and Set VBW > RBW, sweep= (SPAN/3 kHz) e.g., for a span of 1.5 MHz, the sweep should be $1.5 \times 10^6 \div 3 \times 10^3 = 500$ seconds. The peak level measured must be no greater than + 8 dBm.

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	-17.34	-18.32	-18.73
Measurement uncertainty		< 3 Hz		

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483,5	8
5725-5850	8

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 055

Comment: see attached diagram

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

3.8 Radiated Emissions from Receiver Section of Transceiver

FCC Rule: 15.109

Summary table with radiated data of the test plots

RX

Low Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	QP	PK	AV	PK	AV		
H	1733.466	42.63	--	-5.96	36.67	--	--	54	--	17.33	269	322
	1865.731	41.6	--	-4.75	36.85	--	--	54	--	17.15	165	269
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	499.799	--	25.4	19.81	--	45.21	--	46	--	0.79	338	354
	900.601	13.59	--	26.22	39.81	--	--	46	--	6.19	79	267
	125.05	24.35	--	13.88	38.44	--	--	43.5	--	5.27	58	332
	145.15	22.2	--	15.05	37.25	--	--	43.5	--	6.25	216	371

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	AV	PK	AV	PK	AV		
V	1733.466	40.19	--	-5.96	34.23	--	--	54	--	19.77	178	127
	3218.436	39.33	--	0.29	39.62	--	--	54	--	14.38	223	264
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	499.799	--	22.52	19.81	--	42.33	--	46	--	1.83	186	273
	900.601	13.01	--	26.22	39.23	--	--	46	--	6.77	271	383
	145.15	--	25.83	15.05	--	40.88	--	43.5	--	2.62	211	161
	133.226	--	27.93	14.22	--	42.15	--	43.5	--	1.35	183	187

Middle Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	QP	PK	AV	PK	AV		
H	1462.925	43.51	--	-7.92	35.59	--	--	54	--	18.41	263	256
	1733.466	42.55	--	-5.96	36.59	--	--	54	--	17.41	172	268
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	499.799	--	25.52	19.81	--	45.33	--	46	--	0.67	332	318
	900.601	12.78	--	26.22	39	--	--	46	--	7	89	284
	125.05	24.35	--	13.88	38.23	--	--	43.5	--	5.27	62	341
	145.15	21.23	--	15.05	36.28	--	--	43.5	--	7.22	224	374

Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	AV	PK	AV	PK	AV		
V	1733.466	40.36	--	-5.96	34.4	--	--	54	--	19.6	181	123
	3218.468	40.12	--	0.29	40.41	--	--	54	--	13.59	215	255
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	499.799	--	22.75	19.81	--	42.56	--	46	--	1.79	178	271
	900.601	13.79	--	26.22	40.01	--	--	46	--	5.99	275	285
	145.15	--	25.73	15.05	--	40.78	--	43.5	--	2.72	208	154
	133.226	--	27.83	14.22	--	42.05	--	43.5	--	1.45	181	177

High Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	QP	PK	AV	PK	AV		
H	1733.466	41.96	--	-5.96	36	--	--	54	--	18	278	312
	1865.731	40.67	--	-4.75	35.92	--	--	54	--	18.08	163	278
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	900.601	6.41	--	26.22	39.7	--	--	46	--	19.78	312	338
	499.799	--	25.42	19.81	--	45.23	--	46	--	0.77	88	279
	125.05	23.95	--	13.88	37.83	--	--	43.5	--	5.67	61	337
	145.15	22.73	--	15.05	37.78	--	--	43.5	--	5.72	208	375

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	AV		PK	AV	PK	AV	PK	AV		
V	1733.466	39.97	--	-5.96	34.01	--	--	54	--	19.99	178	116
	3218.436	39.59	--	0.29	39.88	--	--	54	--	14.12	208	262
	1462.925	44.53	--	-7.54	36.99	--	--	54	--	17.01	214	293
	Frequency Marker (MHz)	Corrected Reading (dBuV)		Correction Factor (dB)	Test Result (dBuV/m)		Compliance Limit (dBuV/m)		Margin (dB)		Table Azimuth (degree)	Antenna Height (cm)
		PK	QP		PK	QP	PK	QP	PK	QP		
	499.799	--	22.97	19.81	--	42.78	--	46	--	1.68	177	269
	900.601	13.35	--	26.22	39.57	--	--	46	--	6.43	273	283
	133.226	--	26.66	14.22	--	42.63	--	43.5	--	0.87	189	191
	145.15	--	25.27	15.05	--	40.32	--	43.5	--	3.18	206	160

Note

1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Corrected Reading + Correction Factor
3. Detector function in the form : P = Peak, QP = Quasi Peak, AV = Average

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

Digital -Adaptor

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
H	133.226	20.69	15.58	PK	36.27	43.5	7.23	217	345
	149.919	22	15.39	PK	37.39	43.5	6.11	83	362
	166.613	23.14	15.12	PK	38.26	43.5	5.24	196	312
	499.799	23.06	19.81	QP	42.87	46	3.13	83	294
	533.466	20.45	20.37	PK	40.82	46	5.18	172	284
	900.601	14.92	26.25	PK	41.17	46	4.83	183	267

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
V	39.539	22.2	13.58	PK	35.78	40	4.22	83	196
	133.226	27.93	14.22	QP	42.15	43.5	1.35	193	181
	145.15	25.23	15.05	QP	40.28	43.5	3.22	219	162
	499.799	19.19	19.81	PK	39	46	7	79	254
	833.266	14.77	25.54	PK	40.31	46	5.69	156	211
	900.601	12.96	26.25	PK	39.21	46	6.79	271	236

Digital –POE

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
H	299.398	23.38	15.24	PK	38.62	46	7.38	83	248
	499.799	22.3	19.81	PK	42.11	46	3.89	217	256
	265.731	22.23	14.22	PK	36.45	46	9.55	143	294
	65.771	24.51	13.41	QP	37.92	40	2.08	217	362
	133.226	25.11	14.22	PK	39.33	43.5	4.17	168	378
	175.13	25.82	14.55	QP	40.37	43.5	3.13	88	356

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
V	499.799	23.37	19.81	PK	43.18	46	2.82	88	296
	533.466	20.89	20.37	PK	41.26	46	4.74	217	274
	299.398	23.72	15.24	PK	38.96	46	7.04	313	315
	449.989	13.73	13.68	QP	27.41	40	2.59	321	157
	66.112	26.16	12.01	QP	38.17	40	1.83	147	126
	133.567	21.38	14.22	PK	35.6	43.5	7.9	158	178

- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Corrected Reading + Correction Factor
 3. Detector function in the form : P = Peak, QP = Quasi Peak, AV = Average

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 028
ETSTW-RE 029, ETSTW-RE 042, ETSTW-RE 043

Comment: see attached diagram

3.9 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dB μ V)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

(Adaptor)

LISN type	Frequency Marker	Corrected Reading (dBuV)		Correction Factor	Test Result (dBuV)		Compliance Limit (dBuV)		Margin (dB)	
		QP	AV		QP	AV	QP	AV	QP	AV
N	MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	0.64	39.7	32.1	10.1	49.8	42.2	56	46	6.2	3.8
	3.67	31.6	21.6	10.1	41.7	31.7	56	46	14.3	14.3
	8.44	32.6	25.8	10.1	42.7	35.9	60	50	17.3	14.1
	26.06	23.6	17.2	10.1	33.7	27.3	60	50	26.3	22.7

LISN type	Frequency Marker	Corrected Reading (dBuV)		Correction Factor	Test Result (dBuV)		Compliance Limit (dBuV)		Margin (dB)	
		QP	AV		QP	AV	QP	AV	QP	AV
L1	MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	0.64	36.4	22.4	10.1	46.5	32.5	56	46	9.5	13.5
	2.62	32	21.7	10.1	42.1	31.8	56	46	13.9	14.2
	5.99	33.3	26.3	10.1	43.4	36.4	60	50	16.6	13.6
	24.47	20.3	13.7	10.1	30.4	23.8	60	50	29.6	26.2

(POE)

LISN type	Frequency Marker	Corrected Reading (dBuV)		Correction Factor	Test Result (dBuV)		Compliance Limit (dBuV)		Margin (dB)	
		QP	AV		QP	AV	QP	AV	QP	AV
N	MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	0.65	28.72	18.27	10.1	38.82	28.37	56	46	17.18	17.63
	1.15	28.04	14.44	10.1	38.14	24.54	56	46	17.86	21.46
	1.44	27.99	17.4	10.1	38.09	27.5	56	46	17.91	18.5
	7.98	35.69	28.27	10.1	45.79	38.37	60	50	14.21	11.63

Registration number: W6M20605-7003-C-2

FCC ID: PRL-IWE3300

LISN type	Frequency Marker	Corrected Reading (dBuV)		Correction Factor	Test Result (dBuV)		Compliance Limit (dBuV)		Margin (dB)	
		QP	AV		QP	AV	QP	AV	QP	AV
L1	0.64	29.89	22.13	10.1	39.99	32.23	56	46	16.01	13.77
	1.14	29.72	21.64	10.1	39.82	31.74	56	46	16.18	14.26
	1.71	29.77	22.26	10.1	39.87	32.36	56	46	16.13	13.64
	8.04	39.8	31.56	10.1	49.9	41.66	60	50	10.1	8.34

Note: 1. The formula of measured value as: Test Result = Corrected Reading + Correction Factor

2. The Correction Factor = Cable Loss + LISN Insertion Loss

3. Detector function in the form : P = Peak, QP = Quasi Peak, AV = Average

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 003, ETSTW-CE 004, ETSTW-CE 006

Comment: see attached diagram

Appendix

- A Peak Output Power
- B Spurious Emissions radiated – Transmitter operating
- C Band Edge Measurement
- D Minimum 6dB Bandwidth
- E Peak Power Spectral Density
- F Radiated Emissions from Receiver Section of Transceiver
- G Power Line Conducted Emission
- H Pictures




Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix A


Peak Output Power

The measurement diagram are wideband pre-scan results; only for reference.




MAX OUTPUT POWER 802.11g ch 1

Date: 9.AUG.2006 19:22:49



MAX OUTPUT POWER 802.11g ch 6

Date: 9.AUG.2006 19:27:51




MAX OUTPUT POWER 802.11g ch 11

Date: 9.AUG.2006 20:10:12

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.419GHz, Emax: 97.28dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.415GHz, Emax: 109.08dBμV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.439GHz, Emax: 100.99dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.440GHz, Emax: 108.96dBμV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO.: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.464GHz, Emax: 100.88dBμV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.464GHz, Emax: 110.68dBμV/m, RBW: 1MHz





Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix B


Spurious Emissions radiated – Transmitter operating

The measurement diagram are wideband pre-scan results; only for reference.

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


ET: Higher Wireless Access at
MODENO: IWE300 802.11g b1
Approval Holder: Intereph Technologies
Test Site / Operator: ES / Orville
Temperature/Voltage: Temp.: 24.9C/ Unm.: 120 VAC (ac/ dcAdaptor)
Test Specification: adding to 5.247
Comment 1: Dist.: 3m, Ant.: HK116
Freq 125.050MHz, Max 38.62dBu/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 133.226MHz, Emax: 44.03dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 47.04dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 42.94dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.400GHz, Emax: 65.78dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.400GHz, Emax: 87.62dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.639GHz, Emax: 52.09dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.222GHz, Emax: 52.18dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.631GHz, Emax: 48.74dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.663GHz, Emax: 48.70dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.832GHz, Emax: 52.46dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.880GHz, Emax: 53.05dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.466GHz, Emax: 51.13dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.466GHz, Emax: 50.72dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


ET: High Power Wireless Access Point
MODENO: WB300 802.11g ch 6
ApprovalHolder: Interepoch Technology Inc.
Test Site / Operator: ES / Orville
Temperature/Voltage: Temp.: 24.9°C / Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §5.247
Comment 1: Dist.: 3m, Ant.: HK116
Freq 166.613MHz, Max 38.25dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 133.226MHz, Emax: 43.40dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 47.44dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 43.27dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.520GHz, Emax: 47.83dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.398GHz, Emax: 63.56dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.447GHz, Emax: 52.11dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.679GHz, Emax: 52.26dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.671GHz, Emax: 48.64dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.896GHz, Emax: 48.79dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.772GHz, Emax: 52.73dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.723GHz, Emax: 52.19dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.449GHz, Emax: 51.27dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.325GHz, Emax: 51.75dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 166.613MHz, Emax: 37.54dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 133.226MHz, Emax: 44.19dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 46.88dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 42.85dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.484GHz, Emax: 60.35dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.484GHz, Emax: 76.18dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.399GHz, Emax: 54.91dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.383GHz, Emax: 53.23dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.952GHz, Emax: 48.61dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.519GHz, Emax: 48.66dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.844GHz, Emax: 52.76dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.880GHz, Emax: 52.70dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.699GHz, Emax: 51.11dBμV/m, RBW: 1MHz




Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.296GHz, Emax: 51.37dBμV/m, RBW: 1MHz






Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300


Appendix C

Band Edge Measurement



Bandedge 802.11g ch 1

Date: 13.JUN.2006 10:37:33



Bandedge 802.11g ch 11
Date: 13.JUN.2006 10:36:39




Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix D

Minimum 6dB Bandwidth




1 PK
MAXH



6dB BANDWIDTH 802.11g CH 1
Date: 16.JUN.2006 08:58:36



1 PK
MAXH



6dB BANDWIDTH 802.11g CH 6
Date: 16.JUN.2006 09:00:48




*RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz 2.40 dB
*SWT 500 ms 16.538461538 MHz

Ref 33.5 dBm

*Att 25 dB

1 PK
MAXH



Center 2.462 GHz

2 MHz/

Span 20 MHz

6dB BANDWIDTH 802.11g CH11

Date: 16.JUN.2006 08:56:12



Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix E

Peak Power Spectral Density




*RBW 3 kHz Marker 1 [T1]
*VBW 100 kHz -17.34 dBm
*SWT 500 s 2.412697115 GHz

Ref 33.5 dBm

*Att 25 dB

1 PK
MAXH



Center 2.412 GHz

150 kHz/

Span 1.5 MHz

Power density 802.11g ch 1

Date: 13.JUN.2006 10:39:13




*RBW 3 kHz Marker 1 [T1]
*VBW 100 kHz -18.32 dBm
*SWT 500 s 2.437649038 GHz

Ref 33.5 dBm

*Att 25 dB

1 PK
MAXH



A

LVL

Center 2.437 GHz

150 kHz/

Span 1.5 MHz

Power density 802.11g ch 6

Date: 13.JUN.2006 10:40:46




*RBW 3 kHz Marker 1 [T1]
*VBW 100 kHz -18.73 dBm
*SWT 500 s 2.462651442 GHz

Ref 33.5 dBm

*Att 25 dB

1 PK
MAXH



A

LVL

Power density 802.11g ch 11

Date: 13.JUN.2006 10:42:05



Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix F


Radiated Emissions from Receiver Section of Transceiver

The measurement diagram are wideband pre-scan results; only for reference.

Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 125.050MHz Emax: 38.44dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:133.226MHz Emax:43.92dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 47.50dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 44.07dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:1.866GHz Emax:36.85dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.218GHz Emax:39.62dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq: 7.615GHz Emax: 46.02dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.784GHz Emax:46.44dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.655GHz Emax:50.66dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.976GHz Emax:51.00dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.627GHz Emax:52.25dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 1
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.904GHz Emax:52.65dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:125.050MHz Emax:38.23dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:133.226MHz Emax:44.01dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 48.04dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 44.21dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.820GHz Emax:36.65dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.218GHz Emax:40.41dBµV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.776GHz Emax:46.63dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.800GHz Emax:47.10dBµV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.535GHz Emax:51.16dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.992GHz Emax:51.12dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.832GHz Emax:52.39dBµV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 6
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.808GHz Emax:52.08dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:125.050MHz Emax:38.03dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:133.226MHz Emax:44.16dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 47.93dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 44.32dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.982GHz Emax:36.82dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.218GHz Emax:39.88dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.687GHz Emax:46.52dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.423GHz Emax:46.30dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.752GHz Emax:51.10dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.607GHz Emax:51.20dBµV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.820GHz Emax:52.40dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300 802.11g ch 11
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.844GHz Emax:52.54dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:166.613MHz Emax:37.57dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:133.226MHz Emax:43.43dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 43.85dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 833.267MHz Emax: 40.31dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on POE)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:175.130MHz Emax:41.67dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on POE)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 66.112MHz Emax: 48.84dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on POE)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 41.48dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B

EUT: High Power Wireless Access Point
MODEL NO: IWE3300
Approval Holder: Interepoch Technology, Inc.
Test Site / Operator: ETS / Orville
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on POE)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq: 499.800MHz Emax: 42.96dB μ V/m RBW: 100 kHz





Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix G


Power Line Conducted Emission

The measurement diagram are wideband pre-scan results; only for reference.

EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: High power Wireless Access Point
Approval Holder: Interepoch Technology, Inc.
Operating Condition: Unom : 120 VAC (ac/dc adaptor) Tnom : 24.2°C
Test Site: ETS
Operator: Dennis
Test Specification: V-network: ESH3-Z5 N
Comment: model: IWE3300 mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: High power Wireless Access Point
Approval Holder: Interepoch Technology, Inc.
Operating Condition: Unom : 120 VAC (ac/dc adaptor) Tnom : 24.2°C
Test Site: ETS
Operator: Dennis
Test Specification: V-network: ESH3-Z5 L1
Comment: model: IWE3300 mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: High power Wireless Access Point
Approval Holder: Interepoch Technology, Inc.
Operating Condition: Unom : 120 VAC (power on POE) Tnom : 24.2°C
Test Site: ETS
Operator: Dicky
Test Specification: V-network: ESH3-Z5 N
Comment: model: IWE3300 mode: active




EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: High power Wireless Access Point
Approval Holder: Interepoch Technology, Inc.
Operating Condition: Unom : 120 VAC (power on POE) Tnom : 24.2°C
Test Site: ETS
Operator: Dicky
Test Specification: V-network: ESH3-Z5 L1
Comment: model: IWE3300 mode: active





Registration number: W6M20605-7003-C-2
FCC ID: PRL-IWE3300

Appendix H

Pictures