

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC1906-0203(1)
2. Customer
 - Name : SystemBase Co., Ltd.
 - Address : Daerung Post Tower-1 16F, 288, Digital-ro, Guro-gu, Seoul, South Korea
3. Use of Report : FCC Original Grant
4. Product Name / Model Name : Bluetooth USB Adapter / TALUS
FCC ID : PROTALUS2
5. Test Method Used : ANSI C63.10-2013, KDB 558074D01v05r02
Test Specification : FCC Part 15 Subpart C.247
6. Date of Test : 2019.05.16 ~ 2019.05.21
7. Testing Environment : See appended test report.
8. Test Result : Refer to the attached test result.

Affirmation	Tested by	Reviewed by
	Name : WooHyun Rim 	Name : JaeJin Lee 

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2019 . 06 . 17 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRTFCC1906-0203	Jun. 10, 2019	Initial issue
DRTFCC1906-0203(1)	Jun. 17, 2019	Add the test method

Table of Contents

1. General Information	4
1.1 Testing Laboratory	4
1.2 Testing Environment	4
1.3 Measurement Uncertainty	4
1.4 Details of Applicant	5
1.5 Description of EUT	5
1.6 Declaration by the applicant / manufacturer	5
1.7 Information about the FHSS characteristics	6
1.8 Test Equipment List.....	7
1.9 Summary of Test Results.....	8
1.10 Conclusion of worst-case and operation mode.....	9
2. Maximum Peak Output Power Measurement	10
2.1 Test Setup	10
2.2 Limit.....	10
2.3 Test Procedure.....	10
2.4 Test Results	11
3. 20 dB BW	17
3.1 Test Setup	17
3.2 Limit.....	17
3.3 Test Procedure.....	17
3.4 Test Results	17
4. Carrier Frequency Separation	23
4.1 Test Setup	23
4.2 Limit.....	23
4.3 Procedure.....	23
4.4 Test Results	23
5. Number of Hopping Frequencies	28
5.1 Test Setup	28
5.2 Limit.....	28
5.3 Procedure.....	28
5.4 Test Results	28
6. Time of Occupancy (Dwell Time).....	34
6.1 Test Setup	34
6.2 Limit.....	34
6.3 Test Procedure.....	34
6.4 Test Results	34
7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	39
7.1 Test Setup	39
7.2 Limit.....	39
7.3. Test Procedures.....	40
7.3.1. Test Procedures for Radiated Spurious Emissions	40
7.3.2. Test Procedures for Conducted Spurious Emissions.....	41
7.4. Test Results	42
7.4.1. Radiated Emissions.....	42
7.4.2. Conducted Spurious Emissions	52
8. Transmitter AC Power Line Conducted Emission	76
8.1 Test Setup	76
8.2 Limit.....	76
8.3 Test Procedures.....	76
8.4 Test Results	77
9. Antenna Requirement.....	83
APPENDIX I.....	84
APPENDIX II.....	85

1. General Information

1.1 Testing Laboratory

DT&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.		
- FCC MRA Accredited Test Firm No. : KR0034		
www.dtnet.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.2 Testing Environment

Ambient Condition	
▪ Temperature	+20 °C ~ +25 °C
▪ Relative Humidity	39 % ~ 45 %

1.3 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Test items	Measurement uncertainty
Transmitter Output Power	0.9 dB (The confidence level is about 95 %, $k = 2$)
Conducted spurious emission	0.9 dB (The confidence level is about 95 %, $k = 2$)
AC conducted emission	2.4 dB (The confidence level is about 95 %, $k=2$)
Radiated spurious emission (1 GHz Below)	5.1 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (1 GHz ~ 18 GHz)	5.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

1.4 Details of Applicant

Applicant : SystemBase Co., Ltd.
Address : Daerung Post Tower-1 16F, 288, Digital-ro, Guro-gu, Seoul, South Korea
Contact person : Myunghyun Kim

1.5 Description of EUT

EUT	Bluetooth USB Adapter
Model Name	TALUS
Add Model Name	NA
Serial Number	Identical prototype
Power Supply	DC 5 V
Frequency Range	2402 MHz ~ 2480 MHz
Modulation Technique	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels	79
Antenna 1 /Antenna Gain	External Antenna / PK : 5.37 dBi
Antenna 2 /Antenna Gain	External Antenna / PK : 3.17 dBi
Antenna 3 /Antenna Gain	External Antenna / PK : 1.4 dBi

1.6 Declaration by the applicant / manufacturer

- NA

1.7 Information about the FHSS characteristics

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following :

A) The hopping sequence is pseudorandom

Note 1 : Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 42, 54, 72, 09, 01, 11, 33, 41, 34, 42, 65, 73, 53, 69, 06, 22, 04,
20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 41, 58, 44, 60, 76, 13, 03, 11,
35, 43, 37, 45, 69, 77, 52, 71, 08, 24, 06, 24, 48, 56, 45, 46, 70, 01, 72, 06, 25,
33, 12, 28, 49, 60, 45, 58, 74, 13, 05, 18, 37, 49 etc

The System receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronizaton with the transmitted signals.

B) All channels are used equally on average

C) The receiver input bandwidth equals the transmit bandwidth

D) The receiver hops in sequence with the transmit signal

- 15.247(g) : In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h) : In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection / hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h) : The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

1.8 Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	18/12/19	19/12/19	MY50410357
Spectrum Analyzer	Agilent Technologies	N9020A	18/12/19	19/12/19	MY48011700
DC Power Supply	SM techno	SDP30-5D	18/12/18	19/12/18	305DKA013
DC Power Supply	Agilent Technologies	66332A	18/07/02	19/07/02	MY43000211
Multimeter	FLUKE	17B	18/12/18	19/12/18	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	18/12/19	19/12/19	255571
Signal Generator	ANRITSU	MG3695C	18/12/10	19/12/10	173501
Thermohygrometer	BODYCOM	BJ5478	18/12/27	19/12/27	120612-1
Thermohygrometer	BODYCOM	BJ5478	18/07/09	19/07/09	N/A
Loop Antenna	Schwarzbeck	FMZB1513	18/01/30	20/01/30	1513-128
BILOG ANTENNA	Schwarzbeck	VULB 9160	18/07/13	20/07/13	3359
Horn Antenna	ETS-Lindgren	3115	19/01/11	21/01/11	9202-3820
Horn Antenna	Schwarzbeck	BBHA 9120C	17/12/04	19/12/04	9120C-561
Horn Antenna	A.H.Systems Inc.	SAS-574	17/07/31	19/07/31	155
BlueTooth Tester	TESCOM	TC-3000B	18/12/18	19/12/18	3000B640046
Power Splitter	Anritsu	K241B	18/12/18	19/12/18	1301182
PreAmplifier	tsj	MLA-0118-J01-45	18/12/19	19/12/19	17138
PreAmplifier	tsj	MLA-1840-J02-45	18/07/06	19/07/06	16966-10728
PreAmplifier	H.P	8447D	18/12/18	19/12/18	2944A07774
Attenuator	SMAJK	SMAJK-2-3	18/07/02	19/07/02	3
Attenuator	SRTechnology	F01-B0606-01	18/07/02	19/07/02	13092403
Attenuator	Hefei Shunze	SS5T2.92-10-40	18/07/03	19/07/03	16012202
Attenuator	SMAJK	SMAJK-2-3	18/07/04	19/07/04	4
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	18/07/03	19/07/03	3
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	18/07/02	19/07/02	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	18/07/02	19/07/02	1
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A MA2411B	18/12/19	19/12/19	1338004 1306053
EMI Test Receiver	Rohde Schwarz	ESW44	18/08/06	20/08/06	101645
EMI Test Receiver PULSE LIMITER	Rohde Schwarz Rohde Schwarz	ESC17 ESH3-Z2	19/01/30	20/01/30	100910 101333
LISN	SCHWARZBECK	NNLK 8121	19/03/19	20/03/19	06183
Cable	HUBER+SUHNER	SUCOFLEX 106	18/06/25	19/06/25	G-01
Cable	HUBER+SUHNER	SUCOFLEX 104	18/06/25	19/06/25	G-02
Cable	HUBER+SUHNER	SUCOFLEX 104	18/06/25	19/06/25	G-03
Cable	Junkosha	MWX241	18/06/25	19/06/25	G-04
Cable	Junkosha	MWX241	18/06/25	19/06/25	G-07
Cable	DT&C	Cable	18/07/06	19/07/06	G-13
Cable	DT&C	Cable	18/07/06	19/07/06	G-14
Cable	HUBER+SUHNER	SUCOFLEX 104	18/07/06	19/07/06	G-15
Cable	DT&C	Cable	19/01/16	20/01/16	RF-18
Cable	DT&C	CABLE	18/07/05	19/07/05	RF-82

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

1.9 Summary of Test Results

FCC Part RSS Std.	Parameter	Limit (Using in 2400~ 2483.5 MHz)	Test Condition	Status Note 1
15.247(a) RSS-247(5.1)	Carrier Frequency Separation	≥ 25 kHz or $\geq$ Two thirds of the 20 dB BW, whichever is greater.	Conducted	C
	Number of Hopping Frequencies	≥ 15 hops		C
	20 dB Bandwidth	N/A		C
	Dwell Time	≤ 0.4 seconds		C
15.247(b) RSS-247(5.4)	Transmitter Output Power	For FCC ≤ 1 Watt , if CHs ≥ 75 Others ≤ 0.125 W For IC if CHs ≥ 75 ≤ 1 Watt For Conducted Power ≤ 4 Watt For e.i.r.p, Others ≤ 0.125 W For Conducted Power. ≤ 0.5 Watt For e.i.r.p		C
15.247(d) RSS-247(5.5)	Conducted Spurious Emissions	The radiated emission to any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density.	Radiated	C
RSS Gen(6.7)	Occupied Bandwidth (99 %)	N/A		NA
15.247(d) 15.205 & 209 RSS-247(5.5) RSS-Gen (8.9 & 8.10)	Radiated Spurious Emissions	FCC 15.209 Limits	Radiated	C ^{Note3}
15.207 RSS-Gen(8.8)	AC Conducted Emissions	FCC 15.207 Limits	AC Line Conducted	C
15.203	Antenna Requirements	FCC 15.203	-	C

Note 1 : C = Comply NC = Not Comply NT = Not Tested NA = Not Applicable

Note 2 : For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated With OATS.

Note 3 : This test item was performed in each axis and the worst case data was reported.

Note 4: The sample was tested according to the following specifications :

- ANSI C63.10-2013, KDB 558074D01v05r02

1.10 Conclusion of worst-case and operation mode

The EUT has three types of modulation (GFSK, $\pi/4$ DQPSK and 8DPSK).

Therefore all applicable requirements were tested with all the modulations.

And packet type was tested at the worst case(DH5).

The field strength of spurious emission was measured in three orthogonal EUT positions (X-axis, Y-axis and Z-axis).

Tested frequency information,

- Hopping Function : Enable

	TX Frequency (MHz)	RX Frequency (MHz)
Hopping Band	2402 ~ 2480	2402 ~ 2480

- Hopping Function : Disable

	TX Frequency (MHz)	RX Frequency (MHz)
Lowest Channel	2402	2402
Middle Channel	2441	2441
Highest Channel	2480	2480

2. Maximum Peak Output Power Measurement

2.1 Test Setup

Refer to the APPENDIX I.

2.2 Limit

■ FCC Requirements

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. §15.247(b)(1), For frequency hopping systems operating in the 2400 – 2483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725 – 5805 MHz band : 1 Watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

■ IC Requirements

1. RSS-247(5.4) (b), For FHSS operating in the band 2400 - 2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels, the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p shall not exceed 4 W, except as provided in section 5.4(e)

2.3 Test Procedure

1. The RF output power was measured with a spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.
2. The peak output power of the fundamental frequency was measured with the spectrum analyzer using ;
Span = approximately 5 times of the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 20 dB BW
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold

2.4 Test Results


Modulation	Tested Channel	Frame Average Output Power		Peak Output Power	
		dBm	mW	dBm	mW
<u>GFSK</u>	Lowest	8.13	6.50	9.37	8.65
	Middle	10.58	11.43	11.17	13.09
	Highest	11.37	13.71	11.91	15.52
<u>$\pi/4$DQPSK</u>	Lowest	0.32	1.08	3.31	2.14
	Middle	2.95	1.97	5.34	3.42
	Highest	3.71	2.35	6.22	4.19
<u>8DPSK</u>	Lowest	0.39	1.09	3.83	2.42
	Middle	3.02	2.00	5.79	3.79
	Highest	3.75	2.37	6.64	4.61

Note 1: The frame average output power was tested using an average power meter for reference only.

Note 2: See next pages for actual measured spectrum plots.


Peak Output Power

Lowest Channel & Modulation : GFSK




Peak Output Power


Middle Channel & Modulation : GFSK




Peak Output Power

Highest Channel & Modulation : GFSK


Peak Output Power

Lowest Channel & Modulation : $\pi/4$ DQPSK

Peak Output Power


Middle Channel & Modulation : $\pi/4$ DQPSK

Peak Output Power

Highest Channel & Modulation : $\pi/4$ DQPSK


Peak Output Power

Lowest Channel & Modulation : 8DPSK




Peak Output Power

Middle Channel & Modulation : 8DPSK



Peak Output Power

Highest Channel & Modulation : 8DPSK



3. 20 dB BW

3.1 Test Setup

Refer to the APPENDIX I.

3.2 Limit

Limit : Not Applicable

3.3 Test Procedure

1. The 20 dB bandwidth & Occupied bandwidth were measured with a spectrum analyzer connected to RF antenna Connector(conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.

2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using below setting:

RBW = 1% to 5% of the 20 dB BW & Occupied BW

VBW $\geq 3 \times$ RBW

Span = between two times and five times the 20 dB bandwidth & Occupied BW

Sweep = auto

Detector function = peak


Trace = max hold

3.4 Test Results

Modulation	Tested Channel	20 dB BW (MHz)
<u>GFSK</u>	Lowest	0.929
	Middle	0.926
	Highest	0.928
<u>$\pi/4$DQPSK</u>	Lowest	1.318
	Middle	1.317
	Highest	1.315
<u>8DPSK</u>	Lowest	1.286
	Middle	1.297
	Highest	1.300


20 dB BW

Lowest Channel & Modulation : GFSK




20 dB BW


Middle Channel & Modulation : GFSK



20 dB BW


Highest Channel & Modulation : GFSK

20 dB BW

Lowest Channel & Modulation : $\pi/4$ DQPSK


20 dB BW

Middle Channel & Modulation : $\pi/4$ DQPSK




20 dB BW


Highest Channel & Modulation : $\pi/4$ DQPSK



20 dB BW


Lowest Channel & Modulation : 8DPSK

20 dB BW

Middle Channel & Modulation : 8DPSK

20 dB BW

Highest Channel & Modulation : 8DPSK



4. Carrier Frequency Separation

4.1 Test Setup

Refer to the APPENDIX I.

4.2 Limit

Limit : ≥ 25 kHz or $\geq$ Two-Thirds of the 20 dB BW whichever is greater.

4.3 Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to :

Span = wide enough to capture the peaks of two adjacent channels

RBW = Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

4.4 Test Results

FH mode

Hopping Mode	Modulation	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	GFSK	2440.996	2441.996	1.000
	$\pi/4$ DQPSK	2440.994	2441.994	1.000
	8DPSK	2440.995	2441.996	1.001

AFH mode


Hopping Mode	Modulation	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	GFSK	2440.995	2441.995	1.000
	$\pi/4$ DQPSK	2440.996	2441.996	1.000
	8DPSK	2440.996	2441.996	1.000

Note 1 : See next pages for actual measured spectrum


- Minimum Standard :

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
Alternatively, frequency hopping systems operating in the 2400 - 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


Carrier Frequency Separation (FH)

Hopping mode : Enable & GFSK


Carrier Frequency Separation (FH)

Hopping mode : Enable & $\pi/4$ DQPSK

Carrier Frequency Separation (FH) Hopping mode : Enable & 8DPSK



Carrier Frequency Separation (AFH) *Hopping mode : Enable & 8DPSK*



5. Number of Hopping Frequencies

5.1 Test Setup

Refer to the APPENDIX I.

5.2 Limit

Limit : ≥ 15 hops

5.3 Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, two frequency ranges for FH mode within the 2400 ~ 2483.5 MHz were examined.

The spectrum analyzer is set to :

Span for FH mode = 50 MHz Start Frequency = 2391.5 MHz, Stop Frequency = 2441.5 MHz

Start Frequency = 2441.5 MHz, Stop Frequency = 2491.5 MHz

Span for AFH mode = 30 MHz Start Frequency = 2426.0 MHz, Stop Frequency = 2456.0 MHz

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.4 Test Results

FH mode

Hopping mode	Modulation	Test Result (Total Hops)
Enable	GFSK	79
	$\pi/4$ DQPSK	79
	8DPSK	79

AFH mode

Hopping mode	Modulation	Test Result (Total Hops)
Enable	GFSK	20
	$\pi/4$ DQPSK	20
	8DPSK	20


Note 1 : See next pages for actual measured spectrum plots.

- Minimum Standard :

At least 15 hops


Number of Hopping Frequencies 1(FH)

Hopping mode : Enable & GFSK




Number of Hopping Frequencies 2(FH)

Hopping mode : Enable & GFSK




Number of Hopping Frequencies 1(FH)

Hopping mode : Enable & $\pi/4$ DQPSK




Number of Hopping Frequencies 2(FH)

Hopping mode : Enable & $\pi/4$ DQPSK




Number of Hopping Frequencies 1(FH)



Hopping mode : Enable & 8DPSK




Number of Hopping Frequencies 2(FH)

Hopping mode : Enable & 8DPSK



Number of Hopping Frequencies 1(AFH) Hopping mode : Enable & GFSK**Number of Hopping Frequencies 1(AFH) Hopping mode : Enable & $\pi/4$ DQPSK**

Number of Hopping Frequencies 1(AFH) *Hopping mode : Enable & 8DPSK*



6. Time of Occupancy (Dwell Time)

6.1 Test Setup

Refer to the APPENDIX I.

6.2 Limit

The maximum permissible time of occupancy is 400 ms within a period of 400 ms multiplied by the number of hopping channels employed.

6.3 Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz (RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel)

VBW $\geq$ RBW

Detector function = peak

Trace = max hold

6.4 Test Results

FH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	DH 5	79	2.880	3.750	0.307
	2 DH 5	79	2.880	3.750	0.307
	3 DH 5	79	2.880	3.750	0.307

AFH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	DH 5	20	2.880	3.750	0.154
	2 DH 5	20	2.880	3.750	0.154
	3 DH 5	20	2.880	3.750	0.154

Note 1 : Dwell Time = $0.4 \times \text{Hopping channel} \times \text{Burst ON time} \times$


$((\text{Hopping rate} \div \text{Time slots}) \div \text{Hopping channel})$

- Time slots for DH5 = 6 slots (TX = 5 slot / RX = 1 slot)


- Hopping Rate = 1600 for FH mode & 800 for AFH mode

Note 2 : See next pages for actual measured spectrum plots.


Time of Occupancy (FH)

Hopping mode : Enable & DH5


Time of Occupancy (FH)

Hopping mode : Enable & 2-DH5


Time of Occupancy (FH)

Hopping mode : Enable & 3-DH5


Time of Occupancy (AFH)

Hopping mode : Enable & DH5

Time of Occupancy (AFH)

Hopping mode : Enable & 2-DH5

Time of Occupancy (AFH)

Hopping mode : Enable & 3-DH5

7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

7.1 Test Setup

Refer to the APPENDIX I.

7.2 Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1705	24000/F (kHz)	30
1705 ~ 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 - 72 MHz, 76 - 88 MHz, 174 - 216 MHz or 470 - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~ 156.52525	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.7 ~ 156.9	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	162.0125 ~ 167.17	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	167.72 ~ 173.2	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	240 ~ 285	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	322 ~ 335.4	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	960 ~ 1240	3345.8 ~ 3358		
			3600 ~ 4400		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

7.3. Test Procedures

7.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 or 3 meter away from the interference-receiving antenna.
3. For measurements above 1GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.
4. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Measurement Instrument Setting

- Frequencies less than or equal to 1000 MHz
The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- Frequencies above 1000 MHz
The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.
The result of Average measurement is calculated using PK result and duty correction factor.

7.3.2. Test Procedures for Conducted Spurious Emissions

1. The transmitter output was connected to the spectrum analyzer.
2. The **reference level** of the fundamental frequency was measured with the spectrum analyzer using RBW = 100 kHz, VBW = 300 kHz.
3. The conducted spurious emission was tested each ranges were set as below.

Frequency range : 9 kHz ~ 30 MHz

RBW = 100 kHz, VBW = 300 kHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

Frequency range : 30 MHz ~ 10 GHz, 10 GHz ~ 25 GHz

RBW = 1 MHz, VBW = 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2001 to get accurate emission level within 100 kHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

7.4. Test Results

7.4.1. Radiated Emissions

9 kHz ~ 25 GHz Data (Modulation : GFSK) _ Antenna 1

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.40	V	Z	PK	55.02	2.22	N/A	N/A	57.24	74.00	16.76
2324.40	V	Z	AV	55.02	2.22	-24.79	N/A	32.45	54.00	21.55
4804.32	H	Y	PK	50.79	1.63	N/A	N/A	52.42	74.00	21.58
4804.32	H	Y	AV	50.79	1.63	-24.79	N/A	27.63	54.00	26.37
9607.72	V	X	PK	51.46	4.96	N/A	N/A	56.42	74.00	17.58
9607.72	V	X	AV	51.46	4.96	-24.79	N/A	31.63	54.00	22.37
12010.31	H	Y	PK	47.99	8.68	N/A	N/A	56.67	74.00	17.33
12010.31	H	Y	AV	47.99	8.68	-24.79	N/A	31.88	54.00	22.12
14412.54	H	X	PK	45.48	13.58	N/A	N/A	59.06	74.00	14.94
14412.54	H	X	AV	45.48	13.58	-24.79	N/A	34.27	54.00	19.73

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.10	H	Y	PK	52.35	1.61	N/A	N/A	53.96	74.00	20.04
4882.10	H	Y	AV	52.35	1.61	-24.79	N/A	29.17	54.00	24.83
9764.69	V	X	PK	53.22	5.35	N/A	N/A	58.57	74.00	15.43
9764.69	V	X	AV	53.22	5.35	-24.79	N/A	33.78	54.00	20.22
12204.18	H	Y	PK	49.51	8.87	N/A	N/A	58.38	74.00	15.62
12204.18	H	Y	AV	49.51	8.87	-24.79	N/A	33.59	54.00	20.41
14646.34	H	X	PK	46.40	13.53	N/A	N/A	59.93	74.00	14.07
14646.34	H	X	AV	46.40	13.53	-24.79	N/A	35.14	54.00	18.86

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.65	V	Z	PK	54.21	3.26	N/A	N/A	57.47	74.00	16.53
2483.65	V	Z	AV	54.21	3.26	-24.79	N/A	32.68	54.00	21.32
4959.97	H	Y	PK	50.64	1.75	N/A	N/A	52.39	74.00	21.61
4959.97	H	Y	AV	50.64	1.75	-24.79	N/A	27.60	54.00	26.40
9919.35	V	X	PK	55.33	5.72	N/A	N/A	61.05	74.00	12.95
9919.35	V	X	AV	55.33	5.72	-24.79	N/A	36.26	54.00	17.74
12399.31	H	Y	PK	50.13	9.07	N/A	N/A	59.20	74.00	14.80
12399.31	H	Y	AV	50.13	9.07	-24.79	N/A	34.41	54.00	19.59
14881.08	H	X	PK	45.88	13.29	N/A	N/A	59.17	74.00	14.83
14881.08	H	X	AV	45.88	13.29	-24.79	N/A	34.38	54.00	19.62

▪ Note.

1. The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
2. Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
 - Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{\underline{-9.54 \text{ dB}}}$
 - When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
 - Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20$ minimum hopping channels, where T = pulse width = **2.88 ms**
 - $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
 - The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
 - D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = \underline{\underline{-24.79 \text{ dB}}}$
4. Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : $\pi/4$ DQPSK) _ Antenna 1

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.29	V	Z	PK	53.51	2.22	N/A	N/A	55.73	74.00	18.27
2324.29	V	Z	AV	53.51	2.22	-24.79	N/A	30.94	54.00	23.06
4803.92	H	Y	PK	51.41	1.63	N/A	N/A	53.04	74.00	20.96
4803.92	H	Y	AV	51.41	1.63	-24.79	N/A	28.25	54.00	25.75
9607.83	V	X	PK	46.45	4.96	N/A	N/A	51.41	74.00	22.59
9607.83	V	X	AV	45.45	4.96	-24.79	N/A	25.62	54.00	28.38
12010.49	H	Y	PK	46.33	8.68	N/A	N/A	55.01	74.00	18.99
12010.49	H	Y	AV	46.33	8.68	-24.79	N/A	30.22	54.00	23.78
14412.09	H	X	PK	45.19	13.58	N/A	N/A	58.77	74.00	15.23
14412.09	H	X	AV	45.19	13.58	-24.79	N/A	33.98	54.00	20.02

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.79	H	Y	PK	50.39	1.61	N/A	N/A	52.00	74.00	22.00
4881.79	H	Y	AV	50.39	1.61	-24.79	N/A	27.21	54.00	26.79
9763.56	V	X	PK	47.92	5.35	N/A	N/A	53.27	74.00	20.73
9763.56	V	X	AV	47.92	5.35	-24.79	N/A	28.48	54.00	25.52
12204.58	H	Y	PK	46.57	8.87	N/A	N/A	55.44	74.00	18.56
12204.58	H	Y	AV	46.57	8.87	-24.79	N/A	30.65	54.00	23.35
14646.14	H	X	PK	45.39	13.53	N/A	N/A	58.92	74.00	15.08
14646.14	H	X	AV	45.39	13.53	-24.79	N/A	34.13	54.00	19.87

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.54	V	Z	PK	52.95	3.26	N/A	N/A	56.21	74.00	17.79
2483.54	V	Z	AV	52.95	3.26	-24.79	N/A	31.42	54.00	22.58
4960.10	H	Y	PK	49.78	1.75	N/A	N/A	51.53	74.00	22.47
4960.10	H	Y	AV	49.78	1.75	-24.79	N/A	26.74	54.00	27.26
9920.41	V	X	PK	48.98	5.72	N/A	N/A	54.70	74.00	19.30
9920.41	V	X	AV	48.98	5.72	-24.79	N/A	29.91	54.00	24.09
12400.07	H	Y	PK	46.41	9.07	N/A	N/A	55.48	74.00	18.52
12400.07	H	Y	AV	46.41	9.07	-24.79	N/A	30.69	54.00	23.31
14880.41	H	X	PK	44.41	13.29	N/A	N/A	57.70	74.00	16.30
14880.41	H	X	AV	44.41	13.29	-24.79	N/A	32.91	54.00	21.09

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = -24.79 \text{ dB}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : 8DPSK) _ Antenna 1

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.55	V	Z	PK	53.27	2.22	N/A	N/A	55.49	74.00	18.51
2324.55	V	Z	AV	53.27	2.22	-24.79	N/A	30.70	54.00	23.30
4804.29	H	Y	PK	50.86	1.63	N/A	N/A	52.49	74.00	21.51
4804.29	H	Y	AV	50.86	1.63	-24.79	N/A	27.70	54.00	26.30
9608.40	V	X	PK	47.94	4.96	N/A	N/A	52.90	74.00	21.10
9608.40	V	X	AV	47.94	4.96	-24.79	N/A	28.11	54.00	25.89
12009.88	H	Y	PK	46.48	8.68	N/A	N/A	55.16	74.00	18.84
12009.88	H	Y	AV	46.48	8.68	-24.79	N/A	30.37	54.00	23.63
14412.47	H	X	PK	44.54	13.58	N/A	N/A	58.12	74.00	15.88
14412.47	H	X	AV	44.54	13.58	-24.79	N/A	33.33	54.00	20.67

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.11	H	Y	PK	51.23	1.61	N/A	N/A	52.84	74.00	21.16
4882.11	H	Y	AV	51.23	1.61	-24.79	N/A	28.05	54.00	25.95
9763.66	V	X	PK	48.00	5.35	N/A	N/A	53.35	74.00	20.65
9763.66	V	X	AV	48.00	5.35	-24.79	N/A	28.56	54.00	25.44
12204.52	H	Y	PK	46.25	8.87	N/A	N/A	55.12	74.00	18.88
12204.52	H	Y	AV	46.25	8.87	-24.79	N/A	30.33	54.00	23.67
14645.95	H	X	PK	45.85	13.53	N/A	N/A	59.38	74.00	14.62
14645.95	H	X	AV	45.85	13.53	-24.79	N/A	34.59	54.00	19.41

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.61	V	Z	PK	55.68	3.26	N/A	N/A	58.94	74.00	15.06
2483.61	V	Z	AV	55.68	3.26	-24.79	N/A	34.15	54.00	19.85
4960.26	H	Y	PK	50.59	1.75	N/A	N/A	52.34	74.00	21.66
4960.26	H	Y	AV	50.59	1.75	-24.79	N/A	27.55	54.00	26.45
9919.81	V	X	PK	48.70	5.72	N/A	N/A	54.42	74.00	19.58
9919.81	V	X	AV	48.70	5.72	-24.79	N/A	29.63	54.00	24.37
12400.34	H	Y	PK	46.71	9.07	N/A	N/A	55.78	74.00	18.22
12400.34	H	Y	AV	46.71	9.07	-24.79	N/A	30.99	54.00	23.01
14879.94	H	X	PK	44.32	13.29	N/A	N/A	57.61	74.00	16.39
14879.94	H	X	AV	44.32	13.29	-24.79	N/A	32.82	54.00	21.18

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = -24.79 \text{ dB}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : GFSK) _ Antenna 2

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2323.76	V	Z	PK	54.28	2.22	N/A	N/A	56.50	74.00	17.50
2323.76	V	Z	AV	54.28	2.22	-24.79	N/A	31.71	54.00	22.29
4804.31	H	Y	PK	54.41	1.63	N/A	N/A	56.04	74.00	17.96
4804.31	H	Y	AV	54.41	1.63	-24.79	N/A	31.25	54.00	22.75
9608.23	V	X	PK	51.70	4.96	N/A	N/A	56.66	74.00	17.34
9608.23	V	X	AV	51.70	4.96	-24.79	N/A	31.87	54.00	22.13
12009.68	H	Y	PK	47.18	8.68	N/A	N/A	55.86	74.00	18.14
12009.68	H	Y	AV	47.18	8.68	-24.79	N/A	31.07	54.00	22.93

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.64	H	Y	PK	53.08	1.61	N/A	N/A	54.69	74.00	19.31
4881.64	H	Y	AV	53.08	1.61	-24.79	N/A	29.90	54.00	24.10
9763.34	V	X	PK	53.69	5.34	N/A	N/A	59.03	74.00	14.97
9763.34	V	X	AV	53.69	5.34	-24.79	N/A	34.24	54.00	19.76
12204.08	H	Y	PK	48.74	8.87	N/A	N/A	57.61	74.00	16.39
12204.08	H	Y	AV	48.74	8.87	-24.79	N/A	32.82	54.00	21.18

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.55	V	Z	PK	54.33	3.26	N/A	N/A	57.59	74.00	16.41
2483.55	V	Z	AV	54.33	3.26	-24.79	N/A	32.80	54.00	21.20
4959.59	H	Y	PK	51.75	1.75	N/A	N/A	53.50	74.00	20.50
4959.59	H	Y	AV	51.75	1.75	-24.79	N/A	28.71	54.00	25.29
9919.42	V	X	PK	55.43	5.72	N/A	N/A	61.15	74.00	12.85
9919.42	V	X	AV	55.43	5.72	-24.79	N/A	36.36	54.00	17.64
12399.02	H	Y	PK	50.94	9.07	N/A	N/A	60.01	74.00	13.99
12399.02	H	Y	AV	50.94	9.07	-24.79	N/A	35.22	54.00	18.78

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{-9.54 \text{ dB}}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \text{ Log}(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = \underline{-24.79 \text{ dB}}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : $\pi/4$ DQPSK) _ Antenna 2

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.76	V	Z	PK	53.06	2.22	N/A	N/A	55.28	74.00	18.72
2324.76	V	Z	AV	53.06	2.22	-24.79	N/A	30.49	54.00	23.51
4803.73	H	Y	PK	50.65	1.63	N/A	N/A	52.28	74.00	21.72
4803.73	H	Y	AV	50.65	1.63	-24.79	N/A	27.49	54.00	26.51
9608.10	V	X	PK	46.79	4.96	N/A	N/A	51.75	74.00	22.25
9608.10	V	X	AV	46.79	4.96	-24.79	N/A	26.96	54.00	27.04
12009.93	H	Y	PK	45.65	8.68	N/A	N/A	54.33	74.00	19.67
12009.93	H	Y	AV	45.65	8.68	-24.79	N/A	29.54	54.00	24.46

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.49	H	Y	PK	50.72	1.61	N/A	N/A	52.33	74.00	21.67
4882.49	H	Y	AV	50.72	1.61	-24.79	N/A	27.54	54.00	26.46
9764.67	V	X	PK	48.09	5.34	N/A	N/A	53.43	74.00	20.57
9764.67	V	X	AV	48.09	5.34	-24.79	N/A	28.64	54.00	25.36
12205.25	H	Y	PK	45.87	8.87	N/A	N/A	54.74	74.00	19.26
12205.25	H	Y	AV	45.87	8.87	-24.79	N/A	29.95	54.00	24.05

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.61	V	Z	PK	54.45	3.26	N/A	N/A	57.71	74.00	16.29
2483.61	V	Z	AV	54.45	3.26	-24.79	N/A	32.92	54.00	21.08
4959.89	H	Y	PK	50.75	1.75	N/A	N/A	52.50	74.00	21.50
4959.89	H	Y	AV	50.75	1.75	-24.79	N/A	27.71	54.00	26.29
9918.99	V	X	PK	48.78	5.72	N/A	N/A	54.50	74.00	19.50
9918.99	V	X	AV	48.78	5.72	-24.79	N/A	29.71	54.00	24.29
12399.33	H	Y	PK	47.26	9.07	N/A	N/A	56.33	74.00	17.67
12399.33	H	Y	AV	47.26	9.07	-24.79	N/A	31.54	54.00	22.46

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = -24.79 \text{ dB}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : 8DPSK) _ Antenna 2

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.53	V	Z	PK	52.75	2.76	N/A	N/A	55.51	74.00	18.49
2324.53	V	Z	AV	52.75	2.76	-24.79	N/A	30.72	54.00	23.28
4804.24	H	Y	PK	51.82	1.63	N/A	N/A	53.45	74.00	20.55
4804.24	H	Y	AV	51.82	1.63	-24.79	N/A	28.66	54.00	25.34
9607.53	V	X	PK	46.31	4.96	N/A	N/A	51.27	74.00	22.73
9607.53	V	X	AV	46.31	4.96	-24.79	N/A	26.48	54.00	27.52
12010.30	H	Y	PK	46.48	8.68	N/A	N/A	55.16	74.00	18.84
12010.30	H	Y	AV	46.48	8.68	-24.79	N/A	30.37	54.00	23.63

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.86	H	Y	PK	51.44	1.61	N/A	N/A	53.05	74.00	20.95
4881.86	H	Y	AV	51.44	1.61	-24.79	N/A	28.26	54.00	25.74
9763.72	V	X	PK	47.80	5.35	N/A	N/A	53.15	74.00	20.85
9763.72	V	X	AV	47.80	5.35	-24.79	N/A	28.36	54.00	25.64
12204.51	H	Y	PK	45.62	8.87	N/A	N/A	54.49	74.00	19.51
12204.51	H	Y	AV	45.62	8.87	-24.79	N/A	29.70	54.00	24.30

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.55	V	Z	PK	53.91	3.26	N/A	N/A	57.17	74.00	16.83
2483.55	V	Z	AV	53.91	3.26	-24.79	N/A	32.38	54.00	21.62
4959.86	H	Y	PK	50.17	1.75	N/A	N/A	51.92	74.00	22.08
4959.86	H	Y	AV	50.17	1.75	-24.79	N/A	27.13	54.00	26.87
9919.78	V	X	PK	49.71	5.72	N/A	N/A	55.43	74.00	18.57
9919.78	V	X	AV	49.71	5.72	-24.79	N/A	30.64	54.00	23.36
12399.56	H	Y	PK	46.12	9.07	N/A	N/A	55.19	74.00	18.81
12399.56	H	Y	AV	46.12	9.07	-24.79	N/A	30.40	54.00	23.60

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = -24.79 \text{ dB}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : GFSK) _ Antenna 3

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.18	V	Z	PK	54.35	2.22	N/A	N/A	56.57	74.00	17.43
2324.18	V	Z	AV	54.35	2.22	-24.79	N/A	31.78	54.00	22.22
4803.73	H	Y	PK	50.93	1.63	N/A	N/A	52.56	74.00	21.44
4803.73	H	Y	AV	50.93	1.63	-24.79	N/A	27.77	54.00	26.23
9608.37	V	X	PK	47.20	4.96	N/A	N/A	52.16	74.00	21.84
9608.37	V	X	AV	47.20	4.96	-24.79	N/A	27.37	54.00	26.63
12009.61	H	Y	PK	46.06	8.68	N/A	N/A	54.74	74.00	19.26
12009.61	H	Y	AV	46.06	8.68	-24.79	N/A	29.95	54.00	24.05

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.10	H	Y	PK	51.75	1.61	N/A	N/A	53.36	74.00	20.64
4882.10	H	Y	AV	51.75	1.61	-24.79	N/A	28.57	54.00	25.43
9763.44	V	X	PK	48.22	5.34	N/A	N/A	53.56	74.00	20.44
9763.44	V	X	AV	48.22	5.34	-24.79	N/A	28.77	54.00	25.23
12205.41	H	Y	PK	46.60	8.87	N/A	N/A	55.47	74.00	18.53
12205.41	H	Y	AV	46.60	8.87	-24.79	N/A	30.68	54.00	23.32

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2484.02	V	Z	PK	53.25	3.26	N/A	N/A	56.51	74.00	17.49
2484.02	V	Z	AV	53.25	3.26	-24.79	N/A	31.72	54.00	22.28
4959.95	H	Y	PK	53.38	1.75	N/A	N/A	55.13	74.00	18.87
4959.95	H	Y	AV	53.38	1.75	-24.79	N/A	30.34	54.00	23.66
9919.64	V	X	PK	49.94	5.72	N/A	N/A	55.66	74.00	18.34
9919.64	V	X	AV	49.94	5.72	-24.79	N/A	30.87	54.00	23.13
12399.93	H	Y	PK	46.81	9.07	N/A	N/A	55.88	74.00	18.12
12399.93	H	Y	AV	46.81	9.07	-24.79	N/A	31.09	54.00	22.91

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = -24.79 \text{ dB}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : $\pi/4$ DQPSK) _ Antenna 3

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2324.63	V	Z	PK	53.04	2.22	N/A	N/A	55.26	74.00	18.74
2324.63	V	Z	AV	53.04	2.22	-24.79	N/A	30.47	54.00	23.53
4804.18	H	Y	PK	49.82	1.63	N/A	N/A	51.45	74.00	22.55
4804.18	H	Y	AV	49.82	1.63	-24.79	N/A	26.66	54.00	27.34
9608.20	V	X	PK	45.77	4.96	N/A	N/A	50.73	74.00	23.27
9608.20	V	X	AV	45.77	4.96	-24.79	N/A	25.94	54.00	28.06
12009.76	H	Y	PK	45.39	8.68	N/A	N/A	54.07	74.00	19.93
12009.76	H	Y	AV	45.39	8.68	-24.79	N/A	29.28	54.00	24.72

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.33	H	Y	PK	50.04	1.61	N/A	N/A	51.65	74.00	22.35
4882.33	H	Y	AV	50.04	1.61	-24.79	N/A	26.86	54.00	27.14
9764.26	V	X	PK	47.87	5.34	N/A	N/A	53.21	74.00	20.79
9764.26	V	X	AV	47.87	5.34	-24.79	N/A	28.42	54.00	25.58
12204.55	H	Y	PK	45.44	8.87	N/A	N/A	54.31	74.00	19.69
12204.55	H	Y	AV	45.44	8.87	-24.79	N/A	29.52	54.00	24.48

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.92	V	Z	PK	52.19	3.26	N/A	N/A	55.45	74.00	18.55
2483.92	V	Z	AV	52.19	3.26	-24.79	N/A	30.66	54.00	23.34
4959.73	H	Y	PK	51.01	1.75	N/A	N/A	52.76	74.00	21.24
4959.73	H	Y	AV	51.01	1.75	-24.79	N/A	27.97	54.00	26.03
9920.18	V	X	PK	48.68	5.72	N/A	N/A	54.40	74.00	19.60
9920.18	V	X	AV	48.68	5.73	-24.79	N/A	29.62	54.00	24.38
12399.77	H	Y	PK	45.67	9.07	N/A	N/A	54.74	74.00	19.26
12399.77	H	Y	AV	45.67	9.07	-24.79	N/A	29.95	54.00	24.05

▪ Note.

- The radiated emissions were investigated up to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20 \text{ minimum hopping channels}$, where T = pulse width = **2.88 ms**
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$
- The Worst Case Dwell Time = $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = -24.79 \text{ dB}$
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.