



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

Application No.: LE208013(3)

Client : CCP Co., Ltd.
3-1-8, Sakae-cho, Kawaguchi
Saitama

Sample Description : One(1) submitted sample stated to be follow

<u>Description</u>	<u>Model No.</u>
Micro Slider	60-4394
Wicked Wing	60-4395
Rating	: 1 x 9V battery
No. of sample(s)	: Two (2) piece(s) ***

Date Received : 2004 July 13.

Test Period : 2004 July 13 – 2004 August 10.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – Dec 2003
ANSI C63.4 – 2001

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart C.

Remark : All two models are the same in circuitry and components and construction;
and therefore Micro Slider model 60-4394 was chosen to be the representative
of the test sample.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____


Danny Chui

EMC Engineer - EL. Division

Page 1 of 11

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Related Submittal Grants	3
1.3	Location of the test site	4
1.4	List of measuring equipment	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	10
5.1	Bandwidth	10
6	Appendices	11



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for Micro Slider. Operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by 9V battery. There are six buttons and one on / off switch on the EUT. When the A~D button is pressed once, it will transmit a radio frequency for receiver go forward and backward or turn left and turn right. When the E~F button is pressed once, it will transmit a radio frequency for receiver slider sideways running.

The brief circuit description is listed as follows :

- U1 and associated circuit act as encoder.
- Q3 and associated circuit act as power control.
- Q1, X1 and associated circuit act as oscillator.
- Q2 and associated circuit act as amplifier.

The model(s) 60-4395 is the same as model 60-4394 in hardware aspect. The difference between these models is matching with different receiver.

1.2 Related Submittal Grants

This is a single application for certification of a transmitter.

The receiver for this transmitter is exempted from the Part 15 technical rules per 15.101(b).



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart C**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Averaging factor (-dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
27.147	V	60.5	16.4	6.9	70.0	80.0	-10.0
54.294	V	25.8	8.7	-	34.5	40.0	-5.5
81.441	V	27.2	8.0	-	35.2	40.0	-4.8
*108.587	V	19.7	11.8	-	31.5	43.5	-12.0
*135.735	H	19.4	13.1	-	32.5	43.5	-11.0
*162.882	H	22.4	11.0	-	33.4	43.5	-10.1
190.028	H	16.2	10.5	-	26.7	43.5	-16.8
217.175	H	23.3	10.1	-	33.4	46.0	-12.6
*244.323	H	25.5	10.1	-	35.6	46.0	-10.4
*271.469	H	21.5	14.2	-	35.7	46.0	-10.3

FCC ID : PSN5150-TX27

Page 7 of 11

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt 2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 The duty cycle is simply the on-time divided by the period :

The duration of one cycle = 36.90ms

Effective period of the cycle = $(1.6\text{ms} \times 8) + (480\mu\text{s} \times 8)$
= 16.64ms

Duty Cycle = $(16.64 / 36.90) \text{ms}$
= 0.451

Therefore, the average factor is found by $20 \log_{10} 0.451 = -6.9 \text{ dB}$



TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	1 page
A5.	Bandwidth Plot	1 page
A6.	Average Factor	2 pages
A7.	Block Diagram	1 page
A8.	Schematics	1 page
A9.	User Manual	4 pages
A10.	Operation Description	1 page

***** End of Report *****



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT


Report No. : AE014000-001

Date : 2004 August 11

A1. Photos of the set-up of Radiated Emissions



(front view)



(rear view)

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

A2. Photos of External Configurations



External Configuration 1



External Configuration 2

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

A3. Photos of Internal Configurations



Internal Configuration 1



Internal Configuration 2

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

A4. Photos of ID Label



ID Label 1



ID Label 2

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>




TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

A5. Bandwidth Plot



Bandwidth 1

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>




TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11

A6. Average Factor



Duty Cycle 1

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.


Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>




TEST REPORT

Report No. : AE014000-001

Date : 2004 August 11



Duty Cycle 2



Duty Cycle 3

FCC ID : PSN5150-TX27

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>