

TEST REPORT

On behalf of

Savant Technologies LLC, dba GE Lighting, a Savant company

Product Name: Cync Dynamic Effects Smart Café Lights

Model No.: CCF48CDOD/ENS, CCF24CDOD/ENS,
CCF96CDOD/ENS, CCF72CDOD/ENS

FCC ID: PUU-CAFE-CD

Prepared For: Savant Technologies LLC, dba GE Lighting, a Savant company
1975 Noble Road Cleveland, Ohio United States 44112

Prepared By: Audix Technology (Shanghai) Co., Ltd.
3F, Building 34, No. 680 Guiping Rd.,
Caohejing, Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500



TESTING
NVLAP LAB CODE 200371-0

File No. : C1D2409021
Report No. : ACI-F24154
Date of Test : 2024.09.22-25
Date of Report : 2024.10.18

The statement is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS.....	5
1.1 Description of Standards and Results.....	5
2 GENERAL INFORMATION.....	6
2.1 Description of Equipment Under Test.....	6
2.2 EUT Specifications Assessed in Current Report.....	7
2.3 Test Information	7
2.4 Duty Cycle Check	8
2.5 Sample Description	9
2.6 Supported equipment.....	9
2.7 Description of Test Facility	9
3 CONDUCTED EMISSION TEST	10
3.1 Test Equipment.....	10
3.2 Block Diagram of Test Setup	10
3.3 Conducted Emission Limits (§15.207).....	11
3.4 Test Configuration.....	11
3.5 Operating Condition of EUT	11
3.6 Test Procedures	11
3.7 Test Results	12
4 RADIATED EMISSION TEST.....	15
4.1 Test Equipment.....	15
4.2 Block Diagram of Test Setup	16
4.3 Radiated Emission Limit (§15.209)	17
4.4 Test Configuration.....	17
4.5 Operating Condition of EUT	17
4.6 Test Procedures	17
4.7 Test Results	19
5 99% OCCUPIED BANDWIDTH MEASUREMENT	44
5.1 Test Equipment.....	44
5.2 Block Diagram of Test Setup	44
5.3 Operating Condition of EUT	44
5.4 Test Procedure	44
5.5 Test Results	45
6 6 DB BANDWIDTH MEASUREMENT	49
6.1 Test Equipment.....	49
6.2 Block Diagram of Test Setup	49
6.3 Specification Limits (§15.247(a)(2)).....	49
6.4 Operating Condition of EUT	49
6.5 Test Procedure	49
6.6 Test Results	50
7 MAXIMUM OUTPUT POWER MEASUREMENT	54
7.1 Test Equipment.....	54
7.2 Block Diagram of Test Setup	54
7.3 Specification Limits ((§15.247(b)(3))	54

7.4	Operating Condition of EUT	54
7.5	Test Procedure	54
7.6	Test Results	55
8	EMISSION LIMITATIONS MEASUREMENT	59
8.1	Test Equipment.....	59
8.2	Block Diagram of Test Setup	59
8.3	Specification Limits (§15.247(d))	59
8.4	Operating Condition of EUT	59
8.5	Test Procedure	59
8.6	Test Results	61
9	POWER SPECTRAL DENSITY MEASUREMENT	71
9.1	Test Equipment.....	71
9.2	Block Diagram of Test Setup	71
9.3	Specification Limits (§15.247(e))	71
9.4	Operating Condition of EUT	71
9.5	Test Procedure	71
9.6	Test Results	72
10	ANTENNA REQUIREMENT	76
10.1	Specification Limits (§15.203).....	76
10.2	Result.....	76
11	MEASUREMENT UNCERTAINTY LIST	77
APPENDIX I PHOTOGRAPHS OF TEST		
APPENDIX II PHOTOGRAPHS OF EUT		

TEST REPORT

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
EUT Description : Cync Dynamic Effects Smart Café Lights
(A) Model No. : Refer to Sec.2.1
(B) Power Supply : 120V AC 60Hz
(C) Test Voltage : 120V/60Hz, DC 3.3V from text fixture

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART C
AND ANSI C63.10-2013*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: Refer to Sec2.1), which was tested is technically compliance with the FCC limits.


This report applies to above tested Sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

The test results for EUT's BLE function are contained in No.ACI-F24155 report.

Date of Test : 2024.09.22-25 Date of Report : 2024.10.18

Producer : Huimin Yan
HUIMIN YAN / Assistant

Review : LVY LV
LVY LV / Deputy Assistant Manager

 For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : Kamp Chen
Authorized Signature(s) KAMP CHEN/Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The result is determined according to the decision rules of customer selection in the ASC-403 application service form.

1. According to IEC GUIDE 115 Procedure 2 and ILAC-G8, the uncertainties value is not used in determining the PASS/FAIL results.

2. If the required specification or standard already contains the decision rules, it will be carried out in accordance with the regulations or standard documents or the requirements of the competent units. If the required specification or standard does not contain a decision rule, the same paragraph 1.

3. If your company has a required decision rule, it will be implemented in accordance with the requirements and ISO/IEC Guide 98-4 specifications.

The EUT have been tested according to the applicable standards as referenced below:

Description / Test Item	Test Standard	Results	Meets Limit
EMISSION			
Conducted Emission	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.207
Radiated Emission	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.209(a) 15.205(a)(c)
6 dB Bandwidth Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(a)(2)
Maximum Output Power Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(b)(3)
Emission Limitations Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(d)
Band Edge Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(d)
Power Spectral Density Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(e)
Antenna Requirement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.203
N/A is an abbreviation for Not Applicable.			

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : Cync Dynamic Effects Smart Café Lights

Type of EUT : ☒ Production ☐ Pre-product ☐ Pro-type

Model Number : CCF48CDOD/ENS, CCF24CDOD/ENS,
CCF96CDOD/ENS, CCF72CDOD/ENS

Note : The hardware design is the same, but the rear light
string length is different, the number of bulbs is
different

Test Model : CCF96CDOD/ENS

Radio Tech : BLE 4.2;
IEEE 802.11 b/g/n.

Channel Freq. : BLE: 2402MHz-2480MHz;
802.11b/g/n: 2412MHz-2462MHz.

Modulation : BLE: GFSK;
802.11b: DSSS (CCK, DQPSK, DBPSK);
802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK).

Antenna Info. : Antenna Type: PCB Antenna
Antenna Gain: 2 dBi

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
1975 Noble Road Cleveland, Ohio United States 44112

Manufacturer : same as Applicant

Factory : VIETNAM CHANGHONG ELECTRIC COMPANY
LIMITED
Workshop W4(leased by WWWHP), Land plot 4.2B, Dinh Vu
Industrial Zone, Dong Hai 2 Ward, Hai An District, Haiphong
City, VN.

2.2 EUT Specifications Assessed in Current Report

Mode	Modulation	Data Rate(Mbps)
802.11b	DS (DQPSK, DBPSK, CCK)	Up to 11
802.11g	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 54
802.11n	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 72.2

Channel List			
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

2.3 Test Information

The test software “UI_mptool.exe” was used to control EUT work in TX mode, Power Index and select test channel.

Mode	data rate (Mbps)	Power index Setting	Test Channel		Frequency (MHz)
802.11b	11	94	Low:	1	2412
		94	Middle:	6	2437
		94	High:	11	2462
802.11g	6	86	Low:	1	2412
		86	Middle:	6	2437
		86	High:	11	2462
802.11n	MCS0	84	Low:	1	2412
		84	Middle:	6	2437
		84	High:	11	2462

2.4 Duty Cycle Check

Mode	Transmission Duration (ms)	Transmission Period (ms)	Duty Cycle (%)	Duty Cycle Correct Factor
802.11b	1	1	100	N/A
802.11g	1	1	100	N/A
802.11n	1	1	100	N/A



2.5 Sample Description

Test Item	Model Number	Sample Number	Date of receipted
Conducted Emission	CCF96CDOD/ENS	E20240914670-01/03	2024.09.14
Radiated Emission	CCF96CDOD/ENS	E20240914670a-01/02	2024.09.14
Conducted RF Test	CCF96CDOD/ENS	E20240914670a-02/02	2024.09.14

2.6 Supported equipment

Brand : Acer
Product Name: : Notebook PC
Model Name : TravelMate P238 series
Model Number : N15W8

Product Name : Test Fixture
Product Function : USB to TTL

2.7 Description of Test Facility

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F, Building 34, No. 680 Guiping Rd.,
Caohejing, Hi-Tech Park,
Shanghai 200233, China

Accredited by NVLAP, Lab Code : 200371-0

FCC Designation Number : CN5027

Test Firm Registration Number : 954668

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESCI	101302	2024.02.22	1 Year
2.	Artificial Mains Network (AMN)	R&S	ESH2-Z5	843890/011	2024.02.22	1 Year
3.	Fixed Attenuator	SHYL	TTS-1	001	2024.02.22	1 Year
4.	50Ω Coaxial Switch	Anritsu	MP59B	6200655085	2024.02.22	1 Year
5.	Coaxial Cable	Audix	CE Cable	CE-SH1-001	2024.02.22	1 Year
6.	Software	Audix	e3	e3.v9.210616	--	--

3.2 Block Diagram of Test Setup

3.2.1 Conducted Disturbance Test Setup



3.3 Conducted Emission Limits (§15.207)

Frequency Range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0.15 ~ 0.5	66~56	56~46
0.5 ~ 5	56	46
5 ~ 30	60	50
NOTE 1 – The lower limit shall apply at the transition frequencies. NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz		

3.4 Test Configuration

The EUT (listed in Sec.2.1) was installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner which tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

3.5.1 Setup the EUT as shown in Sec. 3.2.

3.5.2 Turn on the power of all equipment.

3.5.3 Turn the EUT on the test mode, and then test.

3.6 Test Procedures

The EUT was placed upon a non-metallic table, which is 0.8 m above the horizontal conducting ground plane and 0.4 m from a vertical reference plane. The EUT was connected to the power mains through an Artificial Mains Network (AMN) to provide a 50 Ω coupling impedance for the measuring equipment. Both sides of AC line (Line & Neutral) were checked to find out the maximum conducted emission according to FCC Part 15 Subpart C and ANSI C63.10: 2013 requirements during conducted disturbance test.

The I.F. bandwidth of Test Receiver ESCI was set at 9 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

Test with a dummy load in lieu of the antenna to determine compliance with Section 15.207 limits within the transmitter's fundamental emission band. (According to KDB 174176 D01 Line Conducted FAQ)

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Worst case emission:

(All models had done the pre-test, and finally the results of the worst model “CCF96CDOD/ENS” showed as below.)

No.	Operation	Mode	Channel	Frequency (MHz)	Data Page
1.	Transmitting	802.11b	1	2412	P13-14


NOTE 1 – Emission Level = Read Level + AMN Factor + Aux Factor + Cable Loss
Margin = Limits - Emission Level

NOTE 2 – “QP” means “Quasi-Peak” values


NOTE 3 – The emission levels which not reported are too low against the official limit.

Worst case emission

Test Date:	2024.09.23	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------

Mode: 802.11b CH2412MHz**Polarization at Line**

Frequency (MHz)	Meter Reading dB (μV)	AMN Factor (dB)	Aux Factor (dB)	Cable Loss (dB)	Emission Level dB (μV)	Limits dB (μV)	Margin (dB)	Remark
0.172	32.23	0.10	9.49	0.10	41.92	64.84	22.93	QP
0.172	20.44	0.10	9.49	0.10	30.13	54.84	24.71	Average
0.316	39.38	0.10	9.49	0.10	49.07	59.81	10.74	QP
0.316	32.62	0.10	9.49	0.10	42.31	49.81	7.49	Average
0.342	30.54	0.10	9.49	0.10	40.23	59.15	18.91	QP
0.342	23.35	0.10	9.49	0.10	33.04	49.15	16.11	Average
0.634	21.95	0.20	9.49	0.12	31.76	56.00	24.24	QP
0.634	10.47	0.20	9.49	0.12	20.28	46.00	25.72	Average
1.022	24.44	0.20	9.49	0.14	34.27	56.00	21.73	QP
1.022	15.06	0.20	9.49	0.14	24.89	46.00	21.11	Average
2.930	12.02	0.30	9.49	0.14	21.95	56.00	34.05	QP
2.930	0.59	0.30	9.49	0.14	10.52	46.00	35.48	Average

Mode: 802.11b CH2412MHz**Polarization at Neutral**

Frequency (MHz)	Meter Reading dB (μV)	AMN Factor (dB)	Aux Factor (dB)	Cable Loss (dB)	Emission Level dB (μV)	Limits dB (μV)	Margin (dB)	Remark
0.172	37.50	0.10	9.49	0.10	47.19	64.84	17.65	QP
0.172	26.04	0.10	9.49	0.10	35.73	54.84	19.11	Average
0.316	43.46	0.10	9.49	0.10	53.15	59.81	6.66	QP
0.316	36.71	0.10	9.49	0.10	46.40	49.81	3.41	Average
0.342	33.45	0.10	9.49	0.10	43.14	59.15	16.01	QP
0.342	26.81	0.10	9.49	0.10	36.51	49.15	12.64	Average
0.634	23.52	0.10	9.49	0.12	33.24	56.00	22.76	QP
0.634	12.20	0.10	9.49	0.12	21.91	46.00	24.09	Average
1.025	19.77	0.20	9.49	0.14	29.60	56.00	26.40	QP
1.025	15.56	0.20	9.49	0.14	25.39	46.00	20.61	Average
2.930	16.11	0.20	9.49	0.14	25.94	56.00	30.06	QP
2.930	5.02	0.20	9.49	0.14	14.85	46.00	31.15	Average

4 RADIATED EMISSION TEST

4.1 Test Equipment

The following test equipment are used during the radiated emission test in a semi-anechoic chamber:


Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Preamplifier	Agilent	8447D	2944A10548	2024.02.22	1 Year
2.	Preamplifier	HP	8449B	3008A00864	2024.02.22	1 Year
3.	EXA Signal Analyzer	Agilent	N9010A	MY52221182	2024.07.25	1 Year
4.	Test Receiver	R&S	ESCI	101303	2024.02.22	1 Year
5.	Bilog Antenna+ 6dB Attenuator	Schwarzbeck	VULB 9168+ EMCI-N-6-06	708+AT-N0638	2024.03.08	1 Year
6.	Horn Antenna	EMCO	3115	96074878	2024.08.09	1 Year
7.	Horn Antenna	EMCO	3116	00062643	2024.01.30	2 Year
8.	Cavity Band Rejection Filter	Microwave	WT-A3882-R10	WT200312-1-1	2024.02.22	1 Year
9.	Coaxial Switch	Anritsu	MP59B	6200655086	2024.02.22	1 Year
10.	Coaxial Cable	SCHAFFNER	RG 212U-MIL C 17+N1K50-EW06 30-N1K50-15m-1	RE-10m-001/ RE-15m-002	2024.02.22	1 Year
11.	Software	Audix	e3	e3.v9.210616	--	--

4.2 Block Diagram of Test Setup


4.2.1 EUT & Peripherals



4.2.2 Below 1GHz



4.2.3 Above 1GHz



4.3 Radiated Emission Limit (§15.209)

Frequency (MHz)	Distance (m)	Field strength limits (μV/m)	
		(μV/m)	(μV/m)
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0
NOTE 1 - Emission Level dB (μV/m) = 20 log Emission Level (μV/m) NOTE 2 - The tighter limit applies at the band edges. NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system. NOTE 4 - The limits shown are based on Quasi-peak value detector below or equal to 1GHz and Average value detector above 1GHz. NOTE 5 - Above 1 GHz, the limit on peak emission is 20 dB above the maximum permitted average emission limit applicable to the EUT			

4.4 Test Configuration

The EUT (listed in Sec.2.1) and the simulators (listed in Sec.2.2) were installed as shown on Sec.4.2 to meet FCC requirements and operating in a manner that tends to maximize its emission level in a normal application.

4.5 Operating Condition of EUT

4.5.1 Setup the EUT as shown in Sec. 4.2.

4.5.2 Connect the EUT and the TTL terminal of Test Fixture through three HCI cables of EUT, as follows (VCC to 3V3, TX to RXD, RX to TXD, GND to GND). Plug the USB terminal of Test Fixture to the USB port of Notebook PC.

4.5.3 Use the software as section 2.3 to select the test mode, and then test.

4.5.4 Repeat step 4.5.3 and 4.5.4, until the test of all modes finished.

4.6 Test Procedures

Radiated emission test applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205. The maximum permitted average field strength is listed in Section 15.209. A pre-amp is necessary for this measurement. For measurement above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

The EUT was placed on a turntable. Below 1 GHz, the table height is 80 cm above the reference ground plane. Above 1 GHz, the table height is 1.5 m. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (Calibrated Bilog Antenna) or Horn antenna was used as

receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.10: 2013 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESCI was set at 120 kHz from 30MHz to 1000MHz.

The bandwidth of Agilent N9010A was set at 1MHz for above 1GHz.

The frequency range from 30 MHz to 25 GHz (Up to 10th harmonics from fundamental frequency) was checked.

All the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Frequency range: below 1GHz (Worst case emission)

No.	Operation	Mode	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P20-21

Frequency range: above 1GHz

No.	Operation	Mode	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P22-23
2.			6	2437 MHz	P24-25
3.			11	2462 MHz	P26-27
4.		802.11g	1	2412 MHz	P28-29
5.		802.11n	1	2412 MHz	P30-31

Band-Edge and Restricted bands:

No.	Operation	Mode	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P32-33
2.			11	2462 MHz	P34-35
3.		802.11g	1	2412 MHz	P36-37
4.			11	2462 MHz	P38-39
5.		802.11n	1	2412 MHz	P40-41
6.			11	2462 MHz	P42-43

NOTE 1 – Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin = Limits - Emission Level.

NOTE 2 – “QP” means “Quasi-Peak” values

NOTE 3 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 4 – The emission levels which not reported are too low against the official limit.

NOTE 5 – The emission levels recorded below is data of EUT configured in Lying direction, for this direction was the maximum emission direction during the test. The data of Side & Standing direction are too low against the official limit to be reported.

NOTE 6 – All reading are Quasi-Peak values below or equal to 1GHz, Peak and Average values above 1GHz.


For above 1GHz test, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

NOTE 7 – The frequency range 2310-2390MHz & 2483.5-2500MHz were tested for Restricted bands.

Radiated emission < 1GHz


Test Date:	2024.09.22	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------

Mode: 802.11b CH2412MHz



Polarization at Horizontal



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
144.082	43.99	19.00	1.40	29.20	35.19	43.50	8.31	QP
160.065	43.28	19.10	1.47	29.16	34.68	43.50	8.82	QP
168.414	43.50	18.76	1.50	29.14	34.63	43.50	8.87	QP
192.419	45.14	16.26	1.61	28.97	34.03	43.50	9.47	QP
199.986	49.54	15.70	1.64	28.90	37.99	43.50	5.51	QP
800.382	33.62	28.10	3.27	29.50	35.49	46.00	10.51	QP

Mode: 802.11b CH2412MHz**Polarization at Vertical**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
144.335	34.35	19.00	1.40	29.20	25.55	43.50	17.95	QP
160.065	33.53	19.10	1.47	29.16	24.93	43.50	18.57	QP
199.986	39.34	15.70	1.64	28.90	27.78	43.50	15.72	QP
532.897	39.99	23.86	2.76	29.80	36.81	46.00	9.19	QP
665.804	32.69	26.12	3.03	29.77	32.07	46.00	13.93	QP
800.382	32.04	28.10	3.27	29.50	33.91	46.00	12.09	QP



Radiated Emission > 1GHz

Test Date:	2024.09.22	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------

Mode: 802.11b CH2412MHz**Polarization at Horizontal**



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3229.125	42.26	31.22	5.95	36.20	43.23	74.00	30.77	Peak
4822.875	50.73	33.25	7.49	35.40	56.08	74.00	17.92	Peak
4822.875	42.22	33.25	7.49	35.40	47.57	54.00	6.43	Average
7234.750	40.21	36.48	9.38	35.52	50.54	74.00	23.46	Peak
8800.875	36.72	38.30	10.45	35.60	49.86	74.00	24.14	Peak
9835.750	35.97	38.47	11.20	35.35	50.29	74.00	23.71	Peak
17785.380	35.38	45.46	15.85	33.06	63.62	74.00	10.38	Peak
17785.380	20.54	45.46	15.85	33.06	48.78	54.00	5.22	Average

Mode: 802.11b CH2412MHz





Polarization at Vertical



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3320.500	45.56	31.34	6.03	36.16	46.77	74.00	27.23	Peak
3717.875	45.46	32.21	6.38	36.00	48.05	74.00	25.95	Peak
4822.875	42.81	33.25	7.49	35.40	48.17	74.00	25.83	Peak
7234.750	41.55	36.48	9.38	35.52	51.88	74.00	22.12	Peak
8888.000	37.12	38.25	10.47	35.60	50.24	74.00	23.76	Peak
9973.875	36.75	38.50	11.31	35.31	51.25	74.00	22.75	Peak
17740.750	35.63	45.32	15.78	33.08	63.66	74.00	10.34	Peak
17740.750	20.26	45.32	15.78	33.08	48.29	54.00	5.71	Average

Mode: 802.11b CH2437MHz**Polarization at Horizontal**



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3271.625	41.07	31.30	5.99	36.18	42.18	74.00	31.82	Peak
4871.750	45.40	33.24	7.55	35.37	50.82	74.00	23.18	Peak
7311.250	39.07	36.90	9.46	35.53	49.90	74.00	24.10	Peak
8622.375	36.92	38.40	10.39	35.60	50.11	74.00	23.89	Peak
9859.125	36.36	38.43	11.21	35.34	50.66	74.00	23.34	Peak
17881.000	34.78	45.74	15.99	33.03	63.48	74.00	10.52	Peak
17881.000	19.28	45.74	15.99	33.03	47.98	54.00	6.02	Average

Mode: 802.11b CH2437MHz**Polarization at Vertical**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3184.500	46.95	31.10	5.91	36.22	47.75	74.00	26.25	Peak
3318.375	45.39	31.34	6.03	36.16	46.60	74.00	27.40	Peak
4873.875	41.15	33.25	7.55	35.37	46.58	74.00	27.42	Peak
7313.375	40.93	36.90	9.46	35.53	51.76	74.00	22.24	Peak
8718.000	36.58	38.42	10.42	35.60	49.82	74.00	24.18	Peak
9659.375	37.54	38.20	11.05	35.40	51.40	74.00	22.60	Peak
17776.880	35.41	45.43	15.84	33.07	63.61	74.00	10.39	Peak
17776.880	20.34	45.43	15.84	33.07	48.54	54.00	5.46	Average



Mode: 802.11b CH2462MHz**Polarization at Horizontal**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3460.750	41.52	31.30	6.16	36.10	42.87	74.00	31.13	Peak
4922.750	43.68	33.39	7.60	35.34	49.33	74.00	24.67	Peak
6293.375	38.54	34.59	8.54	35.36	46.30	74.00	27.70	Peak
7389.875	38.30	36.98	9.54	35.54	49.28	74.00	24.72	Peak
8539.500	37.24	38.40	10.36	35.60	50.40	74.00	23.60	Peak
9956.875	35.91	38.50	11.29	35.31	50.39	74.00	23.61	Peak
17783.250	35.79	45.45	15.84	33.06	64.02	74.00	9.98	Peak
17783.250	20.38	45.45	15.84	33.06	48.61	54.00	5.39	Average

Mode: 802.11b CH2462MHz**Polarization at Vertical**



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3197.250	47.82	31.10	5.92	36.21	48.63	74.00	25.37	Peak
3724.250	45.88	32.25	6.39	36.00	48.51	74.00	25.49	Peak
4924.875	43.17	33.40	7.60	35.34	48.83	74.00	25.17	Peak
7385.625	39.48	36.97	9.54	35.54	50.45	74.00	23.55	Peak
8868.875	37.00	38.32	10.47	35.60	50.19	74.00	23.81	Peak
9848.500	38.14	38.50	11.21	35.34	52.50	74.00	21.50	Peak
17785.380	35.16	45.46	15.85	33.06	63.40	74.00	10.60	Peak
17785.380	20.42	45.46	15.85	33.06	48.66	54.00	5.34	Average

Mode: 802.11g CH2412MHz





Polarization at Horizontal



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3324.750	43.88	31.35	6.04	36.16	45.11	74.00	28.89	Peak
4825.000	42.58	33.25	7.50	35.40	47.93	74.00	26.07	Peak
5893.875	39.98	33.80	8.23	35.30	46.70	74.00	27.30	Peak
7328.250	38.10	36.90	9.48	35.53	48.95	74.00	25.05	Peak
8741.375	37.32	38.19	10.43	35.60	50.33	74.00	23.67	Peak
9959.000	36.37	38.50	11.30	35.31	50.86	74.00	23.14	Peak
17800.250	35.79	45.50	15.87	33.06	64.10	74.00	9.90	Peak
17800.250	20.08	45.50	15.87	33.06	48.39	54.00	5.61	Average

Mode: 802.11g CH2412MHz**Polarization at Vertical**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3188.750	45.61	31.10	5.92	36.22	46.42	74.00	27.58	Peak
3596.750	44.85	31.41	6.28	36.05	46.48	74.00	27.52	Peak
4797.375	40.12	33.26	7.47	35.41	45.44	74.00	28.56	Peak
6195.625	39.79	34.58	8.45	35.34	47.49	74.00	26.51	Peak
8057.125	38.46	37.60	10.21	35.60	50.67	74.00	23.33	Peak
9933.500	36.43	38.37	11.28	35.32	50.76	74.00	23.24	Peak
17808.750	35.47	45.53	15.88	33.06	63.83	74.00	10.17	Peak
17808.750	20.25	45.53	15.88	33.06	48.60	54.00	5.40	Average

Mode: 802.11n CH2412MHz**Polarization at Horizontal**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3320.500	42.05	31.34	6.03	36.16	43.26	74.00	30.74	Peak
4827.125	49.02	33.25	7.50	35.39	54.37	74.00	19.63	Peak
4827.125	40.45	33.25	7.50	35.39	45.80	54.00	8.20	Average
7241.125	39.33	36.53	9.39	35.53	49.72	74.00	24.28	Peak
8845.500	36.98	38.39	10.46	35.60	50.24	74.00	23.76	Peak
9914.375	36.34	38.22	11.26	35.32	50.49	74.00	23.51	Peak
17715.250	35.51	45.25	15.74	33.08	63.42	74.00	10.58	Peak
17715.250	20.45	45.25	15.74	33.08	48.36	54.00	5.64	Average


Mode: 802.11n CH2412MHz**Polarization at Vertical**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3326.875	47.80	31.35	6.04	36.16	49.03	74.00	24.97	Peak
4822.875	41.97	33.25	7.49	35.40	47.32	74.00	26.68	Peak
5991.625	39.60	34.17	8.28	35.30	46.76	74.00	27.24	Peak
7247.500	43.59	36.58	9.39	35.53	54.03	74.00	19.97	Peak
7247.500	34.63	36.58	9.39	35.53	45.08	54.00	8.92	Average
9570.125	37.07	38.10	10.98	35.43	50.72	74.00	23.28	Peak
17798.130	35.12	45.49	15.87	33.06	63.42	74.00	10.58	Peak
17798.130	20.41	45.49	15.87	33.06	48.71	54.00	5.29	Average

Band-Edge and Restricted bands:

Test Date:	2024.09.22	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------


Mode: 802.11b CH2412MHz



Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2357.157	65.76	28.51	5.20	36.89	62.58	74.00	11.42	Peak
2390.000	64.03	28.58	5.23	36.86	60.98	74.00	13.02	Peak

Mode: 802.11b CH2412MHz




Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2377.600	53.03	28.56	5.21	36.87	49.93	54.00	4.07	Average
2390.000	52.46	28.58	5.23	36.86	49.40	54.00	4.60	Average

Mode: 802.11b CH2412MHz

Polarization at Vertical


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2381.890	65.37	28.56	5.22	36.87	62.28	74.00	11.72	Peak
2390.000	62.59	28.58	5.23	36.86	59.54	74.00	14.46	Peak

Mode: 802.11b CH2412MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2364.308	51.52	28.53	5.20	36.89	48.36	54.00	5.64	Average
2390.000	50.92	28.58	5.23	36.86	47.87	54.00	6.13	Average


Mode: 802.11b CH2462MHz



Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	63.17	28.50	5.31	36.77	60.21	74.00	13.79	Peak
2493.355	65.12	28.50	5.31	36.76	62.17	74.00	11.83	Peak

Mode: 802.11b CH2462MHz




Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	52.92	28.50	5.31	36.77	49.96	54.00	4.04	Average
2484.310	53.31	28.50	5.31	36.77	50.35	54.00	3.65	Average

Mode: 802.11b CH2462MHz

Polarization at Vertical


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	62.74	28.50	5.31	36.77	59.78	74.00	14.22	Peak
2489.395	65.34	28.50	5.31	36.76	62.39	74.00	11.61	Peak

Mode: 802.11b CH2462MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	51.22	28.50	5.31	36.77	48.26	54.00	5.74	Average
2489.320	51.27	28.50	5.31	36.76	48.32	54.00	5.68	Average


Mode: 802.11g CH2412MHz



Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2352.413	65.42	28.50	5.19	36.90	62.22	74.00	11.78	Peak
2390.000	63.01	28.58	5.23	36.86	59.95	74.00	14.05	Peak

Mode: 802.11g CH2412MHz




Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2367.915	52.65	28.54	5.21	36.88	49.51	54.00	4.49	Average
2390.000	52.82	28.58	5.23	36.86	49.76	54.00	4.24	Average

Mode: 802.11g CH2412MHz


Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.518	65.88	28.56	5.22	36.87	62.78	74.00	11.22	Peak
2390.000	63.02	28.58	5.23	36.86	59.96	74.00	14.04	Peak

Mode: 802.11g CH2412MHz


Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2352.933	51.43	28.51	5.19	36.90	48.23	54.00	5.77	Average
2390.000	50.86	28.58	5.23	36.86	47.81	54.00	6.19	Average

Mode: 802.11g CH2462MHz


Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	65.36	28.50	5.31	36.77	62.40	74.00	11.60	Peak
2483.695	68.28	28.50	5.31	36.77	65.32	74.00	8.68	Peak

Mode: 802.11g CH2462MHz


Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	53.52	28.50	5.31	36.77	50.56	54.00	3.44	Average
2494.390	52.81	28.50	5.32	36.76	49.87	54.00	4.13	Average

Mode: 802.11g CH2462MHz


Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)	Remark
2483.500	64.90	28.50	5.31	36.77	61.94	74.00	12.06	Peak
2492.620	64.59	28.50	5.31	36.76	61.65	74.00	12.35	Peak

Mode: 802.11g CH2462MHz


Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)	Remark
2483.500	51.39	28.50	5.31	36.77	48.43	54.00	5.57	Average
2488.945	51.17	28.50	5.31	36.76	48.22	54.00	5.78	Average

Mode: 802.11n CH2412MHz

Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2361.577	65.08	28.52	5.20	36.89	61.92	74.00	12.08	Peak
2390.000	63.59	28.58	5.23	36.86	60.54	74.00	13.46	Peak

Mode: 802.11n CH2412MHz

Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.972	52.67	28.56	5.22	36.87	49.58	54.00	4.42	Average
2390.000	52.58	28.58	5.23	36.86	49.53	54.00	4.47	Average


Mode: 802.11n CH2412MHz



Polarization at Vertical


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2377.080	65.28	28.55	5.21	36.87	62.17	74.00	11.83	Peak
2390.000	62.57	28.58	5.23	36.86	59.51	74.00	14.49	Peak

Mode: 802.11n CH2412MHz




Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2366.063	51.75	28.53	5.20	36.89	48.60	54.00	5.40	Average
2390.000	51.27	28.58	5.23	36.86	48.22	54.00	5.78	Average

Mode: 802.11n CH2462MHz


Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	65.08	28.50	5.31	36.77	62.12	74.00	11.88	Peak
2497.405	64.87	28.50	5.32	36.75	61.94	74.00	12.06	Peak

Mode: 802.11n CH2462MHz


Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	53.56	28.50	5.31	36.77	50.60	54.00	3.40	Average
2494.000	52.64	28.50	5.31	36.76	49.70	54.00	4.30	Average

Mode: 802.11n CH2462MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)	Remark
2483.500	64.29	28.50	5.31	36.77	61.33	74.00	12.67	Peak
2493.775	64.75	28.50	5.31	36.76	61.81	74.00	12.19	Peak

Mode: 802.11n CH2462MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)	Remark
2483.500	51.64	28.50	5.31	36.77	48.68	54.00	5.32	Average
2493.355	51.19	28.50	5.31	36.76	48.25	54.00	5.75	Average


5 99% OCCUPIED BANDWIDTH MEASUREMENT

5.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2024.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2024.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2024.09.21	1 Year

5.2 Block Diagram of Test Setup



5.3 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

5.4 Test Procedure

The transmitter output was connected to the spectrum analyzer. The bandwidth of 99% power bandwidth was measure by spectrum analyzer with settings: Span = between 1.5 times and 5.0 times of the OBW, RBW = 1% to 5% of the OBW, VBW $\geq 3 \times$ RBW, Detector = Peak, Trace = Max Hold.

Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

The test procedure is defined in ANSI C63.10-2013 (the 6.9.3 Measurement Procedure “Occupied bandwidth—power bandwidth (99%) measurement procedure” was used).

5.5 Test Results


PASSED.

All the test results are attached in next pages.

(Test Date: 2024.09.24 Temperature: 23°C Humidity: 51 %)

Mode	Channel	Frequency (MHz)	99% Bandwidth (MHz)
802.11b	1	2412	13.944
	6	2437	13.944
	11	2462	13.941
802.11g	1	2412	17.134
	6	2437	17.131
	11	2462	17.129
802.11n	1	2412	18.106
	6	2437	18.108
	11	2462	18.103

802.11b



CH2462



802.11g


CH2412



CH2437



CH2462




802.11n

CH2412



CH2437



CH2462



6 6 dB BANDWIDTH MEASUREMENT

6.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2024.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2024.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2024.09.21	1 Year

6.2 Block Diagram of Test Setup

The Same as Section. 5.2.

6.3 Specification Limits (§15.247(a)(2))

The minimum 6 dB bandwidth shall be at least 500 kHz.

6.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

6.5 Test Procedure

The transmitter output was connected to the spectrum analyzer. The bandwidth of the fundamental frequency was measure by spectrum analyzer with settings: RBW = 100kHz, VBW $\geq 3 \times$ RBW.

The 6 dB bandwidth is defined as the total spectrum the power of which is lower than peak power minus 6 dB .

The test procedure is defined in ANSI C63.10-2013 (the 11.8.2 Measurement Procedure “Option 2” was used).

6.6 Test Results

PASSED.

All the test results are attached in next pages.

(Test Date: 2024.09.25 Temperature: 23°C Humidity: 51 %)


Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit
802.11b	1	2412	7.945	500 kHz
	6	2437	7.947	500 kHz
	11	2462	7.947	500 kHz
802.11g	1	2412	16.55	500 kHz
	6	2437	16.56	500 kHz
	11	2462	16.56	500 kHz
802.11n	1	2412	17.72	500 kHz
	6	2437	17.73	500 kHz
	11	2462	17.72	500 kHz

802.11b

CH2412



CH2437



CH2462



802.11g

CH2412



CH2437



CH2462



802.11n

CH2412



CH2437



CH2462



7 MAXIMUM OUTPUT POWER MEASUREMENT

7.1 Test Equipment

The following test equipment was used during the maximum peak output power measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2024.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2024.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2024.09.21	1 Year

7.2 Block Diagram of Test Setup

The Same as Section. 5.2.

7.3 Specification Limits ((§15.247(b)(3))

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5 MHz is: 1 Watt. (30 dBm)

7.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

7.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Method AVGSA-1 uses trace averaging with the EUT transmitting at full power throughout each sweep.

The procedure for this method is as follows:

- Set span to at least 1.5 times the OBW.
- Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
- Trace average at least 100 traces in power averaging (rms) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power

function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

The test procedure is defined in ANSI C63.10-2013 (11.9.2.2.2 Measurement Procedure “ Method AVGSA-1” was used).

7.6 Test Results

PASSED.

All the test results are listed below.

(Test Date: 2024.09.24 Temperature: 23°C Humidity: 51 %)

Mode	Channel	Frequency (MHz)	Maximum conducted (average) Output Power (dBm)	Limit
802.11b	1	2412	17.71	30 dBm
	6	2437	17.74	30 dBm
	11	2462	17.74	30 dBm
802.11g	1	2412	12.56	30 dBm
	6	2437	12.67	30 dBm
	11	2462	12.63	30 dBm
802.11n	1	2412	11.91	30 dBm
	6	2437	11.94	30 dBm
	11	2462	12.1	30 dBm

802.11b


CH2412



CH2437




CH2462




802.11g


CH2412



CH2437




CH2462




802.11n


CH2412



CH2437



CH2462



8 EMISSION LIMITATIONS MEASUREMENT

8.1 Test Equipment

The following test equipment was used during the emission limitations test:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2024.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2024.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2024.09.21	1 Year

8.2 Block Diagram of Test Setup

The Same as Section. 5.2.

8.3 Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). (※This test result attaching to Section. 3.7)

8.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

8.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 times the DTS bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to

establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Scan up through 10th harmonic.

The test procedure is defined in ANSI C63.10-2013 (11.11.2 Reference level measurement and 11.11.3 Emission level measurement was used).

8.6 Test Results

PASSED.

The test data was attached in the next pages.


(Test Date: 2023.09.24 Temperature: 23°C Humidity: 51 %)

Mode	Channel	Frequency (MHz)	Data Page
802.11b	1	2412	P62
	6	2437	P63
	11	2462	P64
802.11g	1	2412	P65
	6	2437	P66
	11	2462	P67
802.11n	1	2412	P68
	6	2437	P69
	11	2462	P70


802.11b

CH2412



Reference Level



Lower Edge



Emission Level





802.11b

CH2437

Reference Level



Emission Level




802.11b

CH2462



Reference Level



Higher Edge




Emission Level




802.11g

CH2412



Reference Level



Lower Edge




Emission Level





802.11g

CH2437

Reference Level




Emission Level




802.11g

CH2462



Reference Level



Higher Edge




Emission Level




802.11n

CH2412



Reference Level



Lower Edge




Emission Level





802.11n

CH2437

Reference Level




Emission Level




802.11n

CH2462



Reference Level



Higher Edge



Emission Level



9 POWER SPECTRAL DENSITY MEASUREMENT

9.1 Test Equipment

The following test equipment was used during the power spectral density measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2024.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2024.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2024.09.21	1 Year

9.2 Block Diagram of Test Setup

The Same as section 5.2.

9.3 Specification Limits (§15.247(e))

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

9.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Method AVGPSD-1 uses trace averaging with EUT transmitting at full power throughout each sweep.

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to at least 1.5 times the OBW.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = power averaging (rms) or sample detector (when rms not available).
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- Sweep time = auto couple.
- Employ trace averaging (rms) mode over a minimum of 100 traces.

- i) Use the peak marker function to determine the maximum amplitude level.
- j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

The test procedure is defined in ANSI C63.10-2013 (11.10.5 Measurement Procedure “Method AVGPSD-1” was used).

9.6 Test Results

PASSED.

All the test results are attached in next pages.

(Test Date: 2024.09.25 Temperature: 23°C Humidity: 51 %)


Mode	Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limit
802.11b	1	2412	-6.11	8 dBm
	6	2437	-6.212	8 dBm
	11	2462	-6.219	8 dBm
802.11g	1	2412	-20.537	8 dBm
	6	2437	-20.475	8 dBm
	11	2462	-20.564	8 dBm
802.11n	1	2412	-21.905	8 dBm
	6	2437	-21.734	8 dBm
	11	2462	-21.688	8 dBm

802.11b


CH2412



CH2437




CH2462




802.11g


CH2412



CH2437




CH2462




802.11n


CH2412



CH2437



CH2462



10 ANTENNA REQUIREMENT

10.1 Specification Limits (§15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 Result

According to KDB 353028 D1, the following describes the three ways that can be used to demonstrate compliance to Section 15.203:

- a) Antenna permanently attached.
- b) Unique (non-standard) antenna connector.
- c) Professional installation.

For this product, the antenna is:

- ☒ Antenna permanently attached
- ☐ Unique (non-standard) antenna connector
- ☐ Professional installation
- ☐ not meet any of ways list above

that

- ☒ compliant
- ☐ not compliant

with the requirement of Section 15.203.

11 MEASUREMENT UNCERTAINTY LIST

The measurement uncertainty was estimated for test on the EUT according to CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage of K=2.

The uncertainties value is not used in determining the PASS/FAIL results.

Test Items/Facilities	Frequency/Equipment/Unit	Uncertainty
Conducted Emission No.1 Shielded Room	9kHz~150kHz	±3.1 dB
	150kHz~30MHz	±2.6 dB
Conducted Emission No.3 Shielded Room	9kHz~150kHz	±3.1 dB
	150kHz~30MHz	±2.6 dB
Radiated Emission	30MHz~200MHz, Horizontal	±3.8 dB
	30MHz~200MHz, Vertical	±4.1 dB
	200MHz~1000MHz, Horizontal	±3.6 dB
	200MHz~1000MHz, Vertical	±5.1 dB
	1GHz~6GHz	±5.3 dB
	6GHz~18GHz	±5.3 dB
	18GHz~40GHz	±3.5 dB
Output Power Test	50MHz~18GHz	0.77 dB
Power Density Test	9kHz~6GHz	1.08 dB
RF Frequency Test	9kHz~40GHz	6×10^{-4}
Bandwidth Test	9kHz~6GHz	1.5×10^{-3}
RF Radiated Power Test	30MHz~1000MHz	3.06 dB
Conducted Output Power Test	50MHz~18GHz	0.83 dB
AC Voltage(<10kHz) Test	120V~230V	0.04 %
DC Power Test	0V~30V	0.4 %
Temperature	-40°C~+100°C	0.52 °C
Humidity	30%~95%	2.6 %