



TONLY

表格编号: TCLAV-C4-4075001
版本: V 6.9
表格修订日期: 2019-09-06

物料编号: 72-T0GGLE-RG0B2
内容: 操作指南
型号: GE 单火线
图纸版本号: V1.0
是否含美国走向: 含
日期: 2019-12-5
美工制 作 人: 蒋文玲

此文件及附属公司机密文件, 版权属通力电子控股有限公司所有, 任何人未经允许不得复制、抄袭。任何部门如有需求, 须向通力电子研发申请。
These files are confidential documents in company. The copyright totally belongs to Tonly electronic holdings Limited. Anybody who are unauthorized is forbidden to copy and plagiarize the files. Any Department must get permission from the Tonly R&D if they need to use them.

ART WORK FORM

(密级: C级)

品牌名称 (BRAND NAME): GE

文档提供 (FROM): GE

工艺说明 (尺寸单位: 毫米 (mm)):

02/49/54/55/56/57/59/67/79 类:

部品	XXXX
工艺、颜色	
成型及颜色 (直接注塑颜色)	N/A
喷油及颜色	N/A
丝印颜色 /移印颜色	N/A
电镀/真空镀 及颜色	N/A
烫金及颜色	N/A
镭 雕	N/A
其他工艺	N/A
备 注	N/A

74/89 类:

印刷方式	XXXX
备 注	N/A

76 类:

印刷方式	XXXX
表面工艺	XXXX
样板需求	签正式样板 ☐ 签彩稿样板 ☐ 基础机型彩盒样板参考料号: 76-XXXXXX-XXXXX
备 注	N/A

70/72/99 (说明书光盘) 类:

语言种类	N/A
材 质	封面: 157g双铜 内页: 100g双铜
尺 寸	长: 108mm 宽: 83mm
印刷方式	1专色 (cool gray 11C) + 4色
表面工艺	封面封底过哑胶, 内页过哑油
装订方式	N/A
页 数	30P
备 注	N/A

71 类:

表纸材质	型号: XXXX 厚度: XXXX
胶水材质	型号: XXXX 是否可移: XXXX
尺 寸	长: XXXX 宽: XXXX
印刷方式	XXXX
表面工艺	XXXX
打印方式	XXXX
粘贴位置	XXXX
材质库编码	N/A
样板需求	需要签样 ☐ 不需要签样 ☐ 参考料号: 71-XXXXXX-XXXXX
☐ UPC / ☐ EAN / ☐ JAN	N/A
备 注	N/A

制作要求 (* FOR ALL):

- ☒ 条码扫描等级达到C级以上;
- ☒ 美国走向必须满足CP65要求;
- ☒ 必须满足RoHS2.0、REACH要求;
- ☒ 必须符合TCL通力《公司环境管理物质标准》要求;
- ☒ QR Code的制作或打印过程中需选择模型2 (M2);
- ☒ 所用油墨必须达到TCL质量部门检测标准;
- ☒ 胶袋材质、胶袋上透气孔的大小、位置以结构认可书为准;
- ☒ PE材质的胶袋其上面的丝印内容整体长度可允许3mm误差;
- ☒ 珍珠棉等材质的胶袋其上面的丝印内容整体长度可允许5mm误差;

* FOR HUAWEI:

- ☒ 满足无卤要求;
- ☒ 满足不含有邻苯二甲酸盐要求。

* FOR SAMSUNG:

- ☒ VD类产品需满足三星的SS要求, AI类产品需满足三星SA要求。

* FOR SONY:

- ☒ 禁止使用SS-00259中规定的I级环境管理物质。
- ☒ 再生树脂、被覆线材必须从索尼的绿色伙伴认定供应商处采购。

Process CYAN	Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process YELLOW	Process BLACK	Version# (date) 7 (10-31-19) CN
		Bar Code: N/A
		Insert: NONE
		Supplier Project#: N/A
		Print Method: ☐ Offset/Litho ☐ Flexo (direct)
PMS COOL GRAY 11		GE DIE#: NOT CONTROLLED
		PK#: PK-00102798-1

 Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.		
REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Reading – Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability		



Smart Wall Switch
Installation Guide



On/Off Switch

Models
CSWONBLWFINN
CSWONBLPWFINN
CSWONBLTWFINN

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.
3.25"

Process CMAN Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
GE Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities. REVIEWED DATE SIGNATURE PACKAGING GRAPHICS ☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability	
Process CMAN Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
Process CMAN Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"



PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process CMW	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process MAGENTA	Version# (date): 7 (10-31-19) CN
Process YELLOW	Bar Code: N/A
Process BLACK	Insert: NONE
Process CMW	Supplier Project#: N/A
Process CMW	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process CMW	GE DIE#: NOT CONTROLLED
Process CMW	PK#: PK-00102798-1



Lighting Graphics App roval
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Reading - Spelling	☐ Website	
☐ Proof against TDS request	☐ Graphics Printability	

Process CMW	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process MAGENTA	Version# (date): 7 (10-31-19) CN
Process YELLOW	Bar Code: N/A
Process BLACK	Insert: NONE
Process CMW	Supplier Project#: N/A
Process CMW	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process CMW	GE DIE#: NOT CONTROLLED
Process CMW	PK#: PK-00102798-1



Lighting Graphics App roval
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Reading - Spelling	☐ Website	
☐ Proof against TDS request	☐ Graphics Printability	

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Compatibility Requirements

Rating 120V AC 60Hz
Neutral wire is not required
(Wire is usually white or grey and is not required)
Ground wire is required
(Wire is usually green, green with a yellow stripe, or copper) 
W-H 802.11 b/g/n @ 2.4 GHz

Works with halogen, incandescent, and LED bulbs, including C by GE Smart Bulbs.
LED up to 125 amps
Incandescent/halogen up to 3 amps

4. For Help, Go To cbyge.com/switch-support or call 1-844-30C-BYGE

4.25"

! IMPORTANT NOTE ON 3-WAY WIRING:
Some lights have one wall switch, while others are controlled by two switches. If you are installing a switch at both the top and bottom of the stairs, if your lights have more than one switch (called a 3-way), we've created instructions for how to install and enable the capability.

Visit cbyge.com/switch-support for 3-way installation instructions and how-to-videos.

5. For Help, Go To cbyge.com/switch-support or call 1-844-30C-BYGE

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process Cyan	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process Magenta	Version# (date): 7 (10-31-19) CN
	Bar Code: N/A
Process Yellow	Insert: NONE
Process Black	Supplier Project#: N/A
Process Yellow	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
	GE DIE#: NOT CONTROLLED
Process Black	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

Process Cyan	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process Magenta	Version# (date): 7 (10-31-19) CN
	Bar Code: N/A
Process Yellow	Insert: NONE
Process Black	Supplier Project#: N/A
Process Yellow	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
	GE DIE#: NOT CONTROLLED
Process Black	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

Let's Do It

INCLUDED





Approximately 30 minutes of your day to install and setup the switch

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

Process CMAN Process MAGENTA Process YELLOW Process BLACK	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
---	--



Lighting Graphics App roval

Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling

☐ Website

☐ Proof against TDS request

☐ Graphics Printability

Process CMAN Process MAGENTA Process YELLOW Process BLACK	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
---	--



Lighting Graphics App roval

Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling

☐ Website

☐ Proof against TDS request

☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"


IF APPLICABLE

Install adaptor onto C by GE smart or non-dimmable LED bulbs

C by GE smart switches and dimmers are compatible with C by GE smart bulbs. To keep your C by GE bulbs always available and connected, the included bulb adaptor should be used to have full control of C by GE bulbs on the same circuit as the switch.
NOTE: Only one bulb adaptor is needed per switch, even if there are multiple C by GE bulbs on the circuit.

Simply twist the bulb adaptor onto the base of the C by GE smart bulb and screw into the fixture.

NOTE: Keep your bulb adaptor handy. Even if you don't have C by GE bulbs, the bulb adaptor can be used to improve the performance of some traditional LED bulbs. If you begin experiencing any performance issues, if installing in a recessed can fixture, or if you are unsure of the depth of the recessed can to ensure the bulb is flush. Go to: cbyge.com/switch-support for more helpful tips on when to use the bulb adaptor.



For Help, Go To: cbyge.com/switch-support or call 1-844-3DC-BYGE

10

For Help, Go To: cbyge.com/switch-support or call 1-844-3DC-BYGE

11

4.25"

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process COAT Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 585/626 Q3
Process YELLOW Process BLACK	Version# (date): 7 (10-31-19) CN
	Bar Code: N/A
	Insert: NONE
	Supplier Project#: N/A
	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
	GE DIE#: NOT CONTROLLED
MS COAT 6867 11	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

Process COAT Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 585/626 Q3
Process YELLOW Process BLACK	Version# (date): 7 (10-31-19) CN
	Bar Code: N/A
	Insert: NONE
	Supplier Project#: N/A
	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
MS COAT 6867 11	GE DIE#: NOT CONTROLLED
	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

STEP 2

Remove Your Old Switch


1. Remove the existing wall plate and switch from the wall

2. Use voltage tester on the black wires to confirm power to the switch is off (recommended)

3. Before disconnecting the wires from the wall, label each with the provided wire labels

▲ Ground wire is required. If you don't have this wire, the C by GE switch is not compatible.

4. Disconnect wires and remove existing switch.



For Help, Go To: cbyge.com/switch-support or call 1-844-30C-BYGE

13

STEP 2

Remove Your Old Switch


1. Remove the existing wall plate and switch from the wall

2. Use voltage tester on the black wires to confirm power to the switch is off (recommended)

3. Before disconnecting the wires from the wall, label each with the provided wire labels

▲ Ground wire is required. If you don't have this wire, the C by GE switch is not compatible.

4. Disconnect wires and remove existing switch.



For Help, Go To: cbyge.com/switch-support or call 1-844-30C-BYGE

13

4.25"

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process Cyan	Process Magenta	Job#/Project Name: 93120082 NPI C by GE 585/626 Q3
Version# (date): 7 (10-31-19) CN		
Bar Code: N/A		
Insert: NONE		
Supplier Project#: N/A		
Print Method: ☐ Offset/Litho ☐ Flexo (direct)		
GE DIE#: NOT CONTROLLED		
PK#: PK-00102798-1		

Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.		
REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability		

Process Cyan	Process Magenta	Job#/Project Name: 93120082 NPI C by GE 585/626 Q3
Version# (date): 7 (10-31-19) CN		
Bar Code: N/A		
Insert: NONE		
Supplier Project#: N/A		
Print Method: ☐ Offset/Litho ☐ Flexo (direct)		
GE DIE#: NOT CONTROLLED		
PK#: PK-00102798-1		

Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.		
REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability		

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

STEP 3

Connect The Wires

NOTE: Both black wires on the switch are interchangeable and can be connected to either the load or line wire from the wall.


1. Connect the first line/load (black) wire on the switch to the line or load (black bspl) wire from the wall.
2. Connect the second line/load (black) wire on the switch to the line or load (black bspl) wire from the wall.
3. Connect the ground (green) wire from the switch to the ground and green bspl wire from the wall.
4. Cap the 3-wire/multi-way traveler wire with a cap screw.
5. Cap the switch wire from the wall (if applicable). Neutral wire is not required to operate this switch.

Attention: Incorrectly connecting the ground wire from the switch to the ground and green bspl wire will damage the product.

14

For Help, Go To cbyge.com/switch-support or call 1-844-3DC-BYGE

USING WIRE NUTS



15

For Help, Go To cbyge.com/switch-support or call 1-844-3DC-BYGE

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

4.25"

4.25"

Process Cyan	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process Magenta	Version# (date): 7 (10-31-19) CN
Process Yellow	Bar Code: N/A
Process BLACK	Insert: NONE
Process YELLOW	Supplier Project#: N/A
Process BLACK	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process BLACK	GE DIE#: NOT CONTROLLED
Process BLACK	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

Process Cyan	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process Magenta	Version# (date): 7 (10-31-19) CN
Process Yellow	Bar Code: N/A
Process BLACK	Insert: NONE
Process YELLOW	Supplier Project#: N/A
Process BLACK	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process BLACK	GE DIE#: NOT CONTROLLED
Process BLACK	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

STEP 4

Fit Wires Into Wall Box

Neatly push the wires back into the box, rotating the switch so it's oriented according to the image.

16

For Help, Go To cbyge.com/switch-support or call 1-844-30C-WIRE

17

For Help, Go To cbyge.com/switch-support or call 1-844-30C-WIRE

4.25"

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process CMAN	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process MAGENTA	Version# (date): 7 (10-31-19) CN
Process YELLOW	Bar Code: N/A
Process BLACK	Insert: NONE
Process CMAN	Supplier Project#: N/A
Process CMAN	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process CMAN	GE DIE#: NOT CONTROLLED
Process CMAN	PK#: PK-00102798-1



Lighting Graphics App roval
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
---------------	-----------	--------------------

☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability

Process CMAN	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3
Process MAGENTA	Version# (date): 7 (10-31-19) CN
Process YELLOW	Bar Code: N/A
Process BLACK	Insert: NONE
Process CMAN	Supplier Project#: N/A
Process CMAN	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process CMAN	GE DIE#: NOT CONTROLLED
Process CMAN	PK#: PK-00102798-1



Lighting Graphics App roval
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
---------------	-----------	--------------------

☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

STEP 5

Secure The Switch

Using a Phillips screwdriver and the screws provided, secure the switch to the wall until level and flush. Then snap the icecube cover onto the bracket.

18

For Help, Go To: evyge.com/switch-support or call 1-844-30C-EVGE

19

For Help, Go To: evyge.com/switch-support or call 1-844-30C-EVGE

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process Cyan Process Magenta Process Yellow Process Black MS Color Bar V11	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
--	--



Lighting Graphics App roval

Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website

☐ Proof against TDS request ☐ Graphics Printability

Process Cyan Process Magenta Process Yellow Process Black MS Color Bar V11	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
--	--



Lighting Graphics App roval

Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website

☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

STEP 6

Turn The Power Back On

After the switch is secured and faceplate mounted, turn the power back on at the circuit breaker box. At the switch, LED indicator light or the device is wired correctly and the correct wire is secured to the correct button on the switch to enable setup mode if setup mode times out.



LED indicator light or light ring will flash blue until the switch is added to the C by GE app.

LED indicator light or light ring will flash red if the circuit is overloaded. Max load rating 125 amps for LED and 5 amps for incandescent/halogen.

LED indicator light or light ring will not illuminate if wired incorrectly.

IF LIGHTS DON'T TURN ON:

1. Check that power to the switch is on at the breaker.

2. Turn power off at the breaker, return to the switch to confirm the wires are securely and properly wired according to the installation guide.

3. Go to cbyge.com/switch-support for more troubleshooting.

For Help, Go To: cbyge.com/switch-support or call 1-844-30C-BYGE

20

For Help, Go To: cbyge.com/switch-support or call 1-844-30C-BYGE

21

4.25"

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

		Job#/Project Name	39120082 N/A - by GE 5857626 Q3
		Version# (Idet)	7.10-31-19) CN
		Bar Code:	N/A
		Insert:	NONE
		Supplier Project#:	N/A
		Print Method:	☐ Offset/Litho ☐ Flexo direct
		GE DIE#:	NOT CONTROLLED
		PK#:	PK-00102796-1



Lighting Graphics App

royal

Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REQUEST DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Feeding - Spelling		☐ Website
☐ Proof against TDS request		☐ Graphics Printability

	Process CMYK
	Process MAGENTA
Job#/Project Name 39120002 NR C by GE S&S/626 Q3	
Version# (Idlet) 7.10-31-19/CN	
Bar Code: N/A	
Insert NONE	
Supplier Project#: N/A	
Print Method: ☐ Offset/Litho ☐ Flexo (direct)	
GE DIE#: NOT CONTROLLED	
PK#: PK-00102798-1	
	Process YELLOW
	Process BLACK
	PMS 600/11



Lighting Graphics App

Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REPAIRS DATE	SIGNATURE	PACKAGING GRAPHICS
☐ Proof Reading – Spelling ☐ Proof against TDS request	☐ Website ☐ Graphics Printability	

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

Download

the C by GE app

Add

your Smart Switch to the C by GE app

Setup

your Alexa or Google Assistant to follow the instructions in the C by GE app

Next...

Amazon Alexa

To setup, open the Alexa app, search for the C by GE skill, follow the setup instructions.

Google Assistant

To setup, open the Google Assistant or Google Home app, search for the C by GE skill, follow the setup instructions.

Try this...

Alexa, turn off the living room. Alexa, turn on the bedroom.

Try this...

Hey Google, turn on the lights. Hey Google, good morning. Hey Google, I'm leaving.

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

Process COAN Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
GE Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities. REVIEWED DATE SIGNATURE PACKAGING GRAPHICS	☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

Additional Information and Warnings

FCC Compliance Statement Compliance Notice:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. Operation is subject to the following two conditions:
1. This device may not cause harmful interference.
2. This device must accept any interference received, including that which may cause undesired operation.

Harmful interference can be caused by radio frequency energy and, if received in excessive amounts, may cause undesired operation of this equipment. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to the equipment' off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules and Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference received, including that which may cause undesired operation.

Changes or modifications that are not expressly approved by the manufacturer could void the user's authority to operate the equipment.

RF Exposure Information:
This equipment complies with FCC radiation exposure limits set forth in FCC Part 15.2. This equipment has been evaluated and found to comply with the applicable RF exposure limits when used in accordance with the manufacturer's instructions. The maximum SAR for this equipment, when used in accordance with the manufacturer's instructions, is 1.6 W/kg (head and torso combined) when used in the following conditions:
• Normal operation.
• During normal operation.

RF Exposure Statement:
This equipment complies with IC RSS-102 radiation exposure limits set forth for an uncontrolled environment. This transmitter must be installed to provide a separation distance of at least 8 inches between the transmitter and the user or any other person wearing a mobile telephone, pager or other radio transmitting device, or in conjunction with any other antenna or transmitter.

4.25"

4.25"

Process COAN Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3 Version# (date): 7 (10-31-19) CN Bar Code: N/A Insert: NONE Supplier Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct) GE DIE#: NOT CONTROLLED PK#: PK-00102798-1
GE Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities. REVIEWED DATE SIGNATURE PACKAGING GRAPHICS	☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

 Process CMYK  Process MAGENTA  Process YELLOW  Process BLACK		 PMS 660/11  PMS 660/11  PMS 660/11  PMS 660/11		Job#/Project Name: 93120082 NPL C by GE S&S 7/2/20 03 Version# (date): 7.10-31-191 CN Bar Code: N/A Insert: NONE Supply Project#: N/A Print Method: ☐ Offset/Litho ☐ Flexo (direct)		 Lighting Graphics App Approvals designate all items on checklists have been reviewed & are correct in addition to other organizational responsibilities.	
GE PIE# NOT CONTROLLED PK# PK-00102798-1		RELATED DATE: _____ SIGNATURE: _____ PACKAGING GRAPHICS: _____		☐ Proof Reading - Spelling ☐ Website ☐ Proof against TDS request ☐ Graphics Printability			

PC93120082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

PC9312082 INS

This art is supplied at 100% size.

Do not resize, reshape or alter in any way.

3.25"

Ressemblances supplémentaires et mises en garde

Déclaration de conformité aux normes de la FCC :

Cet appareil a été testé et reconnu conforme aux limites fédérales pour les appareils numériques de classe B, selon la section 15 des règlements de la FCC. Ces limitations ne garantissent pas l'absence d'interférence radio, mais elles réduisent considérablement le risque de telles interférences. Cet équipement est produit en vertu de la Loi sur l'accès à l'information et peut désigner une énergie de fréquence radio. Il n'est pas initialement utilisé conformément aux protocoles. Il peut provoquer un brouillage indésirable aux fréquences radio, ce qui peut entraîner des interférences radio. Ce brouillage peut être évité en utilisant une méthode d'installation particulière. Si cet équipement ne provoque pas d'interférence nuisible à la réception de la radio ou de la télévision, ce qu'on peut vérifier en éteignant l'appareil, l'utilisateur doit être en mesure de réajuster le réglage de l'antenne pour éliminer l'interférence en appliquant l'une ou plusieurs des mesures suivantes :

- Réorienter ou repositionner l'antenne de réception.
- Augmenter la distance séparant l'équipement du récepteur.
- Connecter l'équipement à une prise sur un circuit différent de celui auquel le récepteur est branché.
- Consulter le revendeur ou un technicien de radio-TV expérimenté pour obtenir de l'aide.

26

4.25"

4.25"

Process Cyan	Job#/Project Name: 93120082 NPI C by GE 585/626 Q3
Process Magenta	Version# (date): 7 (10-31-19) CN
Process YELLOW	Bar Code: N/A
Process BLACK	Insert: NONE
Process BLACK	Supplier Project#: N/A
Process BLACK	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process BLACK	GE DIE#: NOT CONTROLLED
Process BLACK	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

Process Cyan	Job#/Project Name: 93120082 NPI C by GE 585/626 Q3
Process Magenta	Version# (date): 7 (10-31-19) CN
Process YELLOW	Bar Code: N/A
Process BLACK	Insert: NONE
Process BLACK	Supplier Project#: N/A
Process BLACK	Print Method: ☐ Offset/Litho ☐ Flexo (direct)
Process BLACK	GE DIE#: NOT CONTROLLED
Process BLACK	PK#: PK-00102798-1

**Lighting Graphics App roval**
Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.

REVIEWED DATE

SIGNATURE

PACKAGING GRAPHICS

☐ Proof Reading - Spelling ☐ Website
☐ Proof against TDS request ☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

For supply connections, use copper wire only rated at 75°C.

A CAUTION - High Voltage - Disconnect power supply before servicing

Operation temperature: 0-40°C
For Control or Electronic Ballast, CFL, LED, and LED Lamp, Type 1 Enclosure
IP20
Pollution Degree 2
Impulse Voltage: 2500V
Type 1 action

Indoor use only.

Pour les raccordements d'alimentation, utiliser du fil de cuivre d'une température nominale de 75 °C seulement.

ATTENTION - Haute tension - Débrancher l'alimentation électrique avant d'effectuer l'entretien

Température de fonctionnement : De 0 °C à 40 °C
Pour le contrôle des lampes à ballast électronique, Boîtier de type 1
IP20
Degré de pollution 2
Tension de choc : 2 500 V
Action de type 1

Réservé à un usage intérieur.

4.25"

4.25"

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"

Process CYAN	Process MAGENTA	Job#/Project Name: 93120082 NPI C by GE 5857626 Q3	
		Version# (date) 7 (10-31-19) CN	
		Bar Code: N/A	
		Insert: NONE	
Process YELLOW	Process BLACK	Supplier Project#: N/A	
		Print Method: ☐ Offset/Litho ☐ Flexo (direct)	
		GE DIE#: NOT CONTROLLED	
PMS COOL GRAY 11		PK#: PK-00102798-1	

REVIEWED DATE	SIGNATURE	PACKAGING GRAPHICS
Lighting Graphics App roval Approvals designate all items on checklist have been reviewed & are correct in addition to other organizational responsibilities.		
☐ Proof Reading – Spelling		☐ Website
☐ Proof against TDS request		☐ Graphics Printability

PC93120082 INS

This art is supplied at 100% size.
Do not resize, reshape or alter in any way.

3.25"



4.25"