TESTING LABORATORY
CERTIFICATE#4323.01

FCC PART 15.247

TEST REPORT

For

JiangSu HuiTong Group Co.,Ltd

24#,2 block TaoHuawu new district,ZhenJiang City, JiangSu,P.R.C,ZhenJiang, China

FCC ID: PUW−HTSF2203

Report Type:	**Product Type:**
Original Report	RealityAdapter

Test Engineer:	Stone Zhang
Report Number:	RSHA180906006-00C
Report Date:	2018-10-13
Reviewed By:	Oscar Ye RF Leader
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EQUIPMENT MODIFICATIONS 6
EUT EXERCISE SOFTWARE 6
SUPPORT EQUIPMENT LIST AND DETAILS 10
EXTERNAL I/O CABLE 10
BLOCK DIAGRAM OF TEST SETUP 10
SUMMARY OF TEST RESULTS **12**
TEST EQUIPMENT LIST **13**
FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) **14**
APPLICABLE STANDARD 14
CALCULATED FORMULARY: 14
CALCULATED DATA: 15
FCC §15.203 - ANTENNA REQUIREMENT **16**
APPLICABLE STANDARD 16
ANTENNA CONNECTOR CONSTRUCTION 16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER SETUP 17
TEST PROCEDURE 17
CORRECTED FACTOR & MARGIN CALCULATION 18
TEST RESULTS SUMMARY 18
TEST DATA 18
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **23**
APPLICABLE STANDARD 23
EUT SETUP 23
EMI TEST RECEIVER SETUP 24
TEST PROCEDURE 24
CORRECTED AMPLITUDE & MARGIN CALCULATION 24
TEST RESULTS SUMMARY 24
TEST DATA 25
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH **60**
APPLICABLE STANDARD 60
TEST PROCEDURE 60
TEST DATA 60
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER **70**
APPLICABLE STANDARD 70
TEST PROCEDURE 70
TEST DATA 71

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....74
APPLICABLE STANDARD 74
TEST PROCEDURE 74
TEST DATA 74
FCC §15.247(e) - POWER SPECTRAL DENSITY 80
APPLICABLE STANDARD 80
TEST PROCEDURE 80
TEST DATA 80

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	JiangSu HuiTong Group Co.,Ltd
Tested Model:	SF2203−H1−001
Series Model:	SF2203−H1−002, SF2203−H2−001, SF2203−H2−002
Model Difference:	Colour and Hole Size
Product Type:	RealityAdapter
Dimension:	78 mm(L) × 40 mm(W) × 10 mm(H)
Power Supply:	DC 5V

**All measurement and test data in this report was gathered from production sample serial number: 20180906006. (Assigned by the BACL. The EUT supplied by the applicant was received on 2018-09-06)*

Objective

This report is prepared on behalf of *JiangSu HuiTong Group Co.,Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS submission with FCC ID: PUW-HTSF2203.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB558074 D01 15.247 Meas Guidance v05.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11;

For 802.11n-HT40 mode, EUT was tested with Channel 3, 6 and 9;

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	…	…
…	…	…	…
…	…	…	…
18	2438	38	2478
19	2440	39	2480

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool: QA Tool for Wi-Fi & WCN_Combo_Tool for BLE

Mode	Data Rate	Power Level
802.11b	1 Mbps	20
802.11g	6 Mbps	26
802.11n-HT20	MCS0	26
802.11n-HT40	MCS0	14
BLE	1Mbps	N/A (software default)

Duty Cycle:

802.11b Mode Middle Channel



802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



Date: 20.SEP.2018 15:58:17

802.11n-HT40 Mode Middle Channel



Date: 20.SEP.2018 15:54:47

BLE Mode Middle Channel



Mode	Duty Cycle (%)	T(us)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0
802.11n-HT40	100	/	/	0
BLE	64.74	405	2.47	1.89

Note: "x" means the Duty Cycle.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263
/	Resistance	100W50R	/

External I/O Cable

Cable Description	Length (m)	From Port	To
USB Cable	0.8	EUT	Resistance

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1310& §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test（Chamber 1#）					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
Radiated Emission Test（Chamber 2#）					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-26	2019-08-25
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band notch Filter	BRM50702	/	2018-08-05	2019-08-04
Narda	Attenuator/10dB	10dB	/	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
RF Conducted Test					
Narda	Attenuator/10dB	10dB	/	2018-08-15	2019-08-14
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2017-09-21	2018-09-20
Agilent	Power Meter	N1912A	MY5000492	2017-11-18	2018-11-17
Agilent	Power Sensor	N1921A	MY54210024	2017-11-18	2018-11-17
JiangSu HuiTong Group Co.,Ltd	RF Cable	/	/	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2017-11-12	2018-11-11
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-08-15	2019-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	**Electric Field Strength (V/m)**	**Magnetic Field Strength (A/m)**	**Power Density (mW/cm²)**	**Averaging Time (minutes)**
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4 π R² = power density (in appropriate units, e.g. mW/cm^2);
P = power input to the antenna (in appropriate units, e.g., mW);
G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Turn-up Conducted Output Power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
		(dBi)	(numeric)	(dBm)	(mW)			
Zigbee	2405~2480	0	1.00	15.00	31.62	20	0.0063	1.0
BT3.0	2402-2480	0	1.00	7.00	5.01	20	0.0010	1.0
BLE	2402-2480	0	1.00	7.00	5.01	20	0.0010	1.0
2.4G Wi-Fi	2412-2462	0	1.00	23.00	199.53	20	0.0397	1.0
	2422-2452	0	1.00	20.00	100.00	20	0.0199	1.0

Note: Zigbee and Wi-Fi can transmit simultaneously; the worst condition is Zigbee & 2.4G Wi-Fi as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0397/1.00+0.0063/1.00=0.0397+0.0063=0.046 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance. MPE evaluation of single and simultaneous transmission meets the requirement of standard.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a metal antenna and the antenna gain is 0 dBi, which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz - 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV) - Corrected Amplitude (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	24.1 ℃~24.3 ℃
Relative Humidity:	45 %~50 %
ATM Pressure:	101.1kPa~101.2kPa

The testing was performed by Stone Zhang from 2018-09-11 to 2018-09-12.

Data for Wi-Fi:

EUT operation mode: Transmitting in high channel of 802.11n-HT20 mode. (Worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.155	43.60	QP	9.000	L1	16.06	65.86	22.26	Compliance
0.155	21.05	AV	9.000	L1	16.06	55.86	34.81	Compliance
0.265	31.78	QP	9.000	L1	16.03	62.71	30.93	Compliance
0.265	14.10	AV	9.000	L1	16.03	52.71	38.61	Compliance
0.415	25.64	QP	9.000	L1	16.06	58.43	32.79	Compliance
0.415	20.61	AV	9.000	L1	16.06	48.43	27.82	Compliance
1.700	24.37	QP	9.000	L1	15.86	56.00	31.63	Compliance
1.700	19.57	AV	9.000	L1	15.86	46.00	26.43	Compliance
5.400	18.01	QP	9.000	L1	15.88	60.00	41.99	Compliance
5.400	12.97	AV	9.000	L1	15.88	50.00	37.03	Compliance
18.450	21.19	QP	9.000	L1	16.37	60.00	38.81	Compliance
18.400	16.66	AV	9.000	L1	16.37	50.00	33.34	Compliance

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	44.29	QP	9.000	N	16.06	66.00	21.71	Compliance
0.150	22.77	AV	9.000	N	16.06	56.00	33.23	Compliance
0.250	33.55	QP	9.000	N	16.06	63.14	29.59	Compliance
0.250	14.68	AV	9.000	N	16.06	53.14	38.46	Compliance
0.440	23.18	QP	9.000	N	16.10	57.71	34.53	Compliance
0.440	13.74	AV	9.000	N	16.10	47.71	33.97	Compliance
1.550	21.94	QP	9.000	N	15.92	56.00	34.06	Compliance
1.550	16.38	AV	9.000	N	15.92	46.00	29.62	Compliance
5.100	20.11	QP	9.000	N	15.87	60.00	39.89	Compliance
5.100	14.50	AV	9.000	N	15.87	50.00	35.50	Compliance
18.250	21.93	QP	9.000	N	16.11	60.00	38.07	Compliance
18.250	17.75	AV	9.000	N	16.11	50.00	32.25	Compliance

Note:
1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
2) Margin (dB) = Limit (dBμV) - Corrected Amplitude (dBμV)

Data for BLE:

EUT operation mode: Transmitting in low channel. (Worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	44.66	QP	9.000	L1	16.06	66.00	21.34	Compliance
0.150	21.28	AV	9.000	L1	16.06	56.00	34.72	Compliance
0.260	32.54	QP	9.000	L1	16.02	62.86	30.32	Compliance
0.260	14.04	AV	9.000	L1	16.02	52.86	38.82	Compliance
0.415	25.36	QP	9.000	L1	16.06	58.43	33.07	Compliance
0.415	21.22	AV	9.000	L1	16.06	48.43	27.21	Compliance
1.800	23.87	QP	9.000	L1	15.86	56.00	32.13	Compliance
1.800	18.33	AV	9.000	L1	15.86	46.00	27.67	Compliance
5.300	18.02	QP	9.000	L1	15.87	60.00	41.98	Compliance
5.300	13.85	AV	9.000	L1	15.87	50.00	36.15	Compliance
18.250	21.04	QP	9.000	L1	16.36	60.00	38.96	Compliance
18.250	17.23	AV	9.000	L1	16.36	50.00	32.77	Compliance

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	42.41	QP	9.000	N	16.06	66.00	23.59	Compliance
0.150	31.11	AV	9.000	N	16.06	56.00	24.89	Compliance
0.245	38.75	QP	9.000	N	16.06	63.29	24.54	Compliance
0.245	24.48	AV	9.000	N	16.06	53.29	28.81	Compliance
0.395	36.35	QP	9.000	N	16.09	59.00	22.65	Compliance
0.395	28.11	AV	9.000	N	16.09	49.00	20.89	Compliance
3.800	25.99	QP	9.000	N	15.89	56.00	30.01	Compliance
3.800	19.18	AV	9.000	N	15.89	46.00	26.82	Compliance
7.150	33.68	QP	9.000	N	15.92	60.00	26.32	Compliance
7.100	28.03	AV	9.000	N	15.92	50.00	21.97	Compliance
20.800	34.55	QP	9.000	N	16.17	60.00	25.45	Compliance
20.750	27.00	AV	9.000	N	16.17	50.00	23.00	Compliance

Note:
1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
2) Margin (dB) = Limit (dBμV) - Corrected Amplitude (dBμV)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector	Duty Cycle	Detector
30 MHz – 1000 MHz	120 kHz	/	QP	/	QP
Above 1GHz	1MHz	3 MHz	PK	/	PK
	1MHz	3 MHz	RMS	>98%	Ave.
	1MHz	1/T	PK	<98%	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV /m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The "**Margin**" column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	24.1-24.4 ℃
Relative Humidity:	49-50 %
ATM Pressure:	101.1-101.2kPa

The testing was performed by Stone Zhang from 2018-09-13 to 2018-10-12.

EUT operation mode: Transmitting

Data for Wi-Fi:

Spurious Emission Test:

30MHz-1GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case ***High channel of 802.11n-HT20 mode in X-axis of orientation*** *was recorded*



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	QuasiPeak (dBµV/m)	Height (cm)	Polar (H/V)				
203.974000	29.24	199.0	H	39.0	-12.3	43.50	14.26
215.999950	28.36	199.0	V	112.0	-12.3	43.50	15.14
239.898450	40.51	101.0	H	2.0	-12.1	46.00	5.49
251.953350	42.21	101.0	H	0.0	-12.0	46.00	3.79
263.902150	34.38	199.0	H	344.0	-11.6	46.00	11.62
287.953950	41.73	101.0	H	342.0	-10.9	46.00	4.27

30MHz-1GHz:

The worst case channel 26 of operation and High channel of 802.11n-HT20 mode transmitting simultaneously in X-axis of orientation *was recorded*



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
57.094250	30.44	199.0	V	107.0	-17.8	40.00	9.56
99.596250	29.18	101.0	V	224.0	-15.0	43.50	14.32
132.140750	34.19	199.0	H	341.0	-11.7	43.50	9.31
232.336500	30.18	199.0	H	320.0	-12.2	46.00	15.82
384.005850	33.98	101.0	H	322.0	-8.5	46.00	12.02
600.005850	26.96	199.0	H	204.0	-5.2	46.00	19.04

1GHz-18GHz:

802.11b Mode:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1006.800000	---	33.09	150.0	H	208.0	-10.4	54.00	20.91
1006.800000	47.51	---	150.0	H	208.0	-10.4	74.00	26.49
3070.600000	---	36.17	200.0	V	269.0	-1.5	54.00	17.83
3070.600000	43.35	---	200.0	V	269.0	-1.5	74.00	30.65
4824.000000	---	41.73	100.0	H	293.0	1.9	54.00	12.27
4824.000000	46.53	---	100.0	H	293.0	1.9	74.00	27.47
7236.000000	---	38.46	100.0	V	355.0	9.0	54.00	15.54
7236.000000	47.64	---	100.0	V	355.0	9.0	74.00	26.36
11031.700000	---	41.11	150.0	H	208.0	13.4	54.00	12.89
11031.700000	51.46	---	150.0	H	208.0	13.4	74.00	22.54
17529.100000	---	48.72	150.0	H	15.0	17.2	54.00	5.28
17529.100000	57.09	---	150.0	H	15.0	17.2	74.00	16.91

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1005.100000	---	33.66	100.0	H	230.0	-10.4	54.00	20.34
1005.100000	49.51	---	100.0	H	230.0	-10.4	74.00	24.49
3070.600000	---	38.30	200.0	V	217.0	-1.5	54.00	15.70
3070.600000	44.20	---	200.0	V	217.0	-1.5	74.00	29.80
4874.000000	---	40.75	100.0	H	280.0	1.9	54.00	13.25
4874.000000	47.11	---	100.0	H	280.0	1.9	74.00	26.89
7311.000000	---	38.74	200.0	V	217.0	9.2	54.00	15.26
7311.000000	46.59	---	200.0	V	217.0	9.2	74.00	27.41
10336.400000	---	41.44	100.0	V	24.0	12.7	54.00	12.56
10336.400000	51.05	---	100.0	V	24.0	12.7	74.00	22.95
17609.000000	---	48.03	150.0	H	25.0	17.3	54.00	5.97
17609.000000	56.53	---	150.0	H	25.0	17.3	74.00	17.47

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1011.900000	---	32.45	150.0	H	211.0	-10.4	54.00	21.55
1011.900000	47.72	---	150.0	H	211.0	-10.4	74.00	26.28
3070.600000	---	36.23	200.0	V	275.0	-1.5	54.00	17.77
3070.600000	42.37	---	200.0	V	275.0	-1.5	74.00	31.63
4924.000000	---	39.51	150.0	H	2.0	2.0	54.00	14.49
4924.000000	45.18	---	150.0	H	2.0	2.0	74.00	28.82
7386.000000	---	38.72	150.0	H	226.0	9.4	54.00	15.28
7386.000000	47.95	---	150.0	H	226.0	9.4	74.00	26.05
10309.200000	---	41.71	200.0	V	171.0	12.7	54.00	12.29
10309.200000	51.19	---	200.0	V	171.0	12.7	74.00	22.81
17549.500000	---	48.21	150.0	H	345.0	17.2	54.00	5.79
17549.500000	56.52	---	150.0	H	345.0	17.2	74.00	17.48

802.11g Mode:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1027.200000	---	29.48	150.0	H	192.0	-10.3	54.00	24.52
1027.200000	44.46	---	150.0	H	192.0	-10.3	74.00	29.54
3070.600000	---	37.33	200.0	V	84.0	-1.5	54.00	16.67
3070.600000	44.51	---	200.0	V	84.0	-1.5	74.00	29.49
4824.000000	---	33.65	150.0	V	348.0	2.0	54.00	20.35
4824.000000	44.06	---	150.0	V	348.0	2.0	74.00	29.94
7236.000000	---	40.22	150.0	H	176.0	10.6	54.00	13.78
7236.000000	50.98	---	150.0	H	176.0	10.6	74.00	23.02
11249.300000	---	42.67	200.0	V	308.0	13.2	54.00	11.33
11249.300000	52.43	---	200.0	V	308.0	13.2	74.00	21.57
17615.800000	---	47.52	150.0	H	262.0	17.3	54.00	6.48
17615.800000	56.95	---	150.0	H	262.0	17.3	74.00	17.05

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1018.700000	---	29.93	150.0	H	242.0	-10.4	54.00	24.07
1018.700000	45.30	---	150.0	H	242.0	-10.4	74.00	28.70
3070.600000	---	35.33	200.0	V	77.0	-1.5	54.00	18.67
3070.600000	42.49	---	200.0	V	77.0	-1.5	74.00	31.51
4874.000000	---	33.93	200.0	H	276.0	1.9	54.00	20.07
4874.000000	43.33	---	200.0	H	276.0	1.9	74.00	30.67
7311.000000	---	38.86	150.0	V	3.0	9.1	54.00	15.14
7311.000000	47.89	---	150.0	V	3.0	9.1	74.00	26.11
11217.000000	---	42.60	200.0	H	239.0	13.2	54.00	11.40
11217.000000	51.08	---	200.0	H	239.0	13.2	74.00	22.92
17534.200000	---	48.86	150.0	V	166.0	17.2	54.00	5.14
17534.200000	57.50	---	150.0	V	166.0	17.2	74.00	16.50

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1025.500000	---	29.94	200.0	H	209.0	-10.3	54.00	24.06
1025.500000	45.60	---	200.0	H	209.0	-10.3	74.00	28.40
3070.600000	---	37.15	200.0	V	90.0	-1.5	54.00	16.85
3070.600000	43.59	---	200.0	V	90.0	-1.5	74.00	30.41
4924.000000	---	34.03	200.0	V	288.0	2.0	54.00	19.97
4924.000000	42.93	---	200.0	V	288.0	2.0	74.00	31.07
7386.000000	---	39.62	200.0	H	334.0	9.8	54.00	14.38
7386.000000	49.98	---	200.0	H	334.0	9.8	74.00	24.02
11036.800000	---	42.58	150.0	H	124.0	13.4	54.00	11.42
11036.800000	50.18	---	150.0	H	124.0	13.4	74.00	23.82
17586.900000	---	48.39	200.0	V	229.0	17.3	54.00	5.61
17586.900000	57.37	---	200.0	V	229.0	17.3	74.00	16.63

802.11n-HT20 Mode:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1003.400000	---	32.03	150.0	H	247.0	-10.4	54.00	21.97
1003.400000	46.73	---	150.0	H	247.0	-10.4	74.00	27.27
3070.600000	---	36.49	200.0	V	273.0	-1.5	54.00	17.51
3070.600000	44.16	---	200.0	V	273.0	-1.5	74.00	29.84
4824.000000	---	32.72	150.0	H	279.0	1.9	54.00	21.28
4824.000000	43.16	---	150.0	H	279.0	1.9	74.00	30.84
7236.000000	---	38.01	150.0	H	40.0	8.9	54.00	15.99
7236.000000	46.92	---	150.0	H	40.0	8.9	74.00	27.08
10341.500000	---	41.22	150.0	V	228.0	12.7	54.00	12.78
10341.500000	51.17	---	150.0	V	228.0	12.7	74.00	22.83
17578.400000	---	47.28	150.0	H	153.0	17.3	54.00	6.72
17578.400000	57.22	---	150.0	H	153.0	17.3	74.00	16.78

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1015.300000	---	32.37	150.0	H	244.0	-10.4	54.00	21.63
1015.300000	46.55	---	150.0	H	244.0	-10.4	74.00	27.45
3070.600000	---	37.02	200.0	V	87.0	-1.5	54.00	16.98
3070.600000	43.60	---	200.0	V	87.0	-1.5	74.00	30.40
4874.000000	---	34.19	150.0	H	358.0	1.9	54.00	19.81
4874.000000	42.42	---	150.0	H	358.0	1.9	74.00	31.58
7311.000000	---	38.92	150.0	H	89.0	9.2	54.00	15.08
7311.000000	47.55	---	150.0	H	89.0	9.2	74.00	26.45
10540.400000	---	41.30	200.0	V	359.0	12.8	54.00	12.70
10540.400000	50.54	---	200.0	V	359.0	12.8	74.00	23.46
17558.000000	---	48.87	150.0	H	104.0	17.3	54.00	5.13
17558.000000	57.41	---	150.0	H	104.0	17.3	74.00	16.59

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1017.000000	---	33.64	150.0	H	247.0	-10.4	54.00	20.36
1017.000000	45.64	---	150.0	H	247.0	-10.4	74.00	28.36
3070.600000	---	36.83	200.0	V	90.0	-1.5	54.00	17.17
3070.600000	42.94	---	200.0	V	90.0	-1.5	74.00	31.06
4924.000000	---	35.29	150.0	H	0.0	2.0	54.00	18.71
4924.000000	43.03	---	150.0	H	0.0	2.0	74.00	30.97
7386.000000	---	39.41	150.0	V	2.0	9.3	54.00	14.59
7386.000000	48.81	---	150.0	V	2.0	9.3	74.00	25.19
11689.600000	---	42.35	150.0	H	154.0	13.0	54.00	11.65
11689.600000	53.09	---	150.0	H	154.0	13.0	74.00	20.91
17563.100000	---	48.33	200.0	V	160.0	17.3	54.00	5.67
17563.100000	56.57	---	200.0	V	160.0	17.3	74.00	17.43

802.11n-HT40 Mode:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2422MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1003.400000	---	33.79	150.0	H	241.0	-10.4	54.00	20.21
1003.400000	49.76	---	150.0	H	241.0	-10.4	74.00	24.24
3070.600000	---	36.64	200.0	V	76.0	-1.5	54.00	17.36
3070.600000	43.20	---	200.0	V	76.0	-1.5	74.00	30.80
4844.000000	---	34.09	200.0	H	344.0	1.9	54.00	19.91
4844.000000	42.74	---	200.0	H	344.0	1.9	74.00	31.26
7266.000000	---	37.71	200.0	H	350.0	9.0	54.00	16.29
7266.000000	47.18	---	200.0	H	350.0	9.0	74.00	26.82
10185.100000	---	42.69	150.0	V	25.0	12.7	54.00	11.31
10185.100000	50.73	---	150.0	V	25.0	12.7	74.00	23.27
17556.300000	---	47.77	200.0	H	344.0	17.2	54.00	6.23
17556.300000	57.01	---	200.0	H	344.0	17.2	74.00	16.99

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1013.600000	---	33.26	150.0	H	241.0	-10.4	54.00	20.74
1013.600000	46.27	---	150.0	H	241.0	-10.4	74.00	27.73
3070.600000	---	37.31	200.0	V	77.0	-1.5	54.00	16.69
3070.600000	43.88	---	200.0	V	77.0	-1.5	74.00	30.12
4874.000000	---	33.37	150.0	V	166.0	2.0	54.00	20.63
4874.000000	42.92	---	150.0	V	166.0	2.0	74.00	31.08
7511.000000	---	40.18	150.0	V	319.0	9.9	54.00	13.82
7511.000000	49.70	---	150.0	V	319.0	9.9	74.00	24.30
10866.800000	---	41.38	150.0	H	116.0	13.3	54.00	12.62
10866.800000	51.59	---	150.0	H	116.0	13.3	74.00	22.41
17532.500000	---	47.93	200.0	H	159.0	17.2	54.00	6.07
17532.500000	57.09	---	200.0	H	159.0	17.2	74.00	16.91

High Channel: 2452MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1008.500000	---	33.03	150.0	H	246.0	-10.4	54.00	20.97
1008.500000	47.19	---	150.0	H	246.0	-10.4	74.00	26.81
3070.600000	---	37.93	200.0	V	84.0	-1.5	54.00	16.07
3070.600000	44.40	---	200.0	V	84.0	-1.5	74.00	29.60
4904.000000	---	31.87	150.0	H	151.0	2.0	54.00	22.13
4904.000000	41.84	---	150.0	H	151.0	2.0	74.00	32.16
7356.000000	---	38.43	150.0	V	50.0	9.1	54.00	15.57
7356.000000	47.52	---	150.0	V	50.0	9.1	74.00	26.48
11251.000000	---	42.78	200.0	V	177.0	13.2	54.00	11.22
11251.000000	51.08	---	200.0	V	177.0	13.2	74.00	22.92
17524.000000	---	47.84	200.0	V	99.0	17.2	54.00	6.16
17524.000000	56.15	---	200.0	V	99.0	17.2	74.00	17.85

1GHz-18GHz:

(The worst case channel 26 of operation and High channel of 802.11n-HT20 mode transmitting simultaneously in X-axis of orientation *was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1598.400000	---	24.80	100.0	V	175.0	-7.2	54.00	29.20
1598.400000	38.21	---	100.0	V	175.0	-7.2	74.00	35.79
3070.600000	---	33.97	200.0	V	167.0	-1.5	54.00	20.03
3070.600000	43.10	---	200.0	V	167.0	-1.5	74.00	30.90
4808.000000	57.25	---	100.0	H	196.0	1.8	74.00	16.75
4808.000000	---	48.68	100.0	V	196.0	1.8	54.00	5.32
8174.000000	---	39.46	150.0	V	309.0	10.6	54.00	14.54
8174.000000	50.58	---	150.0	V	309.0	10.6	74.00	23.42
11332.600000	---	40.50	100.0	H	359.0	13.1	54.00	13.50
11332.600000	51.33	---	100.0	H	359.0	13.1	74.00	22.67
17581.800000	---	47.39	100.0	V	95.0	17.3	54.00	6.61
17581.800000	57.84	---	100.0	V	95.0	17.3	74.00	16.16

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case ***High channel of 802.11n-HT20g mode in X-axis of orientation*** *was recorded*

Horizontal



Date: 17.SEP.2018 10:56:51

Vertical



Date: 17.SEP.2018 11:19:21

18GHz-25GHz

***(The worst case channel 26 of operation and High channel of 802.11n-HT20 mode transmitting simultaneously in X-axis of orientation** was recorded)*

Horizontal



Date: 12.OCT.2018 16:58:30

Vertical



Date: 12.OCT.2018 17:22:14

Fundamental Test & Restricted Bands Emissions Test:

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV /m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

802.11b Mode: *(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	---	101.32	100.0	H	244.0	6.1	/	/
2412.000000	103.34	---	100.0	H	244.0	6.1	/	/
2412.000000	---	99.34	200.0	V	163.0	6.1	/	/
2412.000000	101.36	---	200.0	V	163.0	6.1	/	/
2390.000000	---	44.31	150.0	H	181.0	6.0	54.00	9.69
2390.000000	53.65	---	150.0	H	181.0	6.0	74.00	20.35
Middle Channel: 2437MHz								
2437.000000	---	102.61	200.0	V	144.0	6.2	/	/
2437.000000	104.62	---	200.0	V	144.0	6.2	/	/
2437.000000	---	100.66	200.0	H	167.0	6.2	/	/
2437.000000	102.67	---	200.0	H	167.0	6.2	/	/
High Channel: 2462MHz								
2462.000000	---	102.26	150.0	H	326.0	6.3	/	/
2462.000000	104.30	---	150.0	H	326.0	6.3	/	/
2462.000000	---	100.29	150.0	V	218.0	6.3	/	/
2462.000000	102.30	---	150.0	V	218.0	6.3	/	/
2483.500000	---	48.36	200.0	H	189.0	6.3	54.00	5.64
2483.500000	55.59	---	200.0	H	189.0	6.3	74.00	18.41

802.11g Mode: *(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	---	93.23	100.0	H	50.0	6.1	/	/
2412.000000	95.25	---	100.0	H	50.0	6.1	/	/
2412.000000	---	91.29	200.0	V	178.0	6.1	/	/
2412.000000	93.29	---	200.0	V	178.0	6.1	/	/
2390.000000	---	48.63	150.0	H	177.0	6.0	54.00	5.37
2390.000000	58.41	---	150.0	H	177.0	6.0	74.00	15.59
Middle Channel: 2437MHz								
2437.000000	---	93.27	200.0	V	319.0	6.2	/	/
2437.000000	95.32	---	200.0	V	319.0	6.2	/	/
2437.000000	---	91.32	200.0	H	116.0	6.2	/	/
2437.000000	93.36	---	200.0	H	116.0	6.2	/	/
High Channel: 2462MHz								
2462.000000	---	94.16	150.0	H	83.0	6.3	/	/
2462.000000	96.16	---	150.0	H	83.0	6.3	/	/
2462.000000	---	92.14	150.0	V	266.0	6.3	/	/
2462.000000	94.18	---	150.0	V	266.0	6.3	/	/
2483.500000	---	49.69	150.0	H	176.0	6.3	54.00	4.31
2483.500000	62.28	---	150.0	H	176.0	6.3	74.00	11.72

802.11n-HT20 Mode: *(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	---	91.47	100.0	H	276.0	6.1	/	/
2412.000000	93.49	---	100.0	H	276.0	6.1	/	/
2412.000000	---	89.47	200.0	V	69.0	6.1	/	/
2412.000000	91.49	---	200.0	V	69.0	6.1	/	/
2390.000000	---	48.61	100.0	V	179.0	6.0	54.00	5.39
2390.000000	61.43	---	100.0	V	179.0	6.0	74.00	12.57
Middle Channel: 2437MHz								
2437.000000	---	92.35	200.0	V	334.0	6.2	/	/
2437.000000	94.39	---	200.0	V	334.0	6.2	/	/
2437.000000	---	90.35	200.0	H	315.0	6.2	/	/
2437.000000	92.39	---	200.0	H	315.0	6.2	/	/
High Channel: 2462MHz								
2462.000000	---	92.67	150.0	H	28.0	6.3	/	/
2462.000000	94.70	---	150.0	H	28.0	6.3	/	/
2462.000000	---	90.67	150.0	V	32.0	6.3	/	/
2462.000000	92.71	---	150.0	V	32.0	6.3	/	/
2483.500000	---	45.79	200.0	H	198.0	6.3	54.00	8.21
2483.500000	56.51	---	200.0	H	198.0	6.3	74.00	17.49

802.11n-HT40 Mode: *(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2422MHz								
2422.000000	---	86.38	100.0	H	72.0	6.1	/	/
2422.000000	88.40	---	100.0	H	72.0	6.1	/	/
2422.000000	---	84.36	200.0	V	257.0	6.1	/	/
2422.000000	86.40	---	200.0	V	257.0	6.1	/	/
2390.000000	---	48.06	100.0	H	203.0	6.0	54.00	5.94
2390.000000	57.64	---	100.0	H	203.0	6.0	74.00	16.36
Middle Channel: 2437MHz								
2437.000000	---	105.36	200	V	122	6.2	/	/
2437.000000	108.62	---	200	V	122	6.2	/	/
2437.000000	---	105.92	200	H	323	6.2	/	/
2437.000000	107.6	---	200	H	323	6.2	/	/
High Channel: 2452MHz								
2452.000000	---	106.13	150	H	191	6.3	/	/
2452.000000	108.2	---	150	H	191	6.3	/	/
2452.000000	---	105.85	150	H	261	6.3	/	/
2452.000000	107.37	---	150	H	261	6.3	/	/
2483.500000	---	47.68	100.0	V	140.0	6.3	54.00	6.32
2483.500000	57.95	---	100.0	V	140.0	6.3	74.00	16.05

Data for BLE:

Spurious Emission Test:

30MHz-1GHz

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case ***Low channel of operation in the X axis of orientation*** *was recorded)*



Frequency (MHz)	Corrected Amplitude QuasiPeak (dB µ V/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
57.443000	22.58	101.0	V	147.0	-17.8	40.00	17.42
99.951450	34.18	199.0	H	31.0	-14.9	43.50	9.32
144.096800	32.47	199.0	H	175.0	-12.1	43.50	11.03
263.918950	32.51	199.0	H	0.0	-11.6	46.00	13.49
276.078750	40.51	101.0	H	330.0	-11.2	46.00	5.49
57.443000	22.58	101.0	V	147.0	-17.8	40.00	17.42

1GHz-18GHz

*(Pre-scan in the X, Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2402MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	27.65	200.0	V	210.0	-7.2	54.00	26.35
1595.000000	39.88	---	200.0	V	210.0	-7.2	74.00	34.12
3070.600000	---	34.46	200.0	V	84.0	-1.5	54.00	19.54
3070.600000	44.17	---	200.0	V	84.0	-1.5	74.00	29.83
4804.000000	---	32.34	150.0	V	269.0	1.9	54.00	21.66
4804.000000	43.50	---	150.0	V	269.0	1.9	74.00	30.50
7206.000000	---	37.20	150.0	V	281.0	8.9	54.00	16.80
7206.000000	48.40	---	150.0	V	281.0	8.9	74.00	25.60
10458.800000	---	40.43	200.0	H	304.0	12.7	54.00	13.57
10458.800000	52.34	---	200.0	H	304.0	12.7	74.00	21.66
17343.800000	---	44.08	100.0	V	85.0	16.4	54.00	9.92
17343.800000	55.19	---	100.0	V	85.0	16.4	74.00	18.81

Middle Channel: 2440MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1078.200000	---	27.40	200.0	V	251.0	-10.0	54.00	26.60
1078.200000	46.33	---	200.0	V	251.0	-10.0	74.00	27.67
3070.600000	---	34.42	200.0	V	213.0	-1.5	54.00	19.58
3070.600000	44.14	---	200.0	V	213.0	-1.5	74.00	29.86
4880.000000	---	32.57	200.0	V	188.0	1.9	54.00	21.43
4880.000000	41.65	---	200.0	V	188.0	1.9	74.00	32.35
7320.000000	---	37.48	200.0	V	351.0	9.2	54.00	16.52
7320.000000	47.92	---	200.0	V	351.0	9.2	74.00	26.08
11115.000000	---	40.41	200.0	V	314.0	13.3	54.00	13.59
11115.000000	52.10	---	200.0	V	314.0	13.3	74.00	21.90
17694.000000	---	45.05	200.0	H	47.0	17.4	54.00	8.95
17694.000000	57.12	---	200.0	H	47.0	17.4	74.00	16.88

High Channel: 2480MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	25.49	200.0	V	202.0	-7.2	54.00	28.51
1595.000000	38.31	---	200.0	V	202.0	-7.2	74.00	35.69
3070.600000	---	37.26	200.0	H	122.0	-1.5	54.00	36.74
3070.600000	44.04	---	200.0	H	122.0	-1.5	74.00	29.96
4960.000000	---	31.58	150.0	V	3.0	2.1	54.00	22.42
4960.000000	43.69	---	150.0	V	3.0	2.1	74.00	30.31
7440.000000	---	38.37	150.0	V	0.0	9.6	54.00	15.63
7440.000000	48.29	---	150.0	V	0.0	9.6	74.00	25.71
10831.100000	---	40.83	200.0	V	139.0	13.2	54.00	13.17
10831.100000	52.19	---	200.0	V	139.0	13.2	74.00	21.81
17597.100000	---	46.20	150.0	H	242.0	17.3	54.00	7.80
17597.100000	57.00	---	150.0	H	242.0	17.3	74.00	17.00

18GHz-25GHz

*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **Low channel of operation in the X axis of orientation** was recorded)*

Horizontal Plot



Date: 17.SEP.2018 11:42:52

Vertical Plot



Date: 17.SEP.2018 10:16:23

Fundamental Test & Restricted Bands Emissions Test:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)*

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	---	95.42	100.0	H	159.0	6.1	/	/
2402.000000	97.42	---	100.0	H	159.0	6.1	/	/
2402.000000	---	93.42	200.0	V	323.0	6.1	/	/
2402.000000	95.44	---	200.0	V	323.0	6.1	/	/
2390.000000	---	39.51	200.0	V	102.0	6.0	54.00	14.49
2390.000000	48.66	---	200.0	V	102.0	6.0	74.00	25.34
Middle Channel: 2440MHz								
2440.000000	---	96.70	200.0	V	103.0	6.2	/	/
2440.000000	98.74	---	200.0	V	103.0	6.2	/	/
2440.000000	---	94.76	200.0	H	210.0	6.2	/	/
2440.000000	96.79	---	200.0	H	210.0	6.2	/	/
High Channel: 2480MHz								
2480.000000	---	97.52	150.0	H	312.0	6.3	/	/
2480.000000	99.54	---	150.0	H	312.0	6.3	/	/
2480.000000	---	95.53	150.0	V	194.0	6.3	/	/
2480.000000	97.55	---	150.0	V	194.0	6.3	/	/
2483.500000	---	41.52	200.0	V	127.0	6.3	54.00	12.48
2483.500000	51.50	---	200.0	V	127.0	6.3	74.00	22.50

Conducted Spurious Emissions at Antenna Port

802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



802.11g Mode Middle Channel



802.11g Mode High Channel



802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



802.11n-HT40 Mode Low Channel



802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel



BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 * RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	24.1-24.2 ℃
Relative Humidity:	50-51 %
ATM Pressure:	101.2-101.3 kPa

The testing was performed by Stone Zhang from 2018-09-13 to 2018-09-20.

EUT operation mode: Transmitting

Test Result: Pass

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	10.100	≥ 0.5
Middle	2437	10.100	≥ 0.5
High	2462	10.100	≥ 0.5
802.11g Mode			
Low	2412	16.413	≥ 0.5
Middle	2437	16.353	≥ 0.5
High	2462	16.172	≥ 0.5
802.11n-HT20 Mode			
Low	2412	17.615	≥ 0.5
Middle	2437	17.555	≥ 0.5
High	2462	17.194	≥ 0.5
802.11n-HT40 Mode			
Low	2422	35.832	≥ 0.5
Middle	2437	36.313	≥ 0.5
High	2452	36.072	≥ 0.5
BLE Mode			
Low	2402	0.739	≥ 0.5
Middle	2440	0.739	≥ 0.5
High	2480	0.745	≥ 0.5

802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



802.11g Mode Middle Channel



802.11g Mode High Channel



802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



802.11n-HT40 Mode Low Channel



802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel



BLE Mode Low Channel



Date: 13.SEP.2018 15:26:30

BLE Mode Middle Channel



Date: 13.SEP.2018 15:27:57

BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.1 & 11.9.1.3

For Wi-Fi:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



For BLE:

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

1. Set the RBW ≥ DTS bandwidth.
2. Set VBW ≥ 3 x RBW.
3. Set span ≥ 3 x RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data

Environmental Conditions

Temperature:	23.8~26.0℃
Relative Humidity:	48~54 %
ATM Pressure:	101.2 kPa

The testing was performed by Stone Zhang from 2018-09-13 to 2018-09-20.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b Mode				
Low	2412	21.63	≤ 30	Pass
Middle	2437	21.40	≤ 30	Pass
High	2462	22.12	≤ 30	Pass
802.11g Mode				
Low	2412	21.56	≤ 30	Pass
Middle	2437	21.59	≤ 30	Pass
High	2462	21.96	≤ 30	Pass
802.11n-HT20 Mode				
Low	2412	19.98	≤ 30	Pass
Middle	2437	20.50	≤ 30	Pass
High	2462	20.78	≤ 30	Pass
802.11n-HT40 Mode				
Low	2422	19.87	≤ 30	Pass
Middle	2437	19.14	≤ 30	Pass
High	2452	18.19	≤ 30	Pass
BLE Mode				
Low	2402	4.31	≤ 30	Pass
Middle	2440	5.50	≤ 30	Pass
High	2480	6.12	≤ 30	Pass

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.1-24.2 ℃
Relative Humidity:	50-51 %
ATM Pressure:	101.2-101.3 kPa

The testing was performed by Stone Zhang from 2018-09-13 to 2018-09-20.

EUT operation mode: Transmitting

Test Result: Compliance

802.11b Mode Left Side



802.11b Mode Right Side



802.11g Mode Left Side



802.11g Mode Right Side



802.11n-HT20 Mode Left Side



802.11n-HT20 Mode Right Side



802.11n-HT40 Mode Left Side



802.11n-HT40 Mode Right Side



BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: 3kHz≤ RBW≤100 kHz.
2. Set the VBW ≥ 3xRBW.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	24.1-24.2 ℃
Relative Humidity:	50-51 %
ATM Pressure:	101.2-101.3 kPa

The testing was performed by Stone Zhang from 2018-09-13 to 2018-09-20.

EUT operation mode: Transmitting

Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b Mode			
Low	2412	-6.51	≤ 8
Middle	2437	-4.95	≤ 8
High	2462	-6.78	≤ 8
802.11g Mode			
Low	2412	-12.47	≤ 8
Middle	2437	-11.48	≤ 8
High	2462	-11.59	≤ 8
802.11n-HT20 mode			
Low	2412	-10.82	≤ 8
Middle	2437	-12.46	≤ 8
High	2462	-12.50	≤ 8
802.11n-HT40 mode			
Low	2422	-18.69	≤ 8
Middle	2437	-18.07	≤ 8
High	2452	-15.47	≤ 8
BLE Mode			
Low	2402	-11.17	≤ 8
Middle	2440	-10.02	≤ 8
High	2480	-9.49	≤ 8

802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



802.11g Mode Middle Channel



802.11g Mode High Channel



802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



802.11n-HT40 Mode Low Channel



802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel



BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



******* END OF REPORT *******