


Prüfbericht-Nr.: Test report no.:	ULR-TC568820300000024F	Auftrags-Nr.: Order no.:	166451508 0030	Seite 1 von 46 Page 1 of 46
Kunden-Referenz-Nr.: Client reference no.:	NA	Auftragsdatum: Order date:	2019-05-14	
Auftraggeber: Client:	Honeywell International Inc 12, Clintonville Rd, Northford, CT, USA 06472; +1 203 4847161			
Prüfgegenstand: Test item:	CLSS Gateway			
Bezeichnung / Serien-Nr.: Identification / Serial no.:	HON-CGW-MBB			
Auftrags-Inhalt: Order content:	Testing and Issue of FCC and IC certification			
Prüfgrundlage: Test specification:	FCC Part 15 Subpart C 15.247, 15.207 RSS 247 Issue 2 and RSS Gen Issue 5			
Wareneingangsdatum: Date of sample receipt:	2020-05-15			
Prüfmuster-Nr.: Test sample no.:	A002843762-001 A002843762-009			
Prüfzeitraum: Testing period:	2020-05-15 - 2020-06-19			
Ort der Prüfung: Place of testing:	Wireless laboratory, Bangalore			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (India) Pvt. Ltd. 27/B, 2 nd Cross, Electronic City Phase I, Bangalore – 560100, India			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	genehmigt von: authorized by:			
Datum: Date: 2020-05-21		Ausstellatum: Issue date: 2020-08-28		
Stellung / Position:	Raviraj Kamati Engineer	Stellung / Position:	Mahammadgouse Kaladagi Assistant Manager	
Sonstiges / Other:	FCC ID: PV3CGWMB IC:1609A-CGWMB Contains FCC IDs: RI7LE910NAV2, RI7LE910SVV2 Contains IC:5131A-LE910NAV2; 5131A-LE910SVV2			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V05

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 2 von 46
Page 2 of 46

TEST SUMMARY

Test Item	Applicable Standard		Result
	FCC	ISED	
Maximum conducted (average) output power	FCC 15.247(b)(3)	RSS 247 Issue 2, Section 5.4 (d)	Pass
Maximum Power Spectral Density	FCC 15.247(e)	RSS 247 Issue 2, Section 5.2 (b)	NT
DTS Bandwidth	FCC 15.247(a)(2)	RSS 247 Issue 2, Section 5.2 (a)	NT
Emissions in non-restricted frequency bands	FCC 15.247(d)	RSS 247 Issue 2, Section 5.5	NT
Spurious Radiated Emissions and Restricted Bands of Operation	FCC 15.209 / FCC 15.205	RSS-Gen Issue 5, Section 8.9 / 8.10	Pass
Conducted Emissions on a.c Power Lines	FCC 15.207	RSS-Gen Issue 5, Section 8.8	Pass

Note: N/T: Not Tested

CLSS Gateway product was certified with FCC ID: PV3CGWMB , IC:1609A-CGWMB, hence other test cases are excluded which can be found in the test report ULR-TC568819300000099F and ULR-TC5688193000000086F issued to Honeywell by TUV Rheinland India.

Product Category: Electronics Testing
Test Discipline: EMC Test Facility

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 3 von 46
Page 3 of 46

REVISION HISTORY OF THIS REPORT

Report Number	Version	Description	Issue date
ULR-TC568820300000024F	01	Initial issue of report	01.07.2020
ULR-TC568820300000024F	02	Correction in the module identification from CGW-MB to HON-CGW-MBB Note: the Model HON-CGW-MBB covers the addition of Cellular module, hence the changes done to CLSS gateway under C2PC approach shall be only applicable to this model	10.08.2020
ULR-TC568820300000024F	03	Change in HVIN from CCM-BM28 RevA to HON-CGW-MBB	28.08.2020

Table of Contents

1	GENERAL REMARKS	5
1.1	Attachments	5
2	TEST SITES	6
2.1	Testing Facilities.....	6
2.2	List of Test and Measurement Instruments.....	6
3	GENERAL PRODUCT INFORMATION.....	8
3.1	Product Function and Intended Use.....	8
3.2	Ratings and System Details of Equipment under Test	8
3.3	Simultaneous operation	9
3.4	Measurement Uncertainty:	9
4	TEST SET-UP AND OPERATION MODE.....	10
4.1	Principle of Configuration Selection	10
4.2	Operation and Software of the EUT	10
4.3	Test modes – data rates and modulations.....	10
4.4	Special Accessories and Auxiliary Equipment	10
4.5	Countermeasures to achieve EMC Compliance	10
4.6	Report references.....	10
4.7	List of frequencies	11
5	Operational Description of the product	12
6	Block Diagram of the product	12
7	TEST METHODOLOGY	13
7.1	Conducted Spurious Emission Test on AC Power Line.....	13
7.1.1	Test Setup Configuration	13
7.2	Radiated Emission Test	14
7.2.1	Test Setup Configuration	14
8	TEST RESULTS FOR Wi-Fi.....	16
8.1	Maximum Average Conducted Output Power.....	16
8.2	Spurious Radiated Emissions & Restricted Bands of Operation	18
9	TEST RESULTS FOR BLUETOOTH LOW ENERGY	26
9.1	Maximum Peak Conducted Output Power.....	26
9.2	Spurious Radiated Emissions & Restricted Bands of Operation	29
10	Conducted Spurious Emission Test on AC Power Line	41
11	LIST OF TABLES	46

1 GENERAL REMARKS

1.1 Attachments

All attachments are part of this test report and are issued in separate document

1: TEST SETUP PHOTOS

2: EUT EXTERNAL PHOTOS

3: EUT INTERNAL PHOTOS

4: FCC LABEL AND LABEL LOCATION

5: BLOCK DIAGRAM

6: SPECIFICATION OF EUT

7: SCHEMATIC DIAGRAM

8: BILL OF MATERIAL

9: USER MANUAL

10: MAXIMUM PERMISSIBLE EXPOSURE INFORMATION

2 TEST SITES

2.1 Testing Facilities

1. TÜV Rheinland (India) Pvt.Ltd.,
27/B, 2nd Cross,
ElectronicCityPhase1
Bangalore – 560 100,
India
2. TUV Rheinland (India) Private Limited
108 , Beside ISBR Business School,
Electronic city Phase I
Bangalore - 560 100.
India

2.2 List of Test and Measurement Instruments

Table 1: List of test and measurement instruments

Equipment	Manufacturer	Model Name	Serial Number	Firmware Versions	Calibration Due Date	Periodicity	Test Facility
EMI Receiver	Rohde & Schwarz	ESU 40	100288	4.43 SP3	11.10.2020	Yearly	Radiated Spurious Emission
Active loop antenna	Frankonia	LAX-10	LAX-10-800	-	15.07.2020	Yearly	
Biconical Antenna	Schwarzbeck	VHBB9124+BBA 9106	9124-1208+9106-0525	-	16.01.2021	Yearly	
Log - Periodical Antenna	Schwarzbeck	VUSLP 9118 A	VULP9118A-0733	-	17.01.2021	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-1944	-	17.07.2020	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA 9170-0904	-	29.01.2021	Yearly	
Semi Anechoic Chamber	Frankonia	-	-	-	-	-	
Fully Anechoic Chamber	Albatross	-	-	-	-	-	Antenna - Port Measurements
USB Wideband Power Sensor	Boonton	55006	10231	-	07.09.2020	Yearly	
Spectrum Analyser	Agilent Technologies	E4407B	US41192772	A.14.06	28.09.2020	Yearly	AC Power line conducted emission
EMI Receiver	Rohde & Schwarz	ESW 44	101732	-	10.12.2020	Yearly	
LISN	Rohde & Schwarz	ENV 216	100022	-	05.09.2020	Yearly	
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100811	-	01.08.2020	Yearly	

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568820300000024F

Seite 7 von 46

Page 7 of 46

Table 2: Instrument application Software versions

SL. No.	Test Type	Application software	Version
1	Radiated spurious emission measurement in SAC	EMC 32	10.60.00
2	Radiated spurious emission measurement in FAC	EMC 32	10.60.00

3 GENERAL PRODUCT INFORMATION

3.1 Product Function and Intended Use

The gateway acts as a portal among fire alarm panels, and peripheral devices. The gateway connection with the fire alarm panel enables reading the inventory and transmitting the data. The connection with Cloud facilities remotely monitoring and managing the fire detection systems.

3.2 Ratings and System Details of Equipment under Test

Table 3: Ratings and System Details as declared by Client*

Radio Protocol		Wi-Fi	BLE
Operating Frequency Range		2412MHz to 2462MHz	2402MHz to 2480MHz
No. of Channels		11 (Refer Table 6)	40 (Refer Table 7)
Channel Spacing		5MHz	2MHz
Modulation		802.11b: CCK and DSSS 802.11g: OFDM 802.11n: OFDM	GFSK
Number of antennas		2	1
Antenna Gain		3 dBi	
Antenna Type		Printed F Antenna	
Supply Voltage to Product		24V DC (powered through USB Port / NUP(RS232) Port)	
Environmental conditions	Storage	-10°C to +60° C	
	Operating		
EUT Dimension (L x W x T)		200mm x 70mm x 255mm	

Cellular Module	AT & T	Verizon
FCC ID	RI7LE910NAV2	RI7LE910SVV2
IC ID	5131A-LE910NAV2	5131A-LE910SVV2
HVIN	LE910-NA V2	LE910-SV1
PMN	LE910-NA V2	LE910-SV1

Supply Voltage to Product : CLSS gateway can be powered with the following ports	
Port	Powered through
USB Port	Fire alarm control panel
NUP (RS232) Port	Fire alarm control panel

***Disclaimer:** The information/data is supplied by the client and the same is considered to arrive at the final value. Any changes made apart from the specified specification, can directly impact on the tests results. Refer the products user manual for more details.

Note: Product CLSS Gateway has multiple protocols. All the supported wireless protocols and their respective test results are issued in separate test reports, refer clause 4.6 for report reference.

3.3 Simultaneous operation

Mode 1 Combinations of Simultaneous Operations	WiFi - LTE (AT&T) WiFi - WCDMA (AT&T) BLE - LTE (AT&T) BLE - WCDMA (AT&T)
Mode 2 Combinations of Simultaneous Operations	WiFi - LTE (Verizon) BLE - LTE (Verizon)

Cellular Module	AT & T	Verizon
FCC ID	RI7LE910NAV2	RI7LE910SVV2
IC ID	5131A-LE910NAV2	5131A-LE910SVV2
HVIN	LE910-NA V2	LE910-SV1
PMN	LE910-NA V2	LE910-SV1

Note: Simultaneous Operation was performed with the above mentioned combination and worst case test results are mentioned in this report.

3.4 Measurement Uncertainty:

Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$

Table 4: Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±0.51 dB
Power Spectral Density, conducted	±0.85 dB
Unwanted Emissions, conducted	±2.58 dB
SAC, radiated measurement	±3.67 dB
FAC, radiated measurement	±4.95 dB
Temperature	±3 °C
Supply Voltages	±3 %
Time	±5 %

Note: The listed uncertainties are the worst case uncertainty for the entire range of measurements and are for the reporting purpose only and are not used in determining the PASS/FAIL of the results.

4 TEST SET-UP AND OPERATION MODE

4.1 Principle of Configuration Selection

Transmission was enabled with highest possible duty cycle on Low, Mid and High channels.

4.2 Operation and Software of the EUT

Software Name: FW 2.5
Software Version: 3.0.1.16
Hardware Name: CLSS Gateway
Hardware version: HON-CGW-MBB
Hardware Reference: CCM-BM28 RevA

4.3 Test modes – data rates and modulations

Conducted and Radiated spurious emissions tests were performed and reported only for EUT worst case operating modes

4.4 Special Accessories and Auxiliary Equipment

- Test laptop and USB cable
- Fire Alarm control panel (to power up CLSS gateway through USB or NUP(RS232) Port)

4.5 Countermeasures to achieve EMC Compliance

- None

4.6 Report references

Note: Product CLSS Gateway has multiple protocols. All the supported wireless protocols and their respective test results are issued in separate test reports.

SL. No.	RF Protocol / Frequency Bands	Report No.
1	LTE, WCDMA	ULR-TC568820300000023F
2	WLAN 2.4GHz & BLE	ULR-TC568820300000024F
3	BT	ULR-TC568820300000025F
4	WLAN 5GHz	ULR-TC568820300000026F

Table 5: TUV Sample identification details

Samples used for Testing	S/N Number
Antenna port measurement	A002842870-001
Radiated mode test	A002842870-009

4.7 List of frequencies

Frequency Band (MHz)	Channel No.	Channel Frequency (MHz)
2412 – 2462	1	2412
	2	2417
	3	2422
	4	2427
	5	2432
	6	2437
	7	2442
	8	2447
	9	2452
	10	2457
	11	2462

Table 6: List of Wi-Fi center Frequencies

Channel used for Wi-Fi testing

Channel Bandwidth 20MHz

Channel low : 2412MHz

Channel mid : 2442MHz

Channel high : 2462MHz

Frequency Band (GHz)	Channel No.	Frequency (MHz)
BLE (2.4-2.4835)	0	2402
	1	2404
	2	2406
	3	2408
	:	:
	:	:
	18	2438
	19	2440
	20	2437
	:	:
	:	:
	36	2474
	37	2476
	38	2478
	39	2480

Table 7: List of BLE Center frequencies

Channel used for BLE testing

Channel low : 2402MHz

Channel mid : 2440MHz


Channel High : 2480MHz

5 Operational Description of the product

The gateway acts as a portal among fire alarm panels, and peripheral devices. The gateway connection with the fire alarm panel enables reading the inventory and transmitting the data. The connection with Cloud facilities remotely monitoring and managing the fire detection systems.

6 Block Diagram of the product

The Gateway Board's Layout



PCB Layout


7 TEST METHODOLOGY

7.1 Conducted Spurious Emission Test on AC Power Line

Measured levels of ac power-line conducted emission across the 50Ω LISN port (to which the EUT is connected). All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer.

The device is placed on the test table, raised 80cm above the reference ground plane. The vertical conducting plane is located 40cm to the rear of the device. AC Conducted emission measurement is made over frequency range from 150kHz to 30MHz, this measurement was performed with EUT powered by 2 methods and both methods are tested individually, one with an AC adaptor with 110V AC 60Hz supply and second with Wireless charger with supply 110V AC 60Hz.

7.1.1 Test Setup Configuration



7.2 Radiated Emission Test

The radiated emission measurement was performed according to the procedures in ANSI C63.10-2013. The equipment under test (EUT) was placed at the middle of the 80 cm high turntable for below 1 GHz & 1.5 m height for above 1 GHz measurement, and the EUT is 3 meters far from the measuring antenna. The turntable was rotated 360° for obtaining the maximum emission. The height of the measuring antennas was scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained. The measurement above 1000 MHz was performed by horn antenna, The measurement below 30 MHz was performed by loop antenna, Measurement from 30 MHz to 200 MHz was performed by Baloon and Biconical Antenna, and measurement from 200 MHz to 1 GHz was performed by Log-Periodic Antenna.

The EUT was rotated around the X-, Y-, and Z-Axis and the results from worst case axis are recorded.
Field Strength (dBμV/m) = Measured Value(dBμV) + Antenna Factor(dB) + Cable Loss(dB) – Pre Amplifier Gain (dBi)

7.2.1 Test Setup Configuration




Figure 1: Frequency Range 9 kHz - 30 MHz




Figure 2: Frequency Range 30 MHz - 200 MHz




Figure 3: Frequency Range 200 MHz - 1GHz




Figure 4: Frequency Range above 1 GHz

8 TEST RESULTS FOR Wi-Fi


8.1 Maximum Average Conducted Output Power

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (b)(3) / RSS 247 Issue 2, Section 5.4 (d)
Test Method	Subclause 11.9.2.2.4 of ANSI C63.10
Detector	Average sample detector
Port of testing	Antenna port
Requirement	Power ≤ 1 W (30 dBm) & e.i.r.p ≤ 4 W (36 dBm)

Test Method



Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.3 °C Voltage = 24V DC (through UAB Port) Relative humidity = 62 %

KDB Guidelines applied:

Measurements were made as per section 8.3.1.3 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568820300000024F

Seite 17 von 46

Page 17 of 46

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Average Output power (dBm) = Measured Average power (dBm) + Attenuator factor (10dB) + Cable loss (2dB)
3. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 3 dBi
4. Maximum (e.i.r.p) = Maximum Average output power (dBm) + antenna gain (3 dBi)

Mode	Data rate (Mbps)	Channel Frequency (MHz)	Duty cycle %	Duty cycle correction factor (dB)	Maximum Conducted Output Power (dBm)	Maximum Average Output Power (dBm)	Maximum (e.i.r.p) (dBm)	Limit (dBm)	e.i.r.p Limit (dBm)
802.11b	1	2412	100.00	0.00	17.78	14.63	17.63	30	36
		2442	100.00	0.00	17.60	14.49	17.49	30	36
		2462	100.00	0.00	17.38	14.29	17.29	30	36
	11	2412	89.13	0.50	17.11	14.20	17.20	30	36
		2442	89.13	0.50	16.92	13.98	16.98	30	36
		2462	89.13	0.50	16.87	13.90	16.90	30	36
802.11g	6	2412	94.02	0.27	23.87	13.87	16.87	30	36
		2442	94.02	0.27	23.67	13.81	16.81	30	36
		2462	94.02	0.27	23.49	13.60	16.60	30	36
	24	2412	78.80	1.04	23.15	14.08	17.08	30	36
		2442	78.80	1.04	22.93	13.91	16.91	30	36
		2462	78.80	1.04	22.79	13.63	16.63	30	36
	54	2412	57.68	2.39	23.35	14.66	17.66	30	36
		2442	57.68	2.39	23.00	14.50	17.50	30	36
		2462	57.68	2.39	22.54	14.20	17.20	30	36
802.11n (20MHz)	MCS0	2412	94.62	0.24	24.13	13.48	16.48	30	36
		2442	94.62	0.24	23.99	13.28	16.28	30	36
		2462	94.62	0.24	23.58	13.04	16.04	30	36
	MCS4	2412	69.66	1.57	23.65	13.98	16.98	30	36
		2442	69.66	1.57	23.38	13.66	16.66	30	36
		2462	69.66	1.57	23.18	13.56	16.56	30	36
	MCS7	2412	87.70	0.57	23.75	12.47	15.47	30	36
		2442	87.70	0.57	23.61	12.23	15.23	30	36
		2462	87.70	0.57	23.38	12.11	15.11	30	36

*Note: Duty Cycle Correction Factor Calculation

10*LOG (1/X) Where X is Duty Cycle is considered in below results

Duty cycle correction Factor is considered in Final Average Power

8.2 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205) / IC RSS-GEN, Section 8.9 and 8.10
Test Method	ANSI C63.10
Measurement Location	Semi anechoic chamber < 1GHz Fully anechoic chamber > 1GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Reffer TEST METHODOLOGY

Table 8: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Environmental conditions:

Temperature (Norm) = + 24 °C Voltage = 24 V DC (through USB Port and NUP(RS232) Port)
Relative humidity = 62 %

Note: For the above 1 GHz worst case test results observed in power mode 24 V DC (through USB Port)

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 19 von 46
Page 19 of 46

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details

Test Results:


Test results for frequency range 9kHz – 30MHz


No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, have not reported

Test results for frequency range 30MHz – 200MHz

Power Mode: 24V DC Through NUP(RS232) Port

Antenna Polarization	Frequency (MHz)	Peak Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Vertical	30.758	25.16	40.00	-14.84
	97.569	25.02	43.50	-18.48
	113.785	28.78	43.50	-14.72
	120.038	24.97	43.50	-18.53
Horizontal	95.913	17.54	43.50	-25.96
	125.008	34.21	43.50	-9.29
	150.002	36.60	43.50	-6.90






Polarization: Horizontal

Power Mode: 24V DC Through (USB Port)

Antenna Polarization	Frequency (MHz)	Peak Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	38.69	22.30	40.00	-17.70
	49.99	28.12	40.00	-11.88
	124.98	32.09	43.50	-11.41
	149.98	35.02	43.50	-8.48
Horizontal	50.00	21.85	40.00	-18.15
	125.00	30.86	43.50	-12.64
	149.99	34.41	43.50	-9.09
	155.61	32.12	43.50	-11.38




Polarization: Vertical

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 21 von 46
Page 21 of 46



Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568820300000024F

Seite 22 von 46
Page 22 of 46


Test results for frequency range 200MHz – 1GHz

Power Mode: 24V DC Through NUP(RS232) Port

Antenna Polarization	Frequency (MHz)	Peak Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	346.48	28.11	46.00	-17.89
	544.48	32.95	46.00	-13.05
	841.49	32.57	46.00	-13.43
	940.49	37.21	46.00	-8.79
Horizontal	249.97	34.80	46.00	-11.20
	346.49	28.97	46.00	-17.03
	742.48	30.84	46.00	-15.16
	841.50	32.19	46.00	-13.81



Polarization: Vertical



Polarization: Horizontal

Prüfbericht - Nr.:

Test Report No.:


ULR-TC568820300000024F

Seite 23 von 46


Page 23 of 46

Power Mode: 24V DC Through (USB Port)

Antenna Polarization	Frequency (MHz)	Peak Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	346.49	25.12	46.00	-20.88
Vertical	445.50	30.54	46.00	-15.46
Vertical	940.50	32.85	46.00	-13.15
Horizontal	249.96	32.76	46.00	-13.24
Horizontal	544.49	34.07	46.00	-11.93
Horizontal	841.49	31.88	46.00	-14.12



Polarization: Vertical



Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 24 von 46
Page 24 of 46

Test results for the frequencies in the range 1 GHz to 26.5 GHz

Modulation: 802.11b

Data Rate: 11Mbps

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2412	Vertical	2390(Pk)	51.62	74*	-22.38
		2390(Av)	35.16	54*	-18.84
		2402(Pk)	108.56	-	-
		2402(Av)	99.55	-	-
		4824(Pk)	42.47	74	-31.53
		4824(Av)	29.28	54	-24.72
		7236(Pk)	47.94	74	-26.06
		7236(Av)	34.61	54	-19.39
	Horizontal	2390(Pk)	49.12	74*	-24.88
		2390(Av)	33.71	54*	-20.29
		2402(Pk)	105.72	-	-
		2402(Av)	96.98	-	-
		4824(Pk)	42.14	74	-31.86
		4824(Av)	29.11	54	-24.89
		7236(Pk)	46.81	74	-27.19
		7236(Av)	34.53	54	-19.47
2442	Vertical	2442(Pk)	107.72	-	-
		2442(Av)	98.92	-	-
		4884(Pk)	42.10	74*	-31.90
		4884(Av)	30.01	54*	-23.99
		7326(Pk)	46.59	74	-27.41
		7326(Av)	34.57	54	-19.43
	Horizontal	2442(Pk)	105.28	-	-
		2442(Av)	96.59	-	-
		4884(Pk)	44.07	74	-29.93
		4884(Av)	31.46	54	-22.54
		7326(Pk)	46.79	74	-27.21
		7326(Av)	34.39	54	-19.61

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 25 von 46
Page 25 of 46

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2462	Vertical	2462(Pk)	106.48	-	-
		2462(Av)	97.81	-	-
		2483.5(Pk)	49.21	74*	-24.79
		2483.5(Av)	34.67	54*	-19.33
		4924(Pk)	42.96	74	-31.04
		4924(Av)	30.76	54	-23.24
		7386(Pk)	48.49	74	-25.51
		7386(Av)	34.74	54	-19.26
	Horizontal	2462(Pk)	104.52	-	-
		2462(Av)	95.97	-	-
		2483.5(Pk)	48.11	74*	-25.89
		2483.5(Av)	33.41	54*	-20.59
		4924(Pk)	43.12	74	-30.88
		4924(Av)	30.68	54	-23.32
		7386(Pk)	46.75	74	-27.25
		7386(Av)	34.63	54	-19.37

*- : Indicate restricted band of operation §15.205
Pk: Peak Detector; Av: Average Detector

Table 9: RSE Test Results of Simultaneous Operation with Cellular and Non-Cellular:

Note: As specified under the section 3.3 simultaneous combinations mode 1 and mode 2 are performed for AT&T and Verizon Cellular modules, respectively. Only worst-case reported.

Worst case result for WiFi and LTE Combination: LTE Band 2 and Wi-Fi 2.4GHz
Worst case mode : - Mode 1 with AT&T cellular module

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2412	Vertical	4824(Pk)	41.28	74	-32.72
		4824(Av)	29.07	54	-24.93
		7236(Pk)	No Harmonics Found		
		7236(Av)			
	Horizontal	4824(Pk)	43.13	74	-30.87
		4824(Av)	29.93	54	-24.07
		7236(Pk)	46.77	74	-27.23
		7236(Av)	34.12	54	-19.88

9 TEST RESULTS FOR BLUETOOTH LOW ENERGY


9.1 Maximum Peak Conducted Output Power

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (b)(3) / RSS 247 Issue 2, Section 5.4 (d)
Test Method	Subclause 11.9.1.1 of ANSI C63.10
Measurement Bandwidth	300 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	Power ≤ 1 W (30 dBm) & e.i.r.p ≤ 4 W (36 dBm)

Test Method



Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.3 °C Voltage = 24V DC (through UAB Port) Relative humidity = 62 %

KDB Guidelines applied:

Measurements were made as per section 8.3.1 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F


Seite 27 von 46
Page 27 of 46

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (2dB)
3. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 3 dBi
4. Maximum (e.i.r.p) = Maximum Peak output power (dBm) + antenna gain (3 dBi)

Data Rate (Mbps)	Channel Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum (e.i.r.p) (dBm)	Limit (dBm)	e.i.r.p Limit (dBm)
1	2402	5.50	8.50	30	36
	2440	4.29	7.29	30	36
	2480	2.78	5.78	30	36



Channel Frequency: 2402MHz


Prüfbericht - Nr.:

Test Report No.:


ULR-TC568820300000024F

Seite 28 von 46

Page 28 of 46



Channel Frequency: 2440MHz



Channel Frequency: 2480MHz

9.2 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205) / IC RSS-GEN, Section 8.9 and 8.10
Test Method	ANSI C63.10
Measurement Location	Fully anechoic chamber
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Reffer TEST METHODOLOGY

Table 10: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Environmental conditions:

Temperature (Norm) = + 24 °C Voltage = 24 V DC (through USB Port and NUP(RS232) Port)

Relative humidity = 62 %

Note: For the above 1 GHz worst case test results observed in power mode 24 V DC (through USB Port)

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 30 von 46
Page 30 of 46

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details

Test Results:


Test results for frequency range 9kHz – 30MHz


No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, have not reported

Test results for frequency range 30MHz – 200MHz

Power Mode: 24V DC Through NUP(RS232) Port

Antenna Polarization	Frequency (MHz)	Peak Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	30.758	25.16	40.00	-14.84
	97.569	25.02	43.50	-18.48
	113.785	28.78	43.50	-14.72
	120.038	24.97	43.50	-18.53
Horizontal	95.913	17.54	43.50	-25.96
	125.008	34.21	43.50	-9.29
	150.002	36.60	43.50	-6.90






Polarization: Horizontal

Power Mode: 24V DC Through (USB Port)

Antenna Polarization	Frequency (MHz)	Peak Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	38.69	22.30	40.00	-17.70
	49.99	28.12	40.00	-11.88
	124.98	32.09	43.50	-11.41
	149.98	35.02	43.50	-8.48
Horizontal	50.00	21.85	40.00	-18.15
	125.00	30.86	43.50	-12.64
	149.99	34.41	43.50	-9.09
	155.61	32.12	43.50	-11.38




Polarization: Vertical

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 32 von 46
Page 32 of 46




Polarization: Horizontal


Test results for frequency range 200MHz – 1GHz

Power Mode: 24V DC Through NUP(RS232) Port

Antenna Polarization	Frequency (MHz)	Peak Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	346.48	28.11	46.00	-17.89
	544.48	32.95	46.00	-13.05
	841.49	32.57	46.00	-13.43
	940.49	37.21	46.00	-8.79
Horizontal	249.97	34.80	46.00	-11.20
	346.49	28.97	46.00	-17.03
	742.48	30.84	46.00	-15.16
	841.50	32.19	46.00	-13.81




Polarization: Vertical




Polarization: Horizontal

Power Mode: 24V DC Through (USB Port)

Antenna Polarization	Frequency (MHz)	Peak Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	346.49	25.12	46.00	-20.88
Vertical	445.50	30.54	46.00	-15.46
Vertical	940.50	32.85	46.00	-13.15
Horizontal	249.96	32.76	46.00	-13.24
Horizontal	544.49	34.07	46.00	-11.93
Horizontal	841.49	31.88	46.00	-14.12



Polarization: Vertical



Polarization: Horizontal

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568820300000024F

Seite 35 von 46

Page 35 of 46

Test results for the frequencies above 1GHz

Data rate : 1Mbps
Channel Frequency : 2402MHz

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2402	Vertical	2390(Pk)	40.53	74*	-33.47
		2390(Av)	26.50	54*	-27.50
		2402(Pk)	102.60	-	-
		2402(Av)	97.55	-	-
		4804(Pk)	39.88	74	-34.12
		4804(Av)	28.91	54	-25.09
		7206(Pk)	47.48	74	-26.52
		7206(Av)	34.07	54	-19.93
	Horizontal	2390(Pk)	40.91	74*	-33.09
		2390(Av)	25.14	54*	-28.86
		2402(Pk)	99.51	-	-
		2402(Av)	94.41	-	-
		4804(Pk)	41.51	74	-32.49
		4804(Av)	29.78	54	-24.22
		7206(Pk)	47.78	74	-26.22
		7206(Av)	34.14	54	-19.86
2440	Vertical	2440(Pk)	100.49	-	-
		2440(Av)	95.43	-	-
		4880(Pk)	40.2	74	-33.8
		4880(Av)	27.85	54	-26.15
		7320(Pk)	47.1	74	-26.9
		7320(Av)	34.21	54	-19.79
	Horizontal	2440(Pk)	97.7	-	-
		2440(Av)	92.59	-	-
		4880(Pk)	40.26	74	-33.8
		4880(Av)	28.26	54	-26.15
		7320(Pk)	47.09	74	-26.9
		7320(Av)	34.21	54	-19.79

*- : Indicate restricted band of operation §15.205

Pk: Peak Detector; Av: Average Detector

Channel Frequency (MHz)	Measured Frequency (MHz)	Polarization	Measured Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2480	2480(Pk)	Vertical	97.88	-	-
	2480(Av)		92.76	-	-
	2483.5(Pk)		43.22	74*	-30.78
	2483.5(Av)		29.78	54*	-24.22
	4960(Pk)		41.48	74	-32.52
	4960(Av)		28.34	54	-25.66
	7480(Pk)		46.53	74	-27.47
	7480(Av)		34.31	54	-19.69
	2480(Pk)	Horizontal	98.06	-	-
	2480(Av)		92.95	-	-
	2483.5(Pk)		44.11	74*	-29.89
	2483.5(Av)		30.1	54*	-23.9
	4960(Pk)		42.75	74	-31.25
	4960(Av)		31.27	54	-22.73
	7480(Pk)		47.97	74	-26.03
	7480(Av)		34.21	54	-19.79

*- : Indicate restricted band of operation §15.205
Pk: Peak Detector; Av: Average Detector


Table 11: RSE Test Results of Simultaneous Operation with Cellular and Non-Cellular:

Note: As specified under the section 3.3 simultaneous combinations are performed for both AT&T and Verizon Cellular modules, worst-case reported.

Worst case result for BLE and LTE Combination: LTE Band 2 and BLE
Worst case mode : - Mode 1 with AT&T cellular module


Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2402	Vertical	4804(Pk)	No Harmonics Found		
		4804(Av)			
		7206(Pk)	No Harmonics Found		
		7206(Av)			
	Horizontal	4804(Pk)	43.30	74	-30.70
		4804(Av)	32.07	54	-21.93
		7206(Pk)	No Harmonics Found		
		7206(Av)			

Worst Case Test Plots:




Fundamental Frequency

Polarization: Vertical




Fundamental Frequency

Polarization: Horizontal



Frequency range: 1GHz-9.9GHz

Polarization: Vertical




Frequency range: 1GHz-9.9GHz

Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568820300000024F

Seite 39 von 46
Page 39 of 46




Frequency range: 9.9GHz-18GHz

Polarization: Vertical




Frequency range: 9.9GHz-18GHz

Polarization: Horizontal



Frequency range: 18GHz-40GHz

Polarization: Vertical



Frequency range: 18GHz-40GHz

Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 41 von 46
Page 41 of 46

10 Conducted Spurious Emission Test on AC Power Line

Result

Pass

Test Specification : FCC Part 15 Section 15.207 / RSS Gen Issue 5 Section 8.8
Test Method : ANSI C 63.10-2013
Testing Location : Screened room
Measurement Bandwidth : 9kHz
Frequency Range : 150kHz – 30MHz
Supply Voltage : 110VAC, 60Hz
Test Method : Refer TEST METHODOLOGY

***Note: The product has tested with 24 V DC (through USB Port and NUP(RS232) Port)**

Limits of section 15.207

Frequency of emission (MHz)	QP Limit (dBμV)	AV Limit (dBμV/m)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency

Test Conditions:

Temperature (Norm) = + 24 °C Voltage = 24 V DC (through USB Port and NUP(RS232) Port)

Relative humidity = 62 %


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 42 von 46
Page 42 of 46

Test result:


Power Mode: 24V DC Through NUP(RS232) Port



Graph: Line

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC_B_QP			
Trace2:	FCC_B_AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBμV	DELTA	LIMIT dB
2 Average	4.638 MHz	34.41	-11.58	
2 Average	11.554 MHz	34.74	-15.25	
1 Quasi Peak	4.69 MHz	40.67	-15.32	
2 Average	21.038 MHz	33.26	-16.73	
2 Average	16.786 MHz	33.24	-16.75	
1 Quasi Peak	11.554 MHz	38.92	-21.07	
2 Average	198 kHz	31.66	-22.02	
1 Quasi Peak	16.786 MHz	37.53	-22.46	
2 Average	6.53 MHz	26.46	-23.53	
1 Quasi Peak	21.042 MHz	35.17	-24.82	
2 Average	13.562 MHz	24.94	-25.05	
1 Quasi Peak	6.554 MHz	33.41	-26.58	
1 Quasi Peak	198 kHz	36.69	-26.99	

Results: Line




Graph: Neutral

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC_B_QP			
Trace2:	FCC_B_AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB	
2 Average	4.678 MHz	34.40	-11.59	
2 Average	11.35 MHz	35.24	-14.75	
1 Quasi Peak	4.678 MHz	41.09	-14.90	
2 Average	16.686 MHz	34.62	-15.37	
1 Quasi Peak	11.35 MHz	37.76	-22.23	
1 Quasi Peak	16.886 MHz	36.88	-23.11	
2 Average	6.57 MHz	25.98	-24.01	
2 Average	21.09 MHz	25.90	-24.09	
2 Average	198 kHz	29.20	-24.49	
1 Quasi Peak	21.086 MHz	35.28	-24.71	
1 Quasi Peak	6.418 MHz	33.26	-26.73	
1 Quasi Peak	198 kHz	35.64	-28.05	
1 Quasi Peak	29.546 MHz	31.18	-28.81	
1 Quasi Peak	150 kHz	26.27	-39.72	

Results: Neutral


Power Mode: 24V DC Through (USB Port)



Graph: Line

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC_B_QP			
Trace2:	FCC_B_AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB	
2 Average	7.794 MHz	39.57	-10.42	
2 Average	11.35 MHz	37.60	-12.39	
1 Quasi Peak	7.798 MHz	44.40	-15.59	
2 Average	6.426 MHz	34.27	-15.72	
1 Quasi Peak	6.358 MHz	41.10	-18.89	
1 Quasi Peak	11.55 MHz	40.31	-19.68	
2 Average	17.27 MHz	30.02	-19.97	
2 Average	198 kHz	31.76	-21.92	
2 Average	29.878 MHz	25.48	-24.51	
1 Quasi Peak	17.27 MHz	34.26	-25.73	
1 Quasi Peak	29.934 MHz	33.27	-26.73	
1 Quasi Peak	198 kHz	36.36	-27.33	
2 Average	14.078 MHz	19.98	-30.01	
1 Quasi Peak	150 kHz	24.62	-41.37	

Results: Line



Graph: Neutral

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC_B_QP			
Trace2:	FCC_B_AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBμV	DELTA	LIMIT dB
2 Average	11.65 MHz	42.80	-7.19	
2 Average	7.81 MHz	41.73	-8.26	
2 Average	16.578 MHz	41.17	-8.82	
2 Average	29.706 MHz	35.13	-14.86	
1 Quasi Peak	7.806 MHz	44.36	-15.63	
1 Quasi Peak	11.454 MHz	43.66	-16.33	
1 Quasi Peak	16.578 MHz	42.40	-17.59	
1 Quasi Peak	6.398 MHz	40.94	-19.05	
2 Average	23.498 MHz	26.73	-23.26	
2 Average	790 kHz	22.35	-23.64	
1 Quasi Peak	29.606 MHz	35.91	-24.08	
2 Average	198 kHz	29.20	-24.48	
1 Quasi Peak	198 kHz	35.57	-28.12	
1 Quasi Peak	150 kHz	26.44	-39.55	

Graph: Results

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568820300000024F

Seite 46 von 46
Page 46 of 46

11 LIST OF TABLES

Table 1: List of test and measurement instruments	6
Table 2: Instrument application Software versions	7
Table 3: Ratings and System Details as declared by Client*	8
Table 4: Measurement Uncertainty	9
Table 5: TUV Sample identification details	10
Table 6: List of Wi-Fi center Frequencies	11
Table 7: List of BLE Center frequencies	11
Table 8: Transmitter limits for Radiated emission	18
Table 9: RSE Test Results of Simultaneous Operation with Cellular and Non-Cellular:	25
Table 10: Transmitter limits for Radiated emission	29
Table 11: RSE Test Results of Simultaneous Operation with Cellular and Non-Cellular:	36

*****END OF TEST REPORT*****