

FCCID: PVTRAD-TS

CLIENT: IKUSI
EUT: RAD-TS TRANSMITTER
ANTENNA: INTERNAL
FREQ.: 902.25 MHZ
POWER: N/A

3 METER TEST PEAK DETECT DATE: 02/03/2003

FREQUENCY MHz	POLARITY		SPEC A	AF/C	AMP Gain dB	Average Factor dB	Peak E-Field dbuV/m	QP Limit dBuV/m	MARGIN dB	CONDITION
	H	V	dBuV	dB/m						
902.25	H		64.00	24.00	0.00	0.00	88.00	94.00	6.00	PASS
1,804.50	H		39.00	30.60	25.00	0.00	44.60	54.00	9.40	PASS
2,706.75	H		34.00	34.30	25.00	0.00	43.30	54.00	10.70	PASS
3,609.00		V	33.00	36.70	25.00	0.00	44.70	54.00	9.30	PASS
4,511.25		V	32.00	38.80	25.00	0.00	45.80	54.00	8.20	PASS
5,413.50	H		31.00	32.00	25.00	0.00	38.00	54.00	16.00	PASS
6,315.75		V	30.00	32.00	25.00	0.00	37.00	54.00	17.00	PASS
7,218.00	H		25.00	33.50	25.00	0.00	33.50	54.00	20.50	PASS

FCC RADIATED EMISSIONS DATA

CLIENT: IKUSI
EUT: RAD-TS TRANSMITTER
ANTENNA: INTERNAL
FREQ.: 927.75 MHZ
POWER: N/A

3 METER TEST PEAK DETECT DATE: 02/03/2003

FREQUENCY MHz	POLARITY		SPEC A	AF/C	AMP Gain dB	Average Factor dB	Peak E-Field dbuV/m	QP Limit dBuV/m	MARGIN dB	CONDITION
	H	V	dBuV	dB/m						
927.75	H		63.00	24.00	0.00	0.00	87.00	94.00	7.00	PASS
1,855.50	H		40.00	30.60	25.00	0.00	45.60	54.00	8.40	PASS
2,783.25	H		35.00	34.30	25.00	0.00	44.30	54.00	9.70	PASS
3,711.00		V	32.00	36.70	25.00	0.00	43.70	54.00	10.30	PASS
4,638.75		V	31.00	38.80	25.00	0.00	44.80	54.00	9.20	PASS
5,566.50	H		30.00	32.00	25.00	0.00	37.00	54.00	17.00	PASS
6,494.25		V	30.00	32.00	25.00	0.00	37.00	54.00	17.00	PASS
7,422.00	H		25.00	33.50	25.00	0.00	33.50	54.00	20.50	PASS