APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
HONG KONG NATURAL SOUND ELECTRONICS LIMITED

MID
Model No.: PC1016BXC, Trio Stealth G5 10

FCC ID: PWK-PC1016BXC

Prepared for	:	HONG KONG NATURAL SOUND ELECTRONICS LIMITED
Address	:	FLAT/RM M 4/F CONTINENTAL MANSION 300 KING'S ROAD HONG KONG
Prepared by	:	ACCURATE TECHNOLOGY CO., LTD
Address	:	F1, Bldg. A, Chan Yuan New Material Port, Keyuan Rd. Science & Industry Park, Nan Shan, Shenzhen, Guangdong P.R. China Tel: (0755) 26503290 Fax: (0755) 26503396

Report Number	:	ATE20151402
Date of Test	:	Jun 25-Jul 06,2015
Date of Report	:	Jul 07,2015

TABLE OF CONTENTS

Description Page

Test Report Certification
1. GENERAL INFORMATION 4
1.1. Description of Device (EUT) 5
1.2. Carrier Frequency of Channels 6
1.3. Special Accessory and Auxiliary Equipment 6
1.4. Description of Test Facility 7
1.5. Measurement Uncertainty 7
2. MEASURING DEVICE AND TEST EQUIPMENT 8
3. OPERATION OF EUT DURING TESTING 9
3.1. Operating Mode 9
3.2. Configuration and peripherals 9
4. TEST PROCEDURES AND RESULTS 10
5. 6DB BANDWIDTH MEASUREMENT 11
5.1. Block Diagram of Test Setup 11
5.2. The Requirement For Section 15.247(a)(2) 11
5.3. EUT Configuration on Measurement 11
5.4. Operating Condition of EUT 11
5.5. Test Procedure 12
5.6. Test Result 12
6. MAXIMUM PEAK OUTPUT POWER 12
6.1. Block Diagram of Test Setup 14
6.2. The Requirement For Section 15.247(b)(3) 14
6.3. EUT Configuration on Measurement 14
6.4. Operating Condition of EUT 14
6.5. Test Procedure 15
6.6. Test Result 15
7. POWER SPECTRAL DENSITY MEASUREMENT 15
7.1. Block Diagram of Test Setup 17
7.2. The Requirement For Section 15.247(e) 17
7.3. EUT Configuration on Measurement 17
7.4. Operating Condition of EUT 17
7.5. Test Procedure 18
7.6. Test Result 19
8. BAND EDGE COMPLIANCE TEST 21
8.1. Block Diagram of Test Setup 21
8.2. The Requirement For Section 15.247(d) 21
8.3. EUT Configuration on Measurement 21
8.4. Operating Condition of EUT 22
8.5. Test Procedure 22
8.6. Test Result 22
9. RADIATED SPURIOUS EMISSION TEST 28
9.1. Block Diagram of Test Setup 28
9.2. The Limit For Section 15.247(d) 29
9.3. Restricted bands of operation 29
9.4. Configuration of EUT on Measurement 30

9.5. Operating Condition of EUT 30
9.6. Test Procedure 30
9.7. The Field Strength of Radiation Emission Measurement Results 31
10. CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST 43
10.1. Block Diagram of Test Setup 43
10.2. The Requirement of Section 15.247(d) 43
10.3. EUT Configuration on Measurement 43
10.4. Operating Condition of EUT 44
10.5. Test Procedure 44
10.6. Test Result 44
11. POWER LINE CONDUCTED MEASUREMENT 47
11.1. Block Diagram of Test Setup 47
11.2. Power Line Conducted Emission Measurement Limits 47
11.3. Configuration of EUT on Measurement 47
11.4. Operating Condition of EUT 47
11.5. Test Procedure 48
11.6. Power Line Conducted Emission Measurement Results 48
12. ANTENNA REQUIREMENT 53
12.1. The Requirement 53
12.2. Antenna Construction 53

Test Report Certification

Applicant : HONG KONG NATURAL SOUND ELECTRONICS LIMITED

Manufacturer : Natural Sound Electronics (Shenzhen) Co., Ltd.

EUT Description : MID

(A) MODEL NO.: PC1016BXC, Trio Stealth G5 10

(B) Trade Name.: N/A

(C) POWER SUPPLY: DC 3.7V (Powered by battery) or DC 5V (Powered by adapter)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10: 2013

The EUT was tested according to DTS test procedure of Jun 05, 2014 KDB558074 D01 DTS Meas Guidance v03r02 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Jun 25-Jul 06,2015

Date of Report: Jul 07,2015

Prepared by : Eric Zhang

(Eric Zhang, Engineer)

Approved & Authorized Signer :

(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1.Description of Device (EUT)

EUT	:	MID
Model Number	:	PC1016BXC, Trio Stealth G5 10 Note: These samples are same except for the model number is difference. So we prepare the PC1016BXC for test
Frequency Range	:	802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz Bluetooth 4.0: 2402-2480MHz
Number of Channels	:	802.11b/g/n (20MHz):11 802.11n (40MHz): 7 Bluetooth 4.0: 40
Antenna Gain	:	0dBi
Power Supply	:	DC 5V (Power by adapter)&DC 3.7V(Battery)
Adapter	:	Model number: AW010WR-0500200UU Input: AC 100-240V; 50/60Hz 0.4A Output: DC 5V/2A USB line: Non-shielded, Non-detachable, 1.5m
Modulation mode	:	GFSK DSSS,OFDM
Applicant	:	HONG KONG NATURAL SOUND ELECTRONICS LIMITED
Address	:	FLAT/RM M 4/F CONTINENTAL MANSION 300 KING’S ROAD HONG KONG
Manufacturer	:	Natural Sound Electronics (Shenzhen) Co., Ltd.
Address	:	4th Building, Xinyuan Industrial Zone, Gushu Village, Bao’an District, Shenzhen, China
Date of sample received	:	Jun 25,2015
Date of Test	:	Jun 25-Jul 06,2015

1.2.Carrier Frequency of Channels

Channel	Frequceny (MHz)	Channel	Frequceny (MHz)	Channel	Frequceny (MHz)	Channe l	Frequceny (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.3.Special Accessory and Auxiliary Equipment

N/A

1.4.Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen Listed by FCC The Registration Number is 752051 Listed by Industry Canada The Registration Number is 5077A-2 Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.5.Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 10, 2015	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 10, 2015	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 10, 2015	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU1183540-01	3791	Jan. 10, 2015	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2015	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2015	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2015	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2015	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 10, 2015	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 10, 2015	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18G-10SS	N/A	Jan. 10, 2015	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2485-2375/2510-60/11SS	N/A	Jan. 10, 2015	One Year
Switch Unit with OSP-B157	Rohde & Schwarz	OSP120	101130	Jan. 10, 2015	One Year

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **BLE Transmitting mode**
Low Channel: 2402MHz
Middle Channel: 2440MHz
High Channel: 2480MHz

3.2.Configuration and peripherals

EUT

Figure 1 Setup: Transmitting mode

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Power Line Conducted Emission	Compliant
Section 15.247(a)(2)	6dB Bandwidth Test	Compliant
Section 15.247(e)	Power Spectral Density Test	Compliant
Section 15.247(b)(3)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 6DB BANDWIDTH MEASUREMENT

5.1.Block Diagram of Test Setup



(EUT: MID)

5.2.The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3.EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

5.5.Test Procedure

5.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2.Set RBW of spectrum analyzer to 10 kHz and VBW to30 kHz.

5.5.3.The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

5.6.Test Result

Channel	Frequency (MHz)	6 dB Bandwith (MHz)	Minimum Limit(MHz)	PASS/FAIL
0	2402	0.6599	0.5	PASS
19	2440	0.6599	0.5	PASS
39	2480	0.6599	0.5	PASS

The spectrum analyzer plots are attached as below.

channel 0



channel 19



channel 39



6. MAXIMUM PEAK OUTPUT POWER

6.1.Block Diagram of Test Setup



(EUT: MID)

6.2.The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

6.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4.Operating Condition of EUT

6.4.1.Setup the EUT and simulator as shown as Section 6.1.

6.4.2.Turn on the power of all equipment.

6.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

6.5.Test Procedure

6.5.1.Set the RBW ⩾ DTS bandwidth. VBW ⩾ 3 × RBW.

6.5.2.Set span ⩾ 3 x RBW

6.5.3.Sweep time = auto couple.

6.5.4.Detector = peak.

6.5.5.Trace mode = max hold.

6.5.6.Allow trace to fully stabilize.

6.5.7.Use peak marker function to determine the peak amplitude level.

6.6.Test Result

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Output Power (mW)	Peak Power Limit (dBm)	Pass / Fail
0	2402	-3.36	0.46	30	PASS
19	2440	-3.63	0.43	30	PASS
39	2480	-3.82	0.41	30	PASS

The spectrum analyzer plots are attached as below.

channel 0



channel 19



channel 39



7. POWER SPECTRAL DENSITY MEASUREMENT

7.1.Block Diagram of Test Setup



(EUT: MID)

7.2.The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3.EUT Configuration on Measurement

The equipment is installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4.Operating Condition of EUT

7.4.1.Setup the EUT and simulator as shown as Section 8.1.

7.4.2.Turn on the power of all equipment.

7.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The EUT was tested according to DTS test procedure of KDB558074 D01 DTS Meas Guidance v03r02 for compliance to FCC 47CFR 15.247 requirements.

7.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.3. Measurement Procedure PKPSD:

This procedure must be used if maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit, and is optional if the maximum (average) conducted output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.5.4. Measurement the maximum power spectral density.

7.6.Test Result

CHANNEL NUMBER	FREQUENCY (MHz)	PSD (dBm/3KHz)	LIMIT (dBm/3KHz)	PASS/FAIL
0	2402	-18.95	8	PASS
19	2440	-19.31	8	PASS
39	2480	-19.36	8	PASS

The spectrum analyzer plots are attached as below.

channel 0



channel 19



channel 39



8. BAND EDGE COMPLIANCE TEST

8.1.Block Diagram of Test Setup



(EUT: MID)

8.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

8.3.EUT Configuration on Measurement

The equipment is installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4.Operating Condition of EUT

8.4.1.Setup the EUT and simulator as shown as Section 9.1.

8.4.2.Turn on the power of all equipment.

8.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

8.5.Test Procedure

Conducted Band Edge:

8.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

8.5.2.Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

Radiate Band Edge:

8.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

8.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

8.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

8.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

8.5.7.The band edges was measured and recorded.

8.6.Test Result

Pass

Channel	Delta peak to band emission	Limit(dBc)
0	41.89	20
39	43.21	20

channel 0



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40203 GHz	-4.11 dBm		
M2		1	2.39 GHz	-48.55 dBm		
M3		1	2.37727 GHz	-47.23 dBm		
M4		1	2.32081 GHz	-46.70 dBm		

channel 39



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47999 GHz	-4.41 dBm		
M2		1	2.4835 GHz	-49.15 dBm		
M3		1	2.486039 GHz	-48.24 dBm		
M4		1	2.488554 GHz	-47.62 dBm		

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows: Result = Reading + Corrected Factor
3. Display the measurement of peak values.

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2786	Polarization: Vertical
Standard: FCC PK	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 15/07/05/
Temp.(C)/Hum.(%) 26 C / 55 %	Time: 8/50/13
EUT: MID	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report NO.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	42.58	-7.53	35.05	74.00	-38.95	peak			
2	2390.000	33.09	-7.53	25.56	54.00	-28.44	AVG			
3	2400.000	62.53	-7.46	55.07	74.00	-18.93	peak			
4	2400.000	53.10	-7.46	45.64	54.00	-8.36	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2787	Polarization: Horizontal
Standard: FCC PK	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 15/07/05/
Temp.(C)/Hum.(%) 26 C / 55 %	Time: 8/54/19
EUT: MID	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report NO.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	42.37	-7.53	34.84	74.00	-39.16	peak			
2	2390.000	33.24	-7.53	25.71	54.00	-28.29	AVG			
3	2400.000	61.55	-7.46	54.09	74.00	-19.91	peak			
4	2400.000	52.10	-7.46	44.64	54.00	-9.36	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2788	Polarization: Vertical
Standard: FCC PK	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 15/07/05/
Temp.(C)/Hum.(%) 26 C / 55 %	Time: 8/58/44
EUT: MID	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report NO.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	50.21	-7.37	42.84	74.00	-31.16	peak			
2	2483.500	41.25	-7.37	33.88	54.00	-20.12	AVG			
3	2500.000	41.90	-7.40	34.50	74.00	-39.50	peak			
4	2500.000	32.67	-7.40	25.27	54.00	-28.73	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2789
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 26 C / 55 %
EUT: MID
Mode: TX 2480MHz
Model: PC1016BXC
Manufacturer: Natural Sound

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 15/07/05/
Time: 9/03/57
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	49.25	-7.37	41.88	74.00	-32.12	peak			
2	2483.500	38.97	-7.37	31.60	54.00	-22.40	AVG			
3	2500.000	42.42	-7.40	35.02	74.00	-38.98	peak			
4	2500.000	32.10	-7.40	24.70	54.00	-29.30	AVG			

9. RADIATED SPURIOUS EMISSION TEST

9.1.Block Diagram of Test Setup

9.1.1.Block diagram of connection between the EUT and peripherals

EUT

Setup: Transmitting mode

9.1.2.Semi-Anechoic Chamber Test Setup Diagram





9.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3.Restricted bands of operation

9.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

[1]Until February 1, 1999, this restricted band shall be 0.490-0.510
[2]Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

9.4. Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.5. Operating Condition of EUT

9.5.1. Setup the EUT and simulator as shown as Section 10.1.

9.5.2. Turn on the power of all equipment.

9.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

9.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna.
For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
When average radiated emissions measurements are specified there is also a limit on the peak emissions level which is 20 dB above the applicable maximum permitted average emission limit

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz
Peak detector above 1GHz
RBW (1 MHz), VBW (3MHz) for Peak measurement
RBW (1 MHz), VBW (10Hz) for AV measurement

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

9.7.The Field Strength of Radiation Emission Measurement Results

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. The EUT is tested radiation emission at Low, Middle, High channel in three axes. The worst emissions are reported in all channels. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.

3. The radiation emissions from 18-25GHz are not reported, because the test values lower than the limits of 20dB.

4. The average measurement was not performed when peak measured data under the limit of average detection.

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1100	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:42:55
EUT: MID	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	131.6855	56.41	-21.79	34.62	43.50	-8.88	QP			
2	359.7114	48.68	-14.30	34.38	46.00	-11.62	QP			
3	502.2473	46.20	-12.20	34.00	46.00	-12.00	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1101	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:43:37
EUT: MID	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	131.2235	60.61	-21.78	38.83	43.50	-4.67	peak			
2	496.9810	47.23	-12.27	34.96	46.00	-11.04	peak			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1102	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:44:14
EUT: MID	Engineer Signature:
Mode: TX 2440MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	131.2235	57.14	-21.78	35.36	43.50	-8.14	QP			
2	357.1923	50.51	-14.40	36.11	46.00	-9.89	QP			
3	496.9809	46.22	-12.27	33.95	46.00	-12.05	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1103	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:46:47
EUT: MID	Engineer Signature:
Mode: TX 2440MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	134.4911	53.10	-21.90	31.20	43.50	-12.30	QP			
2	500.4857	46.22	-12.24	33.98	46.00	-12.02	QP			
3	807.0831	42.13	-5.77	36.36	46.00	-9.64	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1104	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:48:16
EUT: MID	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	133.5491	52.91	-21.86	31.05	43.50	-12.45	QP			
2	359.7114	50.83	-14.30	36.53	46.00	-9.47	QP			
3	495.2379	47.21	-12.29	34.92	46.00	-11.08	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1105	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:49:04
EUT: MID	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	130.7634	57.53	-21.75	35.78	43.50	-7.72	QP			
2	148.9175	56.67	-22.30	34.37	43.50	-9.13	QP			
3	498.7303	45.31	-12.25	33.06	46.00	-12.94	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1106	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:51:01
EUT: MID	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	17231.008	32.07	15.91	47.98	54.00	-6.02	peak			
2	17231.008	23.14	15.91	39.05	54.00	-14.95	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1107	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:51:48
EUT: MID	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15882.369	34.27	12.75	47.02	54.00	-6.98	peak			
2	15882.369	23.65	12.75	36.40	54.00	-17.60	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1108	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:53:18
EUT: MID	Engineer Signature:
Mode: TX 2440MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	13973.138	35.99	11.61	47.60	54.00	-6.40	peak			
2	13973.138	24.62	11.61	36.23	54.00	-17.77	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1109	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:54:07
EUT: MID	Engineer Signature:
Mode: TX 2440MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	14219.315	34.51	12.84	47.35	54.00	-6.65	peak			
2	14219.315	23.69	12.84	36.53	54.00	-17.47	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1110	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:54:56
EUT: MID	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16399.123	34.83	13.22	48.05	54.00	-5.95	peak			
2	16399.123	24.66	13.22	37.88	54.00	-16.12	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star2015 #1111	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2015/07/03
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15:56:14
EUT: MID	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: PC1016BXC	
Manufacturer: Natural Sound	

Note: Report No.:ATE20151402



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16688.041	33.80	13.93	47.73	54.00	-6.27	peak			
2	16688.041	23.45	13.93	37.38	54.00	-16.62	AVG			

10. CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST

10.1. Block Diagram of Test Setup



(EUT: MID)

10.2. The Requirement of Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3. EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.4.Operating Condition of EUT

10.4.1.Setup the EUT and simulator as shown as Section 11.1.

10.4.2.Turn on the power of all equipment.

10.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

10.5.Test Procedure

10.5.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

10.5.2.Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz

10.5.3.The Conducted Spurious Emission was measured and recorded.

10.6.Test Result

Pass.

The spectrum analyzer plots are attached as below.

BLE Channel Low 2402MHz



BLE Channel Middle 2440MHz



BLE Channel High 2480MHz



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.462 GHz	-4.58 dBm		
M2		1	6.983 GHz	-43.66 dBm		
M3		1	16.674 GHz	-39.89 dBm		
M4		1	20.007 GHz	-39.00 dBm		

11.POWER LINE CONDUCTED MEASUREMENT

11.1.Block Diagram of Test Setup



(EUT: MID)

11.2.Power Line Conducted Emission Measurement Limits

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0
NOTE1: The lower limit shall apply at the transition frequencies. NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.		

11.3.Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 5.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in test mode and measure it.

11.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement.
The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

11.6.Power Line Conducted Emission Measurement Results

PASS.

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

```
EUT:                    MID    M/N:PC1016BXC
Manufacturer:           Natural Sound
Operating Condition:    BT
Test Site:              2#Shielding Room
Operator:               star
Test Specification:     L   120V/60Hz
Comment:                Report No.:ATE20151402
Start of Test:          2015-7-2 / 10:17:25
```

SCAN TABLE: "V 150K-30MHz fin"

```
  Short Description:              _SUB_STD_VTERM2 1.70
  Start      Stop       Step       Detector  Meas.     IF       Transducer
  Frequency  Frequency  Width                Time      Bandw.
  150.0 kHz  30.0 MHz   4.5 kHz    QuasiPeak 1.0 s     9 kHz    LISN(ESH3-Z5)
                                   Average
```



MEASUREMENT RESULT: "KWE004_fin"

2015-7-2 10:19

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.566000	38.90	11.5	56	17.1	QP	L1	GND
1.570000	29.80	11.6	56	26.2	QP	L1	GND
5.262500	21.30	11.8	60	38.7	QP	L1	GND

MEASUREMENT RESULT: "KWE004_fin2"

2015-7-2 10:19

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.598000	28.90	11.5	46	17.1	AV	L1	GND
1.064000	22.20	11.6	46	23.8	AV	L1	GND
4.907000	13.90	11.8	46	32.1	AV	L1	GND

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

```
EUT:                    MID    M/N:PC1016BXC
Manufacturer:           Natural Sound
Operating Condition:    BT
Test Site:              2#Shielding Room
Operator:               star
Test Specification:     N   120V/60Hz
Comment:                Report No.:ATE20151402
Start of Test:          2015-7-2 / 10:19:48
```

SCAN TABLE: "V 150K-30MHz fin"

```
  Short Description:              _SUB_STD_VTERM2 1.70
  Start      Stop       Step       Detector  Meas.     IF       Transducer
  Frequency  Frequency  Width                Time      Bandw.
  150.0 kHz  30.0 MHz   4.5 kHz    QuasiPeak 1.0 s     9 kHz    LISN(ESH3-Z5)
                                   Average
```



MEASUREMENT RESULT: "KWE005_fin"

2015-7-2 10:21

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.542000	40.40	11.5	56	15.6	QP	N	GND
1.144000	31.10	11.6	56	24.9	QP	N	GND
5.573000	28.00	11.8	60	32.0	QP	N	GND

MEASUREMENT RESULT: "KWE005_fin2"

2015-7-2 10:21

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.568000	32.20	11.5	46	13.8	AV	N	GND
1.146000	21.40	11.6	46	24.6	AV	N	GND
5.429000	18.10	11.8	50	31.9	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT:	MID M/N:PC1016BXC
Manufacturer:	Natural Sound
Operating Condition:	BT
Test Site:	2#Shielding Room
Operator:	star
Test Specification:	L 240V/60Hz
Comment:	Report No.:ATE20151402
Start of Test:	2015-7-3 / 9:21:53

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	4.5 kHz	QuasiPeak Average	1.0 s	9 kHz	LISN(ESH3-Z5)



MEASUREMENT RESULT: "MIDA004_fin"

2015-7-3 9:23

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.580000	40.30	11.5	56	15.7	QP	L1	GND
1.278000	36.00	11.6	56	20.0	QP	L1	GND
5.685500	29.50	11.8	60	30.5	QP	L1	GND

MEASUREMENT RESULT: "MIDA004_fin2"

2015-7-3 9:23

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.574000	27.50	11.5	46	18.5	AV	L1	GND
2.265500	20.40	11.7	46	25.6	AV	L1	GND
6.792500	15.50	11.8	50	34.5	AV	L1	GND

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

```
EUT:                    MID   M/N:PC1016BXC
Manufacturer:           Natural Sound
Operating Condition:    BT
Test Site:              2#Shielding Room
Operator:               star
Test Specification:     N 240V/60Hz
Comment:                Report No.:ATE20151402
Start of Test:          2015-7-3 / 9:19:25
```

SCAN TABLE: "V 150K-30MHz fin"

```
  Short Description:            _SUB_STD_VTERM2 1.70
  Start      Stop       Step       Detector  Meas.     IF       Transducer
  Frequency  Frequency  Width                Time      Bandw.
  150.0 kHz  30.0 MHz   4.5 kHz    QuasiPeak 1.0 s     9 kHz    LISN(ESH3-Z5)
                                   Average
```



MEASUREMENT RESULT: "MIDA003_fin"

2015-7-3 9:21

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.580000	44.90	11.5	56	11.1	QP	N	GND
1.292000	39.10	11.6	56	16.9	QP	N	GND
5.901500	31.00	11.8	60	29.0	QP	N	GND

MEASUREMENT RESULT: "MIDA003_fin2"

2015-7-3 9:21

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.574000	37.10	11.5	46	8.9	AV	N	GND
1.242000	31.70	11.6	46	14.3	AV	N	GND
6.369500	21.90	11.8	50	28.1	AV	N	GND

12. ANTENNA REQUIREMENT

12.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

12.2. Antenna Construction

Device is equipped with unique antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.