



WILSON ELECTRONICS TEST REPORT

FOR THE

MOBILE WIRELESS CELLULAR/PCS
SMARTTECH AMPLIFIER, 801201-A

FCC PART 24 & RSS-131

COMPLIANCE

DATE OF ISSUE: JANUARY 17, 2006

PREPARED FOR:

Wilson Electronics
3301 East Deseret Drive
St. George, UT 84790

P.O. No.: DBW801201-3
W.O. No.: 84511

PREPARED BY:

Mary Ellen Clayton
CKC Laboratories, Inc.
5046 Sierra Pines Drive
Mariposa, CA 95338

Date of test: March 21 – December 20, 2005

Report No.: FC06-012

This report contains a total of 117 pages and may be reproduced in full only. Partial reproduction may only be done with the written consent of CKC Laboratories, Inc. The results in this report apply only to the items tested, as identified herein.

TABLE OF CONTENTS

Administrative Information	3
FCC to Canada Standard Correlation Matrix.....	4
Conditions for Compliance	4
Approvals.....	4
Equipment Under Test (EUT) Description	5
Equipment Under Test	5
Peripheral Devices	6
Temperature and Humidity During Testing.....	7
FCC 2.1033(c)(3) User's Manual	7
FCC 2.1033(c)(4) Type of Emissions.....	7
FCC 2.1033(c)(5) Frequency Range.....	7
FCC 2.1033(c)(6) Operating Power.....	7
FCC 2.1033(c)(7) Maximum Power Rating	7
FCC 2.1033(c)(8) DC Voltages	7
FCC 2.1033(c)(9) Tune-Up Procedure	7
FCC 2.1033(c)(10) Schematics and Circuitry Description.....	7
FCC 2.1033(c)(11) Label and Placement	7
FCC 2.1033(c)(12) Submittal Photos	7
FCC 2.1033(c)(13) Modulation Information	7
FCC 2.1033(c)(14)/2.1046/24.232 - RF Power Output	8
FCC 2.1033(c)(14)/2.1047(b) - Audio Frequency Response.....	11
FCC 2.1033(c)(14)/2.1047(b) - Modulation Limiting Response.....	11
FCC 2.1033(c)(14)/2.1049(i) - Occupied Bandwidth Downlink.....	11
FCC 2.1033(c)(14)/2.1049(i) - Occupied Bandwidth Uplink.....	15
FCC 2.1033(c)(14)/2.1051/24.238 - Downlink Block Edge.....	19
FCC 2.1033(c)(14)/2.1051/24.238 - Uplink Block Edge	25
FCC 2.1033(c)(14)/2.1051/24.238 - Intermodulation Attenuation.....	33
FCC 2.1033(c)(14)/2.1051/24.238 - Spurious Emissions at Antenna Terminal - Downlink ..	50
FCC 2.1033(c)(14)/2.1051/24.238 - Spurious Emissions at Antenna Terminal - Uplink.....	60
FCC 2.1033(c)(14)/2.1051/24.238 - Self-Collocation Intermodulation	78
FCC 2.1033(c)(14)/2.1053/24.238 - Field Strength of Spurious Radiation	83
Input Downlink	87
Input Uplink.....	90
Output Downlink	99
Output Uplink	102
RSS-131 Downlink Passband Gain	112
RSS-131 Uplink Passband Gain	113
RSS-131 Downlink Passbandwidth.....	115
RSS-131 Uplink Passband Width	116



ADMINISTRATIVE INFORMATION

DATE OF TEST: March 21 – December 20, 2005

DATE OF RECEIPT: March 21, 2005

FREQUENCY RANGE TESTED: 30MHz-20GHz

MANUFACTURER: Wilson Electronics
3301 East Deseret Drive
St. George, UT 84790

REPRESENTATIVE: Riki Kline

TEST LOCATION: CKC Laboratories, Inc.
5046 Sierra Pines Drive
Mariposa, CA 95338

TEST METHOD: FCC Part 24, TIA/EIA 603 & RSS-131

PURPOSE OF TEST: The EUT contains both uplink and downlink capabilities and was previously certified as model 801201. The EUT was modified as model 801201-A with only changes to the uplink portion of the EUT. This report contains new testing for the uplink and the old downlink data (identified as the old model 801201) because that portion of the EUT has not changed. Therefore this report shows complete compliance for the Mobile Wireless Cellular/PCS SmartTech Amplifier, 801201-A with the requirements for FCC Part 24 & RSS-131 devices.

FCC TO CANADA STANDARD CORRELATION MATRIX

Canadian Standard	Canadian Section	FCC Standard	FCC Section	Test Description
RSS-131	5.4	N/A	N/A	External Controls
RSS-131	5.5	47 CFR	1.1307	RF Exposure
RSS-131	6.1	N/A	N/A	Passband Gain and Bandwidth
RSS-131	6.2	47 CFR	24.232	RF Power Output
RSS-131	6.3	TIA/EIA	603	Non-Linearity (Intermodulation Attenuation)
RSS-131	6.4	47 CFR	24.238	Spurious Emissions Limitations
RSS-131	6.5	N/A	N/A	Frequency Stability (Band Translators)
IC 3082-D		784962		Site Filing No.

CONDITIONS FOR COMPLIANCE

No modifications to the EUT were necessary to comply.

APPROVALS


Steve Behm, Director of Engineering Services

QUALITY ASSURANCE:




Joyce Walker, Quality Assurance Administrative Manager

TEST PERSONNEL:



Mike Wilkinson, Lab Manager



Randy Clark, EMC Engineer



Ryan Rutledge, EMC Test Technologist



EQUIPMENT UNDER TEST (EUT) DESCRIPTION

The customer declares the EUT tested by CKC Laboratories was representative of a production unit.

The following equipment name has been used during testing by CKC Laboratories:

In Vehicle Wireless Dual Band Smart Amplifier

Since the time of testing the manufacturer has chosen to use the following equipment name in its place. Any differences between the names does not affect their EMC characteristics and therefore complies to the level of testing equivalent to the tested model name shown on the data sheets:

Mobile Wireless Cellular/PCS SmartTech Amplifier

The models number 801201 and 801201-A both appear in this test report. The manufacturer declares that the difference between 801201 and 801201-A is a redesign of the uplink path only and that the downlink circuitry and schematics remain unchanged. Therefore, the data regarding only the downlink path of the 801201 is used to demonstrate compliance for the 801201-A. This test report contains the new data for the uplink path of the 801201-A with which compliance is demonstrated.

EQUIPMENT UNDER TEST

Mobile Wireless Cellular/PCS SmartTech Amplifier

Manuf: Wilson Electronics
Model: 801201
Serial: 8012010000006
FCC ID: PWO8012SM

Mobile Wireless Cellular/PCS SmartTech Amplifier

Manuf: Wilson Electronics
Model: 801201-A
Serial: 8012010112702
FCC ID: PWO8012ASM (pending)

PERIPHERAL DEVICES

The EUT was tested with the following peripheral device(s):

Signal Generator

Manuf: HP
Model: E4433B
Serial: US38440697
FCC ID: DoC

DC Power Supply

Manuf: Topward
Model: TPS-2000
Serial: 920035
FCC ID: NA

Signal Generator

Manuf: HP
Model: E4432B
Serial: MY41000298 &
US40052968
FCC ID: DoC

Load

Manuf: JFW
Model: 50T-022
Serial: P04243
FCC ID: DoC

TEMPERATURE AND HUMIDITY DURING TESTING

The temperature during testing was within +15°C and + 35°C.
The relative humidity was between 20% and 75%.

FCC 2.1033(c)(3) USER'S MANUAL

The necessary information is contained in a separate document.

FCC 2.1033 (c)(4) TYPE OF EMISSIONS

GXW, G7W, F9W

FCC 2.1033 (c)(5) FREQUENCY RANGE

Downlink 1930-1990MHz, Uplink 1850-1910MHz

FCC 2.1033 (c)(6) OPERATING POWER

Downlink, 8.31 mWatts (EIRP), Uplink, 1.81 Watts (EIRP)

FCC 2.1033 (c)(7) MAXIMUM POWER RATING

Downlink 15 mW, Uplink 2 Watts EIRP

FCC 2.1033 (c)(8) DC VOLTAGES

The necessary information is contained in a separate document.

FCC 2.1033 (c)(9) TUNE-UP PROCEDURE

The necessary information is contained in a separate document.

FCC 2.1033(c)(10) SCHEMATICS AND CIRCUITRY DESCRIPTION

The necessary information is contained in a separate document.

FCC 2.1033(c)(11) LABEL AND PLACEMENT

The necessary information is contained in a separate document.

FCC 2.1033(c)(12) SUBMITTAL PHOTOS

The necessary information is contained in a separate document.

FCC 2.1033 (c)(13) MODULATION INFORMATION

GSM, EDGE, CDMA



FCC 2.1033(c)(14)/2.1046/24.232 - RF POWER OUTPUT

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz.

RF Power Output Test:

Only one signal is input to the amplifier. The input from the signal generator is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Minimum RF output power of 0.00 Watts is achieved with a 0.00 Watt RF input signal.

Uplink Output Ratings:

CDMA and TDMA (EDGE & GSM) formats: 2Watts EIRP

Downlink Output Ratings:

All: 15mW

RF power output of the amplifier is routed to a spectrum analyzer through suitable attenuation.

Downlink – Conducted Power

<i>Frequency (MHz)</i>	<i>Modulation</i>	<i>Power Output (milliWatts)</i>
1931.25	CDMA	6.60
1960.0	CDMA	9.77
1988.75	CDMA	8.71
1930.28	GSM	6.30
1960.0	GSM	9.77
1989.72	GSM	8.51
1930.28	EDGE	6.30
1960.0	EDGE	9.12
1989.72	EDGE	8.51

Downlink – EIRP Power

<i>Frequency (MHz)</i>	<i>Modulation</i>	<i>Power Output (milliWatts)</i>
1931.25	CDMA	5.62
1960.0	CDMA	8.31
1988.75	CDMA	7.41
1930.28	GSM	5.37
1960.0	GSM	8.31
1989.72	GSM	7.24
1930.3	EDGE	5.37
1960.0	EDGE	7.76
1989.7	EDGE	6.91

Note: Downlink EIRP calculated using 3.2 dBi gain antenna – 3.9 dB coax loss = -0.7 dBi as declared by Wilson Electronics.

Uplink – Conducted Power

<i>Frequency (MHz)</i>	<i>Modulation</i>	<i>Power Output (Watts)</i>
1851.25	CDMA	1.66
1880.0	CDMA	1.99
1908.75	CDMA	1.17
1850.28	GSM	1.62
1880.0	GSM	1.66
1909.72	GSM	1.02
1850.28	EDGE	1.51
1880.0	EDGE	1.62
1909.72	EDGE	1.07

Uplink – EIRP

<i>Frequency (MHz)</i>	<i>Modulation</i>	<i>Power Output (Watts)</i>
1851.25	CDMA	1.50
1880.0	CDMA	1.81
1908.75	CDMA	1.06
1850.28	GSM	1.47
1880.0	GSM	1.50
1909.72	GSM	0.93
1850.28	EDGE	1.37
1880.0	EDGE	1.47
1909.72	EDGE	0.97

The above values are calculated based on the gain of the antenna minus the manufacturer's declared nominal cable loss of 6.55dB:
 $6.12\text{dBi} - 6.55\text{dB} = -0.43\text{dBi}$

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP



**FCC 2.1033(c)(14)/2.1047(a) - MODULATION CHARACTERISTICS - AUDIO
FREQUENCY RESPONSE**

Not applicable to this unit.


**FCC 2.1033(c)(14)/2.1047(b) MODULATION CHARACTERISTICS- Modulation
Limiting Response**

Not applicable to this unit.


FCC 2.1033(c)(14)/2.1049(i)- OCCUPIED BANDWIDTH

Test Conditions: EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Frequency Range Investigated: 30MHz to 20GHz.


FCC 2.1049 DOWNLINK OCCUPIED BANDWIDTH CDMA - PCS BAND



FCC 2.1049 DOWNLINK OCCUPIED BANDWIDTH EDGE - PCS BAND




FCC 2.1049 DOWNLINK OCCUPIED BANDWIDTH GSM - PCS BAND




Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				


FCC 2.1049 UPLINK OCCUPIED BANDWIDTH - CDMA



FCC 2.1049 UPLINK OCCUPIED BANDWIDTH - EDGE



FCC 2.1049 UPLINK OCCUPIED BANDWIDTH - GSM



Test Equipment:


Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP




FCC 2.1033(C)(14)/2.1051/24.238 - DOWNLINK LOWER BLOCK EDGE CDMA - PCS BAND


Test Conditions: EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Frequency Range Investigated: 30MHz to 20GHz.




**FCC 2.1033(C)(14)/2.1051/24.238 - DOWNLINK UPPER BLOCK EDGE CDMA - PCS
BAND**




**FCC 2.1033(C)(14)/2.1051/24.238 - DOWNLINK LOWER BLOCK EDGE EDGE - PCS
BAND**




**FCC 2.1033(C)(14)/2.1051/24.238 - DOWNLINK UPPER BLOCK EDGE EDGE - PCS
BAND**



**FCC 2.1033(C)(14)/2.1051/24.238 - DOWNLINK LOWER BLOCK EDGE GSM - PCS
BAND**



FCC 2.1033(C)(14)/2.1051/24.238 - DOWNLINK UPPER BLOCK EDGE GSM - PCS BAND




Test Equipment:


Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

FCC 2.1033(C)(14)/2.1051/24.238 - UPLINK INTERMODULATION AND BLOCK EDGE CDMA


Wilson Electronics 801201 Amplifier: CDMA 1900 Intermodulation and Block Edges
 Ref Level 126.99 dBμV ATTN 30 dB
 RES BW: 30.0kHz VID BW: 91.0kHz SWP: 675.267msec
 Marker: 1.85GHz 54.4717dBμV




FCC 2.1033(C)(14)/2.1051/24.238 - UPLINK LOWER BLOCK EDGE - EDGE




FCC 2.1033(C)(14)/2.1051/24.238 - UPLINK UPPER BLOCK EDGE - EDGE



FCC 2.1033(C)(14)/2.1051/24.238 - UPLINK LOWER BLOCK EDGE - GSM



FCC 2.1033(C)(14)/2.1051/24.238 - UPLINK UPPER BLOCK EDGE - GSM



Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP



Test Location: CKC Laboratories • 5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/15/2005
 Test Type: **Antenna Terminals** Time: 10:06:10
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 24
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968
Signal Generator	HP	E4432B	US400053750

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: As Indicated. Frequencies Tested: Uplink 1900MHz Band. This mode represents the worst case of emissions. Frequency Range Investigated: 30 MHz to 20 GHz..

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------

Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1910.000M	79.9	+10.2	+1.2		+0.0	91.3	94.0	-2.7	None
								EDGE 1900 Upper Block Edge		
2	1850.000M	77.6	+10.2	+1.2		+0.0	89.0	94.0	-5.0	None
								EDGE 1900 Lower Block Edge		

3	1910.000M	74.8	+10.2	+1.2	+0.0	86.2	94.0	-7.8	None
							GSM 1900 Upper Block Edge		
4	1850.000M	73.3	+10.2	+1.2	+0.0	84.7	94.0	-9.3	None
							GSM 1900 Lower Block Edge		
5	1850.000M	55.5	+10.2	+1.2	+0.0	66.9	94.0	-27.1	None
							CDMA 1900 Lower Block Edge		
6	1910.000M	55.4	+10.2	+1.2	+0.0	66.8	94.0	-27.2	None
							CDMA 1900 Upper Block Edge		

FCC 2.1033(C)(14)/2.1051/24.238 - INTERMODULATION ATTENUATION

ANALYZER BANDWIDTH SETTINGS PER FREQUENCY RANGE			
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
RADIATED EMISSIONS	30MHz	1000MHz	10 kHz
RADIATED EMISSIONS	1000MHz	20GHz	100 kHz

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/28/2005
 Test Type: **Antenna Terminals** Time: 15:48:54
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 54
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Three signals are input to the amplifier through a combining network. The first two input signals are provided by the HP E4432B ESG. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Frequencies Tested: Downlink 1931.25MHz, 1933.75MHz, 1988.75MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1934.200M	69.8	+30.3				+0.0	100.1	117.0	-16.9	None
Fundamental											

2	1988.600M	69.0	+30.3	+0.0	99.3	117.0	-17.7	None
						Fundamental		
3	1931.800M	66.2	+30.3	+0.0	96.5	117.0	-20.5	None
						Fundamental		
4	1929.200M	42.3	+30.3	+0.0	72.6	94.0	-21.4	None
5	1991.400M	39.8	+30.3	+0.0	70.1	94.0	-23.9	None
6	3868.400M	26.0	+29.7	+0.0	55.7	94.0	-38.3	None
7	3977.450M	23.9	+29.6	+0.0	53.5	94.0	-40.5	None
8	1936.800M	44.0	+30.3	+0.0	74.3	117.0	-42.7	None
9	1986.000M	42.7	+30.3	+0.0	73.0	117.0	-44.0	None
10	5966.350M	18.2	+27.8	+0.0	46.0	94.0	-48.0	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/30/2005
 Test Type: **Antenna Terminals** Time: 08:36:04
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 73
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Frequencies Tested: Downlink 1930.3MHz, 1930.9MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1930.920M	81.7	+30.3				+0.0	112.0	117.0	-5.0	None
									Fundamental		
2	1930.300M	81.0	+30.3				+0.0	111.3	117.0	-5.7	None
									Fundamental		
3	1929.980M	46.0	+30.3				+0.0	76.3	94.0	-17.7	None
4	3860.640M	42.6	+29.7				+0.0	72.3	94.0	-21.7	None
5	3861.860M	41.9	+29.7				+0.0	71.6	94.0	-22.4	None

6	1931.160M	49.7	+30.3	+0.0	80.0	117.0	-37.0	None
7	5792.720M	26.5	+27.8	+0.0	54.3	94.0	-39.7	None
8	5790.820M	25.9	+27.8	+0.0	53.7	94.0	-40.3	None
9	7720.860M	24.2	+25.2	+0.0	49.4	94.0	-44.6	None
10	9655.420M	22.5	+24.2	+0.0	46.7	94.0	-47.3	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 05/02/2005
 Test Type: **Antenna Terminals** Time: 16:56:48
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 74
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE Frequencies Tested: Downlink 1989.1 MHz 1989.7 MHz Frequency Range Investigated: 30 MHz to 20 GHz..

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1990.000M	57.1	+30.3				+0.0	87.4	94.0	-6.6	None
2	1990.158M	51.1	+30.3				+0.0	81.4	94.0	-12.6	None
3	1990.444M	43.7	+30.3				+0.0	74.0	94.0	-20.0	None

4	3979.450M	35.8	+29.6	+0.0	65.4	94.0	-28.6	None
5	3978.000M	34.6	+29.6	+0.0	64.2	94.0	-29.8	None
6	5967.410M	22.4	+27.8	+0.0	50.2	94.0	-43.8	None
7	5968.930M	20.6	+27.8	+0.0	48.4	94.0	-45.6	None



Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)
 Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/29/2005
 Test Type: **Antenna Terminals** Time: 12:03:44
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 63
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird 25-A-MFN-30	9949	05/09/2003	05/09/2005	P01572

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Frequencies Tested: Downlink 1930.28MHz, 1930.81MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data:		Reading listed by margin.					Test Distance: None				
#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1930.270M	80.2	+30.3				+0.0	110.5	117.0	-6.5	None
									Fundamental		
2	1930.830M	78.1	+30.3				+0.0	108.4	117.0	-8.6	None
									Fundamental		
3	3860.690M	36.5	+29.7				+0.0	66.2	94.0	-27.8	None
4	1929.980M	27.9	+30.3				+0.0	58.2	94.0	-35.8	None
5	3861.610M	26.5	+29.7				+0.0	56.2	94.0	-37.8	None
6	5790.840M	18.4	+27.8				+0.0	46.2	94.0	-47.8	None
7	9651.960M	9.9	+24.2				+0.0	34.1	94.0	-59.9	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/29/2005
 Test Type: **Antenna Terminals** Time: 13:01:07
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 64
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Frequencies Tested: Downlink 1989.16MHz, 1989.72MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB


Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1989.170M	83.5	+30.3				+0.0	113.8	117.0	-3.2	None
2	1989.720M	82.7	+30.3				+0.0	113.0	117.0	-4.0	None
3	1990.010M	39.1	+30.3				+0.0	69.4	94.0	-24.6	None
4	3979.490M	37.5	+29.6				+0.0	67.1	94.0	-26.9	None
5	3978.180M	36.8	+29.6				+0.0	66.4	94.0	-27.6	None


6	5967.300M	24.2	+27.8	+0.0	52.0	94.0	-42.0	None
7	5969.330M	22.9	+27.8	+0.0	50.7	94.0	-43.3	None
8	7956.630M	21.3	+24.5	+0.0	45.8	94.0	-48.2	None
9	7959.150M	19.5	+24.5	+0.0	44.0	94.0	-50.0	None
10	9948.600M	11.0	+23.2	+0.0	34.2	94.0	-59.8	None

INTERMODULATION ATTENUATION DOWNLINK CDMA - PCS BAND LOWER NARROW SPAN




INTERMODULATION ATTENUATION DOWNLINK CDMA - PCS BAND UPPER NARROW SPAN


Wilson Electronics 801201, Intermodulation Attenuation, Downlink CDMA, PCS Band-Upper Narrow Span
Ref Level 98.99 dB μ V ATTN 2 dB
RES BW: 120.0kHz VID BW: 120.0kHz SVP: 3.733msec




INTERMODULATION ATTENUATION DOWNLINK CDMA - PCS BAND WIDE RANGE




INTERMODULATION ATTENUATION DOWNLINK EDGE - PCS BAND LOW RANGE




INTERMODULATION ATTENUATION DOWNLINK EDGE - PCS BAND HIGH RANGE



INTERMODULATION ATTENUATION DOWNLINK GSM - PCS BAND LOW RANGE



INTERMODULATION ATTENUATION DOWNLINK GSM - PCS BAND HIGH RANGE



Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP





FCC 2.1033(c)(14)/2.1051/24.238 - SPURIOUS EMISSIONS AT ANTENNA TERMINAL - DOWNLINK

ANALYZER BANDWIDTH SETTINGS PER FREQUENCY RANGE			
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
RADIATED EMISSIONS	30MHz	1000MHz	10 kHz
RADIATED EMISSIONS	1000MHz	20GHz	100 kHz

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/28/2005
 Test Type: **Antenna Terminals** Time: 15:23:53
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 52
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird 9949		05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Frequencies Tested: Downlink Mid - 1960.0MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data:		Reading listed by margin.				Test Distance: None					
#	Freq MHz	Rdng dB μ V	T1 dB				Dist Table	Corr dB μ V	Spec dB μ V	Margin dB	Polar Ant
1	1960.020M	86.6	+30.3				+0.0	116.9	117.0	-0.1	None
									Fundamental		
2	3920.150M	35.8	+29.6				+0.0	65.4	94.0	-28.6	None
3	7840.000M	28.1	+24.9				+0.0	53.0	94.0	-41.0	None
4	5880.170M	21.3	+27.8				+0.0	49.1	94.0	-44.9	None
5	9800.020M	16.1	+23.7				+0.0	39.8	94.0	-54.2	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/28/2005
 Test Type: **Antenna Terminals** Time: 15:15:14
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 51
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Frequencies Tested: Downlink Low - 1931.25MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1931.250M	84.9	+30.3				+0.0	115.2	117.0	-1.8	None
									Fundamental		
2	1929.990M	44.4	+30.3				+0.0	74.7	94.0	-19.3	None
3	3862.790M	28.1	+29.7				+0.0	57.8	94.0	-36.2	None
4	7725.290M	16.7	+25.2				+0.0	41.9	94.0	-52.1	None
5	5794.040M	12.5	+27.8				+0.0	40.3	94.0	-53.7	None
6	9656.540M	15.2	+24.2				+0.0	39.4	94.0	-54.6	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/28/2005
 Test Type: **Antenna Terminals** Time: 15:29:55
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 53
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Frequencies Tested: Downlink High - 1988.75MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1988.690M	86.1	+30.3				+0.0	116.4	117.0	-0.6	None
									Fundamental		
2	3977.470M	33.1	+29.6				+0.0	62.7	94.0	-31.3	None
3	5966.510M	20.7	+27.8				+0.0	48.5	94.0	-45.5	None
4	7954.960M	23.1	+24.5				+0.0	47.6	94.0	-46.4	None
5	11932.620M	18.1	+19.9				+0.0	38.0	94.0	-56.0	None
6	9943.650M	14.3	+23.2				+0.0	37.5	94.0	-56.5	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/30/2005
 Test Type: **Antenna Terminals** Time: 08:07:37
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 70
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Frequencies Tested: Downlink Low - 1930.3MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1930.320M	84.7	+30.3				+0.0	115.0	117.0	-2.0	None
									Fundamental		
2	1929.980M	58.3	+30.3				+0.0	88.6	94.0	-5.4	None
3	3860.510M	43.7	+29.7				+0.0	73.4	94.0	-20.6	None
4	5790.950M	34.2	+27.8				+0.0	62.0	94.0	-32.0	None
5	7721.270M	34.9	+25.2				+0.0	60.1	94.0	-33.9	None
6	9651.670M	25.3	+24.2				+0.0	49.5	94.0	-44.5	None



Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/30/2005
 Test Type: **Antenna Terminals** Time: 08:14:46
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 71
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Frequencies Tested: Downlink Mid - 1960.0MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1960.040M	86.3	+30.3				+0.0	116.6	117.0	-0.4	None
									Fundamental		
2	3920.000M	44.4	+29.6				+0.0	74.0	94.0	-20.0	None
3	7840.190M	47.2	+24.9				+0.0	72.1	94.0	-21.9	None
4	5879.820M	35.8	+27.8				+0.0	63.6	94.0	-30.4	None
5	9800.230M	30.6	+23.7				+0.0	54.3	94.0	-39.7	None
6	11760.270M	26.1	+20.1				+0.0	46.2	94.0	-47.8	None



Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)
 Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/30/2005
 Test Type: **Antenna Terminals** Time: 08:23:26
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 72
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird 25-A-MFN-30	9949	05/09/2003	05/09/2005	P01572

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Frequencies Tested: Downlink High - 1989.7MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1989.720M	86.0	+30.3				+0.0	116.3	117.0	-0.7	None
									Fundamental		
2	1990.090M	59.6	+30.3				+0.0	89.9	94.0	-4.1	None
3	3979.570M	40.3	+29.6				+0.0	69.9	94.0	-24.1	None
4	7958.820M	35.1	+24.5				+0.0	59.6	94.0	-34.4	None
5	5969.140M	27.6	+27.8				+0.0	55.4	94.0	-38.6	None
6	9948.520M	24.6	+23.2				+0.0	47.8	94.0	-46.2	None
7	11938.220M	23.1	+19.9				+0.0	43.0	94.0	-51.0	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/29/2005
 Test Type: **Antenna Terminals** Time: 11:11:57
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 60
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Frequencies Tested: Downlink Low - 1930.28MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1930.282M	84.7	+30.3				+0.0	115.0	117.0	-2.0	None
									Fundamental		
2	3860.700M	46.6	+29.7				+0.0	76.3	94.0	-17.7	None
3	1929.998M	35.2	+30.3				+0.0	65.5	94.0	-28.5	None
4	5790.640M	30.0	+27.8				+0.0	57.8	94.0	-36.2	None
5	7721.376M	27.1	+25.2				+0.0	52.3	94.0	-41.7	None
6	9651.654M	14.7	+24.2				+0.0	38.9	94.0	-55.1	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/29/2005
 Test Type: **Antenna Terminals** Time: 11:17:23
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 61
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Frequencies Tested: Downlink Mid - 1960.0MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1959.934M	86.6	+30.3				+0.0	116.9	117.0	-0.1	None
									Fundamental		
2	3920.132M	39.4	+29.6				+0.0	69.0	94.0	-25.0	None
3	7840.286M	41.7	+24.9				+0.0	66.6	94.0	-27.4	None
4	5879.796M	35.7	+27.8				+0.0	63.5	94.0	-30.5	None
5	9799.710M	21.7	+23.7				+0.0	45.4	94.0	-48.6	None
6	11759.290M	16.9	+20.1				+0.0	37.0	94.0	-57.0	None

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Downlink**
 Work Order #: **83305** Date: 03/29/2005
 Test Type: **Antenna Terminals** Time: 11:24:30
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 62
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Spurious Emissions Test: One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Frequencies Tested: Downlink High-1989.72MHz. Frequency Range Investigated: 30MHz to 20GHz.

Transducer Legend:

T1=Pad 30dB

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV	Spec dBμV	Margin dB	Polar Ant
1	1989.736M	86.0	+30.3				+0.0	116.3	117.0	-0.7	None
									Fundamental		
2	1990.002M	36.1	+30.3				+0.0	66.4	94.0	-27.6	None
3	3979.584M	34.1	+29.6				+0.0	63.7	94.0	-30.3	None
4	7959.164M	35.0	+24.5				+0.0	59.5	94.0	-34.5	None
5	5968.956M	29.4	+27.8				+0.0	57.2	94.0	-36.8	None
6	9949.446M	18.5	+23.2				+0.0	41.7	94.0	-52.3	None

FCC 2.1033(c)(14)/2.1051/24.238 - SPURIOUS EMISSIONS AT ANTENNA TERMINAL - UPLINK

Test Location: CKC Laboratories • 5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Uplink**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 14:01:34
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 14
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Input Channel: Low. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz.

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------

Measurement Data:


Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	dB	dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1851.300M	120.2	+10.2	+1.2			+0.0	131.6	94.0 Carrier	+37.6	None

2	1850.000M	73.8	+10.2	+1.2	+0.0	85.2	94.0	-8.8	None
Ave									
^	1850.000M	77.0	+10.2	+1.2	+0.0	88.4	94.0	-5.6	None
4	821.900M	49.6	+9.7	+0.9	+0.0	60.2	94.0	-33.8	None
5	3702.480M	45.9	+10.4	+1.7	+0.0	58.0	94.0	-36.0	None

CKC Laboratories Date: 12/8/2005 Time: 14:01:34 Wilson Electronics W/O#: 84511
FCC 2.1051 Test Distance: None Sequence#: 14
Wilson Electronics M/N 801201 1900 MHz Band CDMA Low Channel





Test Location: CKC Laboratories •5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 Uplink**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 14:09:13
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 15
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Input Channel: Mid. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz.

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------


Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1879.950M	121.3	+10.2	+1.2	+0.0	132.7	94.0 Carrier	+38.7	None
2	822.610M	53.8	+9.7	+0.9	+0.0	64.4	94.0	-29.6	None

CKC Laboratories Date: 12/8/2005 Time: 14:09:13 Wilson Electronics WVO#: 84511
 FCC 2.1051 Test Distance: None Sequence#: 15
 Wilson Electronics M/N 801201 1900 MHz Band CDMA Mid Channel



Test Location: CKC Laboratories •5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 14:21:45
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 16
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Input Channel: High. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz.

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------


Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist dB	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1908.790M	115.4	+10.2	+1.2	+0.0	126.8	94.0 Carrier	+32.8	None
2	821.700M	53.1	+9.7	+0.9	+0.0	63.7	94.0	-30.3	None

CKC Laboratories Date: 12/8/2005 Time: 14:21:45 Wilson Electronics WVO#: 84511
FCC 2.1051 Test Distance: None Sequence#: 16
Wilson Electronics M/N 801201 1900 MHz Band CDMA High Channel





Test Location: CKC Laboratories •5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 2:22:48 PM
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 17
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Input Channel: Low. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz. **No EUT emissions detected within 20dB of the limit.**

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------


Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist dB	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1850.250M	122.5	+10.2	+1.2	+0.0	133.9	94.0 Carrier	+39.9	None

CKC Laboratories Date: 12/8/2005 Time: 2:22:48 PM Wilson Electronics WVO#: 84511
FCC 2.1051 Test Distance: None Sequence#: 17
Wilson Electronics M/N 801201 1900 MHz Band GSM Low Channel





Test Location: CKC Laboratories •5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 2:30:27 PM
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 18
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Input Channel: Mid. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz. **No EUT emissions detected within 20dB of the limit.**


Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------

Measurement Data: Reading listed by margin. Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist dB	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1880.100M	124.3	+10.2	+1.2	+0.0	135.7	94.0 Carrier	+41.7	None

CKC Laboratories Date: 12/8/2005 Time: 2:30:27 PM Wilson Electronics WVO#: 84511
FCC 2.1051 Test Distance: None Sequence#: 18
Wilson Electronics M/N 801201 1900 MHz Band GSM Mid Channel





Test Location: CKC Laboratories •5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 2:39:26 PM
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 19
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: GSM. Input Channel: High. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz. **No EUT emissions detected within 20dB of the limit.**


Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------

Measurement Data: Reading listed by margin. Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist dB	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1909.800M	116.8	+10.2	+1.2	+0.0	128.2	94.0 Carrier	+34.2	None

CKC Laboratories Date: 12/8/2005 Time: 2:39:26 PM Wilson Electronics WVO#: 84511
FCC 2.1051 Test Distance: None Sequence#: 19
Wilson Electronics M/N 801201 1900 MHz Band GSM High Channel





Test Location: CKC Laboratories •5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 2:46:05 PM
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 20
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Input Channel: Low. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz. **No EUT emissions detected within 20dB of the limit.**

Transducer Legend:


T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------

Measurement Data: Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1850.250M	124.0	+10.2	+1.2	+0.0	135.4	94.0 Carrier	+41.4	None

CKC Laboratories Date: 12/8/2005 Time: 2:46:05 PM Wilson Electronics WVO#: 84511
FCC 2.1051 Test Distance: None Sequence#: 20
Wilson Electronics M/N 801201 1900 MHz Band EDGE Low Channel



Test Location: CKC Laboratories • 5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 2:53:23 PM
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 21
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Input Channel: Mid. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz. **No EUT emissions detected within 20dB of the limit.**

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------


Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB		Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1879.950M	125.2	+10.2	+1.2		+0.0	136.6	94.0 Carrier	+42.6	None

CKC Laboratories Date: 12/8/2005 Time: 2:53:23 PM Wilson Electronics WVO#: 84511
FCC 2.1051 Test Distance: None Sequence#: 21
Wilson Electronics M/N 801201 1900 MHz Band EDGE Mid Channel



Test Location: CKC Laboratories • 5046 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **24.238 UPLINK**
 Work Order #: **84511** Date: 12/8/2005
 Test Type: **Antenna Terminals** Time: 15:30:48
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 22
 Manufacturer: Wilson Electronics Tested By: Ryan Rutledge
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: EDGE. Input Channel: High. Frequencies Tested: Uplink 1900 MHz Band. Frequency Range Investigated: 30 MHz to 20 GHz.

Transducer Legend:

T1=Pad 10dB	T2=Cable 40 GHz 48"
-------------	---------------------


Measurement Data:

Reading listed by margin.

Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	T2 dB	Dist dB	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	1909.650M	119.6	+10.2	+1.2	+0.0	131.0	94.0 Carrier	+37.0	None
2	1877.150M	52.6	+10.2	+1.2	+0.0	64.0	94.0	-30.0	None

CKC Laboratories Date: 12/8/2005 Time: 15:30:48 Wilson Electronics W/O#: 84511
 FCC 2.1051 Test Distance: None Sequence#: 22
 Wilson Electronics M/N 801201 1900 MHz Band EDGE High Channel





FCC 2.1033(c)(14)/2.1051/24.238 – SELF-COLLOCATION INTERMODULATION

Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **FCC 2.1051**
 Work Order #: **83305** Date: 05/02/2005
 Test Type: **Antenna Terminals** Time: 16:45:04
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 93
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird 9949		05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894MHz and the 1850 to 1990MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Frequencies Tested: Downlink 1960MHz and 881.5MHz. This mode represents the worst case of emissions. Frequency Range Investigated: 30 MHz to 20 GHz..


Transducer Legend:

T1=Pad 30dB

Measurement Data:		Reading listed by margin.					Test Distance: None				
#	Freq MHz	Rdng dBμV	T1 dB				Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	881.432M	81.8	+30.3				+0.0	112.1	117.0 Carrier	-4.9	None
2	1959.641M	79.8	+30.3				+0.0	110.1	117.0 Carrier	-6.9	None
3	2644.350M	46.8	+29.9				+0.0	76.7	94.0	-17.3	None

4	3920.080M	39.3	+29.6	+0.0	68.9	94.0	-25.1	None
5	7839.978M	41.1	+24.9	+0.0	66.0	94.0	-28.0	None
6	1762.664M	34.6	+30.3	+0.0	64.9	94.0	-29.1	None
7	5879.230M	30.5	+27.8	+0.0	58.3	94.0	-35.7	None

CKC Laboratories Date: 05/02/2005 Time: 16:45:04 Wilson Electronics WVO#: 83305
FCC 2.1053 Test Distance: None Sequence#: 93
Wilson Electronics MN 801201





Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **FCC 2.10531**
 Work Order #: **83305** Date: 05/02/2005
 Test Type: **Antenna Terminals** Time: 16:24:36
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 92
 Manufacturer: Wilson Electronics Tested By: Mike Wilkinson
 Model: 801201
 S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894MHz and the 1850 to 1990MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Intermodulation Attenuation and Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Input Modulation: CDMA. Frequencies Tested: Uplink 1880MHz and 836.5MHz. This mode represents the worst case of emissions. Frequency Range Investigated: 30 MHz to 20 GHz..

Transducer Legend:


T1=Pad 30dB

Measurement Data: Reading listed by margin. Test Distance: None

#	Freq MHz	Rdng dBμV	T1 dB	dB	dB	dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
1	836.496M	98.1	+30.4				+0.0	128.5	140.0	-11.5	None
									Carrier		
2	1879.816M	96.5	+30.3				+0.0	126.8	140.0	-13.2	None
									Carrier		
3	1883.680M	42.4	+30.3				+0.0	72.7	94.0	-21.3	None
4	1885.270M	39.3	+30.3				+0.0	69.6	94.0	-24.4	None

5	8765.240M	43.4	+24.4	+0.0	67.8	94.0	-26.2	None
6	2716.385M	36.6	+29.8	+0.0	66.4	94.0	-27.6	None
7	830.350M	34.8	+30.4	+0.0	65.2	94.0	-28.8	None
8	818.280M	32.7	+30.4	+0.0	63.1	94.0	-30.9	None

CKC Laboratories Date: 05/02/2005 Time: 16:24:36 Wilson Electronics W/O#: 83305
FCC 2.1053 Test Distance: None Sequence#: 92
Wilson Electronics M/N 801201



PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP





FCC 2.1033(c)(14)/2.1053/24.238 - FIELD STRENGTH OF SPURIOUS RADIATION

Test Location: CKC Laboratories • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**
 Specification: **FCC 2.1053**
 Work Order #: **84511** Date: 12/15/2005
 Test Type: **Antenna Terminals** Time: 08:14:08
 Equipment: **In Vehicle Wireless Dual Band Smart Amplifier** Sequence#: 25
 Manufacturer: Wilson Electronics Tested By: Randal Clark
 Model: 801201-A
 S/N: 8012010112702

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Chase CBL6111C Bilog	2456	06/07/2005	06/07/2007	01991
EMCO 3115 Horn Antenna	9307-4085	04/29/2005	04/29/2007	00656
ARA MWH-1826/B Horn Antenna	1005	11/05/2004	11/05/2006	02046
HP 8447D Preamp	1937A02604	03/11/2005	03/11/2007	00099
HP 8449B Preamp	3008A00301	12/14/2004	12/14/2006	2010
Cable, Andrews Hardline HF-005-20	NA	05/27/2005	05/27/2007	P04275

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201-A	8012010112702

Support Devices:

Function	Manufacturer	Model #	S/N
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	US40052968

Test Conditions / Notes:

EUT is a dual band bidirectional amplifier for the 824 to 894 MHz and the 1850 to 1990 MHz bands. Uplink frequency range 824 - 849MHz and 1850 - 1910MHz. Downlink frequency range 869 - 894MHz and 1930 - 1990MHz. Radiated Spurious Emissions Test: The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. The EUT output port is terminated into a resistive load. Input Modulation: CDMA. Frequencies Tested: Uplink 800MHz and 1900MHz Bands. This mode represents the worst case of emissions. Frequency Range Investigated: 30 MHz to 20 GHz. **No EUT Emissions were detected within 20dB of the limit.**

Transducer Legend:

--

Measurement Data: Reading listed by margin. Test Distance: 3 Meters

#	Freq MHz	Rdng dBμV	dB	dB	dB	dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
---	-------------	--------------	----	----	----	----	---------------	----------------	----------------	--------------	--------------



Test Location: CKC Laboratories • 5473A Clouds Rest • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wilson Electronics**

Specification: **24.238**

Work Order #: **83305**

Date: 03/31/2005

Test Type: **Antenna Terminals**

Time: 10:04:08

Equipment: **In Vehicle Wireless Dual Band Smart Amplifier**

Sequence#: 87

Manufacturer: Wilson Electronics

Tested By: Mike Wilkinson

Model: 801201

S/N: 8012010000006

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HP 8447D Preamp	1937A02604	03/11/2005	03/11/2007	00099
Chase CBL6111C Bilog	2456	06/26/2003	06/26/2005	01991
EMCO 3115 Horn Antenna	9006-3413	03/08/2005	03/08/2007	327
HP 8449B Preamp	3008A00301	12/14/2004	12/14/2006	2010
ARA MWH-1826/B Horn Antenna	1005	11/05/2004	11/05/2006	02046

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
In Vehicle Wireless Dual Band Smart Amplifier*	Wilson Electronics	801201	8012010000006

Support Devices:

Function	Manufacturer	Model #	S/N
Signal Generator	HP	E4433B	US38440697
DC Power Supply	Topward	TPS-2000	920035
Signal Generator	HP	E4432B	MY41000298
Load	JFW	50T-022	P04243

Test Conditions / Notes:

EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. Radiated Intermodulation /Spurious Emissions Test: Two signals are input to the amplifier through a combining network. The input signals are set such that the maximum output per channel is provided at the antenna terminals. The internal ALC of the amplifier limits the combined maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Test setup is in accordance with TIA/EIA 603. Signal generators were remotely located under the ground plane. Two input frequency configurations were investigated as follows, 1850.28 & 1850.84MHz and then 1909.16 & 1909.72MHz. Data represents measured worst case and represents all modulation types. Input Modulation: GSM. Frequencies Tested: Uplink. Frequency Range Investigated: 30MHz to 10GHz. Measurement Bandwidth Settings: 10MHz to 1000MHz - RBW=VBW=10kHz, 1000MHz to 10000MHz - RBW=VBW=1MHz. **No EUT Emissions detected within 20dBc of the limit.**

Transducer Legend:

--

Measurement Data: Reading listed by margin. Test Distance: 3 Meters

#	Freq MHz	Rdng dBμV	dB	dB	dB	dB	Dist Table	Corr dBμV/m	Spec dBμV/m	Margin dB	Polar Ant
---	-------------	--------------	----	----	----	----	---------------	----------------	----------------	--------------	--------------

PHOTOGRAPH SHOWING RADIATED EMISSIONS




Radiated Emissions - Front View

PHOTOGRAPH SHOWING RADIATED EMISSIONS




Radiated Emissions - Back View


INPUT DOWNLINK CDMA



INPUT DOWNLINK EDGE




INPUT DOWNLINK GSM




Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				


INPUT UPLINK CDMA LOW CHANNEL




INPUT UPLINK CDMA MID CHANNEL




INPUT UPLINK CDMA HIGH CHANNEL




INPUT UPLINK EDGE LOW CHANNEL




INPUT UPLINK EDGE MID CHANNEL




INPUT UPLINK EDGE HIGH CHANNEL




INPUT UPLINK GSM LOW CHANNEL



INPUT UPLINK GSM MID CHANNEL




INPUT UPLINK GSM HIGH CHANNEL




Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681


OUTPUT DOWNLINK CDMA



OUTPUT DOWNLINK EDGE




OUTPUT DOWNLINK GSM




Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				


OUTPUT UPLINK CDMA LOW CHANNEL




OUTPUT UPLINK CDMA MID CHANNEL




OUTPUT UPLINK CDMA HIGH CHANNEL




OUTPUT UPLINK EDGE LOW CHANNEL




OUTPUT UPLINK EDGE MID CHANNEL




OUTPUT UPLINK EDGE HIGH CHANNEL




OUTPUT UPLINK GSM LOW CHANNEL



OUTPUT UPLINK GSM MID CHANNEL



OUTPUT UPLINK GSM HIGH CHANNEL



Test Equipment:


Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP



RSS-131 DOWNLINK PASSBAND GAIN GSM

Test Conditions: EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Frequency Range Investigated: 30MHz to 20GHz.




Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

RSS-131 UPLINK PASSBAND GAIN

Wilson Electronics 801201 RSS 131 1900 MHz Passband Gain is 37.85dB (Display line shows input level)
Ref Level 137 dBuV ATTN 40 dB
RES BW: 300.0kHz VID BW: 1.0MHz SWP: 20.0msec
Marker: 1.874GHz 124.85dBuV



Test Equipment:


Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP



RSS-131 DOWNLINK PASSBANDWIDTH GSM


Test Conditions: EUT is a bidirectional amplifier for the 1850 to 1990MHz band. Uplink frequency range 1850 - 1910MHz. Downlink frequency range 1930 - 1990MHz. One signal is input to the amplifier. The input signal is set such that the maximum output is provided at the antenna terminals. The internal ALC of the amplifier limits the maximum power output to a factory set level. Power output is continuously variable and directly proportional to the supplied RF input. Frequency Range Investigated: 30MHz to 20GHz.



Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
Attenuator 30dB, Bird	9949	05/09/2003	05/09/2005	P01572
25-A-MFN-30				

RSS-131 UPLINK PASSBAND WIDTH



Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/12/2005	01/12/2007	02660
HF Cable		02/08/2005	02/08/2007	P05203
Weinchel 10dB attenuator	AH5409	05/23/2005	05/23/2007	P01681

PHOTOGRAPH SHOWING DIRECT CONNECT TEST SETUP

