

ALS BETRIEBSGEHEIMNIS ANVERTRAUT. ALLE RECHTE VORBEHALTEN. PROPRIETARY DATA, COMPANY CONFIDENTIAL. ALL RIGHTS RESERVED.

White label with black lettering

1) 2) 14) 3) 4) 14) 7) 8) 10)

SIEMENS SP65 Made xx Xxxxxxx

5) S30880-SXXXX-XXXX-1 YY 4)

6) **CE 0168** FCC ID: PWX-SP65 14)

IC: 267E-SP65

X X X X X X X X S S S S S S C

10) XXXXXXXX Typ-Approval Code TAC

10) SSSSSS Current serial number (6 digits), Assigned by PICS

10) C CHECK DIGIT 15. digit
space between TAC, serial no. and 15.digit

Ink ribbon: TTR-Band Ricoh 110-C

Font: Title blocks concentric

1) Corporate logo: 1.5 SN 66324

2) Product name: Internal font D, size 4

3) Made xx Xxxxxxx Internal font B, size 3 / Depending on production location

4) Code of date: Internal font D, size 4
e.g. F3 — March
L—1995

5) Code number: Internal font D, size 4

6) CE- identification: Corresponding to the number of the transceiver unit part list
Height: 5 mm
according to BABT-Dokument 556 26/93

7) Barcode IMEI-No.: Code: 128 Size: 2 Ratio: 3.0 Height: 3 mm
Typ 128, table C and B
Characteristic: IMEI-No. has 15 digits
Digit 1-14 is generated as Barcode with table C.
Digit 15 is printed with table B.

8) IMEI-No. (plain writing): Internal font D, size 4, space between TAC, serial no. and 15.digit

10) Document for IMEI-No. allocation: DIS xxxxx BOM 000 xx
Valid is the highest level in the system

14) Canada IC and US FCC: Internal font B, size 3

			Date	21.02.2005	Approval label Standard IMEI-Label/SP65	
			Name	Rauch		
				PD HW4 KLF		
1		01.04.04	Rau		LETTERING PLAN	
Version		Date	Token	SIEMENS AG		Page 1
						From 1

A24850-V1-A4-2 VORSTD.DOC

