

CETECOM Inc.



CETECOM Inc.

411 Dixon Landing Road, Milpitas, CA-95035, USA

Phone: +1 408 586 6200 Fax: +1 408 586 6299

www.cetecom.com

Issued test report consists of 51Pages

Page 1 (51)

FCC LISTED, REG. NO.: 101450 & RECOGNIZED BY INDUSTRY CANADA IC – 3925

Test report no.:200FCC/2001
FCC Part 15.247
(SIMPLEFI)

Table of Contents**1 General information****1.1 Notes****1.2 Testing laboratory****1.3 Details of applicant****1.4 Application details****1.5 Test item****1.6 Test standards****2 Technical test****2.1 Summary of test results****2.2 Test report****1 General information****1.1 Notes**

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc USA.

TEST REPORT PREPARED BY:

EMC & Radio Engineer: Harpreet Sidhu

1.2 Testing laboratory**CETECOM Inc.**

411 Dixon Landing Road, Milpitas, CA-95035, USA

Phone: +1 408 586 6200 Fax: +1 408 586 6299

E-mail: lothar.schmidt@cetecomusa.com

Internet: www.cetecom.com

1.3 Details of applicant

Name : Simple Devices Inc.
Street : 111 Anza Blvd, #120
City : Burlingame, CA-94010
Country : USA
Contact : Nick Kalayjian
Telephone : 650 373 7234
Telefax : 650 342 7924
e-mail : nick@simpledevices.com

1.4 Application details

Date of receipt of application : 2001-10-12
Date of receipt of test item : 2001-10-17
Date of test : 2001-10-17

1.5 Test item

Manufacturer : Applicant
Name of EUT : SIMPLEFI
Description : [MP3 Player with wireless network](#)
Model No. : SIMPLEFI
Serial No. : SIMPLEFI-0069
FCC ID :

Additional informations

Frequency : 2.4 – 2.48 GHz
Type of modulation : Home RF
Number of channels : 75
Antenna : Internal Dipole
Power supply : 6VDC
Output power : 100mW

1.6 Test standards: **FCC Part 15 §15.247**

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

Technical responsibility for area of testing :

2001-10-31

EMC & Radio

Lothar Schmidt



Date

Section

Name

Signature

2.2 Testreport

TEST REPORT

**Test report no. : 200FCC/2001
(SIMPLEFI)**

TEST REPORT REFERENCE**LIST OF MEASUREMENTS**

Paragraph	PARAMETER TO BE MEASURED	PAGE
	Transmitter parameters	
§ 15.204	Antenna gain	7
§ 15.247 (a)	Carrier frequency separation	8
§ 15.247 (a)	Number of hopping channels	9
§ 15.247 (a)	Time of occupancy (dwell time)	13
§ 15.247 (a)(1)	Spectrum Bandwidth of a FHSS System	14
§ 15.247 (b)(2)	Maximum peak output power	18
§15.247	Band edge compliance	23
§ 15.247 (c)(1)	Emission limitations	25
§ 15.107/207	AC Line Conducted Emission	41
	Receiver parameters	
§ 15.209	Spurious radiations - Radiated	43
	Test equipment listing	48

Antenna Gain


SUBCLAUSE § 15.204

The max gain is +4.11dBi

(measured effective radiated power – measured conducted power with a temporary RF-connector)

CARRIER FREQUENCY SEPERATION

§15.247(a)




Date: 16.OCT.01 21:59:12

NUMBER OF HOPPING CHANNELS


§15.247(a)

The number of hopping channels is 75 (see next 4 plots)
The right red line corresponds to the left red line from the next plot.


Plot 1: Total 22




Plot 2: Total 25



Plot 3: Total 19



Plot 4: Total 9




TIME OF OCCUPANCY (DWELL TIME) FOR DH1

§15.247(a)

The system makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 75 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 75 channels. So you have each channel 10.66 times per second and so for 30 seconds you have 319.8 times of appearance .

Each Tx-time per appearance is 372.48 µs.

So we have $319.8 * 372.48 \mu s = 119.12 \text{ ms}$ per 30 seconds.



SPECTRUM BANDWIDTH OF FHSS SYSTEM**§15.247(a)****20 dB bandwidth**


TEST CONDITIONS		20 dB BANDWIDTH (kHz)		
Frequency (MHz)		2403	2440	2477
T _{nom} (23) C	V _{nom} (6)V	845.69	901.80	841.68
Measurement uncertainty		±3dB		

RBW / VBW as provided in the "Measurement Guidelines" (DA 00-705, March 30, 2000)**LIMIT****SUBCLAUSE §15.247(a) (1)****The maximum 20dB bandwidth shall be at maximum 1000 KHz**

SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth

§15.247(a)


Lowest Channel: 2403MHz



SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth

§15.247(a)


Mid Channel: 2440MHz



SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth

§15.247(a)

Highest Channel: 2477MHz



**MAXIMUM PEAK OUTPUT POWER
(conducted)****SUBCLAUSE § 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)			
Frequency (MHz)			2403	2440	2477
T _{nom} (23) C	V _{nom} (6)V	PK	17.80	18.01	18.25
Measurement uncertainty		±3dB			


RBW / VBW : 3 MHz**LIMIT****SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)


Lowest Channel: 2403MHz



PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)


Mid Channel: 2440MHz



PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)

Highest Channel: 2477MHz



**MAXIMUM PEAK OUTPUT POWER
(RADIATED)****SUBCLAUSE § 15.247 (b) (1)****EIRP:**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		2403	2440	2477
T _{nom} (23) C	V _{nom} (6)V	21.91	21.90	22.60
Measurement uncertainty		±3dB		


RBW/VBW : 1 MHz**LIMIT****SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

BAND EDGE COMPLIANCE OF CONDUCTED EMISSIONS

§15.247 (c)


Low frequency section
(valid for both hopping ON & OFF)



BAND EDGE COMPLIANCE OF CONDUCTED EMISSIONS

§15.247 (c)

high frequency section
 (valid for both hopping ON & OFF)



EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

LIMITS


In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE: Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Lowest Channel(2403MHz): 30MHz - 25 GHz




NOTE: The peak above the limit line is the carrier frequency.

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Mid Channel(2440MHz): 30MHz - 25GHz




NOTE: The peak above the limit line is the carrier frequency.

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Highest Channel(2477MHz): 30MHz - 25GHz



NOTE: The peak above the limit line is the carrier frequency.

EMISSION LIMITATIONS - Radiated (Transmitter)**SUBCLAUSE § 15.247 (c) (1)****LIMITS**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 18 and 25 GHz very short cable connections to the antenna was used to minimize the noise level.

2. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.


Results for the radiated measurements below 30MHz according § 15.33

Frequency	Measured values	Remarks
10KHz – 30MHz	No emissions found, caused by the EUT	This is valid for all the tested channels

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2403MHz): 30MHz – 1GHz




ANALYZER SETTINGS: RBW = 100KHz VBW = 100KHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2403MHz): 1GHz – 3GHz

NOTE: The peak above the limit line is the carrier frequency.




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2403MHz): 3GHz – 8GHz




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2440MHz): 30MHz – 1GHz




ANALYZER SETTINGS: RBW = 100KHz VBW = 100KHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2440MHz): 1GHz – 3GHz

NOTE: The peak above the limit line is the carrier frequency.




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2440MHz): 3GHz – 8GHz




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2477MHz): 30MHz – 1GHz




ANALYZER SETTINGS: RBW = 100KHz VBW = 100KHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2477MHz): 1GHz – 3GHz

NOTE: The peak above the limit line is the carrier frequency.




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2477MHz): 3GHz – 8GHz




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

8GHz – 18GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

18GHz – 25GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

CONDUCTED EMISSIONS

§ 15.107/207

Measured with AC/DC power adapter

Phase: Line




Technical specification: 15.107 / 15.207 (Revised as of October 1, 1991)

Limit

0.45 to 30 MHz	250 μV / 47.96dBμV
----------------	--------------------

ANALYZER SETTINGS: RBW = 10KHz VBW = 10KHz

Phase: Neutral



Technical specification: 15.107 / 15.207 (Revised as of October 1, 1991)

Limit

0.45 to 30 MHz	250 μV / 47.96dBμV
ANALYZER SETTINGS: RBW = 10KHz VBW = 10KHz	

RECEIVER SPURIOUS RADIATION**§ 15.209****Limits**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

NOTE:


1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 18 and 25 GHz very short cable connections to the antenna was used to minimize the noise level.
2. Measurements were done on low, mid & high channels, but plots depicting the worst case are submitted in the test report.

RECEIVER SPURIOUS RADIATION

§ 15.209

30MHz – 1GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 100KHz VBW = 100KHz

RECEIVER SPURIOUS RADIATION

§ 15.209

1GHz – 8GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

RECEIVER SPURIOUS RADIATION

§ 15.209

8GHz – 18GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

RECEIVER SPURIOUS RADIATION

§ 15.209

18GHz – 25GHz

(This plot is valid for all three channels)



ANALYZER SETTINGS: RBW = 1MHz VBW = 1MHz

[illegible]