



Test Report

Report No.: E20230509197301-4

Customer: Comba Telecom Network Systems Limited

Address: Flat/Rm 10, 3/F, Bio-Informatics Ctr, 2 Science Park West Avenue, HK Science Park, Pak Shek Kok, N.T. Hong Kong

Sample Name: Public Safety DAS

Sample Model: RH78V3-A

Receive Sample Date: May 16, 2023

Test Date: May 17, 2023~ June 4, 2023

Reference Document: FCC PART 90§90.223-RF exposure

Test Result: PASS

FCC ID: PX8RH78V3-A

Prepared
by:

Chen Hailing

Reviewed
by:

Chen Yuxia

Approved by: Wang Jui

GRG METROLOGY & TEST GROUP CO., LTD.

Issued Date: June 13, 2023



GRG METROLOGY & TEST GROUP CO., LTD.

Address: Park No.9, Wu Ke East 3rd Road, WuHou District, ChengDu, 610045, People's Republic of China
Tel: (+86) 028-86496437 FAX: (+86) 028-86496423 Web: <http://www.grgtest.com>

Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.
6. The test report without CMA approval mark is only used for scientific research, teaching, internal quality control and other purposes.

----- **The following blanks** -----

TABLE OF CONTENTS

1.	Applicant information.....	4
1.1.	Client information.....	4
1.2.	Manufacturer and Factory	4
2.	General description of EUT	4
2.1.	Basic description of EUT.....	4
3.	Assessment result summary	5
4.	Laboratory.....	6
4.1.	Laboratory.....	6
4.2.	Accreditations	6
5.	Radio frequency radiation exposure	7
5.1.	Applicable Standard.....	7
5.2.	Limits for Maximum Permissible Exposure (MPE)	7
5.3.	Test results	7
5.3.1.	700MHz Band:	7
5.3.2.	800MHz Band:	8
5.4.	Test Results	9
	APPENDIX A. PHOTOGRAPHS OF EUT	10
A.1	External photos	10

----- The following blanks -----

1. Applicant information

1.1. Client information

Name: Comba Telecom Network Systems Limited
Address: Flat/Rm 10, 3/F, Bio-Informatics Ctr, 2 Science Park West Avenue, HK Science Park, Pak Shek Kok, N.T. Hong Kong

1.2. Manufacturer and Factory

Manufacture Name: Comba Network Systems Company Limited
Address: No. 10 Shenzhou Road, Guangzhou Science City, Guangzhou 510663, Guangdong, P.R.China
Factory: Comba Telecom Technology (Guangzhou) Ltd.
Address: No. 6 Jinbi Road, Economics and Technology Development District, Guangzhou, Guangdong, China

2. General description of EUT

2.1. Basic description of EUT

Product Name: Public Safety DAS
Product Model: RH78V3-A
Trade Name: Comba
Power Supply: Typical working voltage: AC 110V, 50/60Hz
Power cord: AC power cord
Frequency Band: 700MHz Band:
Downlink: 769MHz ~ 775MHz, Uplink: 799MHz ~805MHz
800MHz Band:
Downlink: 851MHz ~861MHz, Uplink: 806MHz ~ 816MHz
Nominal Output Power: Downlink: 32 ± 1 dBm (Center Frequency)
Uplink: 27 ± 1 dBm(Center Frequency)
Nominal System Gain: Downlink: 90 ± 2 dB(Center Frequency)
Uplink: 90 ± 2 dB(Center Frequency)
EUT Operating Temperature: -40°C to $+55^{\circ}\text{C}$
Operating Humidity: 5% to 95%
Antenna Type: N/A^①

NOTE 1: This EUT is a Broadband device, which belongs to Class A signal booster.

NOTE 2: ^① The EUT does not provide antenna by manufacturer's statement, but it is required that the sum of antenna gain and cable loss shall not exceed 4dBi for downlink and 9 dBi for uplink when the project is used by manufacturer's statement.

NOTE 3: Public Safety DAS system consists of Main Unit (MU), Expansion Unit (EU) and Remote Unit (RU), and MU and EU are auxiliary equipment, while RU is the main equipment.

3. Assessment result summary

Item	Assessment Requirement	Assessment Method
RF exposure	FCC PART 90§90.223	FCC PART 1.1307(b) FCC PART 2.1091 FCC PART 2.1093

----- The following blanks -----

4. Laboratory

4.1. Laboratory

The tests & measurements refer to this report were performed by GRG METROLOGY & TEST (CHENGDU) CO., LTD.

Testing Certificate Number: 2861.02

Add. : Park,No.9,Wu Ke East 3rd Road, WuHou District,ChengDu,SiChuan,610045,People's Republic of China

P.C. : 610045

Tel : 028-86496437

Fax : 028-86496437

4.2. Accreditations

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA: A2LA(Certificate #2861.02)

----- **The following blanks** -----

5. Radio frequency radiation exposure

5.1. Applicable Standard

According to the requirements of FCC PART 90 § 90.223, the test method of RF exposure is based on FCC PART 1.1307(b), FCC PART 2.1091 and FCC PART 2.1093, so RF exposure is calculated.

5.2. Limits for Maximum Permissible Exposure (MPE)

The limits are shown in Table 4-1.

Table 4-1 Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ₂)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

Note: f=frequency in MHz; *=Plane-wave equivalent power density

Prediction of MPE limit at given distance, equations from OET Bulletin 65, Edition 97 - 01:

$$S = (P * G) / (4 * \pi * R^2) \text{ (where } PG = \text{EIRP) Where:}$$

S = power density

P= power input to antenna

G= numeric gain of the antenna

R= distance to the center of radiation of the antenna

5.3. Test results

Devices that operate under CFR47 Part 90 are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and limit for power density for general population/uncontrolled exposure is f/1500 W/m². The maximum output power by manufacturer statement is not more than 33dBm for Downlink and 28dBm for Uplink, the sum of antenna gain shall not exceed 4dBi for downlink and 9 dBi for uplink by manufacturer's statement, therefore, in this report, MPE adopts the maximum output power evaluation, so it has the following assessment:

5.3.1. 700MHz Band:

5.3.1.1. Downlink

Prediction frequency (MHz):	769
Maximum peak output power at antenna input terminal (dBm):	33.0
Maximum peak output power at antenna input terminal (W):	2.0
Maximum antenna gain (dBi):	4.0
Maximum RF output power (W):	5.0
MPE limit for uncontrolled exposure at predication frequency (W/ m ²):	0.51
S= f/1500=769/1500	

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5.0}{0.51 * 4 * 3.14}} \approx 0.88\text{m}$$

$$\text{Conversely, when } R > 0.88\text{m, and } S < \frac{PG}{4\pi R^2} = \frac{5.0}{4 \cdot 3.14 \cdot 0.88^2} \approx 0.51 (\text{W/m}^2)$$

5.3.1.2. Uplink

Prediction frequency (MHz):	799.0
Maximum peak output power at antenna input terminal (dBm):	28.0
Maximum peak output power at antenna input terminal (W):	0.63
Maximum antenna gain (dBi):	9.0
Maximum RF output power (W):	5.0
MPE limit for uncontrolled exposure at predication frequency (W/ m²): S= f/1500=798.0/1500	0.53

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5.0}{0.53 \cdot 4 \cdot 3.14}} \approx 0.87\text{m}$$

$$\text{Conversely, when } R > 0.87\text{m, and } S < \frac{PG}{4\pi R^2} = \frac{5.0}{4 \cdot 3.14 \cdot 0.87^2} \approx 0.53 (\text{W/m}^2)$$

5.3.2. 800MHz Band:

5.3.2.1. Downlink

Prediction frequency (MHz):	851
Maximum peak output power at antenna input terminal (dBm):	33.0
Maximum peak output power at antenna input terminal (W):	2.0
Maximum antenna gain (dBi):	4.0
Maximum RF output power (W):	5.0
MPE limit for uncontrolled exposure at predication frequency (W/ m²): S= f/1500=851/1500	0.57

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5.0}{0.57 \cdot 4 \cdot 3.14}} \approx 0.84\text{m}$$

$$\text{Conversely, when } R > 0.84\text{m, and } S < \frac{PG}{4\pi R^2} = \frac{4.79}{4 \cdot 3.14 \cdot 0.84^2} \approx 0.57 (\text{W/m}^2)$$

5.3.2.2. Uplink

Prediction frequency (MHz):	806
Maximum peak output power at antenna input terminal (dBm):	28.0
Maximum peak output power at antenna input terminal (W):	0.63
Maximum antenna gain (dBi):	9.0
Maximum RF output power (W):	5.0

MPE limit for uncontrolled exposure at predication frequency (W/ m²):

$$S = f/1500 = 806/1500$$

0.54

$$R_1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5.0}{0.54 * 4 * 3.14}} \approx 0.86 \text{m}$$

$$\text{Conversely, when } R > 0.86 \text{m, and } S < \frac{PG}{4\pi R^2} = \frac{5.0}{4 * 3.14 * 0.86^2} \approx 0.54 \text{(W/m}^2\text{)}$$

5.4. Test Results

The above all, when the Maximum antenna gain is 4dBi for downlink and the shortest distance from the human specific is 0.88m, the device is compliant with the requirement MPE limit for uncontrolled exposure.

APPENDIX A. PHOTOGRAPHS OF EUT

A.1 External photos



Top surface



Front surface




Side surface-1



Side surface-2



Behind surface



Bottom surface

----- End of Report -----